

MACHINE LEARNING

Q1 to Q11 have only one correct answer. Choose the correct option to answer your question.

1. Movie Recommendation systems are an example of:

- i) Classification
- ii) Clustering
- iii) Regression

Options:

- a) 2 Only
- b) 1 and 2
- c) 1 and 3
- d) 2 and 3

Answer is (b)

2. Sentiment Analysis is an example of:

- i) Regression
- ii) Classification
- iii) Clustering
- iv) Reinforcement

Options:

- a) 1 Only
- b) 1 and 2
- c) 1 and 3
- d) 1, 2 and 4

Answer is (d)

3. Can decision trees be used for performing clustering?

- a) True
- b) False

Answer is (a)

4. Which of the following is the most appropriate strategy for data cleaning before performing clustering analysis, given less than desirable number of data points:

- i) Capping and flooring of variables
- ii) Removal of outliers

Options:

- a) 1 only
- b) 2 only
- c) 1 and 2
- d) None of the above

Answer is (a)

5. What is the minimum no. of variables/ features required to perform clustering?

- a) 0
- b) 1
- c) 2
- d) 3

Answer is (b)

6. For two runs of K-Mean clustering is it expected to get same clustering results?

- a) Yes
- b) No

Answer is (b)

7. Is it possible that Assignment of observations to clusters does not change between successive iterations in K-Means?

MACHINE LEARNING

- a) Yes
- b) No
- c) Can't say
- d) None of these

Answer is (a)

8 Which of the following can act as possible termination conditions in K-Means?

- i) For a fixed number of iterations.
- ii) Assignment of observations to clusters does not change between iterations. Except for cases with a bad local minimum.
- iii) Centroids do not change between successive iterations.
- iv) Terminate when RSS falls below a threshold.

Options:

- a) 1, 3 and 4
- b) 1, 2 and 3
- c) 1, 2 and 4
- d) All of the above

Answer is (d)

9 Which of the following algorithms is most sensitive to outliers?

- a) K-means clustering algorithm
- b) K-medians clustering algorithm
- c) K-modes clustering algorithm
- d) K-medoids clustering algorithm

Answer is (a)

10 How can Clustering (Unsupervised Learning) be used to improve the accuracy of Linear Regression model (Supervised Learning):

- a. Creating different models for different cluster groups.
- b. Creating an input feature for cluster ids as an ordinal variable.
- c. Creating an input feature for cluster centroids as a continuous variable.
- d. Creating an input feature for cluster size as a continuous variable.

Options:

- i. 1 only
- ii. 2 only
- iii. 3 and 4
- iv. All of the above

Answer is (iv) all the above

11 What could be the possible reason(s) for producing two different dendrograms using agglomerative clustering algorithms for the same dataset?

- a) Proximity function used
- b) of data points used
- c) of variables used
- d) All of the above

Answer is (d)

Q12 to Q14 are subjective answers type questions, Answers them in their own words briefly

12 Is K sensitive to outliers?

Yes. K-Means fails to give good results if Dataset contains Outliers.

13 Why is K means better?

K-Means is relatively easy to use and scales better to large and extensive Datasets.

MACHINE LEARNING

14 Is K means a deterministic algorithm?

No. Because running the algorithm on the same data could produce different outcomes.
