Loan Default Prediction

Comparing Classic ML and Neural Networks under Class Imbalance

Minwoo Yoo Nathaniel Badalov

Home Credit Default Risk (Kaggle)

Business Problem and Motivation

Goal

Predict the probability that a loan applicant will default before making a lending decision.

Why it matters

- False negatives: approve borrowers who default
- False positives: reject creditworthy borrowers
- Models help balance risk vs. profitability

Key challenge
Default events are rare (~8%) $\Rightarrow$ strong class imbalance

Approaches to Class Imbalance

Why imbalance matters

- Models can achieve high ROC AUC but still predict no defaults
- Default threshold (0.5) often fails in imbalanced settings

Common solutions

- Reweighting the loss (class weights)
- Resampling the data (e.g., SMOTE)
- Adjusting the decision threshold

Models compared

- Logistic Regression, Random Forest, HistGradientBoosting
- Shallow and Deep MLP

Dataset Overview

What the dataset represents

- Loan applications from Home Credit
- Focus on borrowers with limited credit history
- Tabular structure (Each row = one applicant)
- Goal: predict default risk

Main feature groups

- Demographics (age, family status)
- Employment and income
- Loan details (amount, annuity)
- External credit scores: `EXT_SOURCE_*`

Data Structure and Class Imbalance

Dataset characteristics

- Train data: **307,511**
- Test data: **48,744**
- Features: **122**

Target variable

- 1: default
- 0: repaid

Class imbalance

Defaults: only **8.07%** default

$\Rightarrow$ severe class imbalance



Classic ML Strategy

Why start with classic ML?

- The data is tabular: rows are applicants, columns are features
- Classical models are strong baselines for tabular prediction
- They provide a benchmark for the neural networks

Models tested

- **Logistic Regression**: strong baseline for probability prediction
- **Random Forest**: captures nonlinear patterns and reduces overfitting
- **Histogram Gradient Boosting**: captures complex interactions efficiently

Handling class imbalance

- Logistic Regression and Random Forest give more weight to default cases (`class_weight='balanced'`).
- Histogram Gradient Boosting used without class weights (boosting still captures rare cases well).

Classic ML Results

Model	Best hyperparameters	Val ROC AUC
HistGradientBoosting	`learning_rate`=0.05; `max_iter`=200; `leaf`=100	**0.7595**
Logistic Regression	`C`=0.1; `tol`=1e-5; `class_weight=balanced`	0.7487
Random Forest	`n_estimators`=200; `min_leaf`=1; `balanced`	0.7470

Key takeaways

- Histogram Gradient Boosting performs best (0.7595), suggesting boosted trees capture nonlinear interactions in tabular data effectively.
- Logistic Regression and Random Forest perform similarly, indicating strong linear signal alongside moderate nonlinearities.
- Random Forest shows signs of overfitting (train 0.96 vs val 0.747), while boosting remains more stable.

Neural Network Models

Architectures tested

Architecture	Hidden	Parameters	Val ROC AUC
Shallow MLP	$(64,)$	$\sim$15.7K	0.7405
Deep MLP	$(128, 64, 32)$	$\sim$42K	**0.7416**

Common setup

- ReLU activation, Adam optimizer, early stopping
- Tuned over `alpha` $\in \{10^{-4}, 10^{-3}\}$, `lr_init` $\in \{0.001, 0.005\}$
- Best for both: $\alpha = 10^{-3}$, `lr` $= 0.005$

Key takeaways

- Depth doesn't help: 0.7405 vs 0.7416 (within noise)
- Tripling parameters bought nothing
- Both NNs land below the classic learners

Imbalance Handling on the Best MLP

Three strategies compared (sklearn `MLPClassifier` does not support `class_weight`)

Method	Threshold	ROC AUC	PR AUC	Precision	Recall	F1
Baseline	0.500	0.742	0.217	0.00	0.00	0.00
SMOTE	0.500	**0.648**	0.134	0.16	0.21	0.18
Threshold tuning ⋆	0.139	0.742	0.217	0.22	**0.41**	**0.29**

Key takeaways

- Baseline at 0.5: AUC 0.742 but recall **0%**
- SMOTE hurts: AUC drops 0.09
- Threshold tuning at 0.139 lifts recall to **41%**

Headline

Choosing the threshold matters more than rebalancing the data.

Combined Leaderboard



Final ranking

Model	Val ROC AUC
HistGradBoost	**0.7595**
Logistic Reg.	0.7487
Random Forest	0.7470
Deep MLP	0.7416
Shallow MLP	0.7405

Tree boosting wins by ∼1 AUC point — consistent with the literature on tabular data.

Why NN Underperformed on Our Data

1. **Linear signal is already enough**
   - LR alone reaches val AUC **0.7487** — only 0.011 below HGBC (0.7595)
   - NN's nonlinear capacity adds no value when the signal is mostly linear
2. **Sparse one-hot dominates the feature mix**
   - Our 16 categorical columns expanded into 140 sparse 0/1 dummies
   - 70% of the 244 final features are binary — trees split on them cheaply, MLP must learn weights for every one
3. **Extra NN capacity bought nothing in our experiment**
   - Deep MLP has $\sim 3\times$ the parameters of Shallow MLP (42K vs 15.7K)
   - Yet val AUC moved by only **+0.001** (0.7405 $\rightarrow$ 0.7416)
   - The bottleneck is the feature set, not the model's capacity

Conclusions

What we found

- HGBC wins (val AUC = **0.7595**) — tree boosting captures feature interactions
- Neural networks don't help on this tabular data — both MLPs (0.7405 / 0.7416) score below LR (0.7487), RF (0.7470), and HGBC (0.7595)
  - Even depth doesn't rescue them: tripling parameters moved val AUC by only $+0.001$ ($0.7405 \rightarrow 0.7416$)
  - Why in our case: LR alone reaches 0.7487 ($\approx$ HGBC), and 70% of our 244 features are sparse 0/1 dummies — favoring linear models and trees, not MLPs

Recording

https://youtu.be/aAXtFOcwzck

Minwoo Yoo · Nathaniel Badalov