Home: https://www.postgresql.org/docs/current/plpgsql.html

PLPGSQL
PL = **procedural language** for PostgreSQL.

e.g.

```
DO LANGUAGE PLPGSQL $$
BEGIN
  RAISE INFO 'hello'
END;
$$;
```

e.g. FOR loop

```
DO LANGUAGE PLPGSQL $$
DECLARE
  name text;
BEGIN
  FOR name IN SELECT nspname FROM pg_namespace
  LOOP
    RAISE INFO 'namespace: %', name;
  END LOOP;
END;
$$;
```

*** configurations**
https://www.postgresql.org/docs/12/plpgsql-development-tips.html

plpgsql.check_asserts='on' boolean
plpgsql.extra_warnings='none' none | all | <opt>[,...]
plpgsql.extra_errors='none' none | all | <opt>[,...]
where opts
shadowed_variables

too_many_rows ... INTO x received more than 1 row

strict_multi_assignment

plpgsql.print_strict_params='off' boolean
include error details in STRICT

plpgsql.variable_conflict='error' error|use_variable|use_column
how to handle variable and column name conflict

*** usage: OUT parameter assignment**
OUT parameters can be assigned to **variables** in a PLPGSQL code.

e.g.
Step 1) Define procedure

```
-- Step 1) define procedure
```

```
CREATE OR REPLACE PROCEDURE f(
  a int,
  OUT x int,                  -- NULL initially
  OUT y text,                 -- NULL
  OUT z boolean               -- NULL
) as $$
BEGIN
    x := a + 1;               -- set x
    y := 'hello';             -- set y
END;
$$ LANGUAGE PLPGSQL;
```

Step 2)

```
-- usage 1: call in SQL
> CALL f(1, NULL, NULL, NULL);
> CALL f(1, 1, 'a', TRUE);            -- same. initial values for
OUT parameters are ignored

 x |   y   |  z
---+-------+------
 2 | hello | NULL


-- usage 2: call in PLPGSQL
> DO LANGUAGE PLPGSQL $$
DECLARE
  x int;
  y text;
  z boolean;
BEGIN
  CALL f(100, x, y, z);           -- sets x=101 y='hello' z=NULL
  RAISE INFO '% % %', x, y, z;
END;
$$;

INFO:  101 hello <NULL>
```

==========

== SQL execution ==

Ref: https://www.postgresql.org/docs/current/plpgsql-statements.html

In general, any SQL can be executed **directly**.
e.g.

```
-- direct
SELECT 1 INTO x;
INSERT INTO t VALUES (1);
```

```
-- dynamic
EXECUTE 'SELECT 1' INTO x;
```

However, **features** differ depending on the SQL **type**.
2 types:
1) **cacheable** SQL
Query plan is **cached**
Same as **PREPARE**d statements.

Ref: https://www.postgresql.org/docs/current/sql-prepare.html
SELECT ...
INSERT ...
UPDATE ...
DELETE ...
MERGE ...

2) **non-cacheable** SQL
Everything else.
e.g.
CREATE TABLE ...
COPY ...

*** Feature: execution**
SQL result must either be **assigned** to a variable or explicitly **discarded**.

case A: SQL **queries**

```
-- case: SQL only
-- FORBIDDEN since the output is unhandled
SELECT 1;                       -- ERROR



-- usage 1: PERFORM
-- i.e. discard output
PERFORM 1;                      -- OK  Same as 'SELECT 1'
PERFORM * FROM t;               -- OK

-- usage 2: RETURN
RETURN QUERY SELECT 1;          -- OK



-- usage 3: assign single output to variable
-- LOOP if multiple.
SELECT 1 INTO x;                    -- OK
SELECT * FROM pg_class INTO x;      -- ERROR  Must be exactly ONE
row
                                    -- Use loop instead
FOR x IN                            -- OK LOOP
   SELECT * FROM pg_class
LOOP
   ... x.relid ...
END LOOP;
```

case B: SQL **statements**

```
-- usage 1: call as usual
INSERT INTO t VALUES (1);              -- OK: no output by default

-- usage 2: assign RETURNING
INSERT INTO t VALUES (1)               -- OK
  RETURNING t.value INTO x;

INSERT INTO t VALUES (1), (2)          -- ERROR Must be exactly one
row
  RETURNING t.value INTO x;            -- Use LOOP instead

FOR x IN                               -- OK: LOOP
  INSERT INTO t VALUES (1), (2)
    RETURNING t.value
LOOP
  ...
END LOOP;
```

<u>* Feature: parameter/variable</u>

Only **cacheable queries** can use parameters directly
e.g.

```
CREATE PROCEDURE f(value INT) AS $$
DECLARE
  x INT;
BEGIN
  SELECT value INTO x;                                    -- OK: can
use variable in cacheable SQL

  CREATE TABLE mytable (x INT DEFAULT 1);                 -- OK: can
execute without variable

  CREATE TABLE mytable (x INT DEFAULT value);             -- RUNTIME
ERROR: can't use variable in non-cacheable SQL

  EXECUTE 'CREATE TABLE mytable (x INT DEFAULT %L)'       -- RUNTIME
ERROR: can't use parameter either
    USING value;

  EXECUTE format(                                         -- OK:
dynamic execution
    'CREATE TABLE mytable (x INT DEFAULT %L)',
    value
   );
END;
$$ LANGUAGE PLPGSQL;
```

IMPORTANT: DON'T BUILD DYNAMIC QUERIES MANUALLY
May easily lead to SQL injection

```
EXECUTE 'SELECT * FROM '                    -- NEVER
  || tablename
  || 'WHERE x ='
  || value;

EXECUTE 'SELECT * FROM '                    -- OK, but unsafe
  || quote_ident(tablename)
  || 'WHERE x ='
  || quote_literal(value);

EXECUTE format(                             -- GOOD
  'SELECT * FROM %I WHERE x=$1,             -- %I   same as
quote_ident
  tablename
)
  USING value;
```

*** usage: execution error handling**

e.g.

```
BEGIN
  -- case: non-strict
  --
  -- if more than 1 row:
  SELECT ... INTO x;               -- may raise TOO_MANY_ROW
  IF NOT FOUND THEN                -- check for
  END IF

  SELECT ... INTO STRICT x;        -- may raise TOO_MANY_ROWS

EXCEPTION
  WHEN NO_DATA_FOUND THEN
    ...
  WHEN TOO_MANY_ROWS THEN
    ....

-- Error handling

IF NOT FOUND THEN
  ....
END IF
EXCEPTION
  WHEN TOO_MANY_ROWS THEN
```

```
    ....
```

*** Execution checks (FOUND, DIAGNOSTICS)**
https://www.postgresql.org/docs/current/plpgsql-statements.html

FOUND variable
Special variable indicating whether a query had **at least ONE** result.
e.g.

```
VALUES (1) INTO x;                          -- 1 row     FOUND =
TRUE

SELECT * FROM t WHERE FALSE INTO x;         -- 0 rows    FOUND =
FALSE

VALUES (1), (2) INTO x;                     -- >1 rows   FOUND =
TRUE

-- with STRICT
SELECT ... INTO STRICT x;                   -- 0 rows
NO_DATA_FOUND error
                                            -- >1 rows
TOO_MANY_ROWS error
```

Action	**FOUND**
SELECT ... INTO x	FALSE if 0 rows
PERFORM ...	FALSE if 0 rows
UPDATE ... INTO x INSERT ... INTO x DELETE ... INTO x MERGE ... INTO x	FALSE if 0 rows changed
RETURN QUERY ...	FALSE if 0 rows
FOR ... LOOP	FALSE if 0 loop
EXECUTE ...	NA use GET DIAGNOSTICS

```
-- FOUND
SELECT ... INTO x;
IF NOT FOUND THEN                       -- FOUND=TRUE if x was set
  RAISE EXCEPTION 'x not found';
END IF;


-- GOTCHA: FOUND not supported for EXECUTE
EXECUTE ...;
GET DIAGNOSTICS row_count := ROW_COUNT;
```

```
IF row_count = 0 THEN
  ...
END IF;


-- DIAGNOSTICS: meta info about routine
-- e.g. stacktrace
--
c BIGINT;
ctx TEXT;
id  oid;
GET DIAGNOSTICS
  c := ROW_COUNT,             -- number of rows returned by
previous query
                              -- e.g. 1
  ctx := PG_CONTEXT,          -- current stacktrace
                              -- e.g. "PL/pgSQL function f() line 2
at GET DIAGNOSTICS"
  id := PG_ROUTINE_OID;       -- e.g. 12345
```

*** Syntax**

Ref: https://www.postgresql.org/docs/current/plpgsql-statements.html

```
-- EXECUTE: dynamic SQL
--
-- IMPORTANT: dynamic SQL isn't cached
EXECUTE 'INSERT INTO mytable VALUES (1, 2)';
EXECUTE 'INSERT INTO mytable VALUES ($1, $2)'      -- parameters
  USING x, y;
EXECUTE 'SELECT 1' INTO x;                         -- assignment

-- GOTCHA: can't use parameters for identifiers
EXECUTE 'INSERT INTO $1 VALUES (1, 2)';                    --
ERROR
  USING tablename;
EXECUTE format('INSERT INTO %I VALUES (1, 2)', tablename);  -- OK


-- PERFORM: discard result
PERFORM 1;                        -- OK    Discard return
                                  --       Replace 'SELECT' with
'PERFORM'
PERFORM pg_reload_conf();         -- e.g. typically for side-
effect



-- INTO assignment
--
-- a) SELECT ... INTO
SELECT n INTO x FROM mytable;             -- x=NULL if empty
```

```
                                        -- x=first row if
multiple
SELECT array_agg(n) INTO x FROM mytable;   -- OK
SELECT 1, 'a' INTO r;                      -- record variable
                                        --  r RECORD  where
r.column1=1  r.column2='a'
SELECT 1, 'a' INTO x, y;                   -- multiple variables
                                        -- x=1 y='a'


-- b) RETURNING ... INTO
INSERT INTO mytable
  VALUES (100, 'a')
  RETURNING mytable.id
  INTO x;                               -- x = 100
                                        -- x=NULL if empty
                                        -- x=first row if
multiple

UPDATE ... RETURNING mytable.id INTO x;
DELETE ... RETURNING mytable.id INTO x;
MERGE ... RETURNING mytable.id INTO x;

-- composite type
INSERT INTO mytable               -- d mytable  i.e. d is of type
"mytable"
  ...
  RETURNING (mytable).*
  RETURNING (mytable)             -- BAD
  INTO d;


-- STRICT: MUST return exactly ONE row.
-- In particular, no return value is also an error
SELECT ... INTO STRICT x;                  -- TOO_MANY_ROWS error
if more than 1 row
                                        -- NO_DATA_FOUND error
if NULL
INSERT ... RETURNING t INTO STRICT x;      -- same with INSERT ...
RETURNING
UPDATE ... RETURNING t INTO STRICT x;      -- same with UPDATE ...
RETURNING
...etc
```

```
-- e.g.
BEGIN
  SELECT ... INTO STRICT x;

EXCEPTION
  WHEN NO_DATA_FOUND THEN         -- no rows
    ...
  WHEN TOO_MANY_ROWS THEN         -- > 1 rows
```

```
    ....
END;
```

==========

== Syntax ==

*** BEGIN/END blocks**

Ref: https://www.postgresql.org/docs/current/plpgsql-structure.html

```
---- Blocks
--
-- Basic
DECLARE
  x int;
BEGIN
  RAISE INFO 'x=%', x;
END;

-- DECLARE is optional
BEGIN
  RAISE INFO 'hello';
END;


-- Nesting
DECLARE
  x int = 10;
BEGIN
  -- nest without DECLARE
  BEGIN
    ...
  END;

  -- nest with DECLARE
  DECLARE
   x int = 100;
  BEGIN
    ...
  END;

  -- RETURN from inner block
  BEGIN
    RETURN;       -- OK

    RETURN 1;     -- ERROR. Can't return
  END;
END;
```

```
-- Scope and labels
--
-- Lexical scope
<<o>>                              -- outer scope o
DECLARE
  x int := 1;
BEGIN
  RAISE INFO '% %', x, o.x;        -- x = 1
                                   -- o.x = 1   explicit block

  <<i>>
  DECLARE
    x int := 10;                   -- case: inner block
  BEGIN
    RAISE INFO '%, %, %',          -- x = 10             shadow
      x, i.x, o.x;                 -- i.x = x = 10       explicit
inner block
                                   -- o.x = 1            explicit
outer block

    o.x := -1;                     -- OK. Can set outer block
  END;
  RAISE INFO '%', x;               -- o.x = x = -1
END;
```

*** DECLARE**

Ref: https://www.postgresql.org/docs/current/plpgsql-declarations.html

e.g.

```
-- with declaration
CREATE FUNCTION f() RETURNS INT AS $$
DECLARE
  x INT := 1;
BEGIN
  RETURN x;
END;
$$ LANGUAGE PLPGSQL;

-- without declaration
CREATE FUNCTION f(x INT) RETURNS INT AS $$
BEGIN
  RETURN x;
END;
$$ LANGUAGE PLPGSQL;
```

```
-- Basic syntax
x int;               -- x is NULL
```

```
x int := 1;           -- initialize with 1
x int DEFAULT 1;      -- initial value
x int = 1;            -- same
x int = 1 + 3;        -- any expression
x my_table = (        -- subquery
 SELECT (my_table)    -- GOOD
 SELECT *             -- ERROR
 FROM my_table
 WHERE id=1
);

x int NOT NULL;
x CONSTANT int = 1;
x ALIAS FOR $1;

-- Types
x int;
x y%TYPE;             -- type of variable y e.g.
                      -- e.g. y%type = int  if y is an int
x mytable%ROWTYPE;    -- type of a row
x RECORD;             -- any ROW type
```

*** RETURN values**

3 types of returns

1) **RETURN** with **no value**
i.e. procedure
e.g.

```
CREATE PROCEDURE p() AS $$
BEGIN
  RAISE INFO 'hello';
  RETURN;
END;
```

2) **RETURN** with **single row**
i.e. function

3) **RETURN** with **multiple rows**
e.g.

```
create or replace function f() RETURNS SETOF INT AS $$
BEGIN
  RETURN NEXT 1;                              -- append single row
to result
  RETURN QUERY VALUES (10), (20);             -- append multiple
rows to result
  RETURN;                                     -- finish
```

```
END;
$$ LANGUAGE PLPGSQL;

SELECT * FROM
 f
────
  1
 10
 20
```

```
-- Syntax
RETURN 1;
RETURN SELECT 1;          -- error
RETURN (SELECT 1);        -- OK subquery
RETURN;                   -- early exit

-- multiple rows
RETURN NEXT 1;                -- append single
RETURN QUERY (SELECT ...);    -- append multiple from subquery
RETURN QUERY                  -- dynamic subquery
  EXECUTE 'VALUES (1)';
RETURN QUERY
  EXECUTE 'VALUES ($1), ($2)'
  USING 1,2;
RETURN;
```

*** Basic syntax**
Ref: https://www.postgresql.org/docs/current/plpgsql.html

```
-- Basic
NULL;                 -- do nothing
x = 1                 -- assign
x := 1

-- qualified names
x
f.x              -- qualified function parameter e.g. f(x int)
b.x              -- qualified block parameter
```

```
-- e.g. x with various scopes
> CREATE PROCEDURE f(x INT) AS $$      -- fully qualified f.x
<<b>>
DECLARE
  x INT := 10                         -- fully qualified b.x
BEGIN
  RAISE INFO '
x=%                                   -- 10
f.x=%                                 -- -1
b.x=%                                 -- 10
', x, f.x, b.x;
```

```
END;
$$ LANGUAGE PLPGSQL;


> CALL f(-1);
x=10
f(x)=-1
b.x=10
```

```
-- ASSERT
--
-- Enabled only if
--
-- SET plpgsql.check_asserts='on'
--
ASSERT x = y;
ASSERT x = y, 'FAIL';


---- Conditions
--
-- IFs
IF x = 1 THEN
   ...
ELSIF x = 2 THEN
   ...
ELSE
  ...
END IF;


-- CASE simple
CASE x
  WHEN 1 THEN
    ...
  WHEN 2, 3 THEN      -- multiple cases
   ...
  ELSE
END CASE


-- CASE general
CASE
  WHEN x = 1 THEN
    ...
  WHEN x = 2 THEN
   ...
  ELSE
END CASE
```

*** Loop**

```
---- Looping
--
--
-- Basics
<<a>>                    -- optional label 'a'
a                        -- ERROR MUST be of the form <<LABEL-
NAME>>
LOOP
  ...
  CONTINUE;
  CONTINUE a;            -- label i.e. continue loop a
  CONTINUE WHEN x > 0;   -- conditional

  EXIT;
  EXIT a;                -- label
  EXIT WHEN x > 0;       -- conditional
END LOOP;


-- LOOPs
--
-- do LOOP: loop until explicit exit
LOOP
  ...
  EXIT;
END LOOP;

-- WHILE LOOP: loop until condition
WHILE x > 0 LOOP
  ...
END LOOP;
```

```
> DO LANGUAGE PLPGSQL $$
DECLARE
  c int := 0;
BEGIN
  LOOP
    RAISE INFO '%', c;
    EXIT WHEN c > 10;
    c := c + 1;
  END LOOP;
END;
$$;

INFO:  0
INFO:  1
INFO:  2
INFO:  3
INFO:  4
```

```
INFO:  5
INFO:  6
INFO:  7
INFO:  8
INFO:  9
INFO:  10
INFO:  11
```

```
-- FOR i LOOP
--
-- NOTE: i is declared automatically
FOR i IN 10..20 LOOP           -- i = 10,11,...20
FOR i IN 10..20 BY 2 LOOP      -- explicit step e.g. i =
10,12,14...
FOR i IN REVERSE 10..20 LOOP   -- i= 20,18,...10
  ...
END LOOP;

-- FOREACH: loop array
FOREACH c IN ARRAY a LOOP
FOREACH c SLICE 1 IN ARRAY a LOOP          -- SLICE: dimension of
array
                                           -- 0 = default
  ...
END LOOP;
```

```
DECLARE
  c int := 0;
BEGIN
  -- FOR LOOP
  FOR i in 10..20 by 2 LOOP                -- i declared
automatically
    RAISE INFO '%', i;                     -- i visible here
  END LOOP;

  -- FOREACH LOOP
  FOREACH c IN ARRAY (ARRAY[1,2,3]) LOOP
    RAISE INFO '%', c;
  END LOOP;
END;
```

```
-- FOR IN loo
--
-- e.g. loop series
d date;

FOR d IN
  SELECT *
```

```
  FROM generate_series('2020-01-06'::date, '2025-01-01', interval
'7 days') _(d)
LOOP
  -- 2020-01-06, 2020-01-13, 2020-01-20, ...
  RAISE INFO '%', d;
END LOOP;
```

==========

=== Diagnostics ===

*** RAISE aka logging, error messaging**
Ref: https://www.postgresql.org/docs/current/plpgsql-errors-and-messages.html

RAISE
Command for both **logging** and error throwing
e.g.

```
-- usage 1: logging
RAISE INFO 'x=%', 1                    -- Not an error
 USING HINT='a'


-- usage 2: throw EXCEPTION
RAISE EXCEPTION plgpsql_error          -- throw
   USING MESSAGE='OOPS';

EXCEPTION                              -- catch
  WHEN plpgsql_error THEN
    ...
```

ERRCODE
Ref: https://www.postgresql.org/docs/current/errcodes-appendix.html#ERRCODES-TABLE

P0000	plpgsql_error
P0001	raise_exception
P0002	no_data_found
P0003	too_many_rows
P0004	assert_failure
-	others
MY001	custom code
	any 5 letter alphanum

e.g.

```
DO LANGUAGE PLPGSQL $$
DECLARE
  msg_state text;
  msg_message text;
```

```
  msg_detail text;
  msg_hint text;
  msg_context text;
  msg_schema text;
  msg_table text;
  msg_column text;
  msg_constraint text;
  msg_datatype text;

BEGIN
  RAISE SQLSTATE 'YUI00' USING                -- Step 1: RAISE
EXCEPTION
    MESSAGE='oops',
    DETAIL='some internal error',
    HINT='no hint',
    SCHEMA='myschema',
    TABLE='mytable',
    COLUMN='col1',
    DATATYPE='text',
    CONSTRAINT='CHECK'
    ;

  EXCEPTION                                   -- Step 2: catch
EXCEPTION
    WHEN SQLSTATE 'YUI00' THEN
      GET STACKED DIAGNOSTICS                 -- Step 3:
DIAGNOSTICS
        msg_state := RETURNED_SQLSTATE,
        msg_message := MESSAGE_TEXT,
        msg_detail := PG_EXCEPTION_DETAIL,
        msg_hint := PG_EXCEPTION_HINT,
        msg_context := PG_EXCEPTION_CONTEXT,
        msg_table := TABLE_NAME,
        msg_schema := SCHEMA_NAME,
        msg_column := COLUMN_NAME,
        msg_constraint := CONSTRAINT_NAME,
        msg_datatype := PG_DATATYPE_NAME
        ;

      RAISE INFO '
state=%
message=%
context=%
detail=%
hint=%
schema=%
table=%
column=%
constraint=%
data type=%
',
        msg_state,
        msg_message,
```

```
        msg_context,
        msg_detail,
        msg_hint,
        msg_schema,
        msg_table,
        msg_column,
        msg_constraint,
        msg_datatype
        ;
END;
$$;
```

Output

```
INFO:
state=YUI00
message=oops
context=PL/pgSQL function testerror() line 14 at RAISE
detail=some internal error
hint=no hint
schema=myschema
table=mytable
column=col1
constraint=CHECK
data type=text
```

```
-- RAISE: Logging
--
-- 3 formats
-- a) simple message format
RAISE INFO 'hello';
RAISE INFO 'hello % %', 1, 'a';           -- template
                                          --  Only % is supported
RAISE INFO 'hello %s', 1;                 -- BAD Not format()
RAISE INFO 'hello' || 'a';                -- ERROR  Message cannot
be an expression
RAISE INFO format(...)                    -- ERROR
message := 'a';
RAISE INFO message;                       -- ERROR
RAISE INFO '%', message;                  -- OK


-- b) general message expression
RAISE INFO USING
  MESSAGE='hello'
  MESAAGE='hello' || 'a'                  -- OK any expression

  MESSAGE=format('hello %s %s, 1, 'a');   -- OK template
```

```
-- levels
RAISE ...         -- default is EXCEPTION
RAISE DEBUG ...
RAISE LOG ...
RAISE INFO ...
RAISE NOTICE ...
RAISE WARNING ...
RAISE EXCEPTION ...


-- OPTIONS: provide additional context
-- See GET STACKED DIAGNOSTICS below
RAISE 'hello' USING
  -- basic context
  DETAIL="abc",
  DETAIL=format("abc"),           -- can use any expression
  HINT="...",

  -- additional context
  SCHEMA="...",
  TABLE="...",
  COLUMN="...",
  CONSTRAINT="...",
  DATATYPE="...",
```

```
-- e.g.
RAISE EXCEPTION 'OOPS' USING
  DETAIL = 'something is wrong',
  HINT = 'check lin 1',
  SCHEMA = 'publics',
  DATATYPE = 'mytype';

-- output
ERROR:  OOPS
DETAIL:  something is wrong
HINT:  check lin 1
CONTEXT:  PL/pgSQL function testraise() line 7 at RAISE
```

```
-- RAISE: throw EXCEPTION
--
RAISE EXCEPTION division_by_zero;
RAISE EXCEPTION SQLSTATE '22012';          -- same with code
RAISE division_by_zero;                    -- implicit EXCEPTION
RAISE EXCEPTION SQLSTATE 'ABC00';          -- Custom code. Must be
5 letters.
RAISE EXCEPTION SQLSTATE 'ABC000';         -- ERROR Must be 5
letters.
```

```
-- all same
RAISE EXCEPTION division_by_zero
```

```
  USING MESSAGE=format('error %s', 1);

RAISE EXCEPTION SQLSTATE '22012'
  USING MESSAGE=format('error %s', 1);

RASE EXCEPTION 'error %s', 1
  USING ERRCODE='division_by_zero'

RASE EXCEPTION 'error %s', 1
  USING ERRCODE='22012'
```

*** EXCEPTION: catch error**
Ref: https://www.postgresql.org/docs/current/plpgsql-control-structures.html#PLPGSQL-EXCEPTION-DIAGNOSTICS

EXCEPTION
Catches errors thrown between **BEGIN** and **EXCEPTION**.
e.g.

```
DECLARE
  err_msg text;
BEGIN

    ...work ...

EXCEPTION                                                    --
catches any error between BEGIN and EXCEPTION
   WHEN OTHERS THEN
      GET STACKED DIAGNOSTICS err_msg := MESSAGE_TEXT;
      RAISE INFO 'error: %', err_msg;
END;
```

```
-- EXCEPTION: catch error
--
EXCEPTION
  WHEN no_data_found THEN                            -- with error
name
  WHEN NO_DATA_FOUND THEN                            -- case
insensitive
  WHEN SQLSTATE 'P0002' THEN                         -- same with
code
  WHEN no_data_found OR too_many_rows THEN           -- multiple
    ...
  WHEN assert_failure THEN                           -- another WHEN
   ...

  WHEN OTHER THEN                                    -- SPECIAL:
OTHER catches all errors
   ...
```

```
-- STACKED DIAGNOSTICS:
--
-- MUST be inside exception handler
GET STACKED DIAGNOSTICS
  -- info: see RAISE .. USING <options>
  t := RETURNED_SQLSTATE
  t := MESSAGE_TEXT
  t := PG_EXCEPTION_DETAIL
  t := PG_EXCEPTION_HINT
  t := PG_EXCEPTION_CONTEXT
  t := SCHEMA_NAME
  t := TABLE_NAME
  t := COLUMN_NAME
  t := CONSTRAINT_NAME
  t := PG_DATATYPE_NAME
```

==========

=== OLD ===

```
This
is
code
Monaco 14
```