Help

```
:help functions            Built-in functions
:help function-list        Functions by group
:function                  List of user defined commands
```

Basics

```
"" Call
call printf("Hello")

" Variables
call print(g:x)          " Variable input
let g:x = exists("a")    " Assign output
```

Built-in Functions

```
" See builtin functions
:help functions



""" Expressions
"" escape({expr}, {chars})
"
" Escapes the given chars from the expression.
"   i.e. places a '\' in front
escape('tmp/local/file?', '/?')          " 'tmp\/local\/file\?'


"" expand({expr})
"
" Expand special keywords
" Special characters can be used
" See :help cmdline-special
expand("%")           " current file name
expand("%:p")         " full path
expand("<cword>")     " word under cursor


"" empty({expr})
"
" Returns 1 if empty. 0 otherwise
empty('')             " 1
empty('a')            " 0
empty(1)              " 0
empty([])             " 1
empty([1])            " 0
empty({})             " 1
empty({"a": 1})       " 0
if empty(g:myvar)         "
endif


"" resolve({expr})
"
" Simplifies the path
echo resolve("./.")          " '.'
echo resolve("tmp/../tmp")     " tmp


"" exists({expr})
"
```

```
" Check if a given value exists. The value can be various things.
" Returns 1 if it exists.
exists('&syntax')          " syntax option exists
exists('+syntax')          " syntax option works

exists('*empty')           " function 'empty()' exists

exists(':ech')             " 1. Command starting with 'ech' exists
exists(':echo')            " 2. Command fully matching with 'echo' exists

exists('$PATH')            " Environment variable exists

exists('g:syntastic_debug')     " variable exists


""" Interaction
"" input(PROMPT[, DEFAULT][, COMPLETION])
" Prompt for user input, asking the question PROMPT.
" The answer typed by the user is returned.
" If DEFAULT is provided, then the prompt is initially filled with DEFAULT
let answer = input("Quit? y/n")
let answer = input("Quit? y/n\n")       " Use \n to prompt in new line.

let answer = input("Quit? y/n", "n")    " 'n' is typed in by default.


"" system(CMD[, INPUT)
" Run a shell command CMD
" If INPUT is provided, used as stdin input
system('echo hello')
system('cat', 'hello')          Same as cat < <(echo hello)
```