Basic usage

Help

```
:help set               Set command
:help setlocal
:help setglobal
:help option-list       List of all options
```

Commands

```
"" Show option values
:set                    Show option values differing from default
:set all                All options, including unset/default



"" View and edit options in a window
:options                All options and current values


"" Value options
:set tabstop?           Get
:set tabstop            Same as ?
:set tabstop=4             Set
:set commentstring=--%s    ERROR. Need to be escaped
:set commentstring=\-\-%s OK
:set tabstop&           Reset to default

"" List options
:set tags=./tags,./ctags         Set list (comma separate)
:set tags+=tags                  Append to list
:set tags-=tags                  Remove from list


"" Toggle options
:set number             Enable
:set nonumber           Disable
:set number!            Invert value
:set number?            "number" if enabled, "nonumber" otherwise




" Assign option value to variable
;let x = &tabstop
:let y = &expandtab        " Switch options. 0=not set, 1=not set

" Set option value on variable
:let x=4
:let &tabstop = x     " Value option. Equivalent to :set tabstop=4
:set tabstop=x        " ERROR

:let x=1
:let &number=x        " Toggle option. Equivalent to :set number
:let x=0
```

```
:let &number=x        " Equivalent to :set nonumber
```

Local/global

Local option

Options enabled only in current buffer.
Not all options support local.
See supported options with
    :setlocal all

```
"" set
:set                  Show local options if set. Global otherwise,
:setlocal             Local options only.
:setl                 Same
:setlocal all         See options that support a local value.
:setglobal            Global options only
:setg

" Get value
:set tabstop          Local if set,
:setl tabstop         Local value.
:setg tabstop         Global value

" Set value
:set tabstop=3        Set both local and global
:setl tabstop=3       Set local only
:setg tabstop=3       Set global only
```

==========

Basic options

Help

```
:help option-list          " List of all options

:help '<option name>'      " Help of <option>
:help 'ignorecase'
```

Visual appearance related options

```
"" number [default off]: show line numbers
:set number
:set nonumber


"" ruler [default off]: show current line and colum number in
statusline.
:set ruler


"" showmode [default off]: show current mode in statusline(e.g.  --
INSERT --)
:set showmode


"" ignorecase [default off]: Ignore case in search
```

```
:set ignorecase     " ignore case in search
:set ic


"" hlsearch [default off]: Highlight search results
:set hlsearch        " highlight search results
:set hls


"" incsearch [default off]: Perform search as it is typed
:set incsearch
:set is


"" wrap [default on]: softwrap text to fit screen
" See 'textwidth' for hardwrap.
:set wrap
:set norwrap


"" list [default off]: show hidden characters
:set list
:set nolist



"" listchars: set how hidden characters are displayed
:set listchar=tab:>\ ,nbsp:^
:set listchars=eol:$          " end of line. If not set, shows
blank.
:set listchars=space:.        " space. If not set, shows blank.
:set listchars=nbsp:^         " non-breakable space characters
:set listchars=trail:.        " trailing space.
" When 'wrap' is off
:set listchars=precedes:&
:set listchars=extends:&
" tab uses two characters: first tab, and rest
:set listchars=tab:>-         " e.g. > for one tab. >- for two tabs
```

Status line

```
# See :help statusline
t       file name
f       Relative file path
F       Absolute file path
m       [+] or [-]
r       [RO]
y       e.g. [vim]  file type

l       line number
L       number of lines in buffer
p
=       right align
... etc
```

```
"" status line
"
"
"
:help statusline
:set statusline='%F%=%y'      " %F  full path
                              " %=  right align
                              " %y  file type
```



Buffer related

```
"" bufhidden: what to do with buffer when not open in any window.
:set bufhidden            " Use "hidden" option.
:set bufhidden=hide       " hide but not delete it i.e. can be
reopenen
:set bufhidden=unload     " Like :hide
:set bufhidden=delete     " Like :bdelete
:set bufhidden=wipe       " Like :bwipeout

"" buflisted:
:set buflisted          " Buffer listed in :buffers
:set nobuflisted        " Not listed

"" buftype
:help 'buftype'         " See all types
:set buftype=           " Default. Normal buffer.
:set buftype=nofile     " Buffer not corresponding to a file
:set buftype=nowrite    " Read only
:set buftype=acwrite
:set buftype=quickfix
:set buftype=help
```

Content related options

```
"" tabstop [default 8]: Number of spaces inserted on <Tab> key
:set tabstop=4      " For tabs with the tab key

"" shiftwidth [default 8]:
" Used by
" - autoindent
" - shifting by >> and <<
:set shiftwidth=4
:set shiftwidth=0    " Use same value as tabstop

"" expandtab [default off]: If on, replace tab with spaces
:set expandtab       " use spaces
```

```
:set noexpandtab     " use tab

"" textwidth [default 0]: hardwrap text.
" See 'wrap' for softwrap.
:set textwidth=80
:set textwidth=0      " No hardwrap

"" fileencoding [default ""]: encoding used when writing to a file
"
" Set automatically by 'fileencodings' option.
:set fileencoding=""              " same value as 'encoding'
options
:set fileencoding=utf8            encoding to use when writing

"" fileencodings: encodings tried when reading a file
"
" The encodings are tried in the given order.
" If an encoding is found, it also sets it on 'fileencoding'.
:set fileencodings=utf8,latin1

"" encoding [default latin1 or $LANG]: actual encoding used by
editor
"
" The encoding applies to: text in buffer, registers, etc.
:set encoding=utf-8
:help encoding-names         " list of encoding names.

"" fileformat
" How to interpret new line.
"  unix    <NL>      = \n
"  dos     <CR><NL>  = \r\n
"  mac     <CR>      = \r  (old mac)
:set fileformat=unix
:set fileformat=dos
:set fileformat=mac
```

***) Usage: change file encoding used on read**

e.g. read Shift JS

```
-- Lookup encoding names
:help encoding-names

-- Set file encoding
:set fileencodings=sjis,euc-jp,utf-8

-- Reload
:edit
```


"0","C","8","20","23","6","月遅れ請求分","13","ﾂｷｵｸﾚｾｲｷｭｳﾌﾞﾝ","0","0","0","0
"0","C","8","20","33","6","未来院請求後","12","ﾐﾗｲｲﾝｾｲｷｭｳｺﾞ","0","0","0","0"
"0","C","8","20","35","9","他保険にて請求済み","14","ﾀﾎｹﾝﾆﾃｾｲｷｭｳｽﾞﾐ","0","0"
"0","C","8","20","36","10","他保険者にて請求済み","16","ﾀﾎｹﾝｼｬﾆﾃｾｲｷｭｳｽﾞﾐ","0
"0","C","8","20","37","13","自己注射に用いる注射薬投与","20","ｼﾞｺﾁｭｳｼｬﾆﾓﾁｲﾙﾁ
"0","C","8","20","38","20","自己連続携行式腹膜灌流に用いる注射薬投与","20",
"0","C","8","20","39","18","在宅中心静脈栄養法に用いる注射薬投与","20","ｻﾞｲﾀ
"0","C","8","20","42","4","新規指定","6","ｼﾝｷｼﾃｲ","0","0","0","0","0","0","0
"0","C","8","20","46","3","（サ）","1","ｻ","0","0","0","0","0","0","0","0","
"0","C","8","20","47","3","（減）","3","ｹﾞﾝ","0","0","0","0","0","0","0","0"
"0","C","8","20","50","3","（介）","2","ｶｲ","0","0","0","0","0","0","0","0",
"0","C","8","20","53","4","（検選）","4","ｹﾝｾﾝ","0","0","0","0","0","0","0",
"0","C","8","20","54","5","（リハ選）","4","ﾘﾊｾﾝ","0","0","0","0","0","0","0
"0","C","8","20","55","4","（精選）","4","ｾｲｾﾝ","0","0","0","0","0","0","0",
"0","C","8","20","56","4","画診共同","10","ｶﾞｼﾝｷｮｳﾄﾞｳ","0","0","0","0","0","
"0","C","8","20","94","4","（薬評）","5","ﾔｸﾋｮｳ","0","0","0","0","0","0","0"
NORMAL
sjis | dos | csv
~/Downloads/c_20260807.csv