Hakyll
Hackage: https://hackage.haskell.org/package/hakyll
Home: https://jaspervdj.be/hakyll

Hakyll
A **static site** generator.
A **rule** defines how to process a given source **file** that is served.
Each rule consists of:
- **route**: the route to serve the file
  e.g. ./about.md --> https:<base>/info/about.html

- **compile**: how to process the source file when serving, if any
  e.g. compile Markdown to HTML

e.g.

```
main = hakyll $ do
  match "*.html" $ do
                      -- e.g. HTML files served as is
    route idRoute
    compile copyFileCompiler

  match "*.md" $ do
                      -- e.g. Markdown files converted to
HTML
    route $ setExtension "html"
                      --    ./about.md -> https:<base>/
about.html
    compile $

      pandocCompiler
        >>= loadAndApplyTemplate "templates/
default.html" defaultContext
        >>= relativizeUrls
```

Glob
Pattern: https://hackage.haskell.org/package/hakyll/docs/Hakyll-Core-Identifier-Pattern.html

```
main :: IO ()
main = hakyll $ do
  match "css/*" $ do
    route idRoute
    compile compressCssCompiler
```

```
style.css                     # plain value
css/style.css
*.css                         # wildcard
**                            # any
                              #   file.txt
    match
                              #   data/file.txt
```

```
    match
**/*.css                        # any with at least one
parent
                                #   css/style.css
    match
                                #    css/page1/style.css
    match
                                #   style.css
    not match
```

Template
Hakyll.Web.Template: https://hackage.haskell.org/package/hakyll/docs/Hakyll-Web-Template.html
Hakyll.Web.Template.Context: https://hackage.haskell.org/package/hakyll/docs/Hakyll-Web-Template-Context.html

Template
Creates a document by inserting **fields** provided by the **context** object.

e.g.
site.hs

```
main = hakyll $ do
  match "*index.md" $ do
    route $ setExtension "html"
    compile $
      pandocCompiler
        >>= loadAndApplyTemplate "templates/
default.html" defaultContext               -- context
title=index
        >>= relativizeUrls
                                --          body=content of
index.html
```

templates/default.html

```
<!doctype html>
<html lang="en">
    <head>
        <title>$title$</title>
    </head>
    <body>
        <main role="main">
            $body$
        </main>
    </body>
</html>
```

```
 ============================================================
                              ======
```

```
This
is
code
Monaco 14
```