Get path of current sourced script/script directory
Ref: https://stackoverflow.com/questions/16485748/how-to-get-the-parent-directory-of-a-path-string
Use expand("<sfile>") to get

```
" Help
:help cmdline-special

" <sfile>=path of script
" :p=full path
" resolve() to resolve relative path i.e. get absolute
path
let s:scriptpath=resolve(expand("<sfile>:p"))
" :h=head i.e. directory
let s:scriptdir=fnamemodify(s:scriptpath, ":h")
```

Check if a file/directory exists

```
if !empty(glob('~/myfile'))
     echo 'myfile exists'
endif
```

Edit text e.g. insert, delete
Ref: https://vi.stackexchange.com/questions/21825/how-to-insert-text-from-a-variable-at-current-cursor-position
Use :normal to perform normal commands
Use :exec 'normal ..' if using expressions

```
"" Basic
normal i hello            " insert hello
let x=1
exec 'normal i' . x       " Same, but with variable


" Delete
:normal x                  " delete character
:normal ^dw                " delete first word of line
```

Paste multiple lines of text
Ref: https://stackoverflow.com/questions/2514445/turning-off-auto-indent-when-pasting-text-into-
Use **paste** mode if pasting multiple lines

```
"" Insert text
" multiline
let text =<<EOF
hello
world
EOF


" Multiline with normal
"
" Should use paste mode to disable some edit features
"  e.g. disable autoindent
```

```
" Ref: https://stackoverflow.com/questions/2514445/
turning-off-auto-indent-when-pasting-text-into-vim
set paste
  " start paste mode:
exec 'normal i' . join(text, "\<CR>")

exec 'normal i' . join(text, "\<ESC>:normal
o\<ESC>i")     " Same. MUST be double quote "\<ESC>" NOT
'\<ESC>'
set formatoptions+=o
for line in
text                                              " With
loop
exec 'normal i' . line . "\<CR>"
endfor
set nopaste
```

```
-- e.g. paste mode
-- original text
# Comment
a
b
c

-- exec 'normal i' . join(text, "\<CR>")
# Comment
    -- BAD. Autoindents
  # a
    # b
      # c

-- exec 'normal i' . join(text, "\<ESC>:normal
o\<ESC>i")
# Comment
    -- BAD. Preserves comment symbol
a#
b#
c#

-- set paste
-- exec 'normal i' . join(text, "\<ESC>:normal
o\<ESC>i")     -- GOOD. Edit features disabled for
pasting.
# Comment
a
b
c
```

```
" with append(), if line number is known
append(0, text)                    " insert at top
for i in range(0,len(text)-1)      " same with loop
 aappend(i,text[i])
endfor
```