React.JS

Ynon Perek
ynon@ynonperek.com



Offer a ***consistent*** and ***simple*** way to write web applications

Web Application Challenges

- ☐ Code architecture
- ☐ Split UI to components
- ☐ Navigation
- ☐ Application State

Client Side Frameworks



Why React

- [ ] Easy to learn
- [ ] Carries heavy weight

Who Uses React

React IS NOT

- [ ] An MVC framework
  (it won't tell you how to manage your data)

- [ ] A SPA framework
  (it won't handle client-side routing)

Let's See Some Code (our first React component)

```
1  var HelloWorld = React.createClass({
2    render: function() {
3      return (
4        <div>
5          <h1>Hello React </h1>
6          <p>Markup + Code = Awesome</p>
7        </div>
8      )
9    }
10 });
11
```

React How

- [ ] Use Babel to convert JSX code to JS
- [ ] Use React.render(…) to paint a component on screen

React How

- [ ] Client side React+TDD starter: https://github.com/ynonp/react-tdd-demo

- [ ] Alternatively, fork this pen: http://codepen.io/ynonp/pen/VLyzpW?editors=101

JSX vs. JS

```
var App = React.createClass({
  render: function() {
    return <div>
      Hello React!
      </div>
  }
});

React.render(<App />, document.querySelector('main'));
```

JSX vs. JS

```
'use strict';

var App = React.createClass({
  displayName: 'App',

  render: function render() {
    return React.createElement(
      'div',
      null,
      'Hello React!'
    );
  }
});

React.render(React.createElement(App, null),
document.querySelector('main'));
```

Customising Components

- [ ] Components take properties when created
- [ ] That’s how outer components affect inner

Customising Components

```
var App = React.createClass({
  render: function() {
    return <div>
        {this.props.message}
      </div>
  }
});

React.render(<App message="Hello World" />,
             document.querySelector('main'));
```

Customising Components

- [ ] Can pass any JS object as value for a property
- [ ] Remember JSX -> JS

Customising Components

```
var App = React.createClass({
  render: function() {
    return <div>
        I got {this.props.data.length} numbers
      </div>
  }
});


var numbers = [10, 20, 30, 40];

React.render(<App data={numbers} />,
             document.querySelector('main'));
```

Using Properties

- Changing properties after rendering won’t repaint your components
- So best to keep your properties immutable

Dynamic Components

- A dynamic component has a “state”
- That state changes during the component’s life cycle
- Can have initial state

Demo: Let's Write a Click Counter

- [ ] Internal State: How many clicks performed so far
- [ ] External Input: None

Demo: Clicks Counter

```
1  var Counter = React.createClass({
2    getInitialState: function() {
3      return { clicks: 0 };
4    },
5    clicked: function() {
6      this.setState({clicks: this.state.clicks + 1});
7    },
8    render: function() {
9      return (
10       <div>
11         <button onClick={this.clicked}>Click Me</button>
12         <p>You clicked {this.state.clicks} times</p>
13       </div>
14     )
15   }
16 });
17
```

The Good

- [ ] No need to manipulate DOM nodes
- [ ] Combine components to build larger apps

React Debugging

- [ ] Webpack creates source maps:
  - [ ] Can debug inside chrome devtools
  - [ ] Debug with “original” source
  - [ ] Demo

React Debugging

- [ ] React Chrome App



React: Behind The Scene

Virtual DOM



React: Behind The Scene

Virtual DOM

- form
  - label
  - input
  - label
  - input

Virtual DOM

- form
  - label
  - input

React: Behind The Scene

- [ ] Calculate how to get from virtual DOM tree A to virtual DOM tree B
- [ ] In our example:
  - [ ] Delete last input and label

Component Based UI



Q & A

Handling External Inputs

- [ ] Define properties you component should use
- [ ] Example: Let's build a filterable list
  - [ ] State: current filter text
  - [ ] Properties: array of items to display and filter
- [ ] Solution: http://codepen.io/ynonp/pen/pJbRjV

React + TDD

Agenda

- ☐ TDD short intro
- ☐ The tools
- ☐ React It: translating old JS to React using TDD
- ☐ Conclusions & Takeaways

Hello TDD

- [ ] TDD helps you write easy to test code
- [ ] Write tests first

TDD + React

- [ ] React helps us avoid code pitfalls
- [ ] TDD makes sure we get it right

TDD + React



TDD Workflow



TDD Workflow

- [ ] Run tests from within IDE, while coding
- [ ] Fix code and build more tests as you go along
- [ ] Eventually check look & feel in the browser

TDD Tools

- [ ] Webstorm
- [ ] Webpack
- [ ] Karma
- [ ] Mocha / Sinon / Chai
- [ ] React.addons.TestUtils

Demo: Vanilla -> TDD React

- [ ] Given the square game here: http://codepen.io/ynonp/pen/YXrPNj?editors=101
- [ ] Let's write a React version using TDD

Start with a test

```
describe('Game cells', function() {
  it('renders .square child nodes', function() {
    var game = TestUtils.renderIntoDocument(<Game cells={9} />);

    var squares = TestUtils.scryRenderedDOMComponentsWithClass(game, "square");
    expect(squares.length).to.eq(9);
  });
});
```

Write Some Code

```
render: function () {
  return (
    <div>
    { _.map(_.range(this.props.cells), this.renderItem)}
    </div>
  )
}
```

React.addons.TestUtils

- [ ] renderIntoDocument
- [ ] scry / find functions to find React components and DOM nodes
- [ ] Simulate functions to simulate DOM events

Simulate and stubs

- [ ] Let’s randomise the winner
- [ ] Let’s change the winning square after each click

Problem With Random

Stubbing with sinon

```
it('is selected randomly using _.sample', function() {
  sinon.stub(_, "sample").returns(42);

  var game = TestUtils.renderIntoDocument(<Game cells={3} />);
  expect(game.state.winner).to.eq(42);

  _.sample.restore();
});
```

Other useful stubs

- [ ] Stubbing clocks with sinon.fakeTimers
- [ ] Stubbing ajax with sinon.fakeServer

Other useful stubs

- [ ] Sub components (rewire)
- [ ] Demo: Game Timer

Q & A

Why TDD

- [ ] Coding was fun
- [ ] The tests are useful going forward
- [ ] Better code

React + Flux Architecture

React Architecture

- [ ] No architectural constraints
  - [ ] Some write their own
  - [ ] Some use MVC (backbone, angular, ember)
  - [ ] Some use flux

Flux Architecture



Flux

- [ ] Unidirectional application architecture
- [ ] Has many implementations: Flux, Reflux, Lux, fluxthis and more
- [ ] https://github.com/voronianski/flux-comparison

Flux Components

- [ ] Stores: Save data
- [ ] Dispatcher: handles actions
- [ ] Actions: manage flow
- [ ] React Components

Flux Demo

- [ ] Random message generator:
  - [ ] Users store
  - [ ] Messages store
  - [ ] New messages => create new users
- [ ] Allow pause/resume using a ListeningStore

Q & A

Thanks For Listening

- Ynon Perek
- ynon@ynonperek.com
- www.tocode.co.il