

Some Standard Classes

CHAPTER

4

Anyone who considers arithmetical methods of producing random digits is, of course, in a state of sin.
—John von Neumann (1951)


Chapter Goals

- The Object class
- The String class
- Wrapper classes
- The Math class
- Random numbers

THE Object CLASS

The Universal Superclass

Think of Object as the superclass of the universe. Every class automatically extends Object, which means that Object is a direct or indirect superclass of every other class. In a class hierarchy tree, Object is at the top:



Methods in Object

There are many methods in Object, all of them inherited by every other class. Since Object is not an abstract class, all of its methods have implementations. The expectation is that these methods will be overridden in any class where the default implementation is not suitable. The methods of Object in the AP Java subset are toString and equals.

THE toString METHOD

```
public String toString()
```

This method returns a version of your object in String form.

When you attempt to print an object, the inherited default toString method is invoked, and what you will see is the class name followed by an @ followed by a meaningless number (the address in memory of the object). For example,

```
SavingsAccount s = new SavingsAccount(500);
System.out.println(s);
```

produces something like

```
SavingsAccount@fea485c4
```

To have more meaningful output, you need to override the toString method for your own classes. Even if your final program doesn't need to output any objects, you should define a toString method for each class to help in debugging.

Example 1

```
public class OrderedPair
{
    private double x;
    private double y;

    //constructors and other methods ...

    /** @return this OrderedPair in String form */
    public String toString()
    {
        return "(" + x + "," + y + ")";
    }
}
```

Now the statements

```
OrderedPair p = new OrderedPair(7,10);
System.out.println(p);
```

will invoke the overridden toString method and produce output that looks like an ordered pair:

```
(7,10)
```

Example 2

For a BankAccount class the overridden toString method may look something like this:

```
/** @return this BankAccount in String form */
public String toString()
{
    return "Bank Account: balance = $" + balance;
}
```

The statements

```
BankAccount b = new BankAccount(600);
System.out.println(b);
```

will produce output that looks like this:

```
Bank Account: balance = $600
```

NOTE

1. The + sign is a concatenation operator for strings (see p. 178).
2. Array objects are unusual in that they do not have a toString method. To print the elements of an array, the array must be traversed and each element must explicitly be printed.

THE equals METHOD

```
public boolean equals(Object other)
```

All classes inherit this method from the Object class. It returns true if this object and other are the same object, false otherwise. Being the same object means referencing the same memory slot. For example,

```
Date d1 = new Date("January", 14, 2001);
Date d2 = d1;
Date d3 = new Date("January", 14, 2001);
```

Do not use == to test objects for equality. Use the equals method.

The test if (d1.equals(d2)) returns true, but the test if (d1==d3) returns false, since d1 and d3 do not refer to the same object. Often, as in this example, you may want two objects to be considered equal if their *contents* are the same. In that case, you have to override the equals method in your class to achieve this. Some of the standard classes described later in this chapter have overridden equals in this way. You will not be required to write code that overrides equals on the AP exam.

NOTE

1. The default implementation of equals is equivalent to the == relation for objects: In the Date example above, the test if (d1 == d2) returns true; the test if (d1 == d3) returns false.
2. The operators <, >, and so on, are not overloaded in Java. To compare objects, one must use either the equals method or define a compareTo method for the class.

Optional topic

THE hashCode METHOD

Every class inherits the hashCode method from Object. The value returned by hashCode is an integer produced by some formula that maps your object to an address in a hash table. A given object must always produce the same hash code. Also, two objects that are equal should produce the same hash code; that is, if obj1.equals(obj2) is true, then obj1 and obj2 should have the same hash code. Note that the opposite is not necessarily true. Hash codes do not have to be unique—two objects with the same hash code are not necessarily equal.

To maintain the condition that obj1.equals(obj2) is true implies that obj1 and obj2 have the same hash code, overriding equals means that you should override hashCode at the same time. You will not be required to do this on the AP exam.

(continued)

You should, however, understand that every object is associated with an integer value called its hash code, and that objects that are equal have the same hash code.

THE String CLASS

String Objects

An object of type `String` is a sequence of characters. All *string literals*, such as `"yikes!"`, are implemented as instances of this class. A string literal consists of zero or more characters, including escape sequences, surrounded by double quotes. (The quotes are not part of the `String` object.) Thus, each of the following is a valid string literal:

```
"                //empty string
"2468"
"I must\n go home"
```

`String` objects are *immutable*, which means that there are no methods to change them after they've been constructed. You can, however, always create a new `String` that is a mutated form of an existing `String`.

Constructing String Objects

A `String` object is unusual in that it can be initialized like a primitive type:

```
String s = "abc";
```

This is equivalent to

```
String s = new String("abc");
```

in the sense that in both cases `s` is a reference to a `String` object with contents `"abc"` (see Box on p. 179).

It is possible to reassign a `String` reference:

```
String s = "John";
s = "Harry";
```

This is equivalent to

```
String s = new String("John");
s = new String("Harry");
```

Notice that this is consistent with the immutable feature of `String` objects. `"John"` has not been changed; he has merely been discarded! The fickle reference `s` now refers to a new `String`, `"Harry"`. It is also OK to reassign `s` as follows:

```
s = s + " Windsor";
```

`s` now refers to the object `"Harry Windsor"`.

Here are other ways to initialize `String` objects:

```
String s1 = null;           //s1 is a null reference
String s2 = new String();   //s2 is an empty character sequence
```

```
String state = "Alaska";
String dessert = "baked " + state; //dessert has value "baked Alaska"
```

The Concatenation Operator

The `dessert` declaration above uses the *concatenation operator*, `+`, which operates on `String` objects. Given two `String` operands `lhs` and `rhs`, `lhs + rhs` produces a single `String` consisting of `lhs` followed by `rhs`. If either `lhs` or `rhs` is an object other than a `String`, the `toString` method of the object is invoked, and `lhs` and `rhs` are concatenated as before. If one of the operands is a `String` and the other is a primitive type, then the non-`String` operand is converted to a `String`, and concatenation occurs as before. If neither `lhs` nor `rhs` is a `String` object, an error occurs. Here are some examples:

```
int five = 5;
String state = "Hawaii-";
String tvShow = state + five + "-0"; //tvShow has value
                                     //"Hawaii-5-0"

int x = 3, y = 4;
String sum = x + y;                  //error: can't assign int 7 to String
```

Suppose a `Date` class has a `toString` method that outputs dates that look like this: 2/17/1948.

```
Date d1 = new Date(8, 2, 1947);
Date d2 = new Date(2, 17, 1948);
String s = "My birthday is " + d2; //s has value
                                     //"My birthday is 2/17/1948"

String s2 = d1 + d2;                //error: + not defined for objects
String s3 = d1.toString() + d2.toString(); //s3 has value
                                     //8/2/19472/17/1948
```

Comparison of String Objects

There are two ways to compare `String` objects:

1. Use the `equals` method that is inherited from the `Object` class and overridden to do the correct thing:

```
if (string1.equals(string2)) ...
```

This returns true if `string1` and `string2` are identical strings, false otherwise.

2. Use the `compareTo` method. The `String` class has a `compareTo` method:

```
int compareTo(String otherString)
```

It compares strings in dictionary (lexicographical) order:

- If `string1.compareTo(string2) < 0`, then `string1` precedes `string2` in the dictionary.
- If `string1.compareTo(string2) > 0`, then `string1` follows `string2` in the dictionary.
- If `string1.compareTo(string2) == 0`, then `string1` and `string2` are identical. (This test is an alternative to `string1.equals(string2)`.)

Be aware that Java is case-sensitive. Thus, if `s1` is "cat" and `s2` is "Cat", `s1.equals(s2)` will return false.

Characters are compared according to their position in the ASCII chart. All you need to know is that all digits precede all capital letters, which precede all lowercase letters. Thus "5" comes before "R", which comes before "a". Two strings are compared as follows: Start at the left end of each string and do a character-by-character comparison until you reach the first character in which the strings differ, the *k*th character, say. If the *k*th character of *s1* comes before the *k*th character of *s2*, then *s1* will come before *s2*, and vice versa. If the strings have identical characters, except that *s1* terminates before *s2*, then *s1* comes before *s2*. Here are some examples:

```
String s1 = "HDT", s2 = "HOTEL", s3 = "dog";
if (s1.compareTo(s2) < 0)    //true, s1 terminates first
...
if (s1.compareTo(s3) > 0)    //false, "H" comes before "d"
```

Don't Use == to Test Strings!

The expression `if(string1 == string2)` tests whether `string1` and `string2` are the same reference. It does not test the actual strings. Using `==` to compare strings may lead to unexpected results.

Example 1

```
String s = "oh no!";
String t = "oh no!";
if (s == t) ...
```

The test returns `true` even though it appears that `s` and `t` are different references. The reason is that for efficiency Java makes only one `String` object for equivalent string literals. This is safe in that a `String` cannot be altered.

Example 2

```
String s = "oh no!";
String t = new String("oh no!");
if (s == t) ...
```

The test returns `false` because use of `new` creates a new object, and `s` and `t` are different references in this example!

The moral of the story? Use `equals` not `==` to test strings. It always does the right thing.

Other String Methods

The Java `String` class provides many methods, only a small number of which are in the AP Java subset. In addition to the constructors, comparison methods, and concatenation operator + discussed so far, you should know the following methods:

int length()

Returns the length of this string.

String substring(int startIndex)

Returns a new string that is a substring of this string. The substring starts with the character at `startIndex` and extends to the end of the string. The first character is at index zero. The method throws an `IndexOutOfBoundsException` if `startIndex` is negative or larger than the length of the string. Note that if you're using Java 7 or above, you will see the error `StringIndexOutOfBoundsException`. However, the AP Java subset lists only `IndexOutOfBoundsException`, which is what they will use on the AP exam.

String substring(int startIndex, int endIndex)

Returns a new string that is a substring of this string. The substring starts at index `startIndex` and extends to the character at `endIndex-1`. (Think of it this way: `startIndex` is the first character that you want; `endIndex` is the first character that you *don't* want.) The method throws a `StringIndexOutOfBoundsException` if `startIndex` is negative, or `endIndex` is larger than the length of the string, or `startIndex` is larger than `endIndex`.

int indexOf(String str)

Returns the index of the first occurrence of `str` within this string. If `str` is not a substring of this string, -1 is returned. The method throws a `NullPointerException` if `str` is null.

Here are some examples:

```
"unhappy".substring(2)    //returns "happy"
"cold".substring(4)       //returns "" (empty string)
"cold".substring(5)       //StringIndexOutOfBoundsException
"strawberry".substring(5,7) //returns "be"
"crayfish".substring(4,8)  //returns "fish"
"crayfish".substring(4,9)  //StringIndexOutOfBoundsException
"crayfish".substring(5,4)  //StringIndexOutOfBoundsException
```

```
String s = "funnyfarm";
int x = s.indexOf("farm"); //x has value 5
x = s.indexOf("farmer");   //x has value -1
int y = s.length();       //y has value 9
```

WRAPPER CLASSES

A *wrapper class* takes either an existing object or a value of primitive type, “wraps” or “boxes” it in an object, and provides a new set of methods for that type. The point of a wrapper class is to provide extended capabilities for the boxed quantity:

- It can be used in generic Java methods that require objects as parameters.
- It can be used in Java container classes that require the items be objects (see p. 242).

In each case, the wrapper class allows

1. Construction of an object from a single value (wrapping or boxing the primitive in a wrapper object).
2. Retrieval of the primitive value (unwrapping or unboxing from the wrapper object).

Java provides a wrapper class for each of its primitive types. The two that you should know for the AP exam are the `Integer` and `Double` classes.

The Integer Class

The `Integer` class wraps a value of type `int` in an object. An object of type `Integer` contains just one instance variable whose type is `int`.

Here are the `Integer` methods you should know for the AP exam:

`Integer(int value)`

Constructs an `Integer` object from an `int`. (Boxing.)

`int compareTo(Integer other)`

Returns 0 if the value of this `Integer` is equal to the value of `other`, a negative integer if it is less than the value of `other`, and a positive integer if it is greater than the value of `other`.

`int intValue()`

Returns the value of this `Integer` as an `int`. (Unboxing.)

`boolean equals(Object obj)`

Returns true if and only if this `Integer` has the same `int` value as `obj`.

NOTE

1. This method overrides `equals` in class `Object`.
2. This method throws a `ClassCastException` if `obj` is not an `Integer`.

`String toString()`

Returns a `String` representing the value of this `Integer`.

Here are some examples to illustrate the `Integer` methods:

```
Integer intObj = new Integer(6); //boxes 6 in Integer object
int j = intObj.intValue();      //unboxes 6 from Integer object
```

```
System.out.println("Integer value is " + intObj);
//calls toString() for intObj
//output is
//Integer value is 6
```



```

Object object = new Integer(5); //Integer is a subclass of Object

Integer intObj2 = new Integer(3);
int k = intObj2.intValue();
if (intObj.equals(intObj2)) //OK, evaluates to false
...
if (intObj.intValue() == intObj2.intValue())
... //OK, since comparing primitive types

if (k.equals(j)) //error, k and j not objects
...
if ((intObj.intValue()).compareTo(intObj2.intValue()) < 0)
... //error, can't use compareTo on primitive types

if (intObj.compareTo(object) < 0) //Error. Parameter needs Integer cast
if (intObj.compareTo((Integer) object) < 0) //OK
...
if (object.compareTo(intObj) < 0) //error, no compareTo in Object
...
if (((Integer) object).compareTo(intObj) < 0) //OK
...

```

The Double Class

The Double class wraps a value of type double in an object. An object of type Double contains just one instance variable whose type is double.

The methods you should know for the AP exam are analogous to those for type Integer.

Double(double value)

Constructs a Double object from a double. (Boxing.)

double doubleValue()

Returns the value of this Double as a double. (Unboxing.)

int compareTo(Double other)

Returns 0 if the value of this Double is equal to the value of other, a negative integer if it is less than the value of other, and a positive integer if it is greater than the value of other.

boolean equals(Object obj)

This method overrides equals in class Object and throws a ClassCastException if obj is not a Double. Otherwise it returns true if and only if this Double has the same double value as obj.

String toString()

Returns a String representing the value of this Double.

Here are some examples:

```
Double dObj = new Double(2.5);    //boxes 2.5 in Double object
double d = dObj.doubleValue();    //unboxes 2.5 from Double object

Object object = new Double(7.3);  //Double is a subclass of Object
Object intObj = new Integer(4);
if (dObj.compareTo(object) > 0) //Error. Parameter needs cast to Double
if (dObj.compareTo((Double) object) > 0)    //OK

...
if (dObj.compareTo(intObj) > 0)    //ClassCastException
...                                //can't compare Integer to Double
```

Remember:
Integer, Double,
and String all have a
compareTo method.

NOTE

1. Integer and Double objects are immutable: There are no mutator methods in the classes.
2. See p. 242 for a discussion of auto-boxing and -unboxing. This useful feature will *not* be tested on the AP exam.

THE Math CLASS

This class implements standard mathematical functions such as absolute value, square root, trigonometric functions, the log function, the power function, and so on. It also contains mathematical constants such as π and e .

Here are the functions you should know for the AP exam:

```
static int abs(int x)
```

Returns the absolute value of integer x .

```
static double abs(double x)
```

Returns the absolute value of real number x .

```
static double pow(double base, double exp)
```

Returns base^{exp} . Assumes $\text{base} > 0$, or $\text{base} = 0$ and $\text{exp} > 0$, or $\text{base} < 0$ and exp is an integer.

```
static double sqrt(double x)
```

Returns \sqrt{x} , $x \geq 0$.

```
static double random()
```

Returns a random number r , where $0.0 \leq r < 1.0$. (See the next section, Random Numbers.)

All of the functions and constants are implemented as static methods and variables, which means that there are no instances of Math objects. The methods are invoked using the class name, Math, followed by the dot operator.

Here are some examples of mathematical formulas and the equivalent Java statements.

1. The relationship between the radius and area of a circle:

$$r = \sqrt{A/\pi}$$

In code:

```
radius = Math.sqrt(area / Math.PI);
```

2. The amount of money A in an account after ten years, given an original deposit of P and an interest rate of 5% compounded annually, is

$$A = P(1.05)^{10}$$

In code:

```
a = p * Math.pow(1.05, 10);
```

3. The distance D between two points $P(x_P, y)$ and $Q(x_Q, y)$ on the same horizontal line is

$$D = |x_P - x_Q|$$

In code:

```
d = Math.abs(xp - xq);
```

NOTE

The static import construct allows you to use the static members of a class without the class name prefix. For example, the statement

```
import static java.lang.Math.*;
```

allows use of all Math methods and constants without the Math prefix. Thus, the statement in formula 1 above could be written

```
radius = sqrt(area / PI);
```

Static imports are not part of the AP subset.

Random Numbers

RANDOM REALS

The statement

```
double r = Math.random();
```

produces a random real number in the range 0.0 to 1.0, where 0.0 is included and 1.0 is not.

This range can be scaled and shifted. On the AP exam you will be expected to write algebraic expressions involving `Math.random()` that represent linear transformations of the original interval $0.0 \leq x < 1.0$.

Example 1

Produce a random real value x in the range $0.0 \leq x < 6.0$.

```
double x = 6 * Math.random();
```

Example 2

Produce a random real value x in the range $2.0 \leq x < 3.0$.

```
double x = Math.random() + 2;
```

Example 3

Produce a random real value x in the range $4.0 \leq x < 6.0$.

```
double x = 2 * Math.random() + 4;
```

In general, to produce a random real value in the range $\text{lowValue} \leq x < \text{highValue}$:

```
double x = (highValue - lowValue) * Math.random() + lowValue;
```

RANDOM INTEGERS

Using a cast to `int`, a scaling factor, and a shifting value, `Math.random()` can be used to produce random integers in any range.

Example 1

Produce a random integer, from 0 to 99.

```
int num = (int) (Math.random() * 100);
```

In general, the expression

```
(int) (Math.random() * k)
```

produces a random `int` in the range $0, 1, \dots, k - 1$, where k is called the scaling factor. Note that the cast to `int` truncates the real number `Math.random() * k`.

Example 2

Produce a random integer, from 1 to 100.

```
int num = (int) (Math.random() * 100) + 1;
```

In general, if k is a scaling factor, and p is a shifting value, the statement

```
int n = (int) (Math.random() * k) + p;
```

produces a random integer n in the range $p, p + 1, \dots, p + (k - 1)$.

Example 3

Produce a random integer from 5 to 24.

```
int num = (int) (Math.random() * 20) + 5;
```

Note that there are 20 possible integers from 5 to 24, inclusive.

NOTE

There is further discussion of strings and random numbers, plus additional questions, in Chapter 9 (The AP Computer Science Labs).

Chapter Summary

All students should know about overriding the `equals` and `toString` methods of the `Object` class and should be familiar with the `Integer` and `Double` wrapper classes.

Know the AP subset methods of the `Math` class, especially the use of `Math.random()` for generating random integers. Know the `String` methods `substring` and `indexOf` like the back of your hand, including knowing where exceptions are thrown in the `String` methods.

MULTIPLE-CHOICE QUESTIONS ON STANDARD CLASSES

1. Here is a program segment to find the quantity base^{exp} . Both base and exp are entered at the keyboard.

```
System.out.println("Enter base and exponent: ");
double base = IO.readDouble(); //read user input
double exp = IO.readDouble(); //read user input
/* code to find power, which equals baseexp */
System.out.print(base + " raised to the power " + exp);
System.out.println(" equals " + power);
```

Which is a correct replacement for

/ code to find power, which equals base^{exp} */*?

- I double power;
Math m = new Math();
power = m.pow(base, exp);
- II double power;
power = Math.pow(base, exp);
- III int power;
power = Math.pow(base, exp);

- (A) I only
- (B) II only
- (C) III only
- (D) I and II only
- (E) I and III only

2. Consider the `squareRoot` method defined below:

```

/** @param d a real number such that d >= 0
 *   Postcondition: Returns a Double whose value is the square
 *                   root of the value represented by d.
 */
public Double squareRoot(Double d)
{
    /* implementation code */
}

```

Which `/* implementation code */` satisfies the postcondition?

- I `double x = d.doubleValue();`
`x = Math.sqrt(x);`
`return new Double(x);`
- II `return new Double(Math.sqrt(d.doubleValue()));`
- III `return Double(Math.sqrt(d.doubleValue()));`

- (A) I only
- (B) I and II only
- (C) I and III only
- (D) II and III only
- (E) I, II, and III

3. Here are some examples of negative numbers rounded to the nearest integer.

Negative real number	Rounded to nearest integer
-3.5	-4
-8.97	-9
-5.0	-5
-2.487	-2
-0.2	0

Refer to the declaration

```
double d = -4.67;
```

Which of the following correctly rounds `d` to the nearest integer?

- (A) `int rounded = Math.abs(d);`
- (B) `int rounded = (int) (Math.random() * d);`
- (C) `int rounded = (int) (d - 0.5);`
- (D) `int rounded = (int) (d + 0.5);`
- (E) `int rounded = Math.abs((int) (d - 0.5));`

4. A program is to simulate plant life under harsh conditions. In the program, plants die randomly according to some probability. Here is part of a Plant class defined in the program.

```
public class Plant
{
    /** probability that plant dies, a real number between 0 and 1 */
    private double probDeath;

    public Plant(double plantProbDeath, <other parameters>)
    {
        probDeath = plantProbDeath;
        <initialization of other instance variables>
    }

    /** Plant lives or dies. */
    public void liveOrDie()
    {
        /* statement to generate random number */
        if (/* test to determine if plant dies */)
            <code to implement plant's death>
        else
            <code to make plant continue living>
    }

    //Other variables and methods are not shown.
}
```

Which of the following are correct replacements for

- (1) */* statement to generate random number */* and
 (2) */* test to determine if plant dies */*

- (A) (1) `double x = Math.random();`
 (2) `x == probDeath`
- (B) (1) `double x = (int) (Math.random());`
 (2) `x > probDeath`
- (C) (1) `double x = Math.random();`
 (2) `x < probDeath`
- (D) (1) `int x = (int) (Math.random() * 100);`
 (2) `x < (int) probDeath`
- (E) (1) `int x = (int) (Math.random() * 100) + 1;`
 (2) `x == (int) probDeath`
5. A program simulates fifty slips of paper, numbered 1 through 50, placed in a bowl for a raffle drawing. Which of the following statements stores in winner a random integer from 1 to 50?
- (A) `int winner = (int) (Math.random() * 50) + 1;`
 (B) `int winner = (int) (Math.random() * 50);`
 (C) `int winner = (int) (Math.random() * 51);`
 (D) `int winner = (int) (Math.random() * 51) + 1;`
 (E) `int winner = (int) (1 + Math.random() * 49);`

6. Consider the code segment

```
Integer i = new Integer(20);
/* more code */
```

Which of the following replacements for */* more code */* correctly sets *i* to have an integer value of 25?

- I `i = new Integer(25);`
- II `i.intValue() = 25;`
- III `Integer j = new Integer(25);`
`i = j;`

- (A) I only
- (B) II only
- (C) III only
- (D) I and III only
- (E) II and III only

7. Consider these declarations:

```
Integer intOb = new Integer(3);
Object ob = new Integer(4);
Double doubOb = new Double(3.0);
```

Which of the following will *not* cause an error?

- (A) `if ((Integer) ob.compareTo(intOb) < 0) ...`
- (B) `if (ob.compareTo(intOb) < 0) ...`
- (C) `if (intOb.compareTo(doubOb) < 0) ...`
- (D) `if (intOb.compareTo(ob) < 0) ...`
- (E) `if (intOb.compareTo((Integer) ob) < 0) ...`

8. Refer to these declarations:

```
Integer k = new Integer(8);
Integer m = new Integer(4);
```

Which test will *not* generate an error?

- I `if (k.intValue() == m.intValue())...`
- II `if ((k.intValue()).equals(m.intValue()))...`
- III `if ((k.toString()).equals(m.toString()))...`

- (A) I only
- (B) II only
- (C) III only
- (D) I and III only
- (E) I, II, and III

9. Consider the code fragment

```
Object intObj = new Integer(9);
System.out.println((String) intObj);
```

What will be output as a result of running the fragment?

- (A) No output. A `ClassCastException` will be thrown.
- (B) No output. An `ArithmeticException` will be thrown.
- (C) 9
- (D) "9"
- (E) nine

10. Consider these declarations:

```
String s1 = "crab";
String s2 = new String("crab");
String s3 = s1;
```

Which expression involving these strings evaluates to true?

- I `s1 == s2`
- II `s1.equals(s2)`
- III `s3.equals(s2)`

- (A) I only
- (B) II only
- (C) II and III only
- (D) I and II only
- (E) I, II, and III

11. Suppose that `strA = "TOMATO"`, `strB = "tomato"`, and `strC = "tom"`. Given that "A" comes before "a" in dictionary order, which is true?

- (A) `strA.compareTo(strB) < 0 && strB.compareTo(strC) < 0`
- (B) `strB.compareTo(strA) < 0 || strC.compareTo(strA) < 0`
- (C) `strC.compareTo(strA) < 0 && strA.compareTo(strB) < 0`
- (D) `!(strA.equals(strB)) && strC.compareTo(strB) < 0`
- (E) `!(strA.equals(strB)) && strC.compareTo(strA) < 0`

12. This question refers to the following declaration:

```
String line = "Some more silly stuff on strings!";
//the words are separated by a single space
```

What string will `str` refer to after execution of the following?

```
int x = line.indexOf("m");
String str = line.substring(10, 15) + line.substring(25, 25 + x);
```

- (A) "sillyst"
- (B) "sillystr"
- (C) "silly st"
- (D) "silly str"
- (E) "sillystrin"

13. A program has a `String` variable `fullName` that stores a first name, followed by a space, followed by a last name. There are no spaces in either the first or last names. Here are some examples of `fullName` values: "Anthony Coppola", "Jimmy Carroll", and "Tom DeWire". Consider this code segment that extracts the last name from a `fullName` variable, and stores it in `lastName` with no surrounding blanks:

```
int k = fullName.indexOf(" ");    //find index of blank
String lastName = /* expression */
```

Which is a correct replacement for `/* expression */`?

- I `fullName.substring(k);`
- II `fullName.substring(k + 1);`
- III `fullName.substring(k + 1, fullName.length());`

- (A) I only
- (B) II only
- (C) III only
- (D) II and III only
- (E) I and III only

14. One of the rules for converting English to Pig Latin states: If a word begins with a consonant, move the consonant to the end of the word and add "ay". Thus "dog" becomes "ogday," and "crisp" becomes "rispcay". Suppose `s` is a `String` containing an English word that begins with a consonant. Which of the following creates the correct corresponding word in Pig Latin? Assume the declarations

```
String ayString = "ay";
String pigString;
```

- (A) `pigString = s.substring(0, s.length()) + s.substring(0,1) + ayString;`
- (B) `pigString = s.substring(1, s.length()) + s.substring(0,0) + ayString;`
- (C) `pigString = s.substring(0, s.length()-1) + s.substring(0,1) + ayString;`
- (D) `pigString = s.substring(1, s.length()-1) + s.substring(0,0) + ayString;`
- (E) `pigString = s.substring(1, s.length()) + s.substring(0,1) + ayString;`

15. This question refers to the `getString` method shown below:

```
public static String getString(String s1, String s2)
{
    int index = s1.indexOf(s2);
    return s1.substring(index, index + s2.length());
}
```

Which is true about `getString`? It may return a string that

- I Is equal to `s2`.
- II Has no characters in common with `s2`.
- III Is equal to `s1`.

- (A) I and III only
- (B) II and III only
- (C) I and II only
- (D) I, II, and III
- (E) None is true.

16. Consider this method:

```
public static String doSomething(String s)
{
    final String BLANK = " "; //BLANK contains a single space
    String str = "";          //empty string
    String temp;
    for (int i = 0; i < s.length(); i++)
    {
        temp = s.substring(i, i + 1);
        if (!(temp.equals(BLANK)))
            str += temp;
    }
    return str;
}
```

Which of the following is the most precise description of what `doSomething` does?

- (A) It returns `s` unchanged.
- (B) It returns `s` with all its blanks removed.
- (C) It returns a `String` that is equivalent to `s` with all its blanks removed.
- (D) It returns a `String` that is an exact copy of `s`.
- (E) It returns a `String` that contains `s.length()` blanks.

Questions 17 and 18 refer to the classes Position and PositionTest below.

```

public class Position
{
    /** row and col are both >= 0 except in the default
     *  constructor where they are initialized to -1.
     */
    private int row, col;

    public Position()           //constructor
    {
        row = -1;
        col = -1;
    }

    public Position(int r, int c)    //constructor
    {
        row = r;
        col = c;
    }

    /** @return row of Position */
    public int getRow()
    { return row; }

    /** @return column of Position */
    public int getCol()
    { return col; }

    /** @return Position north of (up from) this position */
    public Position north()
    { return new Position(row - 1, col); }

    //Similar methods south, east, and west
    ...

    /** Compares this Position to another Position object.
     *  @param p a Position object
     *  @return -1 (less than), 0 (equals), or 1 (greater than)
     */
    public int compareTo(Position p)
    {
        if (this.getRow() < p.getRow() || this.getRow() == p.getRow()
            && this.getCol() < p.getCol())
            return -1;
        if (this.getRow() > p.getRow() || this.getRow() == p.getRow()
            && this.getCol() > p.getCol())
            return 1;
        return 0;           //row and col both equal
    }

    /** @return string form of Position */
    public String toString()
    { return "(" + row + "," + col + ")"; }
}

```

```
public class PositionTest
{
    public static void main(String[] args)
    {
        Position p1 = new Position(2, 3);
        Position p2 = new Position(4, 1);
        Position p3 = new Position(2, 3);

        //tests to compare positions
        ...
    }
}
```

17. Which is true about the value of `p1.compareTo(p2)`?

- (A) It equals true.
- (B) It equals false.
- (C) It equals 0.
- (D) It equals 1.
- (E) It equals -1.

18. Which boolean expression about `p1` and `p3` is true?

- I `p1 == p3`
- II `p1.equals(p3)`
- III `p1.compareTo(p3) == 0`

- (A) I only
- (B) II only
- (C) III only
- (D) II and III only
- (E) I, II, and III

Questions 19 and 20 deal with the problem of swapping two integer values. Three methods are proposed to solve the problem, using primitive int types, Integer objects, and IntPair objects, where IntPair is defined as follows:

```
public class IntPair
{
    private int firstValue;
    private int secondValue;

    public IntPair(int first, int second)
    {
        firstValue = first;
        secondValue = second;
    }

    public int getFirst()
    { return firstValue; }

    public int getSecond()
    { return secondValue; }

    public void setFirst(int a)
    { firstValue = a; }

    public void setSecond(int b)
    { secondValue = b; }
}
```

19. Here are three different swap methods, each intended for use in a client program.

```
I public static void swap(int a, int b)
{
    int temp = a;
    a = b;
    b = temp;
}
```

```
II public static void swap(Integer obj_a, Integer obj_b)
{
    Integer temp = new Integer(obj_a.intValue());
    obj_a = obj_b;
    obj_b = temp;
}
```

```
III public static void swap(IntPair pair)
{
    int temp = pair.getFirst();
    pair.setFirst(pair.getSecond());
    pair.setSecond(temp);
}
```

When correctly used in a client program with appropriate parameters, which method will swap two integers, as intended?

- (A) I only
- (B) II only
- (C) III only
- (D) II and III only
- (E) I, II, and III

20. Consider the following program that uses the `IntPair` class:

```
public class TestSwap
{
    public static void swap(IntPair pair)
    {
        int temp = pair.getFirst();
        pair.setFirst(pair.getSecond());
        pair.setSecond(temp);
    }

    public static void main(String[] args)
    {
        int x = 8, y = 6;
        /* code to swap x and y */
    }
}
```

Which is a correct replacement for `/* code to swap x and y */`?

- I `IntPair iPair = new IntPair(x, y);`
`swap(x, y);`
`x = iPair.getFirst();`
`y = iPair.getSecond();`
- II `IntPair iPair = new IntPair(x, y);`
`swap(iPair);`
`x = iPair.getFirst();`
`y = iPair.getSecond();`
- III `IntPair iPair = new IntPair(x, y);`
`swap(iPair);`
`x = iPair.setFirst();`
`y = iPair.setSecond();`

- (A) I only
- (B) II only
- (C) III only
- (D) II and III only
- (E) None is correct.

Refer to the Name class below for Questions 21 and 22.

```
public class Name
{
    private String firstName;
    private String lastName;

    public Name(String first, String last) //constructor
    {
        firstName = first;
        lastName = last;
    }

    public String toString()
    { return firstName + " " + lastName; }

    public boolean equals(Object obj)
    {
        Name n = (Name) obj;
        return n.firstName.equals(firstName) &&
            n.lastName.equals(lastName);
    }

    public int hashCode()
    { /* implementation not shown */ }

    public int compareTo(Name n)
    {
        /* more code */
    }
}
```

21. The `compareTo` method implements the standard name-ordering algorithm where last names take precedence over first names. Lexicographic or dictionary ordering of `Strings` is used. For example, the name Scott Dentes comes before Nick Elser, and Adam Cooper comes before Sara Cooper.

Which of the following is a correct replacement for `/* more code */`

```
I int lastComp = lastName.compareTo(n.lastName);
   if (lastComp != 0)
       return lastComp;
   else
       return firstName.compareTo(n.firstName);
```

```
II if (lastName.equals(n.lastName))
    return firstName.compareTo(n.firstName);
    else
        return 0;
```

```
III if (!(lastName.equals(n.lastName)))
    return firstName.compareTo(n.firstName);
    else
        return lastName.compareTo(n.lastName);
```

- (A) I only
 (B) II only
 (C) III only
 (D) I and II only
 (E) I, II, and III
22. Which statement about the `Name` class is *false*?
- (A) `Name` objects are immutable.
 (B) It is possible for the methods in `Name` to throw a `NullPointerException`.
 (C) If `n1` and `n2` are `Name` objects in a client class, then the expressions `n1.equals(n2)` and `n1.compareTo(n2) == 0` must have the same value.
 (D) The `compareTo` method throws a run-time exception if the parameter is null.
 (E) Since the `Name` class has a `compareTo` method, it *must* provide an implementation for an `equals` method.