Responsible Engineering

เรียบเรียงโดย Wiwat Vatanawood

Agenda

1. Responsible Engineering
2. Versioning, Provenance, and Reproducibility
3. Explainability
4. Fairness
5. Safety
6. Security and Privacy
7. Transparency and Accountability

1. Responsible Engineering

Responsible Engineering

- **Defining the Goal:** Responsible engineering practices aim to identify and reduce the various forms of harm that software systems can cause
- **The ML Challenge:** Unlike traditional software, machine-learned models lack (ML ไม่มี spec ชัด ๆ) explicit specifications and guarantees, introducing new risks like amplified bias, deep fakes, and cognitive manipulation
- **A Holistic View:** Safety, security, and fairness cannot be "bolted on" at the end; they must be deeply embedded in every activity across the development lifecycle

ปกติการสร้าง model ไม่มี spec เพียงแต่ต้องการผลลัพธ์ให้ได้ ดังนั้นมันท้าทาย การควบคุมให้ได้ตาม responsible eng.

เนื้อหาบทนี้ เน้นเรื่อง Responsible Engineering ที่ต้องรับผิดชอบกับระบบต่อผู้ใช้ ทุกเรื่องต้องได้รับการจัดการตลอด dev lifecycle ด้วย

Legal vs. Ethical Responsibilities

- **The Legal Gap:** Historically, software licenses (like the MIT license) have successfully rejected almost all liability for defects or harms
- **Legality vs. Ethics:** Actions may be technically legal but widely perceived as unethical (e.g., predatory pharmaceutical pricing) เช่น ขายยาโรคร้ายแรง ราคาแพง 5000%?
- **Defining Terms:**
  - **Legality:** State-enforced regulations; violations result in lawsuits or penalties.
  - **Ethics:** Moral philosophy identifying right from wrong conduct.
- **Professional Ethics:** Standards of conduct (e.g., ACM Code of Ethics) binding within a profession

ความรับผิดชอบของ Responsible Eng. มักกำหนดทั้งทาง Legal vs Ethical / ทางกฎหมาย vs จริยธรรม

เรามักจะใช้ Open Source License (เช่น MIT License) ซึ่งมีประโยคป้องกันตัวยอดฮิตคือ "Software is provided as is, without warranty of any kind" ซึ่งช่วยให้โปรแกรมเมอร์ **รอดพ้นจากความรับผิดชอบทางกฎหมาย (Legal)** ได้เกือบทั้งหมดหากโค้ดมีบั๊ก

หัวข้อ	Legal (กฎหมาย)	Ethics (จริยธรรม)
นิยามหลัก	กฎเกณฑ์ที่รัฐกำหนดให้ต้องปฏิบัติตาม	หลักการทางศีลธรรมที่บอกว่าอะไรควร/ไม่ควรทำ
ลักษณะการบังคับ	บังคับอย่างเป็นทางการ (Objective & Enforced)	เป็นบรรทัดฐานทางสังคม/จิตสำนึก (Subjective & Voluntary)
ผลของการฝ่าฝืน	โทษทางกฎหมาย (ปรับ, จำคุก, ฟ้องร้อง)	เสื่อมเสียชื่อเสียง, สังคมประณาม, ขัดต่อจรรยาบรรณวิชาชีพ
ความยืดหยุ่น	เปลี่ยนแปลงช้า (ต้องผ่านกระบวนการทางกฎหมาย)	เปลี่ยนแปลงได้ตามยุคสมัยและบริบททางสังคม

Why it Matters: The Power of a Few Lines of Code

- **Outsized Impact:** Seemingly minor technical decisions—like tweaking a loss function or data collection protocol—can have profound effects on society
- **Examples of Local Decisions with Global Consequences:**
  - Optimizing for "clicks" (เน้นให้กดติดตาม) on social media can inadvertently promote content that harms teen mental health (วัยรุ่นมักชอบ แปลกนอกกรอบ อาจรุนแรง)
  - Automating review screening can unintentionally disadvantage minority-owned businesses (อาจกระทบกีดกันทางเพศ เชื้อชาติชนกลุ่มน้อย)
- **Scale and Automation:** Errors in software deployed at scale cause harm much faster and more broadly than manual human errors

ตั้งใจทำเนื้อหาแย่
ให้กด Dislike ก็ได้

ให้มี mindset ว่า การเขียน code ไม่กี่บรรทัดก็ส่งผลกระทบได้ ...

Major Areas of Concern (Part 1)

- **Safety Risks:** Even non-lethal systems can cause harm, such as smart thermostats shutting off heat during freezes or delivery robots blocking wheelchair access at crosswalks.
- **Manipulation and Addiction:** ML is highly effective at exploiting human cognitive biases. "Attention engineering" (e.g., YouTube's recommendation rabbit holes) can lead to addiction or the spread of misinformation.
- **Polarization and Mental Health:** Algorithmic amplification of extreme content fosters "filter bubbles" (คัดกรองและแสดงผลข้อมูลที่ตรงกับความสนใจ ตัดขาดข้อมูลอื่นหลากหลายที่ควรรู้) and can contribute to societal polarization (การแบ่งขั้ว) and depression

ควรคำนึงถึง safety / การยึดติดกับคำตอบ ML อย่างผิด ๆ / การแบ่งขั้วและกระตุ้นให้เกิดอาการซึมเศร้า เช่น ทำให้อินเทอร์เฟซดึงดูดจนผู้ใช้ "ติด" (Engagement) เช่น การใช้สีแดงที่ปุ่มแจ้งเตือน, การเลื่อนหน้าจอแบบไม่มีที่สิ้นสุด (Infinite Scroll), หรือระบบอัลกอริทึมที่คัดกรองเนื้อหาเฉพาะที่เราชอบมาให้ดู การลุ้นว่าจะมีใครมากด Like รูปเราไหม

เหตุการณ์นี้เกิดปัญหาเรื่อง Safety อย่างไร?

Filter Bubble Effect

Echo chambers vs filter bubbles

- Echo chambers describe self-reinforcing information environments where users encounter beliefs similar to their own
- Filter bubbles refer to personalized content curation by algorithms that limit exposure to diverse viewpoints
- Echo chambers often form through user choice while filter bubbles result from algorithmic processes
- Both phenomena can lead to information isolation and reinforcement of existing beliefs
- Echo chambers tend to be more active and social while filter bubbles are more passive and individualized

Echo Chamber Effect



Figure: Building blocks of an echo chamber.
Adapted from Jasny et al. DOI: 10.1038/nclimate2666

Major Areas of Concern (Part 2)

- **Job Loss and Deskilling:** Automation may displace many roles (cashiers, drivers, physicians) and relegate ผลักไสไป remaining human workers to repetitive, low-skill tasks.
- **Weapons and Surveillance:** "Dual-use" technology means search-and-rescue innovations can be adapted for autonomous "killer robots" or mass surveillance that suppresses specific populations.
- **Discrimination:** ML models trained on biased data often reinforce or amplify existing social prejudices (e.g., biased resume screening)

การใช้ ML ทำให้เกิดการลดทักษะ และตกงานได้ / เป็นดาบสองคม ใช้ทางดีและทางร้ายได้ / ผิดพลาดจากข้อมูลที่ biased data

Key Facets of Responsible ML Engineering

- Organizations and governments have proposed several overlapping principles for "Trustworthy AI":

Trustworthy AI

- **Safety and Reliability:** Prevention of malfunction and harm
- **Fairness and Non-discrimination:** Avoiding unfair bias and protecting demographic groups.
- **Privacy and Security:** Protecting data and defending against malicious attacks.
- **Transparency and Explainability:** Making users aware of automated decisions and providing understandable reasons for them.
- **Accountability:** Defining who is responsible when things go wrong

สรุปว่า Responsible Eng. ต้องคำนึงถึง Trustworthy AI (AI เชื่อถือได้) โดยมี Key facets ด้านต่าง ๆ ดังที่กล่าวใน slide นี้

Technical Building Blocks for Responsibility

- **Versioning, Provenance, and Reproducibility:** Essential for debugging and auditing. We must track which model made a prediction, what data it was trained on, and how it was produced.
- **Interpretability and Explainability:** Tools that help developers and users understand model internals are vital for identifying shortcut learning and providing transparency to end-users.
- **System-Wide Integration:** Responsibility is not just a "model property"; it requires requirements engineering, hazard analysis, and testing the system's interaction with the real world

เราใช้ automated tool เพื่อช่วยทำ data and code versioning, data provenance และอื่น ๆ

The Regulatory Landscape

ภาพรวมทางกฎหมาย

- **European Union (EU AI Act):** As of August 2024 (fully effective Aug 2026), this is the most comprehensive regulation. It classifies AI systems by risk (Unacceptable, High, Limited, Minimal)
  - **High-Risk Systems:** Require strict, mandatory conformity assessments, high-quality datasets, human oversight, and detailed documentation
  - **Prohibited Practices:** Systems that pose unacceptable risks, such as indiscriminate biometric surveillance or social scoring, are banned
- **United States:** The US favors a more decentralized, sectoral, and, more recently, pro-innovation approach.
  - **Executive Order 14179 (Jan 2025):** Replaces prior, more restrictive orders to focus on fostering AI innovation, particularly in national security, while suspending rules seen as "obstacles" to development.
  - **NIST AI Risk Management Framework (RMF):** A widely adopted, voluntary standard for managing AI risks.
  - **California SB-53:** A notable state-level law requiring rigorous safety testing for powerful, large-scale AI models
- **China:** Focuses on "state-driven" regulation, with specific rules for Generative AI (effective Aug 2023). These focus on content control, requiring providers to register algorithms and ensure content aligns with "socialist core values"
- **United Kingdom:** Adopts a "pro-innovation," flexible approach, empowering existing sector-specific regulators (e.g., in finance or health) rather than a single central authority
- **International Treaties:** The Council of Europe Framework Convention on AI (Sept 2024) is the first legally binding international treaty, focusing on human rights and democracy

เริ่มมีการบังคับใช้ระเบียบบังคับ หรือกฎหมายด้านการใช้ AI ...เช่นเดียวกับการใช้ data ซึ่งมีกฎหมายเรื่อง PDPA


AI REGULATION LANDSCAPE 2025
How Global Powers Govern Artificial Intelligence
U.S.
AI Executive Orders & NIST AI Rick Framework
• Innovation + safety balance
• Voluntary AI safety guidelines
Approach: Light-touch, inqustry-driven
U.K.
Pro-innovation AI Regulatory Framework
Existing sector regulators
Transparency & fairness
AI Satety Institute
Flexible, adaptive
EU
EU AI Act (2024)
First comprehensive AI law
AI risk classification
Strict compliance
Approsch: Rights, focused, strict compliance-heavy
China
Interim Measures for Genarative AI (2023)
Mandatory security testing
Soclalism-aligned content
Approach: Contralized, state- controlled
COMMONTHEMES: Ethical AI use & testing • Data protection & risk
DIFFERENCES • Balancing innovation & risk • Balancing Innovation & risk
tesseractacademy

Critiques: Ethics Washing vs. Ethics Bashing

- **Ethics Washing:** The concern that companies use lofty ethical mission statements as a "facade" to justify self-regulation and avoid government oversight while continuing harmful practices (ฟอกขาวทางจริยธรรม)
- **Ethics Bashing** ทุบตีเล่นงาน**:** Critics who dismiss all ethical discussions (ผู้ที่ไม่เห็นด้วยกับ ethics) as mere marketing or "ivory tower" activities with no practical engineering value

Ethics Washing เช่น ประกาศว่าจะมีจริยธรรม AI แต่ยังใช้ algo. ที่ลำเอียงไม่ปลอดภัย

Summary and Best Practices

- **Don't Wait for Regulation:** Responsible engineers should proactively adopt practices to mitigate harm before accidents occur.
- **Adopt a Security/Safety Mindset:** Assume models are unreliable and will fail eventually; design the system to handle those failures gracefully
- **Prioritize Human Agency:** Maintain human dignity (ศักดิ์ศรีมนุษย์) by ensuring users are aware of AI decisions and have pathways for appeal (ร้องเรียน/อุทธรณ์)

ลงมือทำ Responsible eng. practices เลย ไม่ต้องรอ regulation ทางการ

Versioning, Provenance and Reproducibility

Definitions of Versioning, Provenance, and Responsibility

- **Versioning:** Ensuring the same versions of models and code are deployed and identifying which version made a specific decision
- **Provenance:** Tracking the origin of data, how it flowed through the system, and what modifications were made by whom
- **Reproducibility:** Understanding the influence of nondeterminism and the ability to recreate a specific model or prediction for debugging or auditing

3 เรื่องที่สำคัญ

Versioning Data-Science Code

- **The Notebook Challenge:** Data scientists often use an exploratory workflow in notebooks that does not align well with traditional version control like Git (Notebook app สู้ Git ไม่ได้)
- **Migration to Production:** Once a model moves beyond exploration, the code should be migrated to modular, well-maintained pipelines and versioned as production code.
- **Dependency Tracking:** It is essential to track versions of frameworks and libraries (e.g., pinning versions in requirements.txt) or package them in Docker containers to ensure environment stability

1) การทำ Pipeline Code Versioning (สำหรับ ML Pipeline Code)

Five Strategies for Versioning Large Datasets

- **Entire Dataset Copies:** Storing a full copy for each change; easy to access but requires massive storage.
- **Deltas/Patches:** Storing only changes between versions; space-efficient but computationally expensive to reconstruct old versions.
- **Append-Only Offsets:** Remembering file sizes/offsets for event-sourced or log data; simple and efficient but limited to append-only data

เหมาะกับ history log file

- **Individual Records:** Versioning each database entry or record independently (e.g., individual customer profiles) แยกเก็บ history ของ record นั้น ๆ เพิ่มออกมา
- **Derived Data Recreation:** Instead of storing large transformed datasets, version the transformation code and original data to recreate them on demand

2) การทำ Data Versioning

เครื่องมือที่ใช้ DVC

Model Versioning and Experiment Tracking

- **Models as Binary Files:** Since most ML updates change many parameters, models are typically stored as full copies rather than deltas
- **Experiment Tracking Tools:** Specialized platforms (e.g., MLflow, ModelDB) store models alongside metadata like hyperparameters, data versions, and accuracy results
- **API Versioning:** Model inference services can offer multiple versions via specific endpoints (e.g., /[modelid]/[version]), allowing clients to choose when to update

3) การทำ Model Versioning (Code ที่ใช้สร้าง model)

MLflow: เน้นการจัดการการทดลองและเวอร์ชันของโมเดล
Airflow: เน้นการจัดการลำดับงานและระบบอัตโนมัติ **ML Pipeline** ทั้งหมด

Provenance: Tracking Data through the System

- **Why:** Teams often fear changing data scripts because they lack information on who else uses that data or how it was originally produced
- **Four Tracking Strategies:**
  - **Manual Documentation:** High-level diagrams (often become outdated)
  - **Custom Metadata Logging:** Adding code to log what data was read and written
  - **Pipeline Frameworks (e.g., DVC):** Enforcing a structure where inputs and outputs are automatically tracked by configuration
  - **Integrated Platforms (ใช้ platform อัตโนมัติ):** Cloud platforms (e.g., AWS SageMaker) that automatically track provenance for all code executed on them

Amazon SageMaker Workflow

aws training and certification



Reproducibility vs. Replicability

- **Reproducibility (Science):** The ability to repeat an experiment with minor differences (e.g., fresh data) and achieve comparable results
- **Replicability (Engineering):** The technical ability to achieve the *exact* same results by running the *exact* same experiment

ML model ยากที่จะทำ replicate ได้ เพราะนำทุกอย่างใน pipeline มาเริ่ม train อีกรอบ ก็อาจจะไม่ได้ bit-to-bit replicability เพราะมี nondeterministic ดังนั้น เราหวังแค่ Reproducible ก็พอ

Explainability in ML Systems

Explainability in ML Systems

- **The "Black Box" Problem:** We often use machine learning for tasks so complex that we cannot solve them with fixed, easy-to-understand rules
- **Defining the Need:** While opaque models can outperform humans in specific tasks, their lack of transparency makes it difficult to **trust, audit, appeal (โต้แย้ง), or debug** them

การให้มี Explainability ไม่ง่าย

Core Concepts: Interpretability vs. Explainability

- **Interpretability (ความสามารถในการตีความได้):** Refers to models that are **inherently understandable** due to their simple internal structure (e.g., small decision trees or linear models)
- **Explainability (ความสามารถในการอธิบาย):** Refers to mechanisms that provide **partial information** about how a model works or why it made a specific prediction
- **Justification (การให้เหตุผลประกอบ):** A post hoc narrative created to show that a decision is **consistent with a set of rules**, even if it doesn't fully explain the internal reasoning process
- **Transparency (ความโปร่งใส):** The broad disclosure of information regarding the **model, training data, and process** to build societal trust and enable scrutiny

Explaining the Model (Global Explanations)

- **Global Strategies:** These techniques aim to explain how a model works **overall**, independent of any specific input
- **Global Surrogate Models:** Training an **interpretable model** (like a shallow decision tree) to mimic the behavior of an opaque model to approximate its logic
- **Feature Importance:** Quantifying the **average explanatory power** of each feature across the entire dataset to see what the model values most การวัดว่าโมเดลพึ่งพาฟีเจอร์แต่ละตัวมากน้อยเพียงใดโดยเฉลี่ยจากข้อมูลทั้งหมด
- **Partial Dependence Plots (PDP):** Visualizing how the predicted output changes as a **single feature is manipulated** while others are held constant การแสดงให้เห็นว่าผลลัพธ์พยากรณ์เปลี่ยนแปลงไปอย่างไรเมื่อเราปรับเปลี่ยนค่าของฟีเจอร์ตัวเดียว โดยคงค่าฟีเจอร์อื่นๆ ไว้

เทคนิคนี้มุ่งเน้นไปที่การอธิบายว่า **โมเดลทำงานอย่างไรในภาพรวม** โดยไม่ขึ้นกับอินพุตเฉพาะเจาะจงตัวใดตัวหนึ่ง

Explaining a Prediction (Local Explanations)

- **Feature Influences (LIME & SHAP):**
  - **LIME:** จะสร้างโมเดลเชิงเส้นขนาดเล็กมาเลียนแบบขอบเขตการตัดสินใจรอบๆ จุดข้อมูลนั้น
  - **SHAP:** จะใช้หลักการทางเกมเพื่อจัดสรรความสำคัญของฟีเจอร์อย่างเป็นธรรม
- **Anchors:** การหาเงื่อนไขที่น้อยที่สุดที่เพียงพอจะทำให้โมเดลได้คำตอบเดิม (เช่น "ถ้าอายุต่ำกว่า 40 และเคยถูกจับเกิน 5 ครั้ง โมเดลจะทำนายว่ามีความเสี่ยงสูงเสมอ")
- **Counterfactual Explanations:** การบอกเงื่อนไขที่น้อยที่สุดที่ต้องปรับเปลี่ยน เพื่อจะทำให้ผลพยากรณ์เปลี่ยนไป เช่น "ถ้าเงินเดือนเพิ่มขึ้นอีก 5,000 บาท สินเชื่อของคุณจะได้รับการอนุมัติ"

เทคนิคนี้มุ่งเน้นไปที่การอธิบายว่า **ทำไมโมเดลถึงพยากรณ์ผลลัพธ์เช่นนั้นสำหรับอินพุตเฉพาะตัวใดตัวหนึ่ง**
เป้าหมาย: เพื่อทำความเข้าใจปัจจัยตัดสินสำหรับกรณีรายบุคคล เช่น ทำไมใบสมัครเงินกู้ของคนนี้ถึงถูกปฏิเสธ?

หัวข้อเปรียบเทียบ	Global Explanation	Local Explanation
ขอบเขต (Scope)	อธิบายการทำงานของทั้งโมเดล	อธิบายการพยากรณ์เพียงครั้งเดียว
มุมมอง	"โมเดลนี้มองว่า 'อายุ' สำคัญกว่า 'ที่อยู่' ในการทำนาย"	"สำหรับคุณเอ, 'จำนวนเงินกู้' เป็นเหตุผลหลักที่ทำให้กู้ไม่ผ่าน"
ประโยชน์หลัก	ใช้ตรวจสอบความยุติธรรม (Audit) และแก้ไขบั๊กภาพรวม	ใช้ในการอุทธรณ์ผลตัดสิน (Appeals) และสร้างความเชื่อมั่นให้ผู้ใช้

Fairness

Fairness in ML Systems

- **The Core Challenge:** Models trained on real-world data often pick up and amplify existing societal biases อคติ
- **Consequences of Unfairness:** Unfair models can reinforce stereotypes (ทัศนคติแบบเหมารวม), create inequality, or provide lower quality of service to specific subpopulations
- **Beyond Accuracy:** High average accuracy can hide poor performance for minority groups; fairness requires a multi-faceted evaluation

Bing's image search results for "CEO"

ส่วนใหญ่เป็นเพศชาย



Bing's image search results for "CEO" show only men in that role.

What is ความเสมอภาค (Equity) vs. ความเท่าเทียม (Equality)?



Foundational Notions: Equality vs. Equity

- **Defining Fairness:** There is no single universal definition; it is often context-dependent and rooted in ethics and law.
- **Equality (Equal Slices):** Every individual or group is treated exactly the same, regardless of their starting position or needs
- **Equity (Unequal Starting Positions):** Providing different levels of support to individuals to achieve a comparable outcome, acknowledging systemic disadvantages



ความเท่าเทียม ความเสมอภาค

A common visualization of the difference between equality and equity when it comes to deciding how much support to provide to individuals starting from different positions. From: Interaction Institute for Social Change | Artist: Angus Maguire.

หัวข้อเปรียบเทียบ	**ความเท่าเทียม (Equality)**	**ความเสมอภาค (Equity)**
นิยามหลัก	การปฏิบัติต่อทุกคนอย่างเท่าเทียมกันและให้โอกาสในการแข่งขันเหมือนกัน โดยไม่คำนึงถึงจุดเริ่มต้นที่ต่างกัน	การให้ทรัพยากรหรือการสนับสนุนเพิ่มเติมแก่กลุ่มที่เสียเปรียบ เพื่อให้บรรลุผลลัพธ์ที่เท่าเทียมกัน
จุดเน้น (Focus)	เน้นที่ **"กระบวนการตัดสินใจ"** (Decision Procedure) ต้องเป็นธรรมและเป็นกลาง	เน้นที่ **"ผลลัพธ์"** (Outcomes) ต้องมีความยุติธรรมในเชิงการกระจายทรัพยากร
เป้าหมาย	เพื่อให้เกิด **"ความเท่าเทียมทางโอกาส"** (Equality of Opportunity)	เพื่อให้เกิด **"ความเท่าเทียมทางผลลัพธ์"** (Equality of Outcomes)
มุมมองด้านกฎหมาย	มักเชื่อมโยงกับการลด **"การปฏิบัติที่แตกต่างกัน"** (Minimize Disparate Treatment)	มักเชื่อมโยงกับการลด **"ผลกระทบที่แตกต่างกัน"** (Minimize Disparate Impact)
ปรัชญาที่เกี่ยวข้อง	ระบบคุณธรรม (Meritocracy)	ความยุติธรรมเชิงกระจาย (Distributive Justice)

Safety

Safety in ML Systems

- **Defining Safety:** The prevention of system failure or malfunction that results in death or serious injury, severe property damage, or harm to the environment and society
- **Broadening the Scope:** Safety is not just for nuclear plants or airplanes; it applies to all ML systems that can cause harm, such as social media feeds affecting mental health or malfunctioning smart alarms creating noise pollution

Hazard Analysis Techniques

- **Forward Analysis (FMEA & HAZOP):** Starts with a component mistake (root cause) and analyzes if it can lead to a hazard.
  - *Example:* What happens if the obstacle detection model fails to see a pedestrian?
- **Backward Analysis (Fault Tree Analysis):** Starts with a potential hazard (e.g., a train collision) and traces back the combination of conditions required to cause it.
- **Leveraging Industry Knowledge:** Use existing safety standards (e.g., ISO 26262 for vehicles) and accident reports as starting points for analysis rather than starting from scratch

Failure Mode Effect Analysis (FMEA)



Process Step	Potential Failure Mode	Potential Failure Effect	SEV[1]	Potential Causes	OCC[2]	Current Process Controls	DET[3]	RPN[4]	Action Recommended
What is the step?	In what ways can the step go wrong?	What is the impact on the customer if the failure mode is not prevented or corrected?	How severe is the effect on the customer?	What causes the step to go wrong (i.e., how could the failure mode occur)?	How frequently is the cause likely to occur?	What are the existing controls that either prevent the failure mode from occurring or detect it should it occur?	How probable is detection of the failure mode or its cause?	Risk priority number calculated as SEV x OCC x DET	What are the actions for reducing the occurrence of the cause or for improving its detection? Provide actions on all high RPNs and on severity ratings of 9 or 10.
ATM Pin Authentication	Unauthorized access	• Unauthorized cash withdrawal • Very dissatisfied customer	8	Lost or stolen ATM card	3	Block ATM card after three failed authentication attempts	3	72	
	Authentication failure	Annoyed customer	3	Network failure	5	Install load balancer to distribute work-load across network links	5	75	
Dispense Cash	Cash not disbursed	Dissatisfied customer	7	ATM out of cash	7	Internal alert of low cash in ATM	4	196	Increase minimum cash threshold limit of heavily used ATMs to prevent out-of-cash instances
	Account debited but no cash disbursed	Very dissatisfied customer	8	• Transaction failure • Network issue	3	Install load balancer to distribute work-load across network links	4	96	
	Extra cash dispensed	Bank loses money	8	• Bills stuck to each other • Bills stacked incorrectly	2	Verification while loading cash in ATM	3	48	

1. **Severity**: Severity of impact of failure event. It is scored on a scale of 1 to 10. A high score is assigned to high-impact events while a low score is assigned to low-impact events.
2. **Occurrence**: Frequency of occurrence of failure event. It is scored on a scale of 1 to 10. A high score is assigned to frequently occurring events while events with low occurrence are assigned a low score.
3. **Detection**: Ability of process control to detect the occurrence of failure events. It is scored on a scale of 1 to 10. A failure event that can be easily detected by the process control is assigned a low score while a high score is assigned to an inconspicuous event.
4. **Risk priority number**: The overall risk score of an event. It is calculated by multiplying the scores for severity, occurrence and detection. An event with a high RPN demands immediate attention while events with lower RPNs are less risky.

1. Failure Modes and Effects Analysis (FMEA)

เป็นการวิเคราะห์ **"ไปข้างหน้า" (Forward Analysis)** โดยเริ่มจากความล้มเหลวของส่วนประกอบย่อย แล้วดูว่าจะส่งผลกระทบอย่างไรต่อระบบ

ตัวอย่าง: ระบบประตูรถไฟอัตโนมัติ (Autonomous Train Door)

- **ส่วนประกอบ:** ML model for Vision-based ที่ตรวจจับคนตรงประตู
- **ลักษณะข้อบกพร่อง (Failure Mode 1):** โมเดลตรวจไม่พบคนทั้งที่มีคนอยู่ตรงประตู
  - **ผลกระทบ:** ประตูอาจปิดหนีบผู้โดยสารจนเกิดการบาดเจ็บ
  - **แนวทางแก้ไข:** เพิ่มเซนเซอร์วัดแรงกด (Pressure sensor) ที่ประตู หรือให้เจ้าหน้าที่ตรวจสอบผ่านกล้องอีกชั้นหนึ่ง
- **ลักษณะข้อบกพร่อง (Failure Mode 2):** โมเดลตรวจพบคนทั้งที่ไม่มีคนอยู่ (False Positive)
  - **ผลกระทบ:** รถไฟออกเดินทางไม่ได้ ทำให้การจราจรล่าช้า


Accident/Incident
AND
Primary Cause
Primary Cause 2
OR
AND
Event
Event
Event
Event
Presented with xmind


Car hits object
AND
Driver does not see object
Car fails to brake
OR
OR
Object just around corner
Driver drunk
Driver asleep
Car going too fast
Brakes weak

2. Fault Tree Analysis (FTA)

เป็นการวิเคราะห์ **"ย้อนกลับ" (Backward Analysis)** โดยเริ่มจากความล้มเหลวของระบบที่ต้องการหลีกเลี่ยง (System Failure) แล้วสืบหาเงื่อนไขย่อยที่รวมกันแล้วทำให้เกิดเหตุการณ์นั้น

ตัวอย่าง: การหนีบผู้โดยสารของประตูรถไฟอัตโนมัติ

- **เหตุการณ์หลัก (Top Event):** ผู้โดยสารโดนประตูหนีบ (ความล้มเหลวด้านความปลอดภัย)
- **เงื่อนไขที่ทำให้เกิด (Gate):** ใช้อุปกรณ์เชื่อมต่อแบบ "AND" และ "OR"
  - **เงื่อนไข AND:** (ระบบ Vision ตรวจพลาด) **และ** (เซนเซอร์วัดแรงกดเสีย)
  - **เงื่อนไข OR:** เจ้าหน้าที่สั่งปิดประตูเองด้วยมือโดยประมาท
- **การจัดการกับ ML:** ใน Fault Tree เรามักถือว่า **"ความล้มเหลวของโมเดล ML" เป็นเหตุการณ์พื้นฐาน (Basic Event)** ที่ไม่สามารถแยกย่อยสาเหตุภายในได้ชัดเจนเนื่องจากโมเดลมีความซับซ้อนและไม่มีข้อกำหนดทางตรรกะที่แน่นอน
- **การออกแบบเพื่อความปลอดภัย:** นักออกแบบสามารถดูภาพรวมจากผังต้นไม้นี้เพื่อเพิ่ม "มาตรการป้องกัน" (Mitigations) เช่น การใส่เซนเซอร์วัดแรงกดเพิ่มเป็น 2 ตัว เพื่อให้ "ชุดตัด" (Cut set) หรือเหตุการณ์ที่จะทำให้พังจริงๆ มีจำนวนมากขึ้นจนโอกาสเกิดความเสียหายลดลง

Security and Privacy in ML Systems

Security and Privacy in ML Systems

- Security is an ongoing arms race where attackers attempt to break system defenses through **confidentiality, integrity, or availability** attacks
- **Unique ML Vulnerabilities (ช่องโหว่):** Beyond traditional software bugs, ML introduces risks related to **training data, model parameters, prompts, and telemetry**
- **The Content Moderation Scenario:** Consider a social media site using models to filter depictions of violence; attackers may try to **evade detection** (หลีกเลี่ยงการตรวจจับ)or **poison (ทำให้เสื่อม) the model** to allow harmful content
- **A Holistic Perspective:** Securing an ML system requires looking beyond the model to include the **learning pipeline, data storage, and inference infrastructure**

Security ต่างกับ Safety อย่างไร?

Security Fundamentals: CIA Triad in ML

- **Confidentiality:** Ensuring sensitive data—including training sets, model internals, and user prompts—is accessed only by authorized parties
- **Integrity:** Preventing unauthorized manipulation of data or system decisions, such as tricking a model into making specific "wrong" predictions.
- **Availability:** Ensuring the system remains operational and is not taken down by resource-exhaustion attacks or model-neutralizing poisoning

Evasion Attacks (Adversarial Examples)

- **Definition:** Attackers craft inputs that look innocent to humans but trick the model into a desired "wrong" prediction at inference time
- **Defense Strategy 1: Adversarial Training:** Hardening the model by intentionally including **adversarial examples** ตัวอย่างที่ถูกดัดแปลงให้หลอกพร้อมคำตอบที่ถูก with correct labels in the training set
- **Defense Strategy 2: Input Sanitation:** Reducing the information reaching the model (e.g., color depth reduction) to remove artifacts an attacker might exploit ลดข้อมูลที่ไม่จำเป็นออก เพื่อไม่เปิดโอกาสให้โจมตีได้

1 การโจมตีแบบหลีกเลี่ยงการตรวจจับ โดยการป้อน Training data ที่ดัดแปลงและหลอกสอนด้วยว่าเป็นคำตอบที่ถูก กล่าวคือ ส่งรูป “Dog” แล้วหลอกสอนว่าเป็น “Cat” เพื่อโจมตี

การแก้ไขคือ การทำ Adversarial training โดยการส่งรูป “Dog” แล้วสอนให้ถูกว่าไม่ใช่ “Cat”


Adversarial Machine Learning
Dog
Cat
Cat
Cat
Misclassifies Dog Image as cat due to Adversarial Attack
Adversarial Manipulation of Dog
EDUCBA

Adversarial Training



Adversarial Training



A model with a decision boundary (black line) correctly detects the original stop sign and many other images in the neighborhood as a stop sign, but not all nearby images; for example, the image with several black and white stickers is not detected as a stop sign. As a whole, the prediction of the original image is not considered robust, because some neighboring inputs pass across the decision boundary of the model.

Poisoning and Model Extraction

- **Poisoning Attacks:** Malicious actors manipulate **training data** to create "backdoors" or render the model inaccurate in production การโจมตีแบบวางยา
- **Targeted vs. Untargeted:** Targeted poisoning aims for a specific outcome (e.g., ignoring a specific malware signature), while untargeted aims to break the model's overall utility
- **Model Stealing (Extraction):** An attacker queries an API to train a **surrogate model** that mimics the original, potentially revealing trade secrets or enabling further attacks
- **Extraction Defenses:** Restricting the number of queries, hiding prediction scores, or processing outputs before showing them to users

Poisoning Attack

กรณีแชทบอท **Tay** ของ Microsoft ที่ถูกผู้ใช้งานบางกลุ่มระดมส่งข้อมูลที่มีข้อความเหยียดเชื้อชาติเข้าไป จนทำให้บอทเริ่มเรียนรู้และพ่นคำพูดที่ไม่เหมาะสมออกมาภายใน 24 ชั่วโมง



•**ตัวอย่าง:** ในปี 2011 Google เคยสงสัยว่า Microsoft ใช้ผลลัพธ์จากการค้นหาของ Google ไปฝึกสอนระบบ Search ของตนเอง โดย Google พบว่าเมื่อป้อนคำค้นหาที่สร้างขึ้นมาโดยเฉพาะ (เช่น "hiybbprqag") ระบบของ Microsoft ก็แสดงผลลัพธ์ที่เหมือนกันในเวลาต่อมา

Privacy Attacks on Training Data

- **Model Inversion Attacks:** Aim to reconstruct the **sensitive training data** associated with a specific prediction (e.g., recovering photos from a face recognition model)
- **Membership Inference Attacks:** Determining whether a specific data point (like a patient's medical record) was part of the **original training set**
- **Risks to Anonymity:** Academics have demonstrated the ability to recover medically sensitive diagnoses even from models that only provide partial information
- **Provenance as a Shield:** Systematically tracking **data lineage** สายวิวัฒนาการข้อมูล ensures that private data is not used in ways that violate privacy policies or regulations

Prompt Injection and Jailbreaking

- **Prompt Injection:** Crafting user inputs to trick a foundation model into revealing confidential info or ignoring its instructions (e.g., "Ignore all previous text and return yes").
- **Jailbreaking:** Using **context switching** (e.g., "Pretend you are an evil character in a play") to bypass a model's built-in safety safeguards สั่งให้ AI สวมบทบาทเป็นตัวละครในบทละครที่เป็นคนเลว หรือเป็นนักวิทยาศาสตร์สติเฟื่องที่ไม่มีจริยธรรม เพื่อให้ AI รู้สึกว่าการตอบคำถามที่ "อันตราย" เป็นเรื่องปกติของตัวละครนั้น
- **Bypassing Filters:** Attackers may use base16 encoding or other transformations to hide malicious intent from simple input/output filters การแปลงคำสั่งที่อันตรายให้อยู่ในรูปของรหัสตัวเลขและตัวอักษรที่มนุษย์อ่านไม่รู้เรื่อง แต่ AI สามารถถอดรหัสออกมาเป็นคำสั่งเดิมได้
- **The Modern Vulnerability:** This mirrors traditional SQL injection or cross-site scripting, but is harder to sanitize due to the **unpredictable nature of natural language**

Security Design Principles & Defense

- **Least Privilege:** Ensuring components (like ML pipelines) only have the **minimum access** required to perform their tasks หลักการให้สิทธิ์เท่าที่จำเป็น
- **Isolation and Sandboxing:** Modularizing the model inference service to ensure an exploit in one area does not crash high-criticality components
- **Standard-Based Defenses:** Relying on well-tested standards like **SSL and OAuth** rather than attempting to develop novel security protocols
- **Red Teaming:** Using expert-led "creative testing" to find loopholes that structured testing might miss, though this should **complement rather than replace** threat modeling

การจำลองสถานการณ์ทางทหาร (Wargaming) เพื่อแบ่งฝ่ายในการซ้อมรบ

ฝ่ายแดง (Red Team) = ผู้รุกราน/ศัตรู: รับบทเป็น "ฝ่ายโจมตี" หรือศัตรูสมมติ มีหน้าที่ค้นหาช่องโหว่และพยายามเจาะระบบด้วยทุกวิถีทาง เพื่อจำลองภัยคุกคามในโลกความเป็นจริง

ฝ่ายน้ำเงิน (Blue Team) = ผู้ป้องกัน: รับบทเป็น "ฝ่ายตั้งรับ" มีหน้าที่ดูแลระบบ ตรวจจับ และตอบโต้การโจมตีจากฝ่ายแดง

Data Privacy and User Agency

- **Defining Privacy:** The "right to be let alone" and the ability for individuals to control **how their shared information is used**
- **Privacy Policies:** Documents explaining what info is gathered and how it is shared; users often must agree to these as a **condition of service**
- **Privacy Controls:** Providing users with fine-grained choices, such as opting out of having their data used for **model retraining**
- **The Data Removal Challenge:** When a user requests data removal (right to be forgotten), engineers must trace and update **all downstream datasets and models**

ความเป็นส่วนตัวของข้อมูลและสิทธิการควบคุมข้อมูลของผู้ใช้งาน

Transparency and Accountability

Transparency and Accountability

- **Defining the Goal:** Transparency and accountability are essential for **enabling user trust** and ensuring human agency and dignity.
- **Transparency:** Relates to making users aware that they are subject to automated decisions and helping them understand **how and why** those decisions were made
- **Accountability:** Focuses on the degree to which humans can **oversee** กำกับดูแล **and correct** the system and identifies who is responsible when problems occur.
- **Interdependence:** These two concepts are multi-faceted and build upon one another to create responsible products

Transparency of the Model's Existence

- **The Awareness Gap:** Users are not always aware that machine-learning components are curating การคัดสรรเฉพาะมาให้ตามประสบการณ์ their experience
- **Facebook Case Study:** A 2015 study found that **62% of users were unaware** of algorithmic feed curation; many reacted with anger when they discovered it ผู้ใช้ไม่รู้ว่ามีการใช้ ML algo ในการคัดสรรข้อมูลมาให้ ทำให้โกรธ
- **The Risk of Hiding:** Hiding the presence of a model prevents users from appealing wrong decisions and can make them feel **deceived** when the model is eventually revealed.
- **The Benefit of Awareness:** Knowing about algorithmic curation can lead to **more active engagement** and a stronger feeling of being in control

Transparency of How the Model Works

- **Defining Trust:** Trust is the belief that the system has the **user's interest in mind** and is built on a reasonable understanding of its risks
- **Understanding Limits:** When users understand a system's capabilities and limitations, they are generally **more satisfied**, even if mistakes occasionally occur
- **Fostering Trust:** Trust is earned through repeated positive experiences and by providing explanations that allow users to **anticipate model behavior**

Defining Accountability

- Accountability asks who is considered **culpable** น่าตำหนิ when a system causes harm or behaves in a biased manner.
- **Avoiding the "Algorithm" Blame:** It is easy but incorrect to blame "the data" or "the code"; problems ultimately originate from **human decisions** made during development
- **Designer Responsibility:** Designers are responsible for the **risk mitigation steps** that were—or were not—implemented to handle unreliable ML components
- **Focus on Process:** Accountability rests on those who built and evaluated the system and determined its **safeguard strategies**

Conclusion

ไม่ควรมองข้าม

- Responsible Engineering
  - Responsible engineering practices aim to identify and reduce the various forms of harm that software systems can cause
- Versioning, Provenance, and Reproducibility
- Explainability
- Fairness
- Safety
- Security and Privacy
- Transparency and Accountability