

Contents lists available at ScienceDirect

International Journal of Greenhouse Gas Control

journal homepage: www.elsevier.com/locate/ijggc



Review

Viscosities, thermal conductivities and diffusion coefficients of CO₂ mixtures: Review of experimental data and theoretical models

Hailong Li a,b,*, Øivind Wilhelmsen , Yuexia Lvb, Weilong Wangb, Jinyue Yan b,c

- ^a SINTEF Energy Research, Kolbjørn Hejes vei 1A, 7465 Trondheim, Norway
- ^b Sustainable Development of Society and Technology, Mälardalen University, 72123 Västerås, Sweden
- ^c Energy Process, Royal Institute of Technology, 10044 Stockholm, Sweden

ARTICLE INFO

Article history: Received 30 April 2011 Received in revised form 14 July 2011 Accepted 15 July 2011 Available online 15 August 2011

Keywords: CO₂-mixtures Transport properties Viscosity Thermal conductivity Diffusion coefficient CO₂ capture and storage

ABSTRACT

Accurate experimental data on the thermo-physical properties of CO₂-mixtures are pre-requisites for development of more accurate models and hence, more precise design of CO₂ capture and storage (CCS) processes. A literature survey was conducted on both the available experimental data and the theoretical models associated with the transport properties of CO₂-mixtures within the operation windows of CCS. Gaps were identified between the available knowledge and requirements of the system design and operation. For the experimental gas-phase measurements, there are no available data about any transport properties of CO₂/H₂S, CO₂/COS and CO₂/NH₃; and except for CO₂/H₂O(/NaCl) and CO₂/amine/H₂O mixtures, there are no available measurements regarding the transport properties of any liquid-phase mixtures. In the prediction of gas-phase viscosities using Chapman-Enskog theory, deviations are typically <2% at atmospheric pressure and moderate temperatures. The deviations increase with increasing temperatures and pressures. Using both the Rigorous Kinetic Theory (RKT) and empirical models in the prediction of gas-phase thermal conductivities, typical deviations are 2.2-9%. Comparison of popular empirical models for estimation of gas-phase diffusion coefficients with newer experimental data for CO₂/H₂O shows deviations of up to 20%. For many mixtures relevant for CCS, the diffusion coefficient models based on the RKT show predictions within the experimental uncertainty. Typical reported deviations of the CO₂/H₂O system using empirical models are below 3% for the viscosity and the thermal conductivity and between 5 and 20% for the diffusion coefficients. The research community knows little about the effect of other impurities in liquid CO₂ than water, and this is an important area to focus in future work.

© 2011 Elsevier Ltd. All rights reserved.

Contents

| 1. | Introd | duction | | 1120 |
|--|--|--|---|------|
| 2. | Operating windows and possible impurities in CCS processes | | | 1120 |
| 3. Experimental data | | | 1121 | |
| | 3.1. | Knowle | dge gaps | 1121 |
| 3.2. The precision, consistency and reliability of the experimental data | | cision, consistency and reliability of the experimental data | 1123 | |
| 4. Available transport property models | | port property models | 1123 | |
| | 4.1. | Transpo | rt property models for pure CO ₂ | 1124 |
| | 4.2. Viscosity models for mixtures | | y models for mixtures | 1125 |
| | | | Gas mixtures | |
| | | 4.2.2. | Liquid mixtures | 1128 |
| | 4.3. | Thermal conductivity models | | 1128 |
| | | | Semi-empirical models | |
| | | 4.3.2. | Empirical models | 1129 |

E-mail address: lihailong@gmail.com (H. Li).

 $^{^{\}ast}$ Corresponding author at: Mälardalen University, PO Box 883, 72123 Västeras, Sweden. Tel.: +46 21 103159; fax: +46 21101480.