

DeepSeek V4 Flash · DSpark 双配置对比

A: mem 0.85 / chunked 16384 / max-running 16 B: mem 0.90 / chunked 32768 / max-running 16

B 吞吐胜出	B 吞吐落后	A 峰值 tok/s	B 峰值 tok/s
8/15	7/15	1260.0	1528.3

两轮均为 30/30 组、900/900 请求成功，Error / Timeout 为 0 / 0，AR/AL 完整。B 在短上下文 C16 提升显著，但 128K 各并发均落后。

核心对比

场景	A Gen	B Gen	B vs A	A AR	B AR	A AL	B AL	A TTFT	B TTFT	A TPOT	B TPOT	A 波动	B 波动
1K/C1	167.78	167.45	-0.20%	0.397	0.399	2.986	2.996	208.0	207.0	5.764	5.775	3.54%	0.05%
1K/C8	804.63	819.50	+1.85%	0.533	0.472	3.666	3.355	587.3	381.8	8.648	8.643	11.03%	6.12%
1K/C16	1094.26	1391.11	+27.13%	0.399	0.541	2.996	3.703	1883.5	1448.5	11.841	9.272	14.42%	19.73%
4K/C1	178.90	184.04	+2.87%	0.455	0.477	3.273	3.382	210.0	208.1	5.395	5.243	6.05%	7.39%
4K/C8	752.38	779.36	+3.59%	0.454	0.461	3.269	3.306	540.6	428.0	9.061	9.020	8.16%	6.78%
4K/C16	1169.05	1135.76	-2.85%	0.443	0.431	3.216	3.159	1211.0	1222.3	11.168	11.415	4.31%	8.99%
16K/C1	203.64	216.16	+6.15%	0.572	0.624	3.860	4.122	233.6	234.0	4.701	4.402	10.59%	1.16%
16K/C8	846.94	886.19	+4.63%	0.553	0.602	3.760	4.008	493.1	498.4	8.144	7.645	0.05%	0.31%
16K/C16	1239.98	1281.29	+3.33%	0.587	0.600	3.934	4.000	1596.4	1285.6	8.991	9.045	1.86%	0.16%
64K/C1	230.01	227.42	-1.12%	0.763	0.752	4.818	4.761	344.1	345.2	4.019	4.065	6.04%	3.82%
64K/C8	961.25	924.21	-3.85%	0.790	0.726	4.944	4.627	772.9	796.4	6.914	7.144	0.10%	4.44%
64K/C16	1258.97	1283.10	+1.92%	0.735	0.761	4.672	4.803	2188.7	2154.6	8.480	7.880	0.17%	16.06%
128K/C1	215.29	191.65	-10.98%	0.798	0.687	4.991	4.433	487.8	493.1	4.172	4.740	2.75%	1.67%
128K/C8	916.97	847.18	-7.61%	0.805	0.718	5.020	4.588	1075.1	1067.4	7.093	7.702	1.27%	0.26%
128K/C16	1153.14	1062.61	-7.85%	0.766	0.655	4.830	4.281	3395.6	3462.6	8.197	9.586	2.88%	2.03%

GPU0-7 资源对比

GPU	A Util	B Util	A Mem GiB	B Mem GiB	A Peak GiB	B Peak GiB	A Power W	B Power W
GPU0	95.7%	95.6%	46.97	50.19	48.40	53.61	185.1	184.5
GPU1	96.2%	96.6%	47.16	50.37	48.58	53.80	190.6	189.7
GPU2	96.3%	96.3%	47.16	50.37	48.58	53.80	192.5	191.8
GPU3	95.9%	95.5%	47.16	50.37	48.58	53.80	187.8	187.9
GPU4	95.6%	95.7%	47.16	50.37	48.58	53.80	183.0	182.6
GPU5	96.1%	95.7%	47.16	50.37	48.58	53.80	189.4	189.0
GPU6	94.6%	95.3%	47.16	50.37	48.58	53.80	191.0	190.8
GPU7	93.1%	94.5%	46.97	50.19	48.40	53.61	183.8	184.3

配置 A：0.85 / 16K / 16 · 30组详细结果

Ctx	C	R	Gen	AR	AL	TTFT mean/p50/p95	TPOT	ITL	Peak GiB	Power	OK	Err/TO
1K	1	1	170.75	0.408	3.041	208.0/207.4/211.8	5.659	5.659	45.39	161.0	30	0/0
1K	1	2	164.81	0.386	2.931	208.0/207.6/211.3	5.870	5.870	45.39	161.6	30	0/0
1K	8	1	760.25	0.545	3.726	789.3/228.6/2577.2	8.887	8.887	45.39	180.7	30	0/0
1K	8	2	849.02	0.522	3.606	385.3/230.2/1306.8	8.409	8.409	45.39	196.4	30	0/0
1K	16	1	1015.33	0.400	3.003	2826.4/3432.0/4382.1	11.920	11.920	45.76	212.0	30	0/0
1K	16	2	1173.18	0.398	2.988	940.6/462.1/1958.9	11.761	11.761	45.76	221.8	30	0/0
4K	1	1	173.49	0.434	3.170	209.3/209.4/212.3	5.565	5.565	45.76	161.3	30	0/0
4K	1	2	184.32	0.475	3.375	210.6/209.4/215.5	5.225	5.225	45.76	161.4	30	0/0
4K	8	1	721.69	0.442	3.211	806.8/236.0/2153.2	9.189	9.189	45.76	188.2	30	0/0
4K	8	2	783.07	0.465	3.327	274.4/228.5/402.1	8.934	8.934	45.76	192.3	30	0/0
4K	16	1	1143.85	0.452	3.258	1488.0/1795.2/1861.4	10.944	10.944	45.76	214.4	30	0/0
4K	16	2	1194.25	0.435	3.174	934.0/545.3/1608.1	11.392	11.391	45.77	220.6	30	0/0
16K	1	1	192.85	0.528	3.637	233.6/232.1/247.0	4.962	4.962	47.50	160.8	30	0/0
16K	1	2	214.43	0.617	4.083	233.6/232.2/241.5	4.439	4.439	47.50	160.4	30	0/0
16K	8	1	846.74	0.566	3.824	611.2/265.4/1524.2	8.049	8.049	47.50	196.7	30	0/0
16K	8	2	847.13	0.539	3.696	375.0/262.2/646.9	8.240	8.240	47.50	196.2	30	0/0
16K	16	1	1228.44	0.584	3.919	2013.2/3187.9/3216.6	9.225	9.225	47.51	203.7	30	0/0
16K	16	2	1251.51	0.589	3.949	1179.6/790.4/3224.7	8.756	8.756	47.51	211.6	30	0/0
64K	1	1	223.05	0.732	4.664	347.0/339.1/402.2	4.148	4.148	48.44	157.6	30	0/0
64K	1	2	236.96	0.794	4.972	341.1/336.1/351.9	3.890	3.890	48.44	157.6	30	0/0
64K	8	1	961.73	0.790	4.942	862.6/537.8/1879.7	6.946	6.946	48.45	196.4	30	0/0
64K	8	2	960.76	0.790	4.947	683.3/394.5/1412.6	6.883	6.883	48.45	196.1	30	0/0
64K	16	1	1257.90	0.747	4.733	2405.8/2457.1/6942.2	8.395	8.395	48.46	208.7	30	0/0
64K	16	2	1260.03	0.723	4.611	1971.6/2449.7/2460.4	8.566	8.566	48.46	209.0	30	0/0
128K	1	1	218.25	0.815	5.074	487.3/486.5/501.5	4.109	4.109	48.57	152.9	30	0/0
128K	1	2	212.33	0.782	4.909	488.2/483.3/514.2	4.236	4.236	48.57	152.0	30	0/0
128K	8	1	922.77	0.818	5.087	1118.4/689.5/2282.0	6.918	6.918	48.58	193.9	30	0/0
128K	8	2	911.17	0.791	4.954	1031.7/571.1/2270.1	7.267	7.267	48.58	196.0	30	0/0
128K	16	1	1169.77	0.801	5.007	3388.1/4051.8/7540.2	7.974	7.974	48.58	206.7	30	0/0
128K	16	2	1136.51	0.731	4.654	3403.0/4183.4/7338.4	8.421	8.421	48.58	209.8	30	0/0

配置 B：0.90 / 32K / 16 · 30组详细结果

Ctx	C	R	Gen	AR	AL	TTFT mean/p50/p95	TPOT	ITL	Peak GiB	Power	OK	Err/TO
1K	1	1	167.41	0.399	2.996	206.1/206.1/208.2	5.777	5.777	47.26	160.8	30	0/0
1K	1	2	167.49	0.399	2.995	207.9/206.9/216.0	5.773	5.773	47.26	161.2	30	0/0
1K	8	1	794.42	0.463	3.312	405.7/227.3/1165.1	8.659	8.659	47.26	189.3	30	0/0
1K	8	2	844.57	0.480	3.398	357.8/226.4/1030.9	8.626	8.626	47.26	192.2	30	0/0
1K	16	1	1253.90	0.538	3.686	2243.3/2938.5/2944.8	9.553	9.553	47.69	204.1	30	0/0
1K	16	2	1528.32	0.543	3.721	653.7/470.2/905.8	8.991	8.991	47.69	214.4	30	0/0
4K	1	1	177.23	0.451	3.251	207.6/206.7/210.6	5.445	5.444	47.69	160.9	30	0/0
4K	1	2	190.84	0.502	3.512	208.5/208.0/214.6	5.041	5.041	47.69	161.2	30	0/0
4K	8	1	752.93	0.448	3.245	584.8/228.4/1528.2	9.161	9.161	47.70	197.8	30	0/0
4K	8	2	805.80	0.473	3.366	271.3/226.9/399.6	8.878	8.878	47.70	195.2	30	0/0
4K	16	1	1084.69	0.443	3.220	1579.9/1650.1/2396.1	11.412	11.412	47.70	209.0	30	0/0
4K	16	2	1186.83	0.419	3.098	864.7/543.7/1770.8	11.419	11.419	47.70	223.9	30	0/0
16K	1	1	214.90	0.620	4.099	233.4/231.1/249.5	4.429	4.429	49.38	160.8	30	0/0
16K	1	2	217.41	0.629	4.146	234.6/232.9/243.7	4.374	4.374	49.38	159.4	30	0/0
16K	8	1	887.57	0.618	4.089	605.4/262.9/1512.6	7.497	7.497	49.38	193.5	30	0/0
16K	8	2	884.80	0.586	3.927	391.5/332.5/597.5	7.794	7.794	49.38	194.1	30	0/0
16K	16	1	1280.25	0.610	4.053	1637.0/2252.5/2259.2	9.078	9.077	49.38	206.6	30	0/0
16K	16	2	1282.33	0.589	3.948	934.3/775.0/1337.5	9.012	9.012	49.38	216.0	30	0/0
64K	1	1	231.76	0.772	4.860	343.7/338.5/359.3	3.982	3.982	53.60	157.3	30	0/0
64K	1	2	223.09	0.732	4.661	346.7/340.6/392.2	4.147	4.147	53.60	156.4	30	0/0
64K	8	1	944.75	0.766	4.826	831.4/543.2/1892.6	6.977	6.977	53.61	191.4	30	0/0
64K	8	2	903.68	0.686	4.429	761.3/642.1/1420.1	7.312	7.312	53.61	196.2	30	0/0
64K	16	1	1386.12	0.869	5.347	2070.1/2441.8/4636.1	7.652	7.652	53.61	202.6	30	0/0
64K	16	2	1180.08	0.653	4.259	2239.1/2276.3/7395.5	8.108	8.108	53.61	200.5	30	0/0
128K	1	1	193.25	0.695	4.475	493.7/487.8/531.0	4.696	4.696	53.79	153.8	30	0/0
128K	1	2	190.05	0.679	4.392	492.4/487.1/526.5	4.784	4.784	53.79	153.9	30	0/0
128K	8	1	848.28	0.707	4.536	1101.2/593.8/2410.7	7.742	7.742	53.79	198.4	30	0/0
128K	8	2	846.08	0.728	4.639	1033.7/569.3/2285.9	7.661	7.661	53.79	195.3	30	0/0
128K	16	1	1073.38	0.675	4.376	3473.7/3795.5/8244.3	9.458	9.458	53.80	209.1	30	0/0
128K	16	2	1051.84	0.636	4.185	3451.4/3908.3/7780.0	9.714	9.714	53.80	211.5	30	0/0

结论与测量口径

32K chunk 在部分中短上下文及高并发场景提高吞吐，但在 128K 场景降低吞吐并增加 TPOT。最终配置应依据主要流量的 Context 分布选择，而不是仅依据单一峰值。Gen 为组级聚合吞吐；AR/AL 来自服务日志；流式响应用于 TTFT/TPOT/ITL；GPU 每 0.5 秒采样。