


Question	Answer	Marks
4(a)	<p>1 mark per bullet point to max 2</p> <ul style="list-style-type: none"> • All computers are of equal status • Each computer provides access to resources and data // data is distributed • Computers can communicate and share resources • Each computer is responsible for its own security 	2
4(b)	<p>1 mark per bullet point to max 2 per drawback</p> <ul style="list-style-type: none"> • Reduced security // no central management of security • ... only as secure as the weakest computer on the network • ... each computer is at risk from viruses from other computers • No central management of backup • ... if the data from one computer is not backed up it is lost to all of them • No central management of files/software • ... consistency may be difficult to maintain • ... each computer may have different software from the others • Individual computers may respond slower • ... because they are being accessed by other computers • In order to share files etc. all the computers involved need to be switched on • ... so the files etc. may not be always available 	4

Question	Answer	Marks															
4(c)(i)	<p>1 mark for first 2 ticks, 1 mark for last 2 (shaded)</p> <table> <tr> <th>Task</th><th>Performed by router</th><th>Not performed by router</th></tr> <tr> <td>Receives packets from devices</td><td>✓</td><td></td></tr> <tr> <td>Finds the IP address of a Uniform Resource Locator (URL)</td><td></td><td>✓</td></tr> <tr> <td>Directs each packet to all devices attached to it</td><td></td><td>✓</td></tr> <tr> <td>Stores the IP and/or MAC address of all devices attached to it</td><td>✓</td><td></td></tr> </table>	Task	Performed by router	Not performed by router	Receives packets from devices	✓		Finds the IP address of a Uniform Resource Locator (URL)		✓	Directs each packet to all devices attached to it		✓	Stores the IP and/or MAC address of all devices attached to it	✓		2
Task	Performed by router	Not performed by router															
Receives packets from devices	✓																
Finds the IP address of a Uniform Resource Locator (URL)		✓															
Directs each packet to all devices attached to it		✓															
Stores the IP and/or MAC address of all devices attached to it	✓																
4(c)(ii)	<p>1 mark per bullet point for justification up to max 3</p> <p>No mark for identification of wired/wireless</p> <p>Wired</p> <ul style="list-style-type: none"> • Faster connection // higher bandwidth • needed as she is downloading/streaming large files • ... less time waiting / less latency / fewer delays • More reliable / stable connection • ... is less susceptible to issues with distance/walls/interference • More secure <p>Wireless</p> <ul style="list-style-type: none"> • Freedom of movement • ... can move between different rooms with a mobile device and still receive/transmit data • ... no need of a physical connection • Easily expanded if friends want to access the same network • Less cabling / expertise is needed • ... making the initial setup less expensive 	3															
4(d)	<p>1 mark for identifying that she is using both.</p> <p>1 mark per bullet point for justification</p> <ul style="list-style-type: none"> • using internet because sending data on the infrastructure • using WWW because accessing a website (that is stored on a web server operated by the webmail) that is part of the WWW 	3															

5(d)

1 mark for each correct line

4



Question	Answer	Marks
8(a)	1 mark per bullet point <ul style="list-style-type: none"> • LAN • Small geographical area • No leasing external infrastructure / transmission media // does not use internet to transmit within the building 	3
8(b)	1 mark per item <ul style="list-style-type: none"> • router • switch • hub 	2
8(c)	1 mark per bullet point to max 4 <ul style="list-style-type: none"> • Provide interface to wireless network • ... as an antenna • Receives analogue radio waves • ... convert them to digital / binary • Checks incoming transmissions for correct MAC / IP address • ... ignore transmissions not intended for it • Encrypts / encodes the data • Decrypts / decodes the data • Takes digital/binary input and converts to analogue waves • ... sends the radio waves via the antenna 	4

Question	Answer	Marks
9(a)	<p>1 mark per difference</p> <ul style="list-style-type: none"> • Private IP is only known within the LAN // Public IP is known outside of the LAN/ on Internet • Public is allocated by ISP // Private is allocated by the router • Public addresses are unique throughout the Internet, private addresses are unique only within the LAN • Private IP addresses are more secure than public IP addresses 	2

Question	Answer	Marks										
9(b)	<p>1 mark for each correct term</p> <table><tr><th>Description</th><th>Term</th></tr><tr><td>Receives data packets from a network and forwards them onto a similar network</td><td>Router</td></tr><tr><td>Manages access to a centralised resource</td><td>Server</td></tr><tr><td>Joins networks that use different sets of rules to transmit data</td><td>Gateway</td></tr><tr><td>Monitors and controls incoming and outgoing network traffic based on set criteria</td><td>Firewall</td></tr></table>	Description	Term	Receives data packets from a network and forwards them onto a similar network	Router	Manages access to a centralised resource	Server	Joins networks that use different sets of rules to transmit data	Gateway	Monitors and controls incoming and outgoing network traffic based on set criteria	Firewall	4
Description	Term											
Receives data packets from a network and forwards them onto a similar network	Router											
Manages access to a centralised resource	Server											
Joins networks that use different sets of rules to transmit data	Gateway											
Monitors and controls incoming and outgoing network traffic based on set criteria	Firewall											

Question	Answer	Marks
11(a)	<p>One mark per bullet point to max 2</p> <ul style="list-style-type: none"> • Web pages/files are saved on servers • Clients send requests to the web servers • Web servers process the requests • ...and return the results to the client • ... client displays the results to the user 	2
11(b)	<p>One mark per bullet point to max 3</p> <p>IPv4</p> <ul style="list-style-type: none"> • Four groups of (denary or Hexadecimal integers) • Numbers between 0 and 255 / 0 and FF • Each stored in 1 byte / 8 bits // the whole is stored in 32 bits / 4 bytes • Separated by full stops • Correct example <p>OR</p> <p>IPv6</p> <ul style="list-style-type: none"> • Eight groups of (Hexadecimal) digits • Numbers between 0 and FFFF • Each stored in 2 bytes/16 bits // the whole stored in 128 bits / 16bytes • Separated by colons • The first instance of multiple groups of zero can be replaced by a double colon • correct example 	3

Question	Answer	Marks
5(a)(i)	<p>1 mark for real-time</p> <p>1 mark per bullet point for justification to max 2</p> <ul style="list-style-type: none"> • It is being watched live • It is not being downloaded to watch later // not already stored online 	3
5(a)(ii)	<p>1 mark per bullet point to max 3</p> <ul style="list-style-type: none"> • Insufficient bandwidth // slow internet connection • ... experiencing problems with buffering • Video is too high quality to stream in real-time • Congestion on the home network • Too much demand for the video from the supplier • Too many applications running on Oscar's computer • Oscar is trying to watch the video in High Definition, his friend is watching the video at a lower resolution 	3

Question	Answer	Marks
8(a)	<p>1 mark per bullet point to max 4</p> <ul style="list-style-type: none"> • The router needs a public IP address so it can be identified on the Internet • The router needs a private IP address so it can be identified on the home network • The router has a public and a private IP address so that it can route data between the two networks (home and Internet) • The laptop needs a private IP address so it can be identified on the home network // so the router knows where to send data • The laptop does not have a public IP address because it does not connect directly to the Internet • ... this is more secure because it hides the laptop from the outside world • ... all data from the Internet must be transmitted via the router 	4
8(b)	<p>1 mark per bullet point to max 3</p> <ul style="list-style-type: none"> • The browser parses the Uniform Resource Locator (URL) to obtain the Domain Name • The domain name is looked-up in the locally cached list of corresponding IP addresses. If it is not found... • The domain name is sent to the closest Domain Name Server (DNS) • The DNS stores a table of Domain Names and corresponding IP addresses // searches its database of Domain Names and corresponding IP • If the DNS finds the Domain Name, it returns the IP address • If it cannot find the Domain Name, it sends the request to a higher DNS / upstream server • If the Domain Name is not found, an error is returned 	3
8(c)	<p>1 mark for any valid example e.g. 192.168.0.1</p>	1