Status	Finished
Started	Wednesday, 21 October 2026, 11:07 AM
Completed	Wednesday, 21 October 2026, 11:13 AM
Duration	5 mins 47 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open("a.txt", "r") ✓

b. infile = open(file = "a.txt", "r")

c. infile = open(file = "a.txt", "r")

d. infile = open(file, "a.txt", "r")

The correct answer is:
infile = open("a.txt", "r")

Question **2**

Correct

Mark 1.00 out of 1.00

Which method is used to close a file in Python?

a. terminate()

b. end()

c. finish()

d. close() ✓

The correct answer is: close()

Question **3**

Correct

Mark 1.00 out of 1.00

What does the seek() method do in file handling?

a. Reads the file line by line

b. Moves the file cursor to the specified position ✓

c. Writes data to the file

d. Deletes the file

The correct answer is: Moves the file cursor to the specified position

Question **4**

Correct

Mark 1.00 out of 1.00

Which method is used to get the current file position?

- a. tell() ✓
- b. current()
- c. position()
- d. locate()

The correct answer is: tell()

Question **5**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

- a. fseek()
- b. tell()
- c. seek() ✓
- d. ftell()

The correct answer is: seek()

Question **6**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

- a. open() ✓
- b. file()
- c. open_file()
- d. openfile()

The correct answer is: open()

Question **7**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. An empty file object is returned
b. The operation is ignored
c. An error is raised ✓
d. A new file is created

The correct answer is: An error is raised

Question **8**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

a. insert()
b. write() ✓
c. read()
d. append()

The correct answer is: write()

Question **9**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. • Move file pointer five characters ahead from the current position. ✓

b. Move file pointer five characters ahead from the beginning

c. • Move file pointer five characters behind ahead from the end of a file.

d. • Move file pointer five characters behind from the current position.

The correct answer is:

- Move file pointer five characters ahead from the current position.

Question **10**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

a. a list of integers

b. a list of single characters

c. str

d. a list of lines ✓

The correct answer is:
a list of lines

Question **11**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

- a. truncate() ✓
- b. reduce()
- c. shrink()
- d. resize()

The correct answer is: truncate()

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following is true about the readlines() method?

- a. It reads the file and returns it as a dictionary
- b. It reads the entire file and returns it as a list of lines ✓
- c. It reads a single line from the file
- d. It reads the entire file and returns it as a string

The correct answer is: It reads the entire file and returns it as a list of lines

Question **13**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

- a. readline() ✓
- b. line()
- c. readlines(1)
- d. read(1)

The correct answer is: readline()

Question **14**

Correct

Mark 1.00 out of 1.00

What does the following code do?

```
fo = open("foo.txt", "w")
```

a. Appends to an existing file

b. Opens an existing file in read mode

c. Opens a file in binary mode

d. Creates a new file for writing ✓

The correct answer is: Creates a new file for writing

Question **15**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. move the file pointer five characters behind from the current position

b. moves the file pointer to the end of a file

c. move the file pointer to beginning of the file

d. move the file pointer five characters ahead from the current position ✓

The correct answer is:
move the file pointer five characters ahead from the current position