

## C Quiz 7 Q&A (30-11-2023)

```
1. #include<stdio.h>
#include<string.h>
#include<stdlib.h>

int main()
{
    char *s;
    char *fun();
    s = fun();
    printf("%s\n", s);
    return 0;
}
char *fun()
{
    char *buffer;
    buffer = (char*)malloc(sizeof(char)*5);
    strcpy(buffer, "RAM");
    return (buffer);
}
```

### Answers

1. Segmentation fault
2. compile time error :function returns address of local variable
3. RAM
4. none of these

2. note: consider 64 bit compilation

```
#include<stdio.h>
#include<stdlib.h>

int main()
{
    int *a[3];
    a[0] = (int*) malloc(sizeof(int)*3);
    a[1] = (int*) malloc(sizeof(int)*3);
    a[2] = (int*) malloc(sizeof(int)*3);

    printf("\n sizeof(a) = %d \n",sizeof(a));
    free(a);
    return 0;
}
```

### Answers

1. sizeof(a) = 24 unable to allocate memory
2. sizeof(24) = 24, 36bytes of memory allocated and segmentation fault
3. sizeof(24) = 24, 36bytes of memory allocated and freeup memory allocated by all malloc.
4. sizeof(24) = 12, 36bytes of memory allocated and segmentation fault

3. Find the output of the following

```
int main()
{
    char *cptr = calloc((char)127,1);
    strcpy(cptr,"sunbeam pune");
    free(*cptr);
    return 0;
}
```

Answers

1. compiler error
2. runtime error
3. will deallocate memory successfully
4. None of the above

4. what will be the output of this code?

```
#include<stdio.h>
#define a 10
#define z(a) a-1
#define SQR(x) (x*x)
int main()
{
    int c, b=3;
    c = z(a) * SQR(b+2);
    printf("%d\n", c);
    return 0;
}
```

Answers

1. -1
2. 225
3. 99
4. 5

5. What is the output of C program with #define.?

```
#define Q 156
int main()
{
    int a=10;
    a = a*'Q';
    printf("a=%d",a);
    return 0;
}
```

Answers

1. 1560
2. 156
3. 810
4. 1130

6. What will be the output of the C program?

```
#include<stdio.h>
#define i 10
int main()
{
    #define i 20
    printf("%d",i);
    return 0;
}
```

Answers

1. Compilation error
2. 20
3. 30
4. Runtime error

7. What will be output of following code?

```
#include<stdio.h>
#define p 11+2
int main()
{
    int i;
    i=p++ * p++;
    printf("%d",i);
    return 0;
}
```

Answers

1. 35
2. 26
3. 169
4. lvalue required error

8. What is the output of C program

```
#include<stdio.h>
#define CONDITION(x)\
printf("Machine Learning\n"+8);
int main()
{
    CONDITION(0);
    return 0;
}
```

Answers

1. Runtime Error
2. Compilation error
3. Learning
4. 0

9. What is the output of C program

```
#include <stdio.h>
#define p 24;
int main()
{
    printf("%d",p);
    return 0;
}
```

Answers

1. Garbage value
2. Runtime error
3. 24
4. Compilation error

```
10. #include<stdio.h>
#include<stdlib.h>
int main()
{
    char *ptr=NULL;
    int alloc_length =16 ;
    int new_length;

    ptr = (char *)malloc(sizeof(char)*alloc_length);

    ptr = realloc(ptr, alloc_length << 1);

    free(ptr);
    ptr=NULL;

    return 0;
}
```

Answers

1. allocated 16bytes and free 32bytes
2. allocated 32bytes and free 32bytes
3. allocated 32bytes and free 16bytes
4. allocated 16bytes and free 16bytes

-----Compiled by Utkarsh Singh -----

**ATTENTION :** This material is strictly confidential and intended solely for your use. It is imperative that you do not disseminate or share this material with the public, under any circumstances. Any breach of confidentiality will result in severe consequences. Protect the integrity of this material and the trust placed in you.