1. Write a query that lists each order number followed by the name of the customer who made the order.

```
d1_96343_yogesh@localhost [sales]> select c.cname , o.onum FROM customers c inner join orders o on o.cnum=c.cnum ;
+----------+------+
| cname    | onum |
+----------+------+
| Cisneros | 3001 |
| Hoffman  | 3003 |
| Pereira  | 3002 |
| Liu      | 3005 |
| Cisneros | 3006 |
| Giovanni | 3009 |
| Grass    | 3007 |
| Clemens  | 3008 |
| Grass    | 3010 |
| Clemens  | 3011 |
+----------+------+
10 rows in set (0.001 sec)
```

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
d1_96343_yogesh@localhost [sales]> select c.cname , o.onum, s.sname FROM customers c inner join orders o on o.cnum=c.cnum inner join salespeople s on o.snum = s.
snum  ;
+----------+------+---------+
| cname    | onum | sname   |
+----------+------+---------+
| Hoffman  | 3003 | Peel    |
| Giovanni | 3009 | Axelrod |
| Liu      | 3005 | Serres  |
| Grass    | 3010 | Serres  |
| Grass    | 3007 | Serres  |
| Clemens  | 3011 | Peel    |
| Clemens  | 3008 | Peel    |
| Cisneros | 3006 | Rifkin  |
| Cisneros | 3001 | Rifkin  |
| Pereira  | 3002 | Motika  |
+----------+------+---------+
10 rows in set (0.001 sec)
```

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
d1_96343_yogesh@localhost [sales]> select c.cname , s.sname , s.comm from customers c inner join salespeople s on c.snum = s.snum  where comm>0.12 ;
+----------+--------+------+
| cname    | sname  | comm |
+----------+--------+------+
| Liu      | Serres | 0.13 |
| Grass    | Serres | 0.13 |
| Cisneros | Rifkin | 0.15 |
+----------+--------+------+
3 rows in set (0.001 sec)
```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
join salespeople s on s.snum = o.snum' at line 1
d1_96343_yogesh@localhost [sales]> select o.onum , o.amt*s.comm  from customers c inner join orders o on c.cnum = o.cnum  inner join salespeople s on s.snum = o.
snum where c.rating>100;
+------+--------------+
| onum | o.amt*s.comm |
+------+--------------+
| 3010 |      40.2935 |
| 3007 |       9.8475 |
| 3005 |     670.8585 |
| 3006 |     164.7240 |
| 3001 |       2.8035 |
| 3009 |     171.3230 |
+------+--------------+
6 rows in set (0.001 sec)
```

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed .

```
[d1_96343_yogesh@localhost [sales]> select s.city,s.sname , s1.sname  from salespeople s inner join salespeople s1 on s1.city = s.city where s.snum!=s1.snum and s
.snum>s1.snum ;
+--------+--------+-------+
| city   | sname  | sname |
+--------+--------+-------+
| London | Motika | Peel  |
+--------+--------+-------+
1 row in set (0.001 sec)
```