1. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
d1_96343_yogesh@localhost [sales]> SELECT * FROM customers WHERE snum=1001;
+------+---------+--------+--------+------+
| cnum | cname   | city   | rating | snum |
+------+---------+--------+--------+------+
| 2001 | Hoffman | London |    100 | 1001 |
| 2006 | Clemens | London |    100 | 1001 |
+------+---------+--------+--------+------+
2 rows in set (0.000 sec)
```

2. Write a select command that produces the rating followed by the name of each customer in San Jose.

```
d1_96343_yogesh@localhost [sales]> SELECT * FROM customers;
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2001 | Hoffman  | London   |    100 | 1001 |
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2006 | Clemens  | London   |    100 | 1001 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
| 2007 | Pereira  | Rome     |    100 | 1004 |
+------+----------+----------+--------+------+
7 rows in set (0.001 sec)

d1_96343_yogesh@localhost [sales]> SELECT cname,rating FROM customers WHERE city='San Jose';
+----------+--------+
| cname    | rating |
+----------+--------+
| Liu      |    200 |
| Cisneros |    300 |
+----------+--------+
2 rows in set (0.000 sec)

d1_96343_yogesh@localhost [sales]>
```

3. Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
d1_96343_yogesh@localhost [sales]> SELECT DISTINCT snum FROM customers ;
+------+
| snum |
+------+
| 1001 |
| 1003 |
| 1002 |
| 1007 |
| 1004 |
+------+
5 rows in set (0.001 sec)

d1_96343_yogesh@localhost [sales]>
```

4. Write a query that will display all the orders for amount more than Rs. 1,000.

```
d1_96343_yogesh@localhost [sales]> SELECT * FROM orders;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 |   75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
10 rows in set (0.001 sec)

d1_96343_yogesh@localhost [sales]> SELECT * FROM orders WHERE amt>1000.0;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
6 rows in set (0.001 sec)

d1_96343_yogesh@localhost [sales]>
```

5. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
d1_96343_yogesh@localhost [sales]> SELECT * FROM salespeople WHERE comm>0.10;
+------+--------+-----------+------+
| snum | sname  | city      | comm |
+------+--------+-----------+------+
| 1001 | Peel   | London    | 0.12 |
| 1002 | Serres | San Jose  | 0.13 |
| 1004 | Motika | London    | 0.11 |
| 1007 | Rifkin | Barcelona | 0.15 |
+------+--------+-----------+------+
4 rows in set (0.001 sec)

d1_96343_yogesh@localhost [sales]>
```

6. Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```
d1_96343_yogesh@localhost [sales]> SELECT * FROM customers WHERE rating>100 OR city = 'Rome';
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
| 2007 | Pereira  | Rome     |    100 | 1004 |
+------+----------+----------+--------+------+
5 rows in set (0.000 sec)

d1_96343_yogesh@localhost [sales]>
```

7. What will be the output from the following query?
Select * from Orders where (amt < 1000 OR NOT (odate = ‘1990-10-03’ AND cnum > 2003));

```
d1_96343_yogesh@localhost [sales]> Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 |   75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
8 rows in set (0.001 sec)
```

8. What will be the output of the following query?
Select * from Orders where NOT (odate = ‘1990-10-03’ OR snum >1006) AND amt >= 1500;

```
d1_96343_yogesh@localhost [sales]> Select * from Orders where NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
3 rows in set (0.001 sec)

d1_96343_yogesh@localhost [sales]>
```

9. What is a simpler way to write this query?
Select snum, sname, city, comm from Salespeople
Where (comm >= .12 AND comm <= .14);

```
d1_96343_yogesh@localhost [sales]> SHOW TABLES;
+-----------------+
| Tables_in_sales |
+-----------------+
| customers       |
| orders          |
| salespeople     |
+-----------------+
3 rows in set (0.002 sec)

d1_96343_yogesh@localhost [sales]> SELECT snum,sname,city,comm from salespeople WHERE comm BETWEEN .12 AND .14;
+------+---------+----------+------+
| snum | sname   | city     | comm |
+------+---------+----------+------+
| 1001 | Peel    | London   | 0.12 |
| 1002 | Serres  | San Jose | 0.13 |
+------+---------+----------+------+
2 rows in set (0.001 sec)

d1_96343_yogesh@localhost [sales]>
```

10. Write a query that selects all orders except those
with amount less than 100.

```
10 rows in set (0.001 sec)

d1_96343_yogesh@localhost [sales]> SELECT * FROM orders WHERE NOT  amt<100;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 |  309.95 | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+------+---------+------------+------+------+
8 rows in set (0.002 sec)

d1_96343_yogesh@localhost [sales]>
```