


Sequence Tagging with Tensorflow

Apr 5, 2017

Code is available on [github](#).

Introduction

I remember the first time I heard about the magic of Deep Learning for **Natural Language Processing (NLP)**. I was just starting a project with a young French startup [Riminder](#) and it was the first time I heard about word embeddings. There are moments in life when the confrontation with a new theory seems to make everything else irrelevant. Hearing about word vectors that encode similarity and meaning between words was one of these moments. I was baffled by the simplicity of the model as I started to play with these new concepts, building my first recurrent neural network for sentiment analysis. A few months later, as part of the master thesis of my master in the French university [Ecole polytechnique](#) I was working on more advanced models for sequence tagging at [Proxem](#).



Tensorflow vs Theano At that time, Tensorflow had just been open sourced and Theano

was the most widely used framework. For those who are not familiar with the two, Theano operates at the matrix level while Tensorflow comes with a lot of pre-coded layers and helpful training mechanisms. Using Theano was sometimes painful but forced me to pay attention to the tiny details hidden in the equations and have a global understanding of how a deep learning library works.

Fastforward a few months: I'm in Stanford and I'm using Tensorflow. One day, here I am, asking myself: "What if you tried to code one of the sequence tagging models in Tensorflow? How long would it take?". The answer is: no more than a few hours.

This post's ambition is to provide an example of how to use Tensorflow to build a state-of-the-art model (similar to this [paper](#)) for sequence tagging and share some exciting NLP knowledge!

Together with this post, I am releasing the [code](#) and hope some will find it useful. You can use it to train your own sequence tagging model. I'll assume conceptual knowledge about Recurrent Neural Networks. By the way, at this point I have to share my admiration for [karpathy's blog](#) (and this post in particular "The Unreasonable Effectiveness of Recurrent Neural Networks"). For readers new to NLP, have a look at the amazing [Stanford NLP class](#).

Task and Data

First, let's discuss what Sequence Tagging is. Depending on your background, you may have heard of it under different names: *Named Entity Recognition*, *Part-of-Speech Tagging*, etc. We'll focus on **Named Entity Recognition (NER)** for the rest of this post. You can check [Wikipedia](#). One example is:

```
John  lives in New    York  and works for the European Union
B-PER O      O  B-LOC I-LOC O    O      O    O    B-ORG  I-ORG
```

In the [CoNLL2003 task](#), the entities are `LOC`, `PER`, `ORG` and `MISC` for *locations*, *persons*, *organizations* and *miscellaneous*. The no-entity tag is `O`. Because some entities (like `New York`) have multiple words, we use a *tagging scheme* to distinguish between the beginning (tag `B-...`), or the inside of an entity (tag `I-...`). Other tagging schemes exist (IOBES, etc). However, if we just pause for a sec and think about it in an abstract manner, we just need a system that assigns a class (a number corresponding to a tag) to each word in a sentence.

"But wait, why is it a problem? Just keep a list of locations, common names and organizations!"

I am glad you asked this question. What makes this problem non-trivial is that a lot of entities, like names or organizations are just made-up names for which we don't have any prior knowledge. Thus, what we really need is something that will extract contextual information from the sentence, just like humans do!

For our implementation, we are assuming that the data is stored in a `.txt` file with one word and its entity per line, like the following example

```
EU B-ORG
rejects O
German B-MISC
call O
to O
boycott O
British B-MISC
lamb O
. O

Peter B-PER
Blackburn I-PER
```

Model

“Let me guess... LSTM?”


You're right. Like most of the NLP systems, ours is gonna rely on a recurrent neural network at some point. But before delving into the details of our model, let's break it into 3 pieces:

- **Word Representation:** we need to use a dense representation $w \in \mathbb{R}^n$ for each word. The first thing we can do is load some pre-trained word embeddings $w_p \in \mathbb{R}^d$ ([GloVe](#), [Word2Vec](#), [Senna](#), etc.). We're also going to extract some meaning from the characters. As we said, a lot of entities don't even have a pretrained word vector, and the fact that the word starts with a capital letter may help for instance.
- **Contextual Word Representation:** for each word in its context, we need to get a meaningful representation $h \in \mathbb{R}^k$. Good guess, we're gonna use an LSTM here.
- **Decoding:** the ultimate step. Once we have a vector representing each word, we can use it to make a prediction.

Word Representation

For each word, we want to build a vector $w \in \mathbb{R}^n$ that will capture the meaning and relevant

features for our task. We're gonna build this vector as a concatenation of the word embeddings $w_p \in \mathbb{R}^{d_1}$ from GloVe and a vector containing features extracted from the character level $w_c \in \mathbb{R}^k$. One option is to use hand-crafted features, like a component with a 0 or 1 if the word starts with a capital for instance. Another fancier option is to use some kind of neural network to make this extraction automatically for us. In this post, we're gonna use a bi-LSTM at the character level, but we could use any other kind of recurrent neural network or even a convolutional neural network at the character or n-gram level.



Word level representation from characters embeddings

Each character c_i of a word $w = [c_1, \dots, c_p]$ (we make the distinction between lowercase and uppercase, for instance `a` and `A` are considered different) is associated to a vector $c_i \in \mathbb{R}^{d_2}$. We run a bi-LSTM over the sequence of character embeddings and concatenate the final states to obtain a fixed-size vector $w_c \in \mathbb{R}^c$. Intuitively, this vector captures the morphology of the word. Then, we concatenate w_c to the word embedding w_p to get a vector representing our word $w = [w_p, w_c]$.

Let's have a look at the Tensorflow code. First let's load the word embeddings. Recall that as

Tensorflow receives batches of words and data, we need to pad sentences to make them the same length. As a result, we need to define 2 placeholders:

```
# shape = (batch size, max length of sentence in batch)
word_ids = tf.placeholder(tf.int32, shape=[None, None])

# shape = (batch size)
sequence_lengths = tf.placeholder(tf.int32, shape=[None])
```

Now, let's use tensorflow built-in functions to load the word embeddings. Assume that `embeddings` is an array with our GloVe embeddings.

```
L = tf.Variable(embeddings, dtype=tf.float32, trainable=False)
# shape = (batch, sentence, word_vector_size)
pretrained_embeddings = tf.nn.embedding_lookup(L, word_ids)
```

You should use `tf.Variable` with argument `trainable=False` instead of `tf.constant`, otherwise you risk memory issues!

Now, let's build our representation from the characters. As we need to pad words to make them the same length, we also need to define 2 placeholders:

```
# shape = (batch size, max length of sentence, max length of word)
char_ids = tf.placeholder(tf.int32, shape=[None, None, None])

# shape = (batch_size, max_length of sentence)
word_lengths = tf.placeholder(tf.int32, shape=[None, None])
```

"Wait, can we use `None` everywhere like that? Why do we need it?"

Well, that's up to us. It depends on how we perform our padding, but in this post we chose to do it dynamically, i.e. to pad to the maximum length in the batch. Thus, sentence length and word length will depend on the batch. Now, we can build the word embeddings from the characters. Here, we don't have any pretrained character embeddings, so we call `tf.get_variable` that will initialize a matrix for us using the default initializer (`xavier_initializer`). We also need to reshape our 4-dimensional tensor to match the requirement of `bidirectional_dynamic_rnn`. Pay extra attention to the type returned by this function. Also, the state of the lstm is a tuple of memory and hidden state.

```
# 1. get character embeddings
```

```

K = tf.get_variable(name="char_embeddings", dtype=tf.float32,
                    shape=[nchars, dim_char])
# shape = (batch, sentence, word, dim of char embeddings)
char_embeddings = tf.nn.embedding_lookup(K, char_ids)

# 2. put the time dimension on axis=1
s = tf.shape(char_embeddings)
# shape = (batch x sentence, word, dim of char embeddings)
char_embeddings = tf.reshape(char_embeddings, shape=[-1, s[-2], s[-1]])
word_lengths = tf.reshape(self.word_lengths, shape=[-1])

# 3. bi lstm on chars
cell_fw = tf.contrib.rnn.LSTMCell(char_hidden_size, state_is_tuple=True)
cell_bw = tf.contrib.rnn.LSTMCell(char_hidden_size, state_is_tuple=True)

_, ((_, output_fw), (_, output_bw)) = tf.nn.bidirectional_dynamic_rnn(cell_fw,
    cell_bw, char_embeddings, sequence_length=word_lengths,
    dtype=tf.float32)
# shape = (batch x sentence, 2 x char_hidden_size)
output = tf.concat([output_fw, output_bw], axis=-1)

# shape = (batch, sentence, 2 x char_hidden_size)
char_rep = tf.reshape(output, shape=[-1, s[1], 2*char_hidden_size])

# shape = (batch, sentence, 2 x char_hidden_size + word_vector_size)
word_embeddings = tf.concat([pretrained_embeddings, char_rep], axis=-1)

```

A special note on `tf.nn.bidirectional_dynamic_rnn` and the `LSTMCell`. You may have noticed that we use the “same” instance of the cell for the forward and backward. However, due to the fact that the parameters of the cell are initialized in the `__call__` method of the cell and that this method is called in 2 different scopes (created by `bidirectional_dynamic_rnn`), we end up with cells with distinct parameters. While this behavior is a good safeguard, it could be unpractical in some corner cases. Imagine for instance that we want to use the same cell for forward and backward...

EDIT:


Big changes to the `RNNCell`, to quote TF 1.2 release note: “`RNNCell` objects now subclass `tf.layers.Layer`. The strictness described in the TensorFlow 1.1 release is gone: The first time an `RNNCell` is used, it caches its scope. All future uses of the `RNNCell` will reuse variables from that same scope. This is a breaking change from the behavior of `RNNCells` in

*TensorFlow versions $\leq 1.0.1$. TensorFlow 1.1 had checks in place to ensure old code works correctly with the new semantics; this version allows more flexible uses of `RNNCell` but can lead to subtle errors if using code meant for TensorFlow $\leq 1.0.1$. For example, writing: `MultiRNNCell([lstm] * 5)` will now build a 5-layer LSTM stack where each layer shares the same parameters. To get 5 layers each with their own parameters, write: `MultiRNNCell([LSTMCell(...) for _ in range(5)])`. If at all unsure, first test your code with TF 1.1; ensure it raises no errors, and then upgrade to TF 1.2.”*

*Also note the use of the special argument `sequence_length` that ensures that the last state that we get is the last **valid** state. Thanks to this argument, for the invalid time steps, the `dynamic_rnn` passes the state through and outputs a vector of zeros.*

Contextual Word Representation

Once we have our word representation w , we simply run a LSTM (or bi-LSTM) over the sequence of word vectors and obtain another sequence of vectors (the hidden states of the LSTM or the concatenation of the two hidden states in the case of a bi-LSTM), $h_i \in \mathbb{R}^k$.



Bidirectional LSTM on top of word representation to extract contextual representation of each word

The tensorflow code is straightforward. This time we use the hidden states of each time step and not just the final states.

```
cell_fw = tf.contrib.rnn.LSTMCell(hidden_size)
cell_bw = tf.contrib.rnn.LSTMCell(hidden_size)

(output_fw, output_bw), _ = tf.nn.bidirectional_dynamic_rnn(cell_fw,
    cell_bw, word_embeddings, sequence_length=sequence_lengths,
    dtype=tf.float32)

context_rep = tf.concat([output_fw, output_bw], axis=-1)
```

Decoding

At this stage, each word w is associated to a vector h that captures information from the meaning of the word, its characters and its context. Let's use it to make a final prediction. We can use a fully connected neural network to get a vector where each entry corresponds to a score for each tag. Then, we have two options:

- for each word, normalize the score vector by using a **softmax** and take the **argmax** to make the final prediction at the **word level**.
- use a **Conditional Random Field (CRF)** to make the prediction at the **sentence level**.

In both cases, we want to be able to compute the probability $\mathbb{P}(y^1, \dots, y^m)$ of a tagging sequence y^t and find the sequence with the highest probability.

"Wait, can you explain the last steps? What's a CRF?"

Let's say we have 9 classes. We take a matrix $W \in \mathbb{R}^{9 \times k}$ and compute a vector of scores $s \in \mathbb{R}^9 = W \cdot h$. We can interpret $s_i \in \mathbb{R}$ as the score of class i for word w . One way to do this in tensorflow is:

```
W = tf.get_variable("W", shape=[2*self.config.hidden_size, self.config.n
                        dtype=tf.float32)

b = tf.get_variable("b", shape=[self.config.ntags], dtype=tf.float32,
                    initializer=tf.zeros_initializer())

ntime_steps = tf.shape(context_rep)[1]
context_rep_flat = tf.reshape(context_rep, [-1, 2*hidden_size])
pred = tf.matmul(context_rep_flat, W) + b
scores = tf.reshape(pred, [-1, ntime_steps, ntags])
```

Note that we use a `zero_initializer` for the bias.

Here we have two options:


- **softmax**: normalize the scores into a vector $p \in \mathbb{R}^9$ such that $p_i = \frac{e^{s_i}}{\sum_{j=1}^9 e^{s_j}}$. Then, p_i can be interpreted as the probability that the word belongs to class i . Eventually, the probability $\mathbb{P}(y)$ of a sequence of tag y is the product $\prod_t p_{y^t}$.
- **linear-chain CRF**: the first method makes local choices. In other words, even if we capture some information from the context in our h thanks to the bi-LSTM, the tagging decision is still local. We don't make use of the neighboring tagging decisions. For instance, in `New York`, the fact that we are tagging `York` as a location should help us to decide that `New` corresponds to the beginning of a location. Given a sequence of

words w^1, \dots, w^m , a sequence of score vectors s^1, \dots, s^m and a sequence of tags y^1, \dots, y^m , a linear-chain CRF defines a global score $s \in \mathbb{R}$ such that

$$s(y^1, \dots, y^m) = b_{y^1} + \sum_{t=1}^m s_{y^t}^t + \sum_{t=1}^{m-1} T_{y^t, y^{t+1}} + e_{y^m}$$

= start + scores + transitions + end

where T is a transition matrix in $\mathbb{R}^{9 \times 9}$ and $e, b \in \mathbb{R}^9$ are vectors of scores that capture the cost of beginning or starting with a given tag. The use of the matrix T captures linear (one step) dependencies between tagging decisions.



The path PER-O-LOC has a score of
 $1 + 10 + 4 + 3 + 2 + 11 + 0 = 31$

The path PER-PER-LOC has a score of
 $1 + 10 + 2 + 4 - 2 + 11 + 0 = 26$

Illustration of the scoring of a sentence with a linear-chain CRF. Between these two possible paths, the one with the best score is PER-O-LOC. Notice that if we make our decision locally, based on the score vector of each word, we would have chosen PER-PER-LOC

Now that we understand the scoring function of the CRF, we need to do 2 things:

1. Find the sequence of tags with the best score.
2. Compute a probability distribution over all the sequence of tags

"This sounds awesome, but don't we have a computational problem as the number of possible tag choices is exponential?"

Finding the best sequence Well, you're right. We cannot reasonably imagine to compute the scores of all the 9^m tagging choices to choose the best one or even normalize each sequence score into a probability. Luckily, the recurrent nature of our formula makes it the perfect candidate to apply dynamic programming. Let's suppose that we have the solution $\tilde{s}^{t+1}(y^{t+1})$ for time steps $t+1, \dots, m$ for sequences that start with y^{t+1} . Then, the solution $\tilde{s}^t(y^t)$ for time steps t, \dots, m that starts with y^t verifies

$$\begin{aligned} \tilde{s}^t(y^t) &= \operatorname{argmax}_{y^t, \dots, y^m} s(y^t, \dots, y^m) \\ &= \operatorname{argmax}_{y^{t+1}} s_{y^t}^t + T_{y^t, y^{t+1}} + \tilde{s}^{t+1}(y^{t+1}) \end{aligned}$$

Then, each recurrence step is done in $O(9 \times 9)$ (taking the argmax for each class). As we perform m steps, our final cost is $O(9 \times 9 \times m)$ which is much better.

Probability Distribution over the sequence of tags The final step of a linear chain CRF is to apply a softmax to the scores of all possible sequences to get the probability $\mathbb{P}(y)$ of a given sequence of tags y . To do that, we need to compute the partition factor

$$Z = \sum_{y^1, \dots, y^m} e^{s(y^1, \dots, y^m)}$$

which is the sum of the scores of all possible sequences. We can apply the same idea as above, but instead of taking the argmax, we sum over all possible paths. Let's call $Z^t(y^t)$ the sum of scores for all sequences that start at time step t with tag y^t . Then, Z^t verifies

$$\begin{aligned} Z^t(y^t) &= \sum_{y^{t+1}} e^{s_{y^t}^t + T_{y^t, y^{t+1}}} \sum_{y^{t+2}, \dots, y^m} e^{s(y^{t+1}, \dots, y^m)} \\ &= \sum_{y^{t+1}} e^{s_{y^t}^t + T_{y^t, y^{t+1}}} Z^{t+1}(y^{t+1}) \\ \log Z^t(y^t) &= \log \sum_{y^{t+1}} e^{s_{y^t}^t + T_{y^t, y^{t+1}}} + \log Z^{t+1}(y^{t+1}) \end{aligned}$$

Then, we can easily define the probability of a given sequence of tags as

$$\mathbb{P}(y^1, \dots, y^m) = \frac{e^{s(y^1, \dots, y^m)}}{Z}$$

Training

Now that we've explained the architecture of our model and spent some time on CRFs, a final word on our objective function. We are gonna use cross-entropy loss, in other words our loss is

$$-\log(\mathbb{P}(\tilde{y}))$$

where \tilde{y} is the correct sequence of tags and its probability \mathbb{P} is given by

- **CRF:** $\mathbb{P}(\tilde{y}) = \frac{e^{s(\tilde{y})}}{Z}$
- **local softmax:** $\mathbb{P}(\tilde{y}) = \prod p_{\tilde{y}^t}^t$.

"I'm afraid that coding the CRF loss is gonna be painful..."

Here comes the magic of open-source! Implementing a CRF only takes one-line! The

following code computes the loss and also returns the matrix T (`transition_params`) that will be useful for prediction.

```
# shape = (batch, sentence)
labels = tf.placeholder(tf.int32, shape=[None, None], name="labels")

log_likelihood, transition_params = tf.contrib.crf.crf_log_likelihood(
    scores, labels, sequence_lengths)

loss = tf.reduce_mean(-log_likelihood)
```

In the case of the local softmax, the computation of the loss is more classic, but we have to pay extra attention to the padding and use `tf.sequence_mask` that transforms sequence lengths into boolean vectors (masks).

```
losses = tf.nn.sparse_softmax_cross_entropy_with_logits(logits=scores, labels=labels)
# shape = (batch, sentence, nclasses)
mask = tf.sequence_mask(sequence_lengths, dtype=tf.bool)
# apply mask
losses = tf.boolean_mask(losses, mask)

loss = tf.reduce_mean(losses)
```

And then, finally, we can define our train operator as

```
optimizer = tf.train.AdamOptimizer(self.lr)
train_op = optimizer.minimize(self.loss)
```

Using the trained model

For the local softmax method, performing the final prediction is straightforward, the class is just the class with the highest score for each time step.

```
labels_pred = tf.cast(tf.argmax(self.logits, axis=-1), tf.int32)
```

For the CRF, we have to use dynamic programming, as explained above. Again, this only takes one line with tensorflow! Pay attention that we make the prediction for only one sample!

```
# shape = (sentence, nclasses)
score = ...
```

```
viterbi_sequence, viterbi_score = tf.contrib.crf.viterbi_decode(  
    score, transition_params)
```

With the previous code you should get an F1 score close to 90!

Conclusion

Tensorflow makes it really easy to implement any kind of deep learning system, as long as the layer you're looking for is already implemented. However, you'll still have to go to deeper levels if you're trying something new...

23 Comments

guillaumegenthial.github.io

1 Login ▾

♥ Recommend 9

🔗 Share

Sort by Best ▾



Join the discussion...

LOG IN WITH



OR SIGN UP WITH DISQUS ?

Name

**Kyeong-Min Nam** • 19 days ago

Thank you! Amazing tutorial

I am building a NER system similar to yours. I have tow questions

1) I want CNN to build a character-level word representation, However, adding the CNN layer causes an error in the LSTM step, what's wrong?

[char embedding_lookup step]

```
from keras.layers import Conv1D
char_cnn = Conv1D(filters=30,
kernel_size=3,
padding='same',
activation= 'sigmoid',
strides=1)(char_embeddings)
```

```
char_max_pooling = MaxPooling1D(pool_size=10)(char_cnn)
```

[char LSTM step]

2) why char-biLSTM, word-biLSTM and concatenate [char-biLSTM, word-biLSTM] ?
Can not we just like concatenate [char-emb , word-emb] and bi-LSTM ?

^ | ▾ • Reply • Share ›

**Sohrab Ark** • 21 days ago

Hey, Thank you so much for your great post. it is very useful and clear. I think there is a typo in this line code:

```
# shape = (batch, sentence, 2 x char_hidden_size)
char_rep = tf.reshape(char_rep, shape=[-1, s[1], 2*char_hidden_size])
```

Inside the reshape it should be "output" variable.

^ | ▾ • Reply • Share ›

Guillaume Genthial blog

 [guillaumegenthial](https://guillaumegenthial.github.io)

Attempt to share some of my
experience in NLP and AI