

Most **frequently used Tailwind CSS classes**, grouped by category so it's easy to remember and apply in real projects:

◆ 1. Layout & Display

Class	Purpose
flex	Makes an element a flexbox container
inline-flex	Flex but in inline flow
grid	Makes an element a grid container
block / inline-block	Control block-level or inline-block display
hidden	Hide an element
w-full / h-full	Full width/height of parent
w-[px] / h-[px]	Custom width/height

◆ 2. Flexbox & Grid Alignment

Class	Purpose
items-center	Vertical align center
justify-center	Horizontal align center
justify-between / justify-around	Spacing between children
gap-x-[px], gap-y-[px], gap-[px]	Control space between children
flex-col	Stack children vertically
flex-row	Default direction (horizontal)

◆ 3. Spacing (Margin & Padding)

Class	Purpose
m-[value] / mt-, mb-, ml-, mr-	Margin
p-[value] / pt-, pb-, pl-, pr-	Padding
Example: px-4 py-2	Padding left/right: 1rem, top/bottom: 0.5rem

You can also use custom spacing like px-[10px].

◆ 4. Typography

Class	Purpose
text-[size]	Control font size (text-sm, text-lg, text-xl, etc.)
font-bold / font-medium / font-light	Font weight
text-center / text-left / text-right	Text alignment
text-[color]	Text color
uppercase / capitalize / lowercase	Text transformation

◆ 5. Background & Border

Class	Purpose
bg-[color]	Background color
rounded, rounded-md, rounded-lg	Border radius

Class	Purpose
border, border-[color]	Add border
shadow, shadow-md, shadow-lg	Add box-shadow

◆ 6. Sizing & Overflow

Class	Purpose
max-w-[value], min-w-[value]	Set max/min widths
overflow-hidden / overflow-scroll / overflow-auto	Control scroll behavior

◆ 7. Positioning

Class	Purpose
relative, absolute, fixed, sticky	Control position
top-[value], left-[value], etc.	Position offsets

◆ 8. Hover / Active / Focus States

Class	Purpose
hover:bg-[color]	Change bg color on hover
hover:scale-105	Slight zoom on hover
focus:outline-none	Remove default focus border
active:bg-[color]	Color when clicked

◆ 9. Responsiveness

Class	Purpose
sm:, md:, lg:, xl:	Prefix for breakpoints
Example: md:flex-row	On medium screen and up, make flex direction row

◆ 10. Animations & Transitions

Class	Purpose
transition-all, duration-300, ease-in-out	Smooth transitions
animate-bounce, animate-pulse	Basic built-in animations