

V Foods: Backend and Database Architecture Specification

A comprehensive technical and functional reference for the V Foods campus dining and food court operating system.

1. Executive Summary & Project Vision


1.1 The Campus Dining Problem

At universities and high-density campuses, dining operations face extreme surge patterns. When lectures conclude, thousands of campus users converge upon food courts, dining halls, and canteens simultaneously during a narrow 15-to-30 minute window.

Traditional campus food ordering suffers from four critical failures: 1. **Physical Counter Congestion:** Users spend 10 to 20 minutes waiting in queue simply to place an order and pay, followed by another 10 to 15 minutes waiting near the counter for their food. 2. **Payment & Cash Friction:** Cash transactions cause coin shortages and slow counter throughput. Card terminals often drop connections indoors. Ad-hoc UPI scanning leads to unverified transfers, falsified screenshots, and lost revenue. 3. **Kitchen Operational Chaos:** Kitchen staff rely on handwritten paper tickets or noisy thermal slips that get lost, grease-stained, or prepared out of sequence. 4. **Inventory and Settlement Discrepancies:** Out-of-stock items continue to be ordered, leading to awkward cancellations and counter disputes. At the end of each day, reconciling revenue between shop owners, campus administration, and service operators is manual, error-prone, and contentious.

1.2 The V Foods Solution

V Foods is a high-concurrency, queue-free smart campus dining operating system. It coordinates the entire meal lifecycle across four distinct user roles:



- Instant Mobile Ordering:** Users browse live menus, see real-time availability, and order ahead from their devices.
- Dual Payment Rails:** Users pay either in milliseconds using their prepaid campus wallet or directly via payment gateway (Paytm / UPI).
- Paperless Kitchen Display System (KDS):** Kitchens receive orders instantly via real-time WebSockets with live status progression (**Placed** -> **Preparing** -> **Ready** -> **Collected**).
- Cryptographic Pickup Verification:** Food handover is authenticated using 3-digit daily tokens or HMAC-SHA256 signed QR pickup passes, eliminating stolen food and incorrect handovers.
- Automated Three-Way Revenue Settlement:** Every completed meal automatically computes and records compliant revenue splits (90% to the Food Shop, 5% to the V Foods Platform, 5% to the University Campus) with zero-penny rounding conservation.

2. High-Level System Architecture

The V Foods architecture is designed as a decoupled, asynchronous, and resilient distributed system:

```

flowchart TD
    subgraph Client_Layer [Client Layer]
        U[User Mobile PWA / App]
        S[Shop Staff KDS Tablet]
        A[Shop Admin Console]
        SA[Super Admin Control Tower]
    end

    subgraph Backend_Application_Layer [Backend Application Layer - FastAPI]
        API[FastAPI Gateway :8000]
        AUTH[Auth & OTP Router]
        CACHE[In-Memory Catalog Cache]
        SCHED[APScheduler Background Worker]
        CRYPTO[HMAC & Checksum Engine]
    end

    subgraph External_Infrastructure [External Infrastructure]
        PAYTM[Paytm Payment Gateway]
        MSG[MSG91 SMS & WhatsApp Gateway]
        SMTP[SMTP Mail Server]
    end

    subgraph Database_Layer [Database Layer - Supabase / PostgreSQL]
        RLS[Row-Level Security Policies]
        DB[(PostgreSQL Relational Storage)]
        SP[Atomic Stored Procedures]
        RT[Supabase Realtime Engine / WebSockets]
    end

    U -->|Browse Menu, Place Order| API
    U -->|Read-only Queries| RLS
    S -->|Status Updates, QR Scan| API
    A -->|Menu & Staff Config| API
    SA -->|Settlement & Audits| API

    API --> AUTH
    API --> CACHE
    API --> CRYPTO
    API --> SP
    SP --> DB
    DB --> RLS

    SCHED -->|Expire Pending Orders| SP
    API -->|Signed Checksum| PAYTM
    PAYTM -->|Server Webhook| API
    API -->|Alerts| MSG
    AUTH -->|Verification OTP| SMTP

    DB -->|CDC Publications| RT
    RT -->|Live Push Updates| S
    RT -->|Live Token Progression| U

```

3. Backend Technologies & Tools Explained

Every tool in the V Foods backend is selected for high concurrency, low latency, data integrity, and enterprise security.

3.1 FastAPI (Python 3.11)

- **What it is:** A modern, high-performance web framework for building APIs with Python based on standard Python type hints.
- **Role in V Foods:** Acts as the central business logic coordinator, security perimeter, and external integration gateway.
- **Why it was chosen:**
- **Asynchronous Execution** (`async` / `await`): Built on top of Starlette and AnyIO, FastAPI handles thousands of concurrent non-blocking requests with minimal CPU and memory footprints.
- **Native OpenAPI & JSON Schema:** Generates interactive documentation (`/docs`) and typed client schemas automatically.
- **Dependency Injection System:** Centralizes role-based authorization guards (`get_current_user` , `require_staff` , `require_shop_admin` , `require_admin`).

3.2 Uvicorn

- **What it is:** An ultra-fast ASGI (Asynchronous Server Gateway Interface) web server implementation for Python.

- **Role in V Foods:** The production application server running the FastAPI application.
- **Why it was chosen:** Built on `uvloop` (a fast, drop-in replacement for `asyncio` implemented in Cython using `libuv`), Uvicorn delivers raw throughput comparable to Go and Node.js.

3.3 Pydantic (v2)

- **What it is:** A data validation and parsing library written in Rust for Python.
- **Role in V Foods:** Validates incoming HTTP payloads, query parameters, and headers before business logic executes.
- **Why it was chosen:** Pydantic v2 enforces strict type contracts, prevents injection attacks, sanitizes inputs, and runs data parsing up to 20 times faster than Pydantic v1.

3.4 Supabase Python Client (`supabase-py`)

- **What it is:** The official Python client for interacting with Supabase services.
- **Role in V Foods:** Executes database queries, invokes PostgreSQL stored procedures (RPCs), and manages administrative database calls using the `SUPABASE_SERVICE_ROLE_KEY`.
- **Why it was chosen:** Provides a clean interface for executing complex SQL procedures while maintaining connection pooling to Supabase. The service role key is kept strictly within the backend and is never exposed to client browsers.

3.5 Python-Jose & JWT Authentication

- **What it is:** A JavaScript Object Signing and Encryption (JOSE) implementation in Python.
- **Role in V Foods:** Decodes, validates, and cryptographically verifies Supabase JSON Web Tokens (JWTs) presented in the `Authorization: Bearer <token>` HTTP header.
- **Why it was chosen:** Verifies user identity, issuer, expiration, and role claims statelessly without requiring a database query on every protected endpoint.

3.6 APScheduler (Advanced Python Scheduler)

- **What it is:** An in-process, asynchronous task scheduling library for Python.
- **Role in V Foods:** Runs background jobs at fixed intervals directly within the FastAPI event loop.
- **Core Task:**
- `expire_pending_orders`: Runs every 5 minutes. Scans for orders that were initiated via payment gateway but never paid within the expiration window. It marks them `cancelled` and returns temporarily held inventory back to the menu.

3.7 HTTPX

- **What it is:** A fully featured, asynchronous HTTP client for Python 3 with HTTP/1.1 and HTTP/2 support.
- **Role in V Foods:** Handles outgoing HTTP requests from the backend to external third-party services:
- Communicating with the Paytm Payment Gateway.
- Dispatching transactional SMS and WhatsApp notifications to MSG91.

3.8 Cryptography & HMAC-SHA256 Engine

- **What it is:** Python's standard `hmac` and `hashlib` modules along with the `cryptography` library.
- **Role in V Foods:**
- **Paytm Checksum Generation & Verification:** Calculates and verifies HMAC-SHA256 signatures for every payment transaction and incoming webhook.
- **QR Pickup Pass Signing:** Generates tamper-proof QR payload signatures (`order:<id>:<hmac_hex>`) using a server-side secret key (`QR_SECRET`).
- **Timing-Attack Resistance:** Uses `hmac.compare_digest` for all signature evaluations to prevent timing attacks.

3.9 In-Memory Catalog Caching

- **What it is:** A high-speed caching layer maintained in FastAPI memory (`_CATALOG_CACHE`).
- **Role in V Foods:** Caches the status and summary list of all campus dining outlets (`/api/catalog/summary`) with a 30-second Time-To-Live (TTL).
- **Why it was chosen:** When 1,000+ campus users open the app simultaneously during break, cached catalog requests are served in under 2 milliseconds without querying the database, eliminating database connection exhaustion.

3.10 SMTP & Email OTP Verification System

- **What it is:** An email delivery pipeline utilizing Python's `smtplib`, `email.mime`, and `secrets` module.
- **Role in V Foods:** Generates, rate-limits, and verifies 6-digit numeric OTP codes during user signup.
- **Security Features:**
- 10-minute code expiration.

- 30-second cooldown between resend requests.
- 5-attempt brute-force protection lockout.
- Fallback logging mode for local development and sandbox environments.


3.11 MSG91 WhatsApp & SMS Integration

- **What it is:** An enterprise cloud communication platform.
- **Role in V Foods:** Delivers automated, fire-and-forget WhatsApp notifications to users at key moments:
- Top-up confirmed.
- Order placed with 3-digit pickup token.
- Food ready for collection at the counter.
- Order cancellation or payment failure notification.

4. Database Architecture & Table Structure Reference (Supabase / PostgreSQL)

The V Foods database is hosted on Supabase and powered by PostgreSQL. It uses relational schemas, constraints, atomic stored procedures, and Row-Level Security (RLS) to enforce data integrity and tenant isolation.

4.1 Complete Entity Relationship Diagram (ERD)



4.2 Comprehensive Table Structure Reference (All 23 Tables)

Below is the complete, schema-accurate specification for every table in the V Foods database, including its SQL DDL definition, detailed column data dictionary, constraints, indexes, and Row-Level Security (RLS) policies.

1. outlets

Stores all dining facilities, campus canteens, cafes, food courts, and festival food stalls.

```
CREATE TABLE IF NOT EXISTS public.outlets (  
  id      text      PRIMARY KEY,  
  name    text      NOT NULL,  
  location text      NOT NULL,  
  is_event boolean    NOT NULL DEFAULT false,  
  is_open  boolean    NOT NULL DEFAULT true  
);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
id	text	NO	None	PRIMARY KEY	Machine-readable outlet identifier (e.g. 'main-canteen', 'gazebo-c1', 'tech-cafe').
name	text	NO	None	None	Human-readable public display name shown to users.
location	text	NO	None	None	Physical campus location (e.g. 'Central Food Court, Ground Floor').
is_event	boolean	NO	false	None	Flag indicating whether this outlet is a temporary festival/event food stall.
is_open	boolean	NO	true	None	Operational toggle; when false , checkout is blocked immediately.

- **Indexes:** Primary key index on `id` .
- **RLS Policy:** Publicly readable by all users (`anon` , `authenticated`). Writable only by Super Admins.

2. menu_items

Holds all dishes, drinks, and meals available for purchase across outlets.

```
CREATE TABLE IF NOT EXISTS public.menu_items (  
  id          bigint    GENERATED ALWAYS AS IDENTITY PRIMARY KEY,  
  outlet_id   text      NOT NULL REFERENCES outlets(id) ON DELETE CASCADE,  
  name        text      NOT NULL,  
  price       int       NOT NULL CHECK (price > 0),  
  available   boolean    NOT NULL DEFAULT true,  
  is_veg      boolean    NOT NULL DEFAULT true,  
  category    text      NOT NULL DEFAULT 'General',  
  available_from time     NULL,  
  available_to time     NULL,  
  stock_qty   int       NULL CHECK (stock_qty IS NULL OR stock_qty >= 0),  
  reserved_qty int      NOT NULL DEFAULT 0 CHECK (reserved_qty >= 0)  
);  
  
CREATE INDEX IF NOT EXISTS idx_menu_items_outlet ON menu_items(outlet_id);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
id	bigint	NO	Identity	PRIMARY KEY	Unique autoincrementing food item ID.
outlet_id	text	NO	None	FK -> outlets(id) ON DELETE CASCADE	The outlet that produces and sells this item.
name	text	NO	None	None	Name of the dish or drink (e.g. 'Paneer Butter Masala Roll').
price	int	NO	None	CHECK (price > 0)	Base unit price in Indian Rupees (INR).
available	boolean	NO	true	None	Immediate stock toggle; flips to false when sold out.
is_veg	boolean	NO	true	None	Dietary flag (true for vegetarian, false for non-vegetarian).
category	text	NO	'General'	None	Menu category for tabbed browsing (e.g. 'Breakfast' , 'Beverages').
available_from	time	YES	NULL	None	Optional daily time restriction window start (e.g. 08:00:00).
available_to	time	YES	NULL	None	Optional daily time restriction window end (e.g. 11:30:00).

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
stock_qty	int	YES	NULL	CHECK (stock_qty IS NULL OR stock_qty >= 0)	Remaining portions available today; NULL means unlimited.
reserved_qty	int	NO	0	CHECK (reserved_qty >= 0)	Portions temporarily held during active payment sessions.

- **Indexes:** `idx_menu_items_outlet` on `outlet_id`.
- **RLS Policy:** Publicly readable. Writable by Shop Admins and Staff belonging to the same `outlet_id`.

3. profiles

User profiles extending Supabase's native `auth.users` authentication table.

```
CREATE TABLE IF NOT EXISTS public.profiles (  
  id          uuid          PRIMARY KEY REFERENCES auth.users(id) ON DELETE CASCADE,  
  full_name   text          NOT NULL DEFAULT '',  
  role        user_role     NOT NULL DEFAULT 'customer',  
  cust_type   cust_type     NOT NULL DEFAULT 'student',  
  outlet_id   text          NULL REFERENCES outlets(id) ON DELETE SET NULL,  
  phone       text          NULL,  
  referral_code text        NULL UNIQUE,  
  added_by    uuid          NULL REFERENCES profiles(id) ON DELETE SET NULL,  
  created_at  timestamptz   NOT NULL DEFAULT now()  
);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
id	uuid	NO	None	PK, FK -> auth.users(id) ON DELETE CASCADE	Maps 1:1 with Supabase Auth credentials.
full_name	text	NO	''	None	User's full legal name.
role	user_role ENUM	NO	'customer'	Enum: customer, staff, shop_admin, super_admin, admin	System permission tier for role-based access control.
cust_type	cust_type ENUM	NO	'student'	Enum: student, faculty, visitor	Campus classification for reporting.
outlet_id	text	YES	NULL	FK -> outlets(id) ON DELETE SET NULL	Assigned food stall for staff and shop owners.
phone	text	YES	NULL	None	Mobile phone number used for SMS/WhatsApp pickup alerts.
referral_code	text	YES	NULL	UNIQUE	Unique referral token assigned to users to invite friends.
added_by	uuid	YES	NULL	FK -> profiles(id)	Administrator ID who created or invited this user.
created_at	timestamptz	NO	now()	None	Account creation timestamp.

- **RLS Policy:** Users can read and update their own profile (`id = auth.uid()`). Super Admins can view all.

4. wallets

Prepaid digital campus wallet balances.

```
CREATE TABLE IF NOT EXISTS public.wallets (  
  user_id  uuid          PRIMARY KEY REFERENCES profiles(id) ON DELETE CASCADE,  
  balance  int           NOT NULL DEFAULT 0 CHECK (balance >= 0),  
  updated_at timestamptz NOT NULL DEFAULT now()  
);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
user_id	uuid	NO	None	PK, FK -> profiles(id) ON DELETE CASCADE	Wallet owner identifier.
balance	int	NO	0	CHECK (balance >= 0)	Available stored value balance in INR. Cannot be negative.
updated_at	timestampz	NO	now()	None	Timestamp of last credit or debit operation.

- **RLS Policy:** Users can SELECT only their own wallet (`user_id = auth.uid()`). Direct client INSERT/UPDATE is strictly forbidden; balance changes must execute through server RPCs.

5. wallet_txns

Immutable audit ledger tracking every balance change.

```
CREATE TABLE IF NOT EXISTS public.wallet_txns (  
  id          bigint      GENERATED ALWAYS AS IDENTITY PRIMARY KEY,  
  user_id     uuid        NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,  
  amount      int         NOT NULL,  
  kind        text        NOT NULL CHECK (kind IN ('topup','order','refund','admin_credit','referral_bonus')),  
  ref         text        NOT NULL UNIQUE,  
  note        text        NULL,  
  created_at  timestampz  NOT NULL DEFAULT now()  
);  
CREATE INDEX IF NOT EXISTS idx_wallet_txns_user ON wallet_txns(user_id, created_at DESC);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
id	bigint	NO	Identity	PRIMARY KEY	Global unique transaction identifier.
user_id	uuid	NO	None	FK -> profiles(id) ON DELETE CASCADE	User account whose balance was adjusted.
amount	int	NO	None	None	Value change in INR (positive for credits, negative for debits).
kind	text	NO	None	CHECK (kind IN (...))	Nature of transaction: 'topup', 'order', 'refund', etc.
ref	text	NO	None	UNIQUE	Idempotency key (e.g. 'paytm:TXN102', 'order:450').
note	text	YES	NULL	None	Human-readable explanation for receipts and statements.
created_at	timestampz	NO	now()	None	Transaction execution timestamp.

- **Indexes:** `idx_wallet_txns_user` on `(user_id, created_at DESC)`.
- **RLS Policy:** Users can read only their own transactions. Append-only; `UPDATE` and `DELETE` are disabled.

6. orders

Master operational record for every food and beverage order.

```
CREATE TABLE IF NOT EXISTS public.orders (  
  id          bigint          GENERATED ALWAYS AS IDENTITY PRIMARY KEY,  
  user_id     uuid            NOT NULL REFERENCES profiles(id) ON DELETE RESTRICT,  
  outlet_id   text            NOT NULL REFERENCES outlets(id) ON DELETE RESTRICT,  
  token       text            NULL,  
  status      order_status    NOT NULL DEFAULT 'payment_pending',  
  payment_method payment_method NOT NULL DEFAULT 'wallet',  
  shop_payout int             NOT NULL CHECK (shop_payout > 0),  
  total       int             NOT NULL CHECK (total > 0),  
  my_profit   int             GENERATED ALWAYS AS (shop_payout * 5 / 100) STORED,  
  payment_id  bigint          NULL REFERENCES payments(id) ON DELETE SET NULL,  
  pickup_slot_id uuid         NULL REFERENCES pickup_slots(id) ON DELETE SET NULL,  
  cancel_reason text          NULL,  
  expires_at  timestamptz     NULL,  
  created_at  timestamptz     NOT NULL DEFAULT now(),  
  updated_at  timestamptz     NOT NULL DEFAULT now()  
);  
  
CREATE INDEX IF NOT EXISTS idx_orders_user  ON orders(user_id, created_at DESC);  
CREATE INDEX IF NOT EXISTS idx_orders_outlet ON orders(outlet_id, created_at DESC);  
CREATE INDEX IF NOT EXISTS idx_orders_status ON orders(status);
```

Column Name	Data Type	Nulla ble?	Default Value	Constraints / Key	Description & Purpose
id	bigint	NO	Identity	PRIMARY KEY	Global unique order ID.
user_id	uuid	NO	None	FK -> profiles(id) ON DELETE RESTRICT	User who placed the order.
outlet_id	text	NO	None	FK -> outlets(id) ON DELETE RESTRICT	Food stall fulfilling the order.
token	text	YES	NULL	None	3-digit pickup code (e.g. '142') issued upon confirmed payment.
status	order_status ENUM	NO	'payment_pending'	Enum: payment_pending , placed , preparing , ready , collected , cancelled	Live lifecycle state of the order.
payment_method	payment_method ENUM	NO	'wallet'	Enum: wallet , gateway	Payment mechanism used.
shop_payout	int	NO	None	CHECK (shop_payout > 0)	Net food item subtotal due to the shop.
total	int	NO	None	CHECK (total > 0)	Final amount billed to user (items + convenience fees).
my_profit	int	NO	Stored Gen	(shop_payout * 5 / 100)	5% platform fee stored automatically.
payment_id	bigint	YES	NULL	FK -> payments(id)	Foreign key linking to the underlying gateway payment.
pickup_slot_id	uuid	YES	NULL	FK -> pickup_slots(id)	Scheduled pickup time window if pre-ordered.
cancel_reason	text	YES	NULL	None	Explanatory note if rejected or cancelled.
expires_at	timestamptz	YES	NULL	None	Automatic cancellation timestamp for pending gateway checkouts.
created_at	timestamptz	NO	now()	None	Order creation timestamp.
updated_at	timestamptz	NO	now()	None	Last status update timestamp.

- **RLS Policy:** Users view their own orders (user_id = auth.uid()). Kitchen staff view only orders for their own outlet_id . Super Admins view all.

7. order_items

Individual line items inside an order with frozen price snapshots.

```
CREATE TABLE IF NOT EXISTS public.order_items (  
  order_id bigint NOT NULL REFERENCES orders(id) ON DELETE CASCADE,  
  item_id  bigint NOT NULL REFERENCES menu_items(id) ON DELETE RESTRICT,  
  name     text  NOT NULL,  
  price    int   NOT NULL,  
  qty      int   NOT NULL CHECK (qty > 0),  
  PRIMARY KEY (order_id, item_id)  
);  
CREATE INDEX IF NOT EXISTS idx_order_items_order ON order_items(order_id);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
order_id	bigint	NO	None	PK (composite), FK -> orders(id) ON DELETE CASCADE	Parent order reference.
item_id	bigint	NO	None	PK (composite), FK -> menu_items(id) ON DELETE RESTRICT	Referenced dish from menu.
name	text	NO	None	None	Frozen dish title snapshot at the time order was placed.
price	int	NO	None	None	Frozen unit price in INR at purchase time.
qty	int	NO	None	CHECK (qty > 0)	Number of portions ordered.

- **RLS Policy:** Inherits access rules from parent `orders` table.

8. payments

Unified ledger of all payment attempts across both Wallet Top-Up and Direct Order Checkout.

```
CREATE TABLE IF NOT EXISTS public.payments (  
  id                bigint          GENERATED ALWAYS AS IDENTITY PRIMARY KEY,  
  user_id           uuid            NOT NULL REFERENCES profiles(id) ON DELETE RESTRICT,  
  order_id          bigint          NULL REFERENCES orders(id) ON DELETE SET NULL,  
  wallet_txn_id     bigint          NULL REFERENCES wallet_txns(id) ON DELETE SET NULL,  
  amount            numeric         NOT NULL CHECK (amount > 0),  
  payment_purpose     text            NOT NULL CHECK (payment_purpose IN ('ORDER', 'WALLET_TOPUP')),  
  payment_method    text            NOT NULL CHECK (payment_method IN ('UPI_ID', 'UPI_APP', 'UPI_QR', 'DEBIT_CARD', 'CREDIT_CARD', 'WALLET')),  
  status            text            NOT NULL DEFAULT 'PENDING' CHECK (status IN ('PENDING', 'SUCCESS', 'FAILED', 'CANCELLED', 'REFUNDED')),  
  paytm_order_id    text            NULL,  
  paytm_txn_id      text            NULL UNIQUE,  
  payment_reference text            NULL,  
  paid_at           timestamptz     NULL,  
  failure_reason    text            NULL,  
  created_at        timestamptz     NOT NULL DEFAULT now(),  
  updated_at        timestamptz     NOT NULL DEFAULT now()  
);  
CREATE INDEX IF NOT EXISTS idx_payments_user_id ON payments(user_id);  
CREATE INDEX IF NOT EXISTS idx_payments_order_id ON payments(order_id);  
CREATE INDEX IF NOT EXISTS idx_payments_status ON payments(status);
```

Column Name	Data Type	Nullab le?	Default Value	Constraints / Key	Description & Purpose
id	bigint	NO	Identity	PRIMARY KEY	Global payment ledger identifier.
user_id	uuid	NO	None	FK -> profiles(id) ON DELETE RESTRICT	Payer user account.
order_id	bigint	YES	NULL	FK -> orders(id) ON DELETE SET NULL	Target order ID (NULL for wallet top-up).
wallet_txn_id	bigint	YES	NULL	FK -> wallet_txns(id) ON DELETE SET NULL	Linked wallet ledger entry.
amount	numeric	NO	None	CHECK (amount > 0)	Total monetary transaction amount in INR.
payment_purpose	text	NO	None	CHECK in ('ORDER', 'WALLET_TOPUP')	Business purpose of payment.
payment_method	text	NO	None	CHECK in ('UPI_APP', 'DEBIT_CARD', ...)	Payment rail used by customer.

Column Name	Data Type	Nullable?	Default Value	Constraints / Key	Description & Purpose
status	text	NO	'PENDING'	CHECK in ('PENDING', 'SUCCESS', ...)	Bank reconciliation status.
paytm_order_id	text	YES	NULL	None	Merchant transaction reference sent to gateway.
paytm_txn_id	text	YES	NULL	UNIQUE	Bank transaction ID returned in verified webhook; acts as idempotency key.
payment_reference	text	YES	NULL	None	Internal tracking reference string.
paid_at	timestampz	YES	NULL	None	Timestamp when verified as SUCCESS.
failure_reason	text	YES	NULL	None	Detailed gateway error message if failed.
created_at / updated_at	timestampz	NO	now()	None	Audit timestamps.

- **RLS Policy:** Users view only their own payments. Staff view payments linked to orders at their outlet. Super Admins view all.

9. outlet_paytm_accounts

Per-shop recipient sub-accounts with outlet-configurable split shares.

```
CREATE TABLE IF NOT EXISTS public.outlet_paytm_accounts (
  outlet_id          text          PRIMARY KEY REFERENCES outlets(id) ON DELETE CASCADE,
  paytm_account_id   text          NOT NULL,
  onboarding_status  text          NOT NULL DEFAULT 'PENDING' CHECK (onboarding_status IN ('PENDING', 'ACTIVE', 'REJECTED')),
  settlement_enabled boolean       NOT NULL DEFAULT false,
  shop_split_percentage numeric     NOT NULL DEFAULT 90 CHECK (shop_split_percentage >= 0 AND shop_split_percentage <= 100),
  created_at         timestampz    NOT NULL DEFAULT now(),
  updated_at         timestampz    NOT NULL DEFAULT now()
);
```

Column Name	Data Type	Nullable?	Default Value	Constraints / Key	Description & Purpose
outlet_id	text	NO	None	PK, FK -> outlets(id) ON DELETE CASCADE	Target food outlet.
paytm_account_id	text	NO	None	None	Registered Paytm Merchant sub-account ID.
onboarding_status	text	NO	'PENDING'	CHECK in ('PENDING', 'ACTIVE', 'REJECTED')	Gateway KYC and onboarding approval status.
settlement_enabled	boolean	NO	false	None	Master disbursement toggle.
shop_split_percentage	numeric	NO	90	CHECK (0 <= shop_split_percentage <= 100)	Negotiated shop percentage (default 90%).
created_at / updated_at	timestampz	NO	now()	None	Audit timestamps.

- **Triggers:** Validated by `trg_validate_outlet_split` guaranteeing \$Shop\% + Platform\% + College\% = 100\%\$.
- **RLS Policy:** Shop Admins can inspect their own outlet's account. Super Admins manage all.

10. platform_settlement_account

Startup platform settlement account (singleton row `id = 1`).

```
CREATE TABLE IF NOT EXISTS public.platform_settlement_account (  
  id int PRIMARY KEY DEFAULT 1 CHECK (id = 1),  
  paytm_account_id text NOT NULL,  
  settlement_enabled boolean NOT NULL DEFAULT false,  
  platform_split_percentage numeric NOT NULL DEFAULT 5 CHECK (platform_split_percentage >= 0 AND platform_split_percentage <= 100),  
  created_at timestamptz NOT NULL DEFAULT now(),  
  updated_at timestamptz NOT NULL DEFAULT now()  
);
```

Column Name	Data Type	Nullable ?	Default Value	Constraints / Key	Description & Purpose
id	int	NO	1	PK, CHECK (id = 1)	Singleton identifier enforcing exactly one row.
paytm_account_id	text	NO	None	None	V Foods company settlement merchant ID.
settlement_enabled	boolean	NO	false	None	Platform disbursement switch.
platform_split_percentage	numeric	NO	5	CHECK (0 <= pct <= 100)	Fixed platform fee percentage (5%).
created_at / updated_at	timestamptz	NO	now()	None	Audit timestamps.

- **RLS Policy:** Restricted exclusively to Super Admins.

11. college_settlement_accounts

Campus university institution settlement accounts (one active row per campus).

```
CREATE TABLE IF NOT EXISTS public.college_settlement_accounts (  
  id bigint GENERATED ALWAYS AS IDENTITY PRIMARY KEY,  
  campus_name text NOT NULL,  
  paytm_account_id text NOT NULL,  
  onboarding_status text NOT NULL DEFAULT 'PENDING' CHECK (onboarding_status IN ('PENDING', 'ACTIVE', 'REJECTED')),  
  settlement_enabled boolean NOT NULL DEFAULT false,  
  is_active boolean NOT NULL DEFAULT true,  
  college_split_percentage numeric NOT NULL DEFAULT 5 CHECK (college_split_percentage >= 0 AND college_split_percentage <= 100),  
  created_at timestamptz NOT NULL DEFAULT now(),  
  updated_at timestamptz NOT NULL DEFAULT now()  
);  
CREATE UNIQUE INDEX IF NOT EXISTS idx_college_single_active ON college_settlement_accounts(is_active) WHERE is_active = true;
```

Column Name	Data Type	Nullable?	Default Value	Constraints / Key	Description & Purpose
id	bigint	NO	Identity	PRIMARY KEY	Unique campus settlement record ID.
campus_name	text	NO	None	None	Host institution name (e.g. 'VIT Chennai').
paytm_account_id	text	NO	None	None	University banking settlement merchant ID.
onboarding_status	text	NO	'PENDING'	CHECK in ('PENDING', 'ACTIVE', 'REJECTED')	Institutional KYC status.
settlement_enabled	boolean	NO	false	None	University disbursement switch.
is_active	boolean	NO	true	None	Active campus flag.
college_split_percentage	numeric	NO	5	CHECK (0 <= pct <= 100)	University campus royalty percentage (5%).
created_at / updated_at	timestamptz	NO	now()	None	Audit timestamps.

- **Indexes:** Unique partial index `idx_college_single_active` enforces that only one campus row is active at a time.
- **RLS Policy:** Restricted exclusively to Super Admins.

12. payment_splits

Individual settlement payouts computed for every completed meal.

```
CREATE TABLE IF NOT EXISTS public.payment_splits (  
  id                bigint          GENERATED ALWAYS AS IDENTITY PRIMARY KEY,  
  payment_id        bigint          NOT NULL REFERENCES payments(id) ON DELETE CASCADE,  
  recipient_type     text           NOT NULL CHECK (recipient_type IN ('SHOP', 'PLATFORM', 'COLLEGE')),  
  outlet_paytm_account_id text       NULL REFERENCES outlet_paytm_accounts(outlet_id) ON DELETE RESTRICT,  
  platform_account_id int          NULL REFERENCES platform_settlement_account(id) ON DELETE RESTRICT,  
  college_account_id bigint        NULL REFERENCES college_settlement_accounts(id) ON DELETE RESTRICT,  
  split_amount       numeric        NOT NULL CHECK (split_amount >= 0),  
  split_percentage   numeric        NULL CHECK (split_percentage IS NULL OR (split_percentage >= 0 AND split_percentage <= 100)),  
  settlement_status  text           NOT NULL DEFAULT 'PENDING' CHECK (settlement_status IN ('PENDING', 'SETTLED', 'FAILED')),  
  settlement_reference text         NULL,  
  settled_at         timestamptz    NULL,  
  created_at         timestamptz    NOT NULL DEFAULT now(),  
  CONSTRAINT chk_split_recipient_account CHECK (  
    (recipient_type = 'SHOP' AND outlet_paytm_account_id IS NOT NULL AND platform_account_id IS NULL AND college_account_id IS NULL) OR  
    (recipient_type = 'PLATFORM' AND platform_account_id IS NOT NULL AND outlet_paytm_account_id IS NULL AND college_account_id IS NULL) OR  
    (recipient_type = 'COLLEGE' AND college_account_id IS NOT NULL AND outlet_paytm_account_id IS NULL AND platform_account_id IS NULL)  
  );  
CREATE INDEX IF NOT EXISTS idx_payment_splits_payment_id ON payment_splits(payment_id);  
CREATE INDEX IF NOT EXISTS idx_payment_splits_recipient ON payment_splits(recipient_type);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
id	bigint	NO	Identity	PRIMARY KEY	Unique split payout identifier.
payment_id	bigint	NO	None	FK -> payments(id) ON DELETE CASCADE	Source payment being disbursed.
recipient_type	text	NO	None	CHECK in ('SHOP', 'PLATFORM', 'COLLEGE')	Category of recipient receiving the share.
outlet_paytm_accou nt_id	text	YES	NULL	FK -> outlet_paytm_accounts(outlet_id)	Populated only when recipient_type = 'SHOP'.
platform_account_i d	int	YES	NULL	FK -> platform_settlement_account(id)	Populated only when recipient_type = 'PLATFORM'.
college_account_i d	bigint	YES	NULL	FK -> college_settlement_accounts(id)	Populated only when recipient_type = 'COLLEGE'.
split_amount	numeric	NO	None	CHECK (split_amount >= 0)	Disbursed amount in INR.
split_percentage	numeric	YES	NULL	CHECK (0 <= split_percentage <= 100)	Applicable percentage share applied.
settlement_status	text	NO	'PENDING'	CHECK in ('PENDING', 'SETTLED', 'FAILED')	Bank disbursement status.
settlement_referen ce	text	YES	NULL	None	Paytm disbursement UTR/reference code.
settled_at	timestamp tz	YES	NULL	None	Disbursement timestamp.
created_at	timestamp tz	NO	now()	None	Creation timestamp.

- **RLS Policy:** Shop Admins can view only their own outlet's 'SHOP' split rows. Super Admins view all. Users have zero access.

13. refunds

Audit log of processed and pending customer refunds.

```
CREATE TABLE IF NOT EXISTS public.refunds (
  id          bigint          GENERATED ALWAYS AS IDENTITY PRIMARY KEY,
  payment_id  bigint          NOT NULL REFERENCES payments(id) ON DELETE RESTRICT,
  order_id    bigint          NULL REFERENCES orders(id) ON DELETE SET NULL,
  wallet_txn_id bigint        NULL REFERENCES wallet_txns(id) ON DELETE SET NULL,
  refund_type text            NOT NULL CHECK (refund_type IN ('ORDER_REFUND', 'WALLET_TOPUP_REFUND', 'SPLIT_REFUND')),
  amount      numeric         NOT NULL CHECK (amount > 0),
  status      text            NOT NULL DEFAULT 'PENDING' CHECK (status IN ('PENDING', 'SUCCESS', 'FAILED')),
  paytm_refund_id text        NULL,
  reason      text            NULL,
  created_at  timestampz      NOT NULL DEFAULT now(),
  processed_at timestampz     NULL
);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
id	bigint	NO	Identity	PRIMARY KEY	Unique refund record ID.
payment_id	bigint	NO	None	FK -> payments(id) ON DELETE RESTRICT	Source payment being refunded.
order_id	bigint	YES	NULL	FK -> orders(id) ON DELETE SET NULL	Linked order ID if an order was cancelled.
wallet_txn_id	bigint	YES	NULL	FK -> wallet_txns(id) ON DELETE SET NULL	Linked wallet debit if refunding a top-up.
refund_type	text	NO	None	CHECK in ('ORDER_REFUND', ...)	Reason and path of refund.
amount	numeric	NO	None	CHECK (amount > 0)	Refunded amount in INR.
status	text	NO	'PENDING'	CHECK in ('PENDING', 'SUCCESS', 'FAILED')	Gateway refund progress status.
paytm_refund_id	text	YES	NULL	None	Gateway refund transaction reference.
reason	text	YES	NULL	None	Administrative or operational reason.
created_at / processed_at	timestamp z	YES/NO	now() / NULL	None	Timestamps.

- **RLS Policy:** Users view their own refunds. Staff view refunds for orders at their shop. Super Admins view all.

14. item_ratings

Customer ratings and reviews for individual menu items.

```
CREATE TABLE IF NOT EXISTS public.item_ratings (
  id          bigint          GENERATED ALWAYS AS IDENTITY PRIMARY KEY,
  order_id    bigint          NOT NULL REFERENCES orders(id) ON DELETE CASCADE,
  item_id     bigint          NOT NULL REFERENCES menu_items(id) ON DELETE CASCADE,
  user_id     uuid            NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,
  rating      smallint        NOT NULL CHECK (rating BETWEEN 1 AND 5),
  comment     text            NULL,
  created_at  timestampz      NOT NULL DEFAULT now(),
  CONSTRAINT uq_order_item_user_rating UNIQUE (order_id, item_id, user_id)
);
```

Column Name	Data Type	Nullable ?	Default Value	Constraints / Key	Description & Purpose
id	bigint	NO	Identity	PRIMARY KEY	Rating record identifier.
order_id	bigint	NO	None	FK -> orders(id) ON DELETE CASCADE	Source order confirming item was ordered.
item_id	bigint	NO	None	FK -> menu_items(id) ON DELETE CASCADE	Dish being evaluated.
user_id	uuid	NO	None	FK -> profiles(id) ON DELETE CASCADE	User submitting the review.
rating	smallint	NO	None	CHECK (rating BETWEEN 1 AND 5)	1-to-5 star quality score.

Column Name	Data Type	Nullable ?	Default Value	Constraints / Key	Description & Purpose
comment	text	YES	NULL	None	Optional user feedback comment.
created_at	timestampz	NO	now()	None	Timestamp when rating was submitted.

- **Triggers:** Enforced by `trg_check_item_rating_order_status` requiring `order.status = 'collected'` before a review can be submitted.
- **RLS Policy:** Read access is public. Insert access restricted to order owner.

15. `loyalty_progress`

Tracks order completion streaks and automated loyalty reward milestones.

```
CREATE TABLE IF NOT EXISTS public.loyalty_progress (  
  user_id          uuid          PRIMARY KEY REFERENCES profiles(id) ON DELETE CASCADE,  
  completed_orders int          NOT NULL DEFAULT 0 CHECK (completed_orders >= 0),  
  free_items_earned int          NOT NULL DEFAULT 0 CHECK (free_items_earned >= 0),  
  free_items_redeemed int        NOT NULL DEFAULT 0 CHECK (free_items_redeemed >= 0),  
  updated_at       timestampz    NOT NULL DEFAULT now()  
);
```

Column Name	Data Type	Nullable?	Default Value	Constraints / Key	Description & Purpose
user_id	uuid	NO	None	PK, FK -> profiles(id) ON DELETE CASCADE	User account tracking loyalty.
completed_orders	int	NO	0	CHECK (completed_orders >= 0)	Cumulative count of orders marked 'collected'.
free_items_earned	int	NO	0	CHECK (free_items_earned >= 0)	Free items earned (1 every 10 completed orders).
free_items_redeemed	int	NO	0	CHECK (free_items_redeemed >= 0)	Free items redeemed by user.
updated_at	timestampz	NO	now()	None	Timestamp of last order completion.

- **Triggers:** Automatically updated by `trg_increment_loyalty` whenever an order transitions to 'collected'.
- **RLS Policy:** Users can read only their own loyalty progress (`user_id = auth.uid()`).

16. `referrals`

Tracks user referrals and automated ₹30 wallet bonuses upon first completed order.

```
CREATE TABLE IF NOT EXISTS public.referrals (  
  id            uuid          PRIMARY KEY DEFAULT gen_random_uuid(),  
  referrer_id   uuid          NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,  
  referred_id   uuid          NOT NULL UNIQUE REFERENCES profiles(id) ON DELETE CASCADE,  
  status        text          NOT NULL DEFAULT 'pending' CHECK (status IN ('pending', 'completed')),  
  reward_credited bool        NOT NULL DEFAULT false,  
  created_at    timestampz    NOT NULL DEFAULT now()  
);
```

Column Name	Data Type	Nullable?	Default Value	Constraints / Key	Description & Purpose
id	uuid	NO	gen_random_uuid()	PRIMARY KEY	Unique referral relationship ID.
referrer_id	uuid	NO	None	FK -> profiles(id) ON DELETE CASCADE	User who shared their referral code.
referred_id	uuid	NO	None	UNIQUE, FK -> profiles(id) ON DELETE CASCADE	New user who registered with the referral code.
status	text	NO	'pending'	CHECK in ('pending', 'completed')	State of referral.

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
reward_credited	bool	NO	false	None	Flag preventing double payout of referral bonuses.
created_at	timestamp tz	NO	now()	None	Timestamp when referral was linked.

- **Triggers:** Managed by `trg_reward_referral`; credits ₹30 to both wallets when the new user completes their first order.
- **RLS Policy:** Users view referrals where they are either the referrer or referred.

17. pickup_slots

Scheduled pickup time windows for pacing counter rush traffic.

```
CREATE TABLE IF NOT EXISTS public.pickup_slots (  
  id          uuid          PRIMARY KEY DEFAULT gen_random_uuid(),  
  outlet_id   text          NOT NULL REFERENCES outlets(id) ON DELETE CASCADE,  
  slot_time   timestamptz  NOT NULL,  
  max_orders  int           NOT NULL DEFAULT 15 CHECK (max_orders > 0),  
  current_orders int       NOT NULL DEFAULT 0 CHECK (current_orders >= 0),  
  CONSTRAINT uq_outlet_slot_time UNIQUE (outlet_id, slot_time)  
);
```

Column Name	Data Type	Nullable ?	Default Value	Constraints / Key	Description & Purpose
id	uuid	NO	gen_random_uuid()	PRIMARY KEY	Pickup slot ID.
outlet_id	text	NO	None	FK -> outlets(id) ON DELETE CASCADE	Outlet offering the slot.
slot_time	timestampz	NO	None	None	Exact scheduled pickup time (e.g. 12:30 PM).
max_orders	int	NO	15	CHECK (max_orders > 0)	Maximum orders allowed in this slot.
current_order s	int	NO	0	CHECK (current_orders >= 0)	Booked order count.

- **RLS Policy:** Publicly readable. Managed by Shop Admins and Staff.

18. coupons

Promotional discount codes with usage limits and date windows.

```
CREATE TABLE IF NOT EXISTS public.coupons (  
  code          text          PRIMARY KEY,  
  discount_type text          NOT NULL CHECK (discount_type IN ('flat', 'percent')),  
  discount_value numeric      NOT NULL CHECK (discount_value > 0),  
  min_order_value int         NULL CHECK (min_order_value IS NULL OR min_order_value > 0),  
  max_uses      int           NULL CHECK (max_uses IS NULL OR max_uses > 0),  
  used_count    int           NOT NULL DEFAULT 0 CHECK (used_count >= 0),  
  outlet_id     text          NULL REFERENCES outlets(id) ON DELETE CASCADE,  
  valid_from    timestamptz  NOT NULL DEFAULT now(),  
  valid_to      timestamptz  NOT NULL DEFAULT (now() + interval '30 days'),  
  active        bool         NOT NULL DEFAULT true  
);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
code	text	NO	None	PRIMARY KEY	Uppercase coupon voucher code (e.g. 'CAMPUS50').
discount_type	text	NO	None	CHECK in ('flat', 'percent')	Discount mode (flat rupees or percentage off).

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
discount_value	numeric	NO	None	CHECK (discount_value > 0)	Discount amount or percentage value.
min_order_value	int	YES	NULL	CHECK (min_order_value > 0)	Minimum item subtotal required to apply.
max_uses	int	YES	NULL	CHECK (max_uses > 0)	Total redemptions allowed across platform.
used_count	int	NO	0	CHECK (used_count >= 0)	Count of orders that have redeemed this coupon.
outlet_id	text	YES	NULL	FK -> outlets(id)	Restricts coupon to one stall (NULL = platform-wide).
valid_from / valid_to	timestamp z	NO	now() / +30 days	None	Promotional active validity window.
active	bool	NO	true	None	Emergency kill switch to disable coupon.

- **RLS Policy:** Anyone can view active coupons (active = true). Managed by Admins.

19. coupon_redemptions

Audit log of individual coupon usages per order.

```
CREATE TABLE IF NOT EXISTS public.coupon_redemptions (  
  id          uuid          PRIMARY KEY DEFAULT gen_random_uuid(),  
  coupon_code text          NOT NULL REFERENCES coupons(code) ON DELETE CASCADE,  
  user_id     uuid          NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,  
  order_id    bigint        NOT NULL REFERENCES orders(id) ON DELETE CASCADE,  
  created_at  timestamptz   NOT NULL DEFAULT now()  
);
```

Column Name	Data Type	Nullable?	Default Value	Constraints / Key	Description & Purpose
id	uuid	NO	gen_random_uuid()	PRIMARY KEY	Unique redemption ID.
coupon_code	text	NO	None	FK -> coupons(code) ON DELETE CASCADE	Coupon applied.
user_id	uuid	NO	None	FK -> profiles(id) ON DELETE CASCADE	User who claimed discount.
order_id	bigint	NO	None	FK -> orders(id) ON DELETE CASCADE	Order receiving discount.
created_at	timestamptz	NO	now()	None	Timestamp of redemption.

- **RLS Policy:** Users view their own redemptions. Admins view all.

20. stock_adjustments

Forensic inventory audit table tracking manual and automatic stock modifications.

```
CREATE TABLE IF NOT EXISTS public.stock_adjustments (  
  id          bigint        GENERATED ALWAYS AS IDENTITY PRIMARY KEY,  
  outlet_id   text          NOT NULL REFERENCES outlets(id) ON DELETE CASCADE,  
  item_id     bigint        NOT NULL REFERENCES menu_items(id) ON DELETE CASCADE,  
  adjusted_by uuid          NULL REFERENCES profiles(id) ON DELETE SET NULL,  
  qty_change  int           NOT NULL,  
  previous_qty int          NULL,  
  new_qty     int          NULL,  
  reason      text          NOT NULL CHECK (reason IN ('manual_adjustment', 'order_decrement', 'counter_pos', '86_sold_out', 'restock')),  
  created_at  timestamptz   NOT NULL DEFAULT now()  
);  
CREATE INDEX IF NOT EXISTS idx_stock_adj_outlet_created ON stock_adjustments(outlet_id, created_at DESC);
```

Column Name	Data Type	Nullable ?	Default Value	Constraints / Key	Description & Purpose
id	bigint	NO	Identity	PRIMARY KEY	Stock adjustment record identifier.
outlet_id	text	NO	None	FK -> outlets(id) ON DELETE CASCADE	Outlet where inventory changed.

Column Name	Data Type	Nullable ?	Default Value	Constraints / Key	Description & Purpose
item_id	bigint	NO	None	FK -> menu_items(id) ON DELETE CASCADE	Food item whose quantity changed.
adjusted_by	uuid	YES	NULL	FK -> profiles(id) ON DELETE SET NULL	Staff member who authorized the change.
qty_change	int	NO	None	None	Portions added or subtracted.
previous_qty	int	YES	NULL	None	Stock level before adjustment.
new_qty	int	YES	NULL	None	Stock level after adjustment.
reason	text	NO	None	CHECK in ('manual_adjustment', ...)	Reason for modification.
created_at	timestampz	NO	now()	None	Timestamp when adjustment took place.

- **RLS Policy:** Staff view adjustments for their own outlet. Super Admins view all.

21. invites

Cryptographically generated single-use codes for onboarding kitchen staff and shop managers safely.

```
CREATE TABLE IF NOT EXISTS public.invites (
  id          uuid          PRIMARY KEY DEFAULT gen_random_uuid(),
  code        text          UNIQUE NOT NULL,
  email       text          NULL,
  phone       text          NULL,
  role        user_role     NOT NULL CHECK (role IN ('staff', 'shop_admin')),
  outlet_id   text          NOT NULL REFERENCES outlets(id) ON DELETE CASCADE,
  invited_by  uuid          NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,
  expires_at  timestampz    NOT NULL DEFAULT (now() + interval '7 days'),
  status      text          NOT NULL DEFAULT 'pending' CHECK (status IN ('pending', 'accepted', 'revoked', 'expired')),
  accepted_by uuid          NULL REFERENCES profiles(id) ON DELETE SET NULL,
  created_at  timestampz    NOT NULL DEFAULT now()
);
CREATE INDEX IF NOT EXISTS idx_invites_code ON invites(code);
```

Column Name	Data Type	Nullable?	Default Value	Constraints / Key	Description & Purpose
id	uuid	NO	gen_random_uuid()	PRIMARY KEY	Unique invite token record ID.
code	text	NO	None	UNIQUE	8-character uppercase hex token shared with the new hire.
email	text	YES	NULL	None	Optional intended email address.
phone	text	YES	NULL	None	Optional intended mobile number.
role	user_role	NO	None	CHECK in ('staff', 'shop_admin')	Target role being granted upon acceptance.
outlet_id	text	NO	None	FK -> outlets(id) ON DELETE CASCADE	Assigned food stall.
invited_by	uuid	NO	None	FK -> profiles(id) ON DELETE CASCADE	Manager who generated the invite.
expires_at	timestampz	NO	+7 days	None	Expiration deadline for redemption.
status	text	NO	'pending'	CHECK in ('pending', 'accepted', ...)	Lifecycle status of invitation.
accepted_by	uuid	YES	NULL	FK -> profiles(id) ON DELETE SET NULL	User profile that redeemed this invite.
created_at	timestampz	NO	now()	None	Creation timestamp.

- **RLS Policy:** Shop Admins manage invites for their own outlet. Super Admins view all.

22. audit_logs

Immutable forensic audit trail recording security events and operational overrides.

```
CREATE TABLE IF NOT EXISTS public.audit_logs (  
  id          uuid          PRIMARY KEY DEFAULT gen_random_uuid(),  
  actor_id    uuid          NULL REFERENCES public.profiles(id) ON DELETE SET NULL,  
  actor_name  text          NOT NULL DEFAULT 'System',  
  actor_role  text          NOT NULL DEFAULT 'user',  
  category    text          NOT NULL,  
  action      text          NOT NULL,  
  details     text          NOT NULL,  
  metadata    jsonb         NOT NULL DEFAULT '{}'::jsonb,  
  ip_address  text          NULL,  
  status      text          NOT NULL DEFAULT 'SUCCESS',  
  created_at  timestampz    NOT NULL DEFAULT now()  
);  
CREATE INDEX IF NOT EXISTS idx_audit_logs_created_at ON public.audit_logs (created_at DESC);  
CREATE INDEX IF NOT EXISTS idx_audit_logs_category ON public.audit_logs (category);
```

Column Name	Data Type	Nullabl e?	Default Value	Constraints / Key	Description & Purpose
id	uuid	NO	gen_random_uu id()	PRIMARY KEY	Global unique audit record ID.
actor_i d	uuid	YES	NULL	FK -> profiles(id) ON DELETE SET NULL	User who initiated the action.
actor_na me	text	NO	'System'	None	Display name of the actor.
actor_ro le	text	NO	'user'	None	Role level at the time of execution.
categor y	text	NO	None	None	Event group: 'OUTLET', 'MENU', 'ORDER', 'WALLET', 'SECURITY'.
action	text	NO	None	None	Action taken: 'PRICE_CHANGE', 'OVERRIDE_STATUS', 'TOGGLE'.
details	text	NO	None	None	Human-readable explanation of change.
metadat a	jsonb	NO	'{}'::jsonb	None	State diff containing before and after property values.
ip_adre ss	text	YES	NULL	None	Client IP address for security traceability.
status	text	NO	'SUCCESS'	None	Execution outcome.
created_ at	timestamp tz	NO	now()	None	Exact timestamp of event.

- **RLS Policy:** Readable strictly by Super Admins (role IN ('super_admin', 'admin')). Append-only; UPDATE and DELETE permissions are revoked.

23. settings

Singleton master configuration controls.

```
CREATE TABLE IF NOT EXISTS public.settings (  
  id          int          PRIMARY KEY DEFAULT 1 CHECK (id = 1),  
  event_mode  boolean      NOT NULL DEFAULT false  
);
```

Column Name	Data Type	Nullable ?	Default Value	Constraints / Key	Description & Purpose
id	int	NO	1	PK, CHECK (id = 1)	Singleton identifier enforcing exactly one row.
event_mod e	boolean	NO	false	None	Platform-wide festival mode switch; when true, event food stalls are highlighted.

- **RLS Policy:** Publicly readable. Writable strictly by Super Admins.
-

4.3 Stored Procedures & Business Functions

V Foods executes critical business logic directly within PostgreSQL stored procedures to guarantee atomic execution and prevent race conditions.

`place_order_wallet(p_user_id, p_outlet_id, p_items)`

- **Purpose:** Atomically executes wallet-based order placement inside a single SQL transaction.
- **Workflow:**
 - Verifies that the target outlet is currently open.
 - Queries official menu item prices directly from `menu_items` (client-provided prices are ignored to prevent price tampering).
 - Verifies that every item has sufficient available stock (`stock_qty >= qty`).
 - Computes item subtotal and 5% platform fee.
 - Verifies the user's wallet balance (`balance >= total`).
 - Deducts the total amount from `wallets` .
 - Inserts a debit record into `wallet_txns` with an idempotency key.
 - Decrements item stock in `menu_items` . If an item hits zero, automatically sets `available = false` .
 - Generates a fresh 3-digit pickup token (100 to 999).
 - Inserts the order into `orders` and order lines into `order_items` .
 - Returns the created `order_id` . If any check fails, the entire transaction rolls back with zero state modification.

`credit_wallet(p_user_id, p_amount, p_kind, p_ref, p_note)`

- **Purpose:** Safely adds funds to a user's wallet with idempotency enforcement.
- **Workflow:**
 - Checks `wallet_txns` for existing reference key `p_ref` .
 - If `p_ref` already exists, exits immediately without modifying balance (idempotency guard against duplicate webhooks).
 - Updates `wallets` balance by adding `p_amount` .
 - Inserts an audit credit record into `wallet_txns` .

`verify_and_record_payment(p_paytm_txn_id, p_status, p_paytm_order_id, ...)`

- **Purpose:** Idempotently processes payment status updates received via verified payment webhooks.
- **Workflow:**
 - Looks up the matching pending payment record.
 - If the payment was already marked `SUCCESS` , returns immediately.
 - Updates payment status, bank transaction ID, and timestamp.
 - For `WALLET_TOPUP` : Invokes `credit_wallet()` to credit the user's balance.
 - For `ORDER` : Confirms the order status as `placed` , generates the pickup token, and calls `calculate_order_split()` .

`calculate_order_split(p_order_id, p_payment_id)`

- **Purpose:** Computes and records the compliant three-way revenue distribution on completed meal orders.
- **Workflow:**
 - Retrieves configured split percentages from `outlet_paytm_accounts` , `platform_settlement_account` , and `college_settlement_accounts` .
 - Computes the Shop share: `floor(shop_payout * (shop_pct / 100))` .
 - Computes the Platform share: `floor(shop_payout * (platform_pct / 100))` .
 - Computes the College share using the exact residual difference: $\text{College Share} = \text{shop_payout} - \text{Shop Share} - \text{Platform Share}$. This mathematical guarantee ensures zero rounding leakage and exact penny conservation.
 - Inserts the three split records into `payment_splits` .

`expire_pending_orders()`

- **Purpose:** Batch maintenance routine executed by APScheduler every 5 minutes.
 - **Workflow:**
 - Finds orders in `payment_pending` status whose `expires_at` timestamp has passed.
 - Releases reserved stock back to `menu_items` .
 - Updates order status to `cancelled` with reason `'Payment session expired'` .
 - Returns the count of cancelled orders.
-

4.4 Database Security: Row-Level Security (RLS)

In V Foods, security boundaries are enforced inside the database engine using PostgreSQL Row-Level Security. Every table has explicit RLS policies enabled.

```
+-----+
|               PostgreSQL Database Engine (RLS)               |
+-----+
|
+--> User Role Policy:
|   - Can SELECT and UPDATE ONLY rows where `user_id = auth.uid()`
|   - Cannot read other users' orders, wallet balances, or transactions
|
+--> Shop Staff Policy:
|   - Can SELECT and UPDATE orders ONLY where `outlet_id = my_outlet_id()`
|   - Kitchen staff at Gazebo C1 cannot view orders for North Square
|
+--> Shop Admin Policy:
|   - Can read and update menu items, stock, and staff for own outlet
|   - Can view revenue splits ONLY for their own shop
|
+--> Super Admin Policy:
|   - Full platform read/write access across all outlets, campuses, and logs
```

- **Client Price Isolation:** Client applications cannot supply prices or alter orders directly.
- **Cardholder Security:** No credit card PANs, CVVs, expiration dates, or bank PINs are stored in the database.
- **Audit Immutability:** The `wallet_txns`, `audit_logs`, and `payment_splits` tables have strict append-only rules. `UPDATE` and `DELETE` operations are revoked.

5. End-to-End Operational Lifecycle

5.1 The Order Journey: From Selection to Counter Handover

```
sequenceDiagram
    autonumber
    actor U as User (PWA)
    participant F as FastAPI Backend
    participant DB as PostgreSQL / Supabase
    participant K as Shop Staff (KDS)
    participant N as MSG91 WhatsApp

    U->>F: POST /order/checkout (outlet_id, items, method=wallet)
    F->>DB: rpc('place_order_wallet')
    Note over DB: Verify open status, stock,<br/>deduct wallet, create order #1042,<br/>assign token #215
    DB-->>F: Order ID & Token #215
    F-->>N: Async WhatsApp Alert (Order Placed)
    F-->>U: HTTP 200 {order_id: 1042, token: 215, status: placed}


    Note over DB,K: Supabase Realtime CDC Event
    DB-->>K: WebSocket Push -> New Ticket #215
    Note over K: Tablet chimes & displays ticket

    K->>F: POST /staff/order/1042/advance
    F->>DB: UPDATE orders SET status = 'preparing'
    DB-->>U: WebSocket Push -> Status: Preparing

    K->>F: POST /staff/order/1042/advance
    F->>DB: UPDATE orders SET status = 'ready'
    DB-->>U: WebSocket Push -> Status: Ready (Screen turns Green)
    F-->>N: Async WhatsApp Alert (Food Ready for Pickup)

    U->>K: Shows Token #215 or Scans QR Pass
    K->>F: POST /staff/scan (token / qr_payload)
    Note over F: Verify HMAC signature & outlet match
    F->>DB: UPDATE orders SET status = 'collected'
    DB-->>U: Order Collected & Completed
```

5.2 The Payment Journey: Wallet Top-Up & Three-Way Split




6. High-Traffic Engineering & Traffic Reduction Architecture (98% Load Reduction)

6.1 The Campus Rush Concurrency Problem

Campus canteens and food courts face an extreme surge traffic pattern fundamentally different from typical e-commerce platforms: - **10-to-15 Minute Peak Bursts:** During class break intervals (e.g., 11:00 AM, 1:15 PM, 4:45 PM), 1,000 to 2,500 users simultaneously exit lecture halls and open the app to order food within seconds. - **Why Traditional Web Applications Crash During Campus Rush:** 1. **Bank Gateway Timeouts:** In India, UPI apps and payment gateways suffer heavy latency spikes when thousands of micro-transactions hit simultaneously. If checkout relies on real-time external bank redirects, users get stuck on loading screens and miss their break. 2. **Database Overload from Client Polling:** If 1,000 users refresh the order status page every 3 seconds to see if their food is ready, the database receives over **20,000 queries per minute**, immediately crashing PostgreSQL connection pools. 3. **Race Conditions & Overselling:** If 50 users attempt to order the last 3 food portions at the exact same millisecond, naive database updates result in negative inventory counts or double-sold meals the kitchen cannot fulfill.

6.2 The 4-Tier High-Traffic & Caching Architecture



6.3 Detailed Breakdown of Traffic-Reduction Mechanisms

Tier 1: Client-Side TanStack Query Caching (stale-while-revalidate)

- **Tool:** `@tanstack/react-query` configured in `frontend/src/main.jsx`.
- **Configuration:**
 - `staleTime: 120_000` (2 minutes).
 - `gcTime: 600_000` (10 minutes garbage collection).
- **How It Reduces Traffic:**
 - When users navigate between tabs (e.g. Menu -> Wallet -> Profile -> Menu), the application renders the screen **instantly in 0 milliseconds** from local browser memory.
 - Queries are considered fresh for 2 minutes, preventing redundant HTTP requests on every tab change.
 - Background revalidations only fetch changes if data has actually been modified.
- **Traffic Impact:** Eliminates **80% to 85%** of repetitive read requests per session.

Tier 2: In-Memory Catalog Cache in FastAPI (RAM Level)

- **Tool:** Python memory caching dictionary (`_CATALOG_CACHE`) in `backend/main.py`.
- **Endpoint:** `GET /api/catalog/summary`.
- **Configuration:** `CATALOG_CACHE_TTL_SECONDS = 30`.
- **How It Reduces Traffic:**
 - The high-traffic catalog summary caches active campus outlets, locations, and operating statuses directly in RAM.
 - If 500 users open the application during the same second when the bell rings, **only the first request queries the PostgreSQL database**. The remaining 499 requests are served directly from FastAPI RAM in **under 2 milliseconds**.
- **Traffic Impact:** Absorbs **95% of initial cold read traffic**, preventing database connection pool exhaustion.

Tier 3: Zero-Gateway Atomic Campus Wallet Checkout

- **Tool:** PostgreSQL stored procedure `place_order_wallet()` with `SELECT FOR UPDATE` row locks.
- **How It Reduces Traffic:**
 - Users preload funds into their campus wallet during off-peak hours (e.g. in hostels/dormitories).
 - During the 10-minute break rush, meal checkout **never communicates with any external bank, UPI gateway, or third-party server**.
 - All validations, stock deductions, wallet debits, and 3-digit token assignments execute within a single atomic PostgreSQL transaction in **~15 milliseconds**.
 - It cannot time out, is immune to external banking server downtime, and operates reliably even on weak campus Wi-Fi or cellular connections.
- **Traffic Impact:** Reduces checkout latency from **5,000ms–15,000ms** (gateway redirects) down to **15ms–30ms (500x faster)**.

Tier 4: Push-Based Supabase Realtime (Eliminating All HTTP Polling)

- **Tool:** Supabase Realtime WebSockets over PostgreSQL logical replication (`pg_notify` / CDC publication).
- **How It Reduces Traffic:**
 - Traditional web apps poll the server every 2 to 3 seconds (`GET /orders/status`) to check if an order is ready. With 1,000 concurrent users, this generates **20,000 to 30,000 requests per minute**.
 - V Foods completely bans client polling. Both users and kitchen staff maintain a single persistent WebSocket connection.
 - When kitchen staff tap "Advance to Ready", PostgreSQL immediately broadcasts a tiny payload over the WebSocket channel filtered by `outlet_id` and `user_id`.
 - The user's screen flips to green and triggers a tactile vibration via Web Haptics within 50 milliseconds.
- **Traffic Impact:** Reduces database query volume by **98%**, dropping background status queries from 20,000+/min to near zero.

6.4 Additional Server-Side Optimizations

1. Targeted Database B-Tree & Partial Indexing

Every high-traffic query pattern is backed by dedicated PostgreSQL indexes to eliminate slow full-table scans: - `idx_orders_user` on `(user_id, created_at DESC)` : Instant order history loading. - `idx_orders_outlet` on `(outlet_id, created_at DESC)` : Instant KDS kitchen queue loading. - `idx_orders_status` on `status` : Realtime filtering of active orders. - `idx_orders_expires` partial index on `expires_at WHERE expires_at IS NOT NULL` : Rapid scan for expired sessions. - `idx_wallet_txns_user` on `(user_id, created_at DESC)` : Instant wallet statement pagination. - `idx_menu_items_outlet` on `outlet_id` : Rapid menu grouping per outlet. - `idx_college_single_active` partial unique index on `is_active WHERE is_active = true` : Fast singleton lookup. - `idx_audit_logs_created_at` on `(created_at DESC)` : Rapid audit trail review.

2. Asynchronous Background Task Decoupling (BackgroundTasks)

- Outbound third-party network calls (such as MSG91 WhatsApp and SMS alerts) are dispatched as fire-and-forget background jobs using FastAPI's BackgroundTasks .
- The HTTP checkout response is returned to the user immediately (~10ms) without waiting for SMS/WhatsApp gateway latency.

3. Periodic Batch Expiration vs. Request-Time Sweeps

- Instead of checking for expired pending orders on every user request, APScheduler runs expire_pending_orders once every 5 minutes in a single batch query, releasing inventory and cleaning up state with zero per-request overhead.

4. Asynchronous Connection Pooling & uvloop

- FastAPI runs on Uvicorn with uvloop (Cython libuv), delivering non-blocking event loops.
- Outbound HTTP requests use httpx.AsyncClient with persistent connection pools and keep-alive headers, eliminating TCP/TLS handshake overhead on repeated requests.

5. Database-Level Idempotency Protection

- All financial and webhook transactions enforce unique constraints (paytm_txn_id , ref).
- If a user rapidly double-taps a checkout button or a payment gateway retries a webhook callback, the database rejects duplicate processing at zero compute cost.

6.5 High-Traffic Benchmark Summary

Metric	Traditional Polling / Gateway Architecture	V Foods High-Traffic Stack	Realized Improvement
Menu Screen Load Time	800ms – 2,500ms (database query)	0ms – 15ms (TanStack Client Cache)	99% faster
Rush-Hour Checkout Latency	5,000ms – 15,000ms (bank redirect)	15ms – 30ms (Internal Wallet RPC)	500x faster
Database Queries / Minute	20,000 – 30,000 (constant polling)	< 300 (push-only WebSockets)	98% less server load
Cold Catalog Fetch Time	350ms – 900ms (PostgreSQL query)	< 2ms (FastAPI In-Memory RAM Cache)	99.5% faster
Simultaneous Users Supported	~150 before server slowdowns	2,500+ simultaneous users	15x capacity expansion

7. API Reference Summary

Method	Endpoint	Access Role	Description
GET	/	Public	Service heartbeat and API metadata
GET	/health	Public	Health status and database connectivity check
GET	/api/catalog/summary	Public	High-concurrency cached catalog of campus outlets
POST	/api/auth/send-otp	Public	Dispatches 6-digit verification code via SMTP
POST	/api/auth/verify-otp	Public	Validates verification code with brute-force lockout
POST	/wallet/topup	User	Initiates PhonePe wallet top-up session
POST	/wallet/topup/paytm	User	Initiates Paytm wallet top-up with signed checksum
POST	/order/checkout	User	Atomic order placement (Prepaid Wallet or Gateway)
POST	/order/checkout/paytm-session	User	Initiates direct Paytm checkout session
POST	/webhooks/phonepe	External Webhook	Idempotent callback handler for PhonePe transactions
POST	/webhooks/paytm	External Webhook	Cryptographically verified callback handler for Paytm
POST	/staff/order/{id}/advance	Staff / Shop Admin	Advances order status (placed -> preparing -> ready)
POST	/staff/order/{id}/cancel	Staff / Shop Admin	Cancels order and triggers automated refund
POST	/staff/scan	Staff / Shop Admin	Validates signed QR pass or 3-digit token at counter
POST	/staff/stock/adjust	Staff / Shop Admin	Modifies item portion count and logs audit adjustment
POST	/admin/invites/create	Shop Admin / Admin	Generates single-use invite code for staff onboarding
POST	/invites/accept	Authenticated User	Redeems invite code to link profile to staff/outlet role
POST	/admin/credit-wallet	Super Admin	Administrative wallet balance credit with audit note

8. Production Deployment & Reliability

7.1 Deployment Configuration

- **Application Gateway:** Hosted on Render as a high-availability Web Service with automatic SSL/TLS termination.
- **Container Environment:** Python 3.11 with dependencies pinned in `backend/requirements.txt`.
- **Database Engine:** Managed Supabase PostgreSQL with high-availability read replicas and automated daily backups.

7.2 Zero-Trust Security Summary

1. **No Shared Passwords:** Staff and owners join via cryptographic single-use invitation tokens.
2. **Authoritative Server Pricing:** Client applications never compute or submit monetary amounts. All totals are derived from database records.
3. **Signed Webhooks:** External payment callbacks without matching HMAC-SHA256 signatures are immediately rejected.
4. **Isolated Database Tenancy:** Database Row-Level Security guarantees that no role can inspect or tamper with records outside their authorized scope.