
# V Foods — Complete Architecture & Technology Concepts Guide

> **A Plain-English Reference Guide to Servers, Hosting, Databases, Backends, APIs, and Cloud Infrastructure**

## 1. Executive Summary: How Modern Web Applications Work

Every modern web application in the world—from **V Foods** to Netflix, Uber, Swiggy, and Instagram—is built using three primary layers:




## 2. The Restaurant Analogy (Understand Everything in 2 Minutes)

If computer terms feel confusing, picture a **busy restaurant**:

| Computer Term | Restaurant Equivalent | What It Does In Real Life |
|---|---|---|
| **Frontend** | **The Dining Table, Menu Card & Waiter** | The customer looks at the physical printed menu, decides what they want, and taps the order button. |
| **API** | **The Waiter Taking the Notepad to the Kitchen** | The messenger that carries the customer's request from the table to the kitchen and brings the food back. |
| **Backend** | **The Kitchen & Master Chef** | Follows recipes, checks if ingredients are fresh, verifies payment tokens, and prepares orders securely. |
| **Database** | **The Order Book & Ingredient Ledger** | The strict accounting book where every single rupee, past meal, and current stock count is written down. |
| **File Storage** | **The Cold Storage Pantry & Photo Gallery** | Large shelves where bulky items (food photo files, banners, brand logos) are kept safe. |
| **Server** | **The Physical Kitchen Equipment & Stove** | The physical machine that stays powered on 24 hours a day to do the cooking and calculations. |
| **Hosting (Render)** | **The Landlord Rented Commercial Space** | The company that provides the building, electricity, cooling, and internet so the kitchen runs 24/7. |
| **Domain Name** | **The Street Signboard & Building Address** | The friendly name on the building ( `vfoods.onrender.com` ) so visitors don't have to navigate by raw GPS coordinates (IP addresses). |

---

## 3. Core Terminology Explained Simply

### A. Frontend (Client-Side)

- **In Simple Words**: Everything that executes directly inside the user's web browser (such as Google Chrome, Apple Safari, or Mozilla Firefox) on their smartphone or laptop.
- **Our App**: Built using **React 19 + TypeScript + Vite PWA** (Progressive Web App).
- **What It Does**:
- Shows food menus, prices, and outlet cards.
- Lets users add food items to a shopping cart.
- Shows real-time countdowns and live order statuses (Preparing, Ready for Pickup).
- Runs the Cashier Quick-Bill counter and Outlet Kitchen Display System (KDS).

### B. Backend (Server-Side)

- **In Simple Words**: Software code that runs on a remote cloud computer 24 hours a day. The user can never see, modify, or inspect this code.
- **Our App**: Built using **Python 3.11 + FastAPI** together with the **Supabase Cloud Engine**.

- **What It Does**:
- Verifies payment gateway transactions so people cannot spoof payments.
- Generates tamper-proof, single-use, cryptographic QR pickup codes.
- Sends automated WhatsApp and SMS order confirmation alerts.
- Calculates platform commission and outlet financial settlements.

### C. API (Application Programming Interface)

- **In Simple Words**: A standard set of rules and web addresses that lets two different software programs talk to each other.
- **Example**: When the React frontend wants to verify a payment, it sends an HTTP POST request to `https://vfoods-api.onrender.com/api/payment/verify`. The backend checks the payment and returns `{ "status": "PAID" }`.

### D. Server

- **In Simple Words**: A computer without a screen, keyboard, or mouse that stays plugged into the wall and connected to the high-speed internet 24 hours a day, 365 days a year, waiting to answer requests.
- **Local vs. Cloud**:
- *Local Server*: Your personal laptop running `npm run dev` on `http://localhost:5173`. Only you can access it.
- *Cloud Server*: A machine sitting in an enterprise data center (like Singapore) accessible to anyone worldwide.

### E. Hosting & Cloud Platforms

- **In Simple Words**: The service that rents you cloud computers and keeps your application online.
- **Our App**: Hosted on **Render.com** (located in the AWS Singapore `ap-southeast-1` data center).
- **How It Works**: Every time we commit and push code to GitHub (`main` branch), Render automatically detects the changes, compiles the code, and updates the live website within 60 seconds with zero downtime.


### F. Domain & URL

- **In Simple Words**: The human-readable web name used to visit a website instead of remembering difficult computer IP numbers (like `152.199.19.161`).
- **Our App URLs**:
- **Frontend Web App**: `https://vfoods.onrender.com`
- **Backend API Server**: `https://vfoods-api.onrender.com`
- **Database & BaaS**: `https://wahftohnwfoepuszvzrx.supabase.co`

---

## 4. Databases Demystified: SQL vs. NoSQL

A **database** is a specialized computer program engineered to store, organize, index, and retrieve structured information at lightning speed.




**The Difference in One Sentence:**

- **SQL (Relational)** stores data in **strict tables with rows and columns** (like an Excel workbook with rigid validation rules and connected sheets).
- **NoSQL (Document)** stores data in **free-form, flexible JSON documents** (like a digital folder containing loose Word or text files).

**Detailed Engine Comparison:**

| Database Engine | Type | Data Structure | Everyday Analogy | Best Used For | Used in V Foods? |
|---|---|---|---|---|---|
| **PostgreSQL** | SQL (Relational) | Rigid relational tables with strict data types and foreign keys | A master Excel workbook with formula links and strict rules | Food orders, wallet balances, payments, user profiles | **YES (Primary Database)** |
| **MySQL** | SQL (Relational) | Relational tables and columns | Another spreadsheet engine | WordPress sites, legacy enterprise systems | No |
| **MongoDB** | NoSQL (Document) | Flexible JSON documents ( `{ item: "Dosa", toppings: [...] }` ) | A folder of free-form notes and cards | Social media feeds, chat apps, unstructured logs | No |
| **Firestore** | NoSQL (Document) | Cloud-hosted document collections inside Google Firebase | Nested digital folders | Rapid mobile app prototypes | No |

**Why V Foods Uses PostgreSQL (SQL) Instead of MongoDB:**

1. **Money & Accounting Require Rigid Rules**: In an ordering app, an order must always belong to an existing user ( `user_id` ) and an existing outlet ( `outlet_id` ). If an outlet is deleted, we cannot leave "orphan" money orders. SQL enforces this automatically with foreign keys.
2. **ACID Transactions**: If a user pays ₹100, the system must add ₹100 to the outlet's pending settlement and mark the order as `PAID` at the exact same instant. If one fails, both must cancel. PostgreSQL guarantees this without data corruption.

---


## 5. What is a "Backend-as-a-Service" (BaaS)?

**The Problem With Raw Databases:**

If you download a raw database like **MySQL**, **PostgreSQL**, or **MongoDB**: * They are **just data storage engines**. * A raw database **cannot talk to a mobile phone or web browser directly**! * In traditional software engineering, developers had to spend weeks writing custom backend servers (in Node.js or Python) just to: 1. Hash passwords, generate JWT tokens, and manage user login sessions. 2. Write CRUD REST API routes for every single table ( `/get-menu` , `/update-price` ). 3. Build WebSocket infrastructure for live real-time notifications. 4. Build image upload pipelines to save photos to cloud storage.

**The BaaS Solution:**

A **Backend-as-a-Service (BaaS)** takes a raw database and wraps it inside a complete suite of **pre-built, managed cloud backend tools**:



**BaaS Comparison: Supabase vs. Firebase**

| Feature | Supabase (What V Foods Uses) | Google Firebase |
|---|---|---|
| **Underlying Database** | **PostgreSQL (Relational SQL)** | **Firestore (NoSQL Document Store)** |
| **Open Source?** | ✅ Yes (100% open source) | ❌ No (Proprietary Google technology) |
| **Query Language** | Standard SQL (Joins, Aggregations, Triggers) | Proprietary NoSQL query syntax |
| **Data Integrity** | Strict schema validation, foreign keys | Schema-less (developers must validate manually) |
| **Realtime Sync** | Built-in via PostgreSQL replication | Built-in via Firestore snapshots |
| **File Storage** | Built-in S3-compatible storage buckets | Built-in Google Cloud Storage buckets |
| **Vendor Lock-in** | Low (can export raw Postgres to any cloud) | High (difficult to migrate away from Google) |

---

## 6. The Top Questions & Doubts Answered

**Question 1: "Is Supabase a database or a backend?"**

> **Answer: It is both!**

Think of a **Luxury Car**: * **PostgreSQL** is the **Engine** (the raw data storage mechanism). * **Supabase** is the **Complete Assembled Car**: * **Engine**: PostgreSQL Database * **Door Locks & Smart Key**: Supabase Auth (User Google login & Email OTP) * **Two-Way Radio**: Supabase Realtime (WebSockets for live order tracking) * **Luggage Trunk**: Supabase Storage (Food photos and image files) * **Dashboard Controls**: Supabase Studio (Web browser admin interface) * **Transmission**: PostgREST (Auto-converts SQL tables into instant APIs)

Because Supabase handles both database operations and pre-built backend services, it is classified as a **Backend-as-a-Service**.

---

**Question 2: "Through Supabase, can we access MongoDB or MySQL?"**

> **Answer: No.**

- **Supabase is built strictly and exclusively on PostgreSQL.** When you spin up a Supabase project, Supabase configures a dedicated PostgreSQL cluster. You cannot connect MongoDB or MySQL inside Supabase.
- **Firebase is built strictly on Google Firestore.** You cannot put MySQL or MongoDB inside Firebase.

- Each BaaS platform is hard-wired to its specific underlying database engine.

---

**Question 3: "If Supabase is already a backend, why did we use FastAPI (Python)?"**

> **Answer: Because Supabase is for database management. FastAPI is our secure transaction guard.**

Supabase allows the React frontend to talk directly to the database using a security feature called **Row Level Security (RLS)**. This is fantastic and handles 90% of everyday app operations (viewing menus, checking active orders, browsing canteens).

However, **there are 4 critical security operations that must NEVER happen on the user's phone or in public client code**:

**1. Payment Gateway Secret Keys**

- Payment providers (PhonePe, Paytm, Razorpay) issue two keys:
- A `Public Key` (safe to show).
- A private `MERCHANT_SECRET_KEY` (must remain completely confidential).
- If you placed the merchant secret key inside React or browser code, any user could press `F12` (Inspect Element), extract the secret key, and forge fake payment confirmations!
- **FastAPI holds the secret key safely on the cloud server** and receives official webhooks (`/api/payment/callback`) directly from PhonePe's servers.

**2. Cryptographic Anti-Fraud Food Pickup QR Codes**

- When food is cooked and ready, the user presents a QR code at the outlet pickup counter.
- If the QR code was generated in the browser, anyone could take a screenshot of a friend's QR code or forge yesterday's code to claim free meals.
- **FastAPI uses a secret cryptographic key (`QR_SECRET`) and HMAC-SHA256 encryption** to generate dynamic, single-use, timestamped tokens that expire in 120 seconds.

**3. WhatsApp & SMS Automated Notifications**

- Sending automated order confirmation messages requires private API credentials from telecom gateways (such as MSG91).
- **FastAPI securely connects to the MSG91 API** from the server to dispatch instant WhatsApp alerts.

**4. Escrow Financial Reconciliation**

- Calculating platform fees (5% commission to the platform vs. 95% revenue to the canteen owner) and generating automated bank payout statements.

---

**Question 4: "What is the difference between Database Storage and File/Object Storage?"**


> **Answer: Databases store numbers and text; Object Storage stores big binary files (like photos).**

| Feature | Database (PostgreSQL) | Object Storage (Supabase Storage) |
|---|---|---|
| **What It Stores** | Text, numbers, dates, IDs, passwords, prices | High-resolution JPG, PNG, WEBP, and PDF files |
| **How It Organizes** | Tables with rows and columns | Buckets and folders (like Google Drive) |
| **Size Limit** | Optimized for small records (kilobytes) | Optimized for large files (megabytes or gigabytes) |
| **Why Not Put Photos in SQL?** | Storing millions of photo bytes inside a database row slows down search queries and bloats backups. | Storing photos on a file server and saving only the *URL link* ( `https://.../burger.jpg` ) inside the database keeps the database lightning fast. |

---

## 7. The Complete Technology Stack of V Foods

Here is the exact infrastructure powering **V Foods**:




| Component | Technology Used | Cloud Location / Provider | Purpose |
|---|---|---|---|
| **Frontend Web App** | React 19, TypeScript, Vite, Tailwind CSS | Render.com Static CDN | The responsive web app and Progressive Web App (PWA). |
| **Backend API Server** | Python 3.11, FastAPI, Uvicorn | Render.com (Singapore Web Service) | Secures payments, verifies QR pickup tokens, dispatches WhatsApp alerts. |
| **Database Engine** | PostgreSQL 15+ | Supabase Cloud (AWS Singapore) | Stores orders, menus, outlets, user profiles, and wallets. |
| **Authentication** | Supabase Auth | Supabase Cloud | Handles Google OAuth 2.0 login and Email One-Time Passwords (OTP). |
| **Live Sync** | Supabase Realtime | Supabase Cloud | WebSockets pushing order status updates to kitchen counters instantly. |
| **File Storage** | Supabase Storage | Supabase Cloud S3 Buckets | Hosts food photos, canteen logos, and outlet header banners. |
| **Payment Gateway** | PhonePe PG Sandbox / Paytm / UPI | PhonePe Secure Gateway | Handles digital transactions and UPI payments. |
| **SMS / WhatsApp** | MSG91 Business Gateway | MSG91 Cloud | Delivers instant order confirmation and pickup notifications to phones. |

---

## 8. Life of a Food Order: How Everything Connects

Here is the exact step-by-step path when a user buys a meal on **V Foods**:


[User's Phone]
[FastAPI Server]
[PhonePe / UPI]
[Supabase DB]
1. Taps "Pay ₹120"
Initiates order checkout
2. Creates payment request
Returns secure UPI URL
Opens PhonePe / GPay app
3. User enters UPI PIN
4. Payment successful!
(Sends Webhook)
Validates secret signature
5. Writes Order record: status = "PAID"
6. Real
ring
7. Triggers MSG91 WhatsApp alert to user's phone
[Us
"Order
8. Shows animated order tracker & HMAC QR pickup badge!

## 9. Quick Summary Reference Table

| If someone asks... | The Simple Answer |
| --- | --- |
| "*What is our frontend?*" | **React 19 + Vite**, hosted on Render at `vfoods.onrender.com`. |
| "*What is our backend?*" | We use a **two-part backend**: **Supabase** for database/auth/realtime, and **FastAPI (Python)** for payment verification and anti-fraud QR signing. |
| "*What is our database?*" | **PostgreSQL**, hosted and managed inside **Supabase**. |
| "*Can we use MongoDB or MySQL with Supabase?*" | **No.** Supabase is built specifically on PostgreSQL. |
| "*Where are our servers located?*" | In **Singapore** (AWS region `ap-southeast-1`), managed by Render and Supabase. |
| "*Where are food images stored?*" | In **Supabase Cloud Storage buckets**, not inside database tables. |
| "*Why do we need FastAPI if we have Supabase?*" | To safely protect private payment keys, generate tamper-proof QR codes, and trigger WhatsApp messages without exposing secrets to the frontend browser. |

---

*Document Version: 1.0.0*
*Project: V Foods Smart Campus Dining System*
*Last Updated: October 2026*