

Experiment 11

Execute and display the results for the following Nmap Timing and Performance commands in Kali Linux Operating System:

- i) Aggressive speed scan
- ii) Insane speed scan

Aim

To study the aggressive and insane Nmap timing options for performing faster network scans.

Procedure

1. Open the Kali Linux Terminal.
2. Select an authorized target system for scanning.
3. Execute the Nmap scan using the aggressive timing option.
4. Execute the Nmap scan using the insane timing option.
5. Observe the scanning time and results.
6. Record the output obtained from both scans.

```
labex:project/ $ nmap -T4 127.0.0.1
Starting Nmap 7.80 ( https://nmap.org ) at 2026-10-08 13:06 CST
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00013s latency).
Not shown: 998 closed ports
PORT      STATE SERVICE
22/tcp    open  ssh
3001/tcp   open  nessus

Nmap done: 1 IP address (1 host up) scanned in 0.05 seconds
labex:project/ $ nmap -T5 127.0.0.1
Starting Nmap 7.80 ( https://nmap.org ) at 2026-10-08 13:06 CST
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00015s latency).
Not shown: 998 closed ports
PORT      STATE SERVICE
22/tcp    open  ssh
3001/tcp   open  nessus

Nmap done: 1 IP address (1 host up) scanned in 0.07 seconds
labex:project/ $
```

Result

Thus, the aggressive and insane Nmap timing options were successfully executed and their scanning performance was observed in Kali Linux.

