

Experiment 9

Execute and display the results for the following Nmap Timing and Performance commands in Kali Linux Operating System:

- i) Polite IDS evasion
- ii) Normal IDS evasion

Aim

To study the polite and normal timing options of Nmap for controlling scan speed and performance.

Procedure

1. Open the Kali Linux Terminal.
2. Select an authorized target for scanning.
3. Execute the Nmap command with the polite timing option.
4. Execute the Nmap command with the normal timing option.
5. Observe the difference in scanning speed and output.
6. Record the results.

```
$ pwsh
PowerShell 7.6.2

(kali@kali)-[/home/kali]
PS> nmap -T2 -F 127.0.0.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-03 04:01 -0400
Nmap scan report for localhost (127.0.0.1)
Host is up (0.000073s latency).
All 100 scanned ports on localhost (127.0.0.1) are in ignored states.
Not shown: 100 closed tcp ports (reset)

Nmap done: 1 IP address (1 host up) scanned in 40.21 seconds

(kali@kali)-[/home/kali]
PS> nmap -T3 -F 127.0.0.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-03 04:03 -0400
Nmap scan report for localhost (127.0.0.1)
Host is up (0.0000030s latency).
All 100 scanned ports on localhost (127.0.0.1) are in ignored states.
Not shown: 100 closed tcp ports (reset)

Nmap done: 1 IP address (1 host up) scanned in 0.05 seconds

(kali@kali)-[/home/kali]
PS>
```

Result

Thus, the polite and normal Nmap timing options were successfully executed and their scanning behavior was observed.