

RUBY IF...ELSE, CASE, UNLESS

http://www.tutorialspoint.com/ruby/ruby_if_else.htm

Copyright © tutorialspoint.com

Ruby offers conditional structures that are pretty common to modern languages. Here we will explain all the conditional statements and modifiers available in Ruby

Ruby *if...else* Statement:

Syntax:

```
if conditional [then]
  code...
[elsif conditional [then]
  code...]...
[else
  code...]
end
```

if expressions are used for conditional execution. The values *false* and *nil* are false, and everything else are true. Notice Ruby uses *elsif*, not *else if* nor *elif*.

Executes *code* if the *conditional* is true. If the *conditional* is not true, *code* specified in the *else* clause is executed.

An *if* expression's *conditional* is separated from code by the reserved word *then*, a newline, or a semicolon.

Example:

```
#!/usr/bin/ruby

x=1
if x > 2
  puts "x is greater than 2"
elsif x <= 2 and x!=0
  puts "x is 1"
else
  puts "I can't guess the number"
end
```

```
x is 1
```

Ruby *if* modifier:

Syntax:

```
code if condition
```

Executes *code* if the *conditional* is true.

Example:

```
#!/usr/bin/ruby

$debug=1
print "debug\n" if $debug
```

This will produce following result:

```
debug
```

Ruby *unless* Statement:

Syntax:

```
unless conditional [then]
  code
[else
  code ]
end
```

Executes *code* if *conditional* is false. If the *conditional* is true, code specified in the else clause is executed.

Example:

```
#!/usr/bin/ruby

x=1
unless x>2
  puts "x is less than 2"
else
  puts "x is greater than 2"
end
```

This will produce following result:

```
x is less than 2
```

Ruby *unless* modifier:

Syntax:

```
code unless conditional
```

Executes *code* if *conditional* is false.

Example:

```
#!/usr/bin/ruby

$var = 1
print "1 -- Value is set\n" if $var
print "2 -- Value is set\n" unless $var

$var = false
print "3 -- Value is set\n" unless $var
```

This will produce following result:

```
1 -- Value is set
3 -- Value is set
```

Ruby *case* Statement

Syntax:

```
case expression
[when expression [, expression ...] [then]
  code ]...
```

```
[else  
  code ]  
end
```

Compares the *expression* specified by case and that specified by when using the `===` operator and executes the *code* of the when clause that matches.

The *expression* specified by the when clause is evaluated as the left operand. If no when clauses match, *case* executes the code of the *else* clause.

A when statement's expression is separated from code by the reserved word then, a newline, or a semicolon.

Thus:

```
case expr0  
when expr1, expr2  
  stmt1  
when expr3, expr4  
  stmt2  
else  
  stmt3  
end
```

is basically similar to the following:

```
_tmp = expr0  
if expr1 === _tmp || expr2 === _tmp  
  stmt1  
elsif expr3 === _tmp || expr4 === _tmp  
  stmt2  
else  
  stmt3  
end
```

Example:

```
#!/usr/bin/ruby  
  
$age = 5  
case $age  
when 0 .. 2  
  puts "baby"  
when 3 .. 6  
  puts "little child"  
when 7 .. 12  
  puts "child"  
when 13 .. 18  
  puts "youth"  
else  
  puts "adult"  
end
```

This will produce following result:

```
little child
```