

FLEX - DEPLOY APPLICATION

http://www.tutorialspoint.com/flex/flex_deploy_application.htm

Copyright © tutorialspoint.com


This tutorial will explain you how to create an application **war** file and how to deploy that in Apache Tomcat Webserver root. If you understood this simple example then you will also be able to deploy a complex Flex application following the same steps.

Let us follow the following steps to create a Flex application:


Step	Description
1	Create a project with a name <i>HelloWorld</i> under a package <i>com.tutorialspoint.client</i> as explained in the <i>Flex - Create Application</i> chapter.
2	Modify <i>HelloWorld.mxml</i> as explained below. Keep rest of the files unchanged.
3	Compile and run the application to make sure business logic is working as per the requirements.

Follow the following steps to create a release build of a Flex application and then deploy it to tomcat server:

The first step is to create a release build using Flash Builder IDE. Launch release build wizard using the option **File > Export > Flash Builder > Release Build**



Select project as *HelloWorld* using the wizard window as follows



Leave other default values as such and click Finish Button. Now Flash Builder will create a bin-release folder containing the project's release build.

Now our release build is ready ,let us follow the following steps to deploy a Flex application:

Step	Description
1	Zip the content of the bin-release folder of the application in the form of HelloWorld.war file and deploy it in Apache Tomcat Webserver.
2	Launch your web application using appropriate URL as explained below in the last step.

Following is the content of the modified mxml file **src/com.tutorialspoint/HelloWorld.mxml**.

```
<?xml version="1.0" encoding="utf-8"?>
<s:Application xmlns:fx="http://ns.adobe.com/mxml/2009"
  xmlns:s="library://ns.adobe.com/flex/spark"
  xmlns:mx="library://ns.adobe.com/flex/mx"
  width="100%" height="100%"
  minWidth="500" minHeight="500"
  initialize="application_initializeHandler(event)">
  <fx:Style source="/com/tutorialspoint/client/Style.css"/>
  <fx:Script>
    <![CDATA[
      import mx.controls.Alert;
      import mx.events.FlexEvent;
```


```

protected function btnClickMe_clickHandler(event:MouseEvent):void
{
    Alert.show("Hello World!");
}

protected function application_initializeHandler(event:FlexEvent):void
{
    lblHeader.text = "My Hello World Application";
}
]]>
</fx:Script>
<s:BorderContainer width="500" height="500"
    styleName="container">
    <s:VGroup width="100%" height="100%" gap="50" horizontalAlign="center"
        verticalAlign="middle">
        <s:Label
            styleName="heading"/>
        <s:Button label="Click Me!"
            click="btnClickMe_clickHandler(event)" styleName="button" />
    </s:VGroup>
</s:BorderContainer>
</s:Application>

```

Once you are ready with all the changes done, let us compile and run the application in normal mode as we did in [Flex - Create Application](#) chapter. If everything is fine with your application, this will produce following result: [[Try it online](#)]



Create WAR File

Now our applictaion is working fine and we are ready to export it as a war file. Follow the following steps:

- Go into your project's **bin-release** directory **C:\workspace\HelloWorld\bin-release**
- Select all the files & folders available inside bin-release directory.

- Zip all the selected files & folders in a file called *HelloWorld.zip*.
- Rename *HelloWorld.zip* to *HelloWorld.war*.

Deploy WAR file

- Stop the tomcat server.
- Copy the *HelloWorld.war* file to **tomcat installation directory > webapps folder**.
- Start the tomcat server.
- Look inside webapps directory, there should be a folder **HelloWorld** got created.
- Now HelloWorld.war is successfully deployed in Tomcat Webserver root.

Run Application

Enter a url in web browser: **<http://localhost:8080/HelloWorld/HelloWorld.html>** to launch the application

Server name (localhost) and port (8080) may vary as per your tomcat configuration.

