

MATRIX First Release Manual

Operational guide for the implemented ORACLE/MATRIX tools

MATRIX Development Notes

June 27, 2026

Abstract

This manual defines the first release boundary of **MATRIX** and gives the operational contract for the implemented tools. **MATRIX** is the framework: each tool reads and writes shared enriched **xyzin** sections, uses shared libraries for repeated tasks, and can run independently when its required sections are already present. Fragment search, nano-LEGO assembly and the production TRINITY optimizer are reserved for the next release; this release is closed by the preprocessing, GIC, GF/PED, MORPHEUS, rovibrational, anharmonic, DVR, QM-adapter and GUI workflows documented here.

Contents

1	Release Boundary	2
2	Shared Container Contract	2
3	ORACLE-Babel and Preprocessing	3
4	QM Adapters	3
5	NEO / GICForge	3
6	GF/PED	4
7	MORPHEUS / SEFit	4
8	Rotational Spectroscopy / WMS-Rot	4
9	Vibrational Spectroscopy	5
10	Thermochemistry and Kinetics	5
11	VPT2 / VCI	6
12	DVR	6
13	ORACLE GUI	6
14	Regression and Release Tests	7
15	First Release Closure	7

1 Release Boundary

The first **MATRIX** release is a refactored, documented and testable replacement for the corresponding implemented parts of Merlino/ORACLE. The release is complete when the following conditions hold:

- every implemented scientific tool can run from the command line using only its declared **xyzin** sections;
- the GUI launches the same public commands and does not contain private parsers or scientific algorithms;
- all external file formats enter through one adapter per format;
- the same libraries are used for geometry, topology, symmetry, normal-mode data, diagonalization and publication exports;
- manuals identify consumed sections, produced sections, standalone commands, GUI placement and regression tests.

The next release owns robust fragment search, nano-LEGO fragmentation and assembly, LCB25 fragment indexing, the production TRINITY external energy/gradient optimization loop, PySCF launch/analysis adapters, VSCF for local anharmonic oscillators, vibronic spectroscopy, ionization potentials, electron affinities and online help/manual generation. The current release keeps the fragment and TRINITY schemas, command skeletons and GUI entry points so downstream design does not need another reorganization.

2 Shared Container Contract

The central object is the enriched **xyzin** file. Each tool appends or updates sections instead of passing private scratch formats between modules. A tool must not reparse Gaussian, Molpro, MRCC, SMILES or geometry data if the corresponding shared section is already present.

Section	Owner	Main consumers
#BASIC	ORACLE-Babel / chemistry layer	all molecular tools
#SYMMETRY	ORACLE-Babel	NEO/GICForge, GUI
#TOPOLOGY	ORACLE-Babel	synthons, fragments, GICs
#SYNTHONS	ORACLE-Babel	GF/PED, MORPHEUS, future fragments
#GIC, #SYCART	NEO/GICForge	GF/PED, MORPHEUS, TRINITY
#CARTESIAN_HESSIAN	QM adapters	GF/PED, diagnostics
#NORMAL_MODES	QM adapters	vibrational comparison, hybrid spectra
#QFF	QM adapters	VPT2/VCI
#ROTATIONAL	rovib/QM adapters	WMS-Rot, thermo
#VIBRATIONAL	rovib/QM adapters	spectra, thermo, DOS
#GF_PED	GF/PED	GUI, vibrational workbench

#MORPHEUS	MORPHEUS/SEFit	GUI, reports
#THERMO	thermo	publication exports
#VPT2_VCI	VPT2/VCI	vibrational workbench
#DVR	DVR	GUI, post-run analysis

The practical rule is simple: if two tools need the same information, that information belongs in a shared section and in a shared library, not in two tool-local parsers.

3 ORACLE-Babel and Preprocessing

ORACLE-Babel is the preprocessing gate. It obtains an initial Cartesian geometry by reading an XYZ file directly, importing from a supported QM format, or building from SMILES through RDKit. It then performs symmetry detection, topology analysis, synthon typing and validation once, and writes the results back to the same `xyzin` container.

```
oracle babel preprocess input.xyz molecule.xyzin
oracle babel preprocess smiles.txt molecule.xyzin --source-format smiles
oracle validate molecule.xyzin
```

The output sections are normally `#SOURCE`, `#BASIC`, `#SYMMETRY`, `#TOPOLOGY` and `#SYNTHONS`. Downstream tools must consume those sections rather than re-detecting bonds, rings, point groups or atom classes.

Avogadro remains the preferred manual 3D inspection and editing tool. After the user accepts the molecular structure, the GUI displays the 2D molecular view and all later tasks work from the enriched `xyzin` state.

4 QM Adapters

QM adapters are the only code allowed to understand external program outputs. Gaussian, Molpro and MRCC data are promoted into shared sections. Scientific tools consume these sections and never scan log files privately.

```
oracle gaussian promote-fchk calc.fchk molecule.xyzin
oracle gaussian promote-rovib calc.log molecule.xyzin
oracle gaussian promote-electronic calc.log molecule.xyzin
oracle molpro promote-output molpro.out molecule.xyzin
oracle mrcc promote-output mrcc.out molecule.xyzin
```

The main promoted sections are `#CARTESIAN_HESSIAN`, `#NORMAL_MODES`, `#QFF`, `#ROTATIONAL`, `#VIBRATIONAL`, `#DELTABVIB`, `#ELECTRONIC`, `#TRANSITIONS` and `#ORBITALS`. Orbital files are passed to Molden, Avogadro or MOrbVis-compatible viewers through the GUI command layer.

5 NEO / GICForge

The implemented GIC tool is still exposed as `gicforge` in the command line, with `neo` as an alias. The planned tool name is NEO, “Nonredundant Equivariant Orthogonalizer”. The specialist manual `gicforge_manual.pdf` remains the detailed reference for primitive construction, ring puckering, symmetry projectors, special fragment-aware coordinates, B-matrix construction and Python/Fortran parity.

```
oracle gicforge molecule.xyzin
oracle neo molecule.xyzin
oracle gic-bmatrix oracle.gic.definition.json geometry.xyz
```

NEO consumes `#VALIDATION`, `#SYMMETRY`, `#TOPOLOGY`, `#SYNTHONS` and optional `#FRAGMENTS`. It produces `#GIC` and `#SYCART`. Symmetry-adapted GIC labels begin with the irrep label; totally symmetric blocks can therefore be selected directly in optimization or least-squares workflows.

6 GF/PED

GF/PED consumes a frozen GIC basis and a Cartesian Hessian. The specialist manual `gf_manual.pdf` is the detailed reference for Wilson GF theory, internal force constants, PEDs, local force-field approximations and Pulay-style scaling of force constants in GIC space.

```
oracle gf --xyzin molecule.xyzin --out gf.report
oracle gf --xyzin molecule.xyzin --csv-dir gf_tables
```

The module writes `#GF_PED`. It can subtract electrostatic and van der Waals non-bonded terms before a local force-field model is built. Frequency scaling is not a MATRIX vibrational-spectrum operation; scaling belongs here, at the force-constant level, where diagonal class scaling and geometric-mean off-diagonal scaling are chemically meaningful.

7 MORPHEUS / SEFit

MORPHEUS performs semiexperimental geometry refinement. It includes the SEFit single-structure workflow and the multi-structure class-correction workflows. The detailed manuals are `morpheus_manual.pdf` and `multistrucre_manual.pdf`.

```
oracle semiexp --xyzin molecule.xyzin --job job.toml --outdir run
oracle semiexp-ensemble ensemble.toml --outdir ensemble_run
oracle semiexp-benchmark snapshot.json --outdir benchmark
```

MORPHEUS consumes isotopologue data and optional `#GIC`, `#SYCART` or `#MORPHEUS` state. It writes `#MORPHEUS`, diagnostics, CSV tables and paper-oriented summaries. The local `se_geometries` library is an implemented support library; large-scale fragment search and nano-LEGO assembly remain next-release work.

8 Rotational Spectroscopy / WMS-Rot

The rotational workbench uses the local WMS-Rot Hamiltonian engine imported from the group web service. MATRIX does not reimplement the Hamiltonian. It normalizes constants, dipoles and vibration-rotation corrections through `#ROTATIONAL`, `#VIBRATIONAL` and `#DELTAVIB`, then calls the local engine.

```
oracle ro vib summarize molecule.xyzin
oracle ro vib wmsrot-input molecule.xyzin --out wmsrot.in
oracle ro vib wmsrot-run molecule.xyzin --out rotational_lines.csv
```

The run writes line lists suitable for plotting and publication export. Future database comparison should query microwave/submillimeter catalogs through a shared experimental-spectrum adapter,

not from GUI-local code. The planned catalog targets are CDMS, JPL and Splatalogue, with molecule identifiers, frequency windows, isotopic species and provenance saved in export metadata.

9 Vibrational Spectroscopy

The vibrational workbench plots IR, Raman, VCD and ROA spectra when the corresponding harmonic or anharmonic data are present in `#VIBRATIONAL`. It can compare spectra from one or two `xyzin` files. For ordinary IR and Raman comparisons, the second trace is plotted with negative intensity. VCD and ROA are signed observables and are therefore not mirrored.

```
oracle ro vib-spectrum molecule.xyzin --observable IR \
  --source harmonic --csv ir.csv --plot ir.svg

oracle ro vib-compare level1.xyzin level2.xyzin \
  --observable IR --first-source harmonic --second-source anharmonic \
  --csv compare.csv --plot compare.svg
```

Hybrid spectra are implemented as

$$\nu_{\text{hybrid}} = \nu_{\text{harm}}(\text{level1}) + [\nu_{\text{anh}}(\text{level2}) - \nu_{\text{harm}}(\text{level2})].$$

Before applying the correction, MATRIX reads `#NORMAL_MODES` from both files and performs a global assignment that maximizes the absolute normal-mode overlap. If any assigned overlap is below the threshold, the hybrid spectrum is rejected.

```
oracle ro vib-spectrum level1.xyzin --source hybrid \
  --level2-xyzin level2.xyzin --observable IR \
  --csv hybrid.csv --plot hybrid.svg \
  --mode-match-csv mode_matches.csv --min-mode-overlap 0.70
```

Experimental NIST IR spectra are fetched automatically only when the NIST JCAMP record declares a gas-phase state. Condensed-phase records, missing records and unparseable records are returned to the GUI as states requiring user instructions.

```
oracle ro vib nist-ir 74-82-8 --out methane_nist_ir.csv
```

10 Thermochemistry and Kinetics

The implemented thermochemistry tool consumes normalized molecular, rotational and vibrational sections and writes `#THERMO`. The GUI Thermo/Kinetics workbench displays the generated thermochemical tables and rovibrational density-of-states outputs. Production kinetics models and `#KINETICS` are a future extension boundary, not a blocker for this release.

```
oracle thermo molecule.xyzin --out thermo.report
oracle ro vib dos molecule.xyzin --out dos_vib.dat
oracle ro vib dos-ro vib molecule.xyzin --out dos_ro vib.dat --q-out ro vib_qt.dat
```

Publication exports should keep temperature, pressure, symmetry number, frequency set, rotational constants and data provenance in the table metadata.

11 VPT2 / VCI

The VPT2/VCI package consumes #QFF. Gaussian FCHK or QFF text is only an adapter input; standalone operation reads the normalized xyzin section. Reports and CSV tables are attached to the vibrational workbench.

```
oracle vpt2-vci --xyzin molecule.xyzin --run-dir vpt2_run
oracle vpt2-vci --xyzin molecule.xyzin --run-dir vci_run --model vci
```

VPT2/VCI uses the shared diagonalization policy where matrix diagonalization is the dominant cost. GPU acceleration is delegated to the shared `oracle_core.diagonalizer` layer when supported by the local machine.

12 DVR

DVR workflows prepare and run scan/path DVR calculations and then normalize the post-run outputs into the GUI state. Large Hamiltonian diagonalizations are routed through the same shared diagonalizer used by other MATRIX modules.

```
oracle dvr prepare molecule.xyzin --scan-log scan.log --run-dir dvr_run
oracle dvr run --xyzin molecule.xyzin --run-dir dvr_run
oracle dvr status molecule.xyzin
```

The implemented GUI state is #DVR. New DVR engines must not add private diagonalization wrappers; they should call the shared diagonalizer so CPU/GPU policy is controlled in one place.

13 ORACLE GUI

The GUI keeps the ORACLE name in the MATRIX framework. Its planned expansion is “Operator for Routing, Analysis, Control, Launch and Exploration”. The GUI owns project state, command construction, missing-section guidance, file selection, external viewer launches and publication export orchestration. It does not own scientific parsers or algorithms.

```
python -m oracle_gui molecule.xyzin
oracle-gui molecule.xyzin
```

The first-release GUI exposes:

- project dashboard and section readiness;
- structure/synthon/topology inspection and Avogadro handoff;
- NEO/GICForge, GF/PED, MORPHEUS, VPT2/VCI, DVR and TRINITY panels;
- rotational, vibrational, electronic and thermochemistry workbenches;
- orbital viewer launch through Molden, Avogadro or MOrbVis-compatible external viewers;
- missing-section suggestions that point to the owning adapter or tool.

14 Regression and Release Tests

The release gate is the full test suite plus focused smoke tests for workflows that cross tool boundaries. The minimum command is:

```
source scripts/oracle_env.sh
oracle-set
python -m ruff check packages tests
python -m pytest -q
```

Important cross-module checks include:

- Python/Fortran NEO/GICForge primitive, GIC and B-row agreement;
- GF/PED writing and reading #GF_PED;
- MORPHEUS standalone and multi-structure runs;
- WMS-Rot local line-list generation;
- vibrational mirror comparison and hybrid level1+level2 normal-mode matching;
- VPT2/VCI and DVR diagonalizer routing;
- GUI command builders matching the public CLI.

15 First Release Closure

With this manual and the specialist manuals present, the first **MATRIX** release can be declared closed when the repository is clean, the full tests pass, and the manuals are generated from source. The next release then starts from a clear scope: robust fragments, nano-LEGO, LCB25 fragment indexing, production TRINITY optimization, PySCF adapters, VSCF, vibronic spectroscopy, IP/EA workflows and online help/manual generation.