

Supporting Information for SONIC: Symmetry-Oriented Non-redundant Internal Coordinates

Vincenzo Barone

Norbornane SMITH/SONIC Standalone Input and Gaussian 16 Export

This Supporting Information records the minimal standalone input required to generate the norbornane SONIC coordinate contract and the corresponding commercial Gaussian 16 **ReadAllGIC** input used in the compatibility test. The first listing is intentionally not the enriched **xyzin** container written after molecular perception and coordinate construction. It contains only a standard XYZ geometry followed by the minimum SMITH directives needed for this Gaussian-compatible export. The standalone workflow selects the commercial Gaussian 16 profile by default, including Gaussian-style improper-dihedral construction in place of native SONIC out-of-plane rows. For this one-file example, the standalone package uses its pinned reduced ORACLE profile to supply the graph, cycles, symmetry, ordinary redundant primitives and their Wilson B source matrix, and continuous atom descriptors needed by SMITH. This convenience profile is recorded in the generated provenance and is distinct from the full ORACLE perception application, a development of PROXIMA that will be described separately. The full application is currently in final testing and will be released when ready.

The exact standalone workflow is:

```
python -m matrix smith standalone norbornane_smith_input.xyzin norbornane.xyzin
python -m matrix smith gaussian-input norbornane.xyzin norbornane.g16_readallgic.gjf \
--title "norbornane SONIC ReadAllGIC optimization" \
--route "#p hf/sto-3g opt=(readallgic,calcfc,maxcycle=80)"
```

Equivalently, after installation of MATRIX the console-script shorthand is **smith standalone ...** followed by **smith gaussian-input ...**. The reduced package distributed with the manuscript constructs the same contract with **smith-sonic build norbornane.smith.xyz norbornane.xyzin** and automatically writes both **norbornane.smith.out** and **norbornane.g16.gjf**. The default Gaussian 16 profile suppresses active composite, U-based ring-puckering SONIC rows in the Gaussian file and writes their terminally translated component periodic **D(...)** coordinates instead; the non-redundant SONIC rows remain in the **xyzin** contract used for post-processing.

SMITH/SONIC input

Listing 1: Minimal norbornane SMITH/SONIC standalone input: standard XYZ block plus the required export directives.

```
19
Norbornane starting geometry for standalone SMITH/SONIC ReadAllGIC export
C      1.25441300      0.78233900     -0.49340600
C      0.00000000      1.13336700      0.33992900
C     -0.00000000     -1.13336700      0.33992900
C      1.25441300     -0.78233900     -0.49340600
H      1.20544300      1.20489500     -1.50351600
H      2.16019200      1.17688700     -0.01817100
H      1.20544300     -1.20489500     -1.50351600
H      2.16019200     -1.17688700     -0.01817100
C      0.00000000      0.00000000      1.38887600
H     -0.89255700      0.00000000      2.02655300
H      0.89255700     -0.00000000      2.02655300
C     -1.25441300      0.78233900     -0.49340600
```

H	-2.16019200	1.17688700	-0.01817100
H	-1.20544300	1.20489500	-1.50351600
C	-1.25441300	-0.78233900	-0.49340600
H	-2.16019200	-1.17688700	-0.01817100
H	-1.20544300	-1.20489500	-1.50351600
H	0.00000000	2.15523000	0.73149700
H	-0.00000000	-2.15523000	0.73149700

```
#SMITH
schema = matrix.smith.input.v1
symmetrize = false
```

Generated Gaussian 16 input

Listing 2: Commercial Gaussian 16-compatible ReadAllGIC input generated automatically from the SMITH/SONIC contract. Composite U-based SONIC ring-puckering rows are absent by construction; their terminally translated component periodic dihedrals appear as V0001, V0002,

```
#p hf/sto-3g opt=(readallgic,calcfc,maxcycle=80) output=pickett

norbornane SONIC ReadAllGIC optimization

O 1
C 1.25441300 0.78233900 -0.49340600
C 0.00000000 1.13336700 0.33992900
C -0.00000000 -1.13336700 0.33992900
C 1.25441300 -0.78233900 -0.49340600
H 1.20544300 1.20489500 -1.50351600
H 2.16019200 1.17688700 -0.01817100
H 1.20544300 -1.20489500 -1.50351600
H 2.16019200 -1.17688700 -0.01817100
C 0.00000000 0.00000000 1.38887600
H -0.89255700 0.00000000 2.02655300
H 0.89255700 -0.00000000 2.02655300
C -1.25441300 0.78233900 -0.49340600
H -2.16019200 1.17688700 -0.01817100
H -1.20544300 1.20489500 -1.50351600
C -1.25441300 -0.78233900 -0.49340600
H -2.16019200 -1.17688700 -0.01817100
H -1.20544300 -1.20489500 -1.50351600
H 0.00000000 2.15523000 0.73149700
H -0.00000000 -2.15523000 0.73149700

GIC001(Value=0.0) = 0.707106781187*(R(9,10))-0.707106781187*(R(9,11))
GIC002(Value=2.93156150623) = 0.707106781187*(R(9,10))+0.707106781187*(R(9,11))
GIC003(Value=1.09633572703) = R(1,6)
GIC004(Value=1.09633572703) = R(4,8)
GIC005(Value=1.09633572703) = R(12,13)
GIC006(Value=1.09633572703) = R(15,16)
GIC007(Value=1.09602638934) = R(4,7)
GIC008(Value=1.09602638934) = R(12,14)
GIC009(Value=1.09602638934) = R(15,17)
GIC010(Value=1.09602638934) = R(1,5)
GIC011(Value=1.09431690538) = R(2,18)
GIC012(Value=1.09431690538) = R(3,19)
GIC013(Value=1.564678) = R(1,4)
GIC014(Value=1.564678) = R(12,15)
GIC015(Value=0.0) = 0.707106781187*(R(3,4))-0.707106781187*(R(3,15))
GIC016(Value=0.0) = -0.707106781187*(R(1,2))+0.707106781187*(R(2,12))
GIC017(Value=4.13260235459) = 0.707106781187*(R(3,4))+0.707106781187*(R(3,15))
GIC018(Value=4.13260235459) = 0.707106781187*(R(1,2))+0.707106781187*(R(2,12))
GIC019(Value=0.0) = -0.707106781187*(R(2,9))+0.707106781187*(R(3,9))
GIC020(Value=4.12706024365) = 0.707106781187*(R(2,9))+0.707106781187*(R(3,9))
GIC021(Value=-0.0573424722848) = 0.816496580928*(A(5,1,6))-0.408248290464*(A(2,1,5))-0.408248290464*(A(2,1,6))
GIC022(Value=0.0136523036609) = 0.707106781187*(A(2,1,5))-0.707106781187*(A(2,1,6))
GIC023(Value=-0.0650891780287) = 0.816496580928*(A(5,1,6))-0.408248290464*(A(4,1,5))-0.408248290464*(A(4,1,6))
GIC024(Value=0.0195508295595) = 0.707106781187*(A(4,1,5))-0.707106781187*(A(4,1,6))
GIC025(Value=0.0337761539671) = 0.816496580928*(A(18,2,9))-0.408248290464*(A(18,2,12))-0.408248290464*(A(18,2,1))
GIC026(Value=0.0) = 0.707106781187*(A(18,2,12))-0.707106781187*(A(18,2,1))
GIC027(Value=0.0337761539671) = 0.816496580928*(A(19,3,9))-0.408248290464*(A(19,3,15))-0.408248290464*(A(19,3,4))
GIC028(Value=0.0) = 0.707106781187*(A(19,3,15))-0.707106781187*(A(19,3,4))
GIC029(Value=-0.0650891780287) = 0.816496580928*(A(7,4,8))-0.408248290464*(A(1,4,7))-0.408248290464*(A(1,4,8))
GIC030(Value=0.0195508295595) = 0.707106781187*(A(1,4,7))-0.707106781187*(A(1,4,8))
GIC031(Value=-0.0573424722848) = 0.816496580928*(A(7,4,8))-0.408248290464*(A(3,4,7))-0.408248290464*(A(3,4,8))
GIC032(Value=0.0136523036609) = 0.707106781187*(A(3,4,7))-0.707106781187*(A(3,4,8))
GIC033(Value=-0.0619062683331) = 0.816496580928*(A(10,9,11))-0.408248290464*(A(2,9,10))-0.408248290464*(A(2,9,11))
```

```

GIC034(Value=0.0) = 0.707106781187*(A(2,9,10))-0.707106781187*(A(2,9,11))
GIC035(Value=-0.0619062683331) = 0.816496580928*(A(10,9,11))-0.408248290464*(A(3,9,10))-0.408248290464*(A(3,9,11))
GIC036(Value=0.0) = 0.707106781187*(A(3,9,10))-0.707106781187*(A(3,9,11))
GIC037(Value=-0.0573424722848) = 0.816496580928*(A(13,12,14))-0.408248290464*(A(2,12,13))-0.408248290464*(A(2,12,14))
GIC038(Value=-0.0136523036609) = 0.707106781187*(A(2,12,13))-0.707106781187*(A(2,12,14))
GIC039(Value=-0.0650891780287) = 0.816496580928*(A(13,12,14))-0.408248290464*(A(15,12,13))-0.408248290464*(A(15,12,14))
GIC040(Value=-0.0195508295595) = 0.707106781187*(A(15,12,13))-0.707106781187*(A(15,12,14))
GIC041(Value=-0.0573424722848) = 0.816496580928*(A(16,15,17))-0.408248290464*(A(3,15,16))-0.408248290464*(A(3,15,17))
GIC042(Value=-0.0136523036609) = 0.707106781187*(A(3,15,16))-0.707106781187*(A(3,15,17))
GIC043(Value=-0.0650891780287) = 0.816496580928*(A(16,15,17))-0.408248290464*(A(12,15,16))-0.408248290464*(A(12,15,17))
GIC044(Value=-0.0195508295595) = 0.707106781187*(A(12,15,16))-0.707106781187*(A(12,15,17))
GIC045(Value=-0.0207227541011) = 0.632455532034*(A(3,4,1))-0.511667273602*(A(4,1,2))+0.195439507585*(A(1,2,9))
+0.195439507585*(A(2,9,3))-0.511667273602*(A(9,3,4))
GIC046(Value=-0.063778079142) = 0.37174803446*(A(4,1,2))-0.601500955008*(A(1,2,9))+0.601500955008*(A(2,9,3))-0.37174803446*(A(9,3,4))
GIC047(Value=-0.0207227541011) = 0.632455532034*(A(3,15,12))-0.511667273602*(A(15,12,2))+0.195439507585*(A(12,2,9))
+0.195439507585*(A(2,9,3))-0.511667273602*(A(9,3,15))
GIC048(Value=-0.063778079142) = 0.37174803446*(A(15,12,2))-0.601500955008*(A(12,2,9))+0.601500955008*(A(2,9,3))
-0.37174803446*(A(9,3,15))
V0001(Value=-55.8772472164) = D(1,2,9,3)
V0002(Value=55.8772472164) = D(2,9,3,4)
V0003(Value=-35.2663208258) = D(9,3,4,1)
V0004(Value=0.0) = D(3,4,1,2)
V0005(Value=35.2663208258) = D(4,1,2,9)
V0006(Value=55.8772472164) = D(12,2,9,3)
V0007(Value=-55.8772472164) = D(2,9,3,15)
V0008(Value=35.2663208258) = D(9,3,15,12)
V0009(Value=0.0) = D(3,15,12,2)
V0010(Value=-35.2663208258) = D(15,12,2,9)

```

Gaussian 16 output excerpt

The complete Gaussian log is retained in the reproducibility archive. The excerpt below records the optimization progress and termination diagnostics.

Listing 3: Selected Gaussian 16 output lines for the norbornane `ReadAllGIC` run.

```

138: CrdQ2X: Updating Cartesian coordinates based on modified values of the internal ones.
590: SCF Done: E(RHF) = -268.892840294 A.U. after 9 cycles
913: Step number 1 out of a maximum of 80
1272: SCF Done: E(RHF) = -268.893823525 A.U. after 7 cycles
1332: Step number 2 out of a maximum of 80
1425: Optimization completed.
1426: -- Stationary point found.
1853: Normal termination of Gaussian 16 at Wed Jul 8 13:46:24 2026.

```

Advanced Standalone Interface Probes

The standalone distribution also contains two examples that exercise the interfaces not covered by a single covalent molecule. Every build writes three coordinated artifacts: the frozen `xyzin` contract, a readable `.smith.out` report modeled on the essential coordinate section of the former Merlino output, and a commercial Gaussian 16 `ReadAllGIC` input. The report records the family, reduction class, irrep, active/frozen status, reference value, native unit, and primitive coefficients of each selected coordinate. Non-totally symmetric coordinates are present in the Gaussian file with the `Frozen` option; helper center and fragment definitions are written as inactive Gaussian functions.

Formic-acid-water non-covalent complex

The eight-atom complex is processed with the reduced perception profile and an automatic connected-component fragment definition. It closes at rank 18/18. The final six protected rows are three relative fragment translations and three relative fragment orientations; the other twelve rows span the intramolecular motions. The excerpt below is generated, not manually transcribed.

Listing 4: Coordinate-definition excerpt for the formic-acid-water complex. The complete report is supplied as `si/formic_acid_water_smith_report.txt`.

Coordinate Definitions

```

1 GIC001 Str0001 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=1.095460024 unit=angstrom components=P001:+1
2 GIC002 Str0002 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=1.211503996 unit=angstrom components=P002:+1
3 GIC003 Str0003 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=1.325944816 unit=angstrom components=P003:+1
4 GIC004 Str0004 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=0.985874998 unit=angstrom components=P004:+1
5 GIC005 Str0005 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=0.9603233822 unit=angstrom components=P005:+1
6 GIC006 Str0006 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=0.9705527871 unit=angstrom components=P006:+1
7 GIC007 Bend0001 family=BEND class=ORDINARY irrep=A state=ACTIVE value=2.151557636 unit=radian components=P016:+1
8 GIC008 Bend0002 family=BEND class=ORDINARY irrep=A state=ACTIVE value=1.936214312 unit=radian components=P017:+1
9 GIC009 ImpD0001 family=IMPROPER_DIHEDRAL class=ORDINARY irrep=A state=ACTIVE value=3.141106217 unit=radian components=
  P023:+1
10 GIC010 Bend0004 family=BEND class=ORDINARY irrep=A state=ACTIVE value=1.886705122 unit=radian components=P019:+1
11 GIC011 Bend0005 family=BEND class=ORDINARY irrep=A state=ACTIVE value=1.856621311 unit=radian components=P020:+1
12 GIC012 Tors0001 family=TORSION class=ORDINARY irrep=A state=ACTIVE value=-3.141071603 unit=radian components=P021:+1
13 GIC013 FTrn0001 family=FRAG_TRANSLATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=2.794364267 unit=angstrom
  components=P008:+1
14 GIC014 FTrn0002 family=FRAG_TRANSLATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=-0.5396128667 unit=angstrom
  components=P009:+1
15 GIC015 FTrn0003 family=FRAG_TRANSLATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=0.1935490667 unit=angstrom
  components=P010:+1
16 GIC016 FRot0001 family=FRAG_ORIENTATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=0 unit=radian components=
  P011:+1
17 GIC017 FRot0002 family=FRAG_ORIENTATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=0 unit=radian components=
  P012:+1
18 GIC018 FRot0003 family=FRAG_ORIENTATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=0 unit=radian components=
  P013:+1

```

Listing 5: Gaussian 16 ReadAllGIC input generated for the formic-acid-water fragment contract. Fragment objects and body-frame helpers are declared before the 18 active rows.

```

#p hf/sto-3g opt=(readallgic,calcf, maxcycle=80) output=pickett

formic_acid_water SMITH/SONIC Gaussian 16 optimization

O 1
C      -1.17172700      -0.01899900      -0.00137000
H      -2.25686900       0.13036900      -0.01510700
O      -0.65137600      -1.11304500       0.00496400
O      -0.53354400       1.14322800       0.00760300
H       0.43520300       0.96063300       0.01934300
O       1.93014500      -0.02597600      -0.05226900
H       2.59464300      -0.12891700       0.63334500
H       1.35131700      -0.80263400       0.00883100

F001=Fragment(1-5)
F002=Fragment(6-8)
CxFO01(Inactive)=XCntr(F001)
CyFO01(Inactive)=YCntr(F001)
CzFO01(Inactive)=ZCntr(F001)
CxFO02(Inactive)=XCntr(F002)
CyFO02(Inactive)=YCntr(F002)
CzFO02(Inactive)=ZCntr(F002)
RPF001(Inactive)=SQRT((X(5)-CxFO01)**2+(Y(5)-CyFO01)**2+(Z(5)-CzFO01)**2)
PxFO01(Inactive)=[X(5)-CxFO01]/RPF001
PyFO01(Inactive)=[Y(5)-CyFO01]/RPF001
PzFO01(Inactive)=[Z(5)-CzFO01]/RPF001
QQxF001(Inactive)=PyFO01*[Z(3)-CzFO01]-PzFO01*[Y(3)-CyFO01]
QQyF001(Inactive)=PzFO01*[X(3)-CxFO01]-PxFO01*[Z(3)-CzFO01]
QQzF001(Inactive)=PxFO01*[Y(3)-CyFO01]-PyFO01*[X(3)-CxFO01]
RQF001(Inactive)=SQRT(QQxF001**2+QQyF001**2+QQzF001**2)
QxF001(Inactive)=QQxF001/RQF001
QyF001(Inactive)=QQyF001/RQF001
QzF001(Inactive)=QQzF001/RQF001
SxF001(Inactive)=PyFO01*QzF001-PzFO01*QyFO01
SyFO01(Inactive)=PzFO01*QxF001-PxFO01*QzFO01
SzFO01(Inactive)=PxFO01*QyFO01-PyFO01*QxF001
RPF002(Inactive)=SQRT((X(8)-CxFO02)**2+(Y(8)-CyFO02)**2+(Z(8)-CzFO02)**2)
PxFO02(Inactive)=[X(8)-CxFO02]/RPF002
PyFO02(Inactive)=[Y(8)-CyFO02]/RPF002
PzFO02(Inactive)=[Z(8)-CzFO02]/RPF002
QQxF002(Inactive)=PyFO02*[Z(6)-CzFO02]-PzFO02*[Y(6)-CyFO02]
QQyF002(Inactive)=PzFO02*[X(6)-CxFO02]-PxFO02*[Z(6)-CzFO02]
QQzF002(Inactive)=PxFO02*[Y(6)-CyFO02]-PyFO02*[X(6)-CxFO02]
RQF002(Inactive)=SQRT(QQxF002**2+QQyF002**2+QQzF002**2)
QxF002(Inactive)=QQxF002/RQF002
QyF002(Inactive)=QQyF002/RQF002
QzF002(Inactive)=QQzF002/RQF002
SxF002(Inactive)=PyFO02*QzF002-PzFO02*QyFO02

```

```

SyF002(Inactive)=PzF002*QxF002-PxF002*QzF002
SzF002(Inactive)=PxF002*QyF002-PyF002*QxF002
R11F002F001(Inactive)=PxF002*PxF001+PyF002*PyF001+PzF002*PzF001
R12F002F001(Inactive)=PxF002*QxF001+PyF002*QyF001+PzF002*QzF001
R13F002F001(Inactive)=PxF002*SxF001+PyF002*SyF001+PzF002*SzF001
R21F002F001(Inactive)=QxF002*PxF001+QyF002*PyF001+QzF002*PzF001
R22F002F001(Inactive)=QxF002*QxF001+QyF002*QyF001+QzF002*QzF001
R23F002F001(Inactive)=QxF002*SxF001+QyF002*SyF001+QzF002*SzF001
R31F002F001(Inactive)=SxF002*PxF001+SyF002*PyF001+SzF002*PzF001
R32F002F001(Inactive)=SxF002*QxF001+SyF002*QyF001+SzF002*QzF001
R33F002F001(Inactive)=SxF002*SxF001+SyF002*SyF001+SzF002*SzF001
KwF002F001(Inactive)=0.5*SQRT(R11F002F001+R22F002F001+R33F002F001+1)
KxF002F001(Inactive)=(R23F002F001-R32F002F001)/(4*KwF002F001)
KyF002F001(Inactive)=(R31F002F001-R13F002F001)/(4*KwF002F001)
KzF002F001(Inactive)=(R12F002F001-R21F002F001)/(4*KwF002F001)
KnF002F001(Inactive)=SQRT(KxF002F001**2+KyF002F001**2+KzF002F001**2+1.0D-24)
ThF002F001(Inactive)=2*ATAN(KnF002F001/KwF002F001)
ExF002F001(Inactive)=ThF002F001*KxF002F001/KnF002F001
EyF002F001(Inactive)=ThF002F001*KyF002F001/KnF002F001
EzF002F001(Inactive)=ThF002F001*KzF002F001/KnF002F001
GIC001(Value=1.09546002426) = R(1,2)
GIC002(Value=1.21150399623) = R(1,3)
GIC003(Value=1.32594481625) = R(1,4)
GIC004(Value=0.985874997976) = R(4,5)
GIC005(Value=0.960323382242) = R(6,7)
GIC006(Value=0.9705527871) = R(6,8)
GIC007(Value=123.275171935) = A(2,1,3)
GIC008(Value=110.936908332) = A(2,1,4)
GIC009(Value=179.972129264) = D(2,1,4,3)
GIC010(Value=108.100240696) = A(1,4,5)
GIC011(Value=106.376565278) = A(7,6,8)
GIC012(Value=-179.970146027) = D(2,1,4,5)
GIC013 = CxF002-CxF001
GIC014 = CyF002-CyF001
GIC015 = CzF002-CzF001
GIC016 = ExF002F001
GIC017 = EyF002F001
GIC018 = EzF002F001

```

η^3 allyl-palladium interaction center

The ten-atom idealized allyl-PdCl probe consumes a frozen ORACLE-state fixture. Its center record has identifier C001, kind ETA3_CENTER, and atoms 3–5. SMITH retains the Pd-center distance as a protected CENTER_ATOM_DISTANCE; the contract closes at rank 24/24 and gives a reference value of 1.8000 Å. This is a perception/coordinate interface test rather than an optimized transition-metal benchmark.

Listing 6: Coordinate-definition excerpt for the η^3 allyl-palladium probe. The complete report is supplied as `si/eta3_allyl_palladium_smith_report.txt`.

```

Coordinate Definitions
-----
1 GIC001 CnAt0001 family=CENTER_ATOM_DISTANCE class=SPECIAL_PROTECTED irrep=UNASSIGNED state=ACTIVE value=1.8 unit=
  angstrom components=P012:+1
2 GIC002 Str0001 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.3 unit=angstrom components=P001:+1
3 GIC003 Str0002 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.140093456 unit=angstrom components=
  P002:+1
4 GIC004 Str0003 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2 unit=angstrom components=P003:+1
5 GIC005 Str0004 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.140093456 unit=angstrom components=
  P004:+1
6 GIC006 Str0005 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.334166406 unit=angstrom components=
  P005:+1
7 GIC007 Str0006 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.070046728 unit=angstrom components=
  P006:+1
8 GIC008 Str0007 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.087428159 unit=angstrom components=
  P007:+1
9 GIC009 Str0009 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.09 unit=angstrom components=P009:+1
10 GIC010 Str0010 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.070046728 unit=angstrom components=
  P010:+1
11 GIC011 Str0011 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.087428159 unit=angstrom components=
  P011:+1
12 GIC012 Bend0001 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.488746022 unit=radian components=P013
  :+1
13 GIC013 LinB0001 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P014:+1
14 GIC014 LinB0003 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P021:+1
15 GIC015 LinB0004 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P022:+1

```

```

16 GIC016 Bend0007 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.400238589 unit=radian components=P023
: +1
17 GIC017 Bend0009 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.000947705 unit=radian components=P025
: +1
18 GIC018 LinB0005 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P029: +1
19 GIC019 LinB0006 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P030: +1
20 GIC020 LinB0007 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P035: +1
21 GIC021 LinB0008 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P036: +1
22 GIC022 Bend0017 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.400238589 unit=radian components=P037
: +1
23 GIC023 Bend0019 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.000947705 unit=radian components=P039
: +1
24 GIC024 Tors0005 family=TORSION class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P045: +1

```

Listing 7: Gaussian 16 ReadAllGIC input for the η^3 probe. The Cartesian components of the ligand center are inactive helper functions and the Pd-center distance is the first active GIC.

```

#p hf/sto-3g opt=(readallgic,calcf, maxcycle=80) output=pickett

eta3_allyl_palladium SMITH/SONIC Gaussian 16 optimization

O 1
Pd 0.00000000 0.00000000 0.00000000
Cl 0.00000000 0.00000000 -2.30000000
C -1.30000000 0.00000000 1.70000000
C 0.00000000 0.00000000 2.00000000
C 1.30000000 0.00000000 1.70000000
H -1.95000000 0.00000000 2.55000000
H -1.65000000 0.90000000 1.20000000
H 0.00000000 0.00000000 3.09000000
H 1.95000000 0.00000000 2.55000000
H 1.65000000 -0.90000000 1.20000000

Cx001(Inactive)=(X(3)+X(4)+X(5))/3
Cy001(Inactive)=(Y(3)+Y(4)+Y(5))/3
Cz001(Inactive)=(Z(3)+Z(4)+Z(5))/3
GIC001 = SQRT((Cx001-X(1))**2+(Cy001-Y(1))**2+(Cz001-Z(1))**2)
GIC002(Value=2.3) = R(1,2)
GIC003(Value=2.1400934559) = R(1,3)
GIC004(Value=2.0) = R(1,4)
GIC005(Value=2.1400934559) = R(1,5)
GIC006(Value=1.33416640641) = R(3,4)
GIC007(Value=1.07004672795) = R(3,6)
GIC008(Value=1.08742815855) = R(3,7)
GIC009(Value=1.09) = R(4,8)
GIC010(Value=1.07004672795) = R(5,9)
GIC011(Value=1.08742815855) = R(5,10)
GIC012(Value=142.594643369) = A(2,1,3)
GIC013 = L(2,1,4,0,-1)
GIC014 = L(1,3,6,0,-1)
GIC015 = L(1,3,6,0,-2)
GIC016(Value=80.2277614486) = A(1,3,7)
GIC017(Value=114.645858551) = A(4,3,7)
GIC018 = L(1,4,8,0,-1)
GIC019 = L(1,4,8,0,-2)
GIC020 = L(1,5,9,0,-1)
GIC021 = L(1,5,9,0,-2)
GIC022(Value=80.2277614486) = A(1,5,10)
GIC023(Value=114.645858551) = A(4,5,10)
GIC024(Value=0.0) = D(4,3,1,5)

```

Both generated `xyzin` files were read directly by MORPHEUS without format translation. LINK constructed SONIC optimizer direction matrices of dimensions 18×24 and 24×30 , respectively, confirming that the serialized contracts are consumable by the two downstream workflows.

Pagodane and Indane Ring-Coordinate Fixtures

Two supplied Cartesian structures are retained verbatim as publication fixtures in the MATRIX test distribution. The first is pagodane, $C_{20}H_{20}$; ORACLE perceives 50 covalent bonds, 11 rings, no aromatic atoms and a D_{2h} reference assignment. Its redundant PIC contract and the SMITH SONIC basis both have Cartesian rank 114. The second structure is indane, C_9H_{10} ; ORACLE perceives 20 bonds, two fused rings, six aromatic atoms and a C_s reference assignment, while SMITH closes at rank 51. The name “indane” follows the fused benzene-cyclopentane connectivity of the provided structure rather than its original generic filename.

Central finite differences of every final SONIC row give maximum absolute analytic-row errors of 4.02×10^{-10} for pagodane and 4.77×10^{-10} for indane. The indane set contains stretch, bend, cyclic-bend, butterfly and ring-puckering-component families. All 114 pagodane and all 51 indane motions are constructed in both signs from the pseudoinverse of the B matrix frozen at the reference geometry. The resulting Cartesian frames are exactly symmetric and are checked for the first-order SONIC displacement, unchanged connectivity, proper orientation, a maximum atom displacement not above 0.10 Å, and a maximum relative reference-bond change below 0.15. Every three-frame XYZ file and Cartesian-vector table is parsed by the GUI data contract. The version-2 manifest also records the optional Euclidean or mass-weighted right-inverse metric, the explicit average/default-isotope/ Hessian/isotopologue mass provenance, coordinate conditioning and localization, the number of complete ORACLE topology evaluations, local-domain and local/global total-symmetry labels, and canonical ring order with primitive coefficients. A distributed JSON Schema and dependency-free validator define the current machine contract, while the reader accepts archived version-1 manifests. Animation amplitude is independent of the mathematical step and is normalized to a selected maximum atom displacement. The GUI can filter the resulting set by family, local domain, local pseudogroup and local or global total-symmetry character.

Local-Pseudosymmetry Validation

The machine-readable results in `data/local_salc_validation.json` can be regenerated from an explicitly selected MATRIX checkout:

```
export MATRIX_ROOT=/path/to/your/MATRIX
python scripts/run_local_salc_validation.py
```

The cases comprise the C_1/C_{3v} methyl probe, benzene, toluene, azulene, 20 ideal/distorted CN 5–9 templates, generic CN 10/12 centers, distorted SF₆, and square-antiprismatic [ZrF₈]⁴⁻. Recorded checks include rank, rotation/permutation invariance, template score/margin and ambiguity fallback, ring/fused-edge behavior, and Python–Fortran row-space residuals. Local labels apply only to domains; the molecular point-group projector remains final.