

Supporting Information for SONIC: Symmetry-Oriented Non-redundant Internal Coordinates

Vincenzo Barone

Norbornane SMITH/SONIC Standalone Input and Gaussian 16 Export

This Supporting Information records the minimal standalone input required to generate the norbornane SONIC coordinate contract and the corresponding commercial Gaussian 16 **ReadAllGIC** input used in the compatibility test. The first listing is intentionally not the enriched **xyzin** container written after molecular perception and coordinate construction. It contains only a standard XYZ geometry followed by the minimum SMITH directives needed for this Gaussian-compatible export. The standalone workflow selects the commercial Gaussian 16 profile by default, including Gaussian-style improper-dihedral construction in place of native SONIC out-of-plane rows. For this one-file example, the standalone package uses its pinned reduced ORACLE profile to supply the graph, cycles, symmetry and continuous atom descriptors needed by SMITH. This convenience profile is recorded in the generated provenance and is distinct from the full ORACLE perception application, a development of PROXIMA that will be described separately. The full application is currently in final testing and will be released when ready.

The exact standalone workflow is:

```
python -m matrix smith standalone norbornane_smith_input.xyzin norbornane.xyzin
python -m matrix smith gaussian-input norbornane.xyzin norbornane.g16_readallgic.gjf \
--title "norbornane SONIC ReadAllGIC optimization" \
--route "#p hf/sto-3g opt=(readallgic,calcfc,maxcycle=80)"
```

Equivalently, after installation of MATRIX the console-script shorthand is **smith standalone ...** followed by **smith gaussian-input** The reduced package distributed with the manuscript constructs the same contract with **smith-sonic build norbornane.smith.xyz norbornane.xyzin** and automatically writes both **norbornane.smith.out** and **norbornane.g16.gjf**. The default Gaussian 16 profile suppresses active multi-dihedral SONIC rows in the Gaussian file and writes their component periodic **D(...)** coordinates instead; the non-redundant SONIC rows remain in the **xyzin** contract used for post-processing.

SMITH/SONIC input

Listing 1: Minimal norbornane SMITH/SONIC standalone input: standard XYZ block plus the required export directives.

```
19
Norbornane starting geometry for standalone SMITH/SONIC ReadAllGIC export
C      1.25441300      0.78233900     -0.49340600
C      0.00000000      1.13336700      0.33992900
C     -0.00000000     -1.13336700      0.33992900
C      1.25441300     -0.78233900     -0.49340600
H      1.20544300      1.20489500     -1.50351600
H      2.16019200      1.17688700     -0.01817100
H      1.20544300     -1.20489500     -1.50351600
H      2.16019200     -1.17688700     -0.01817100
C      0.00000000      0.00000000      1.38887600
H     -0.89255700      0.00000000      2.02655300
H      0.89255700     -0.00000000      2.02655300
C     -1.25441300      0.78233900     -0.49340600
H     -2.16019200      1.17688700     -0.01817100
H     -1.20544300      1.20489500     -1.50351600
C     -1.25441300     -0.78233900     -0.49340600
```

```

H      -2.16019200      -1.17688700      -0.01817100
H      -1.20544300      -1.20489500      -1.50351600
H      0.00000000       2.15523000      0.73149700
H      -0.00000000      -2.15523000      0.73149700

#SMITH
schema = matrix.smith.input.v1
symmetrize = false

```

Generated Gaussian 16 input

Listing 2: Commercial Gaussian 16-compatible ReadAllGIC input generated automatically from the SMITH/SONIC contract. Multi-dihedral SONIC ring-puckering rows are absent by construction; their component periodic dihedrals appear as V0001, V0002,

```

#p hf/sto-3g opt=(readallgic,calcf, maxcycle=80) output=pickett

norbornane SONIC ReadAllGIC optimization

O 1
C      1.25441300      0.78233900     -0.49340600
C      0.00000000      1.13336700      0.33992900
C     -0.00000000     -1.13336700      0.33992900
C      1.25441300     -0.78233900     -0.49340600
H      1.20544300      1.20489500     -1.50351600
H      2.16019200      1.17688700     -0.01817100
H      1.20544300     -1.20489500     -1.50351600
H      2.16019200     -1.17688700     -0.01817100
C      0.00000000      0.00000000      1.38887600
H     -0.89255700      0.00000000      2.02655300
H      0.89255700     -0.00000000      2.02655300
C     -1.25441300      0.78233900     -0.49340600
H     -2.16019200      1.17688700     -0.01817100
H     -1.20544300      1.20489500     -1.50351600
C     -1.25441300     -0.78233900     -0.49340600
H     -2.16019200     -1.17688700     -0.01817100
H     -1.20544300     -1.20489500     -1.50351600
H      0.00000000      2.15523000      0.73149700
H     -0.00000000     -2.15523000      0.73149700

GIC001(Value=0.0) = 0.707106781187*(R(9,10))-0.707106781187*(R(9,11))
GIC002(Value=2.93156150623) = 0.707106781187*(R(9,10))+0.707106781187*(R(9,11))
GIC003(Value=1.09633572703) = R(1,6)
GIC004(Value=1.09633572703) = R(4,8)
GIC005(Value=1.09633572703) = R(12,13)
GIC006(Value=1.09633572703) = R(15,16)
GIC007(Value=1.09602638934) = R(4,7)
GIC008(Value=1.09602638934) = R(12,14)
GIC009(Value=1.09602638934) = R(15,17)
GIC010(Value=1.09602638934) = R(1,5)
GIC011(Value=1.09431690538) = R(2,18)
GIC012(Value=1.09431690538) = R(3,19)
GIC013(Value=1.564678) = R(1,4)
GIC014(Value=1.564678) = R(12,15)
GIC015(Value=0.0) = 0.707106781187*(R(3,4))-0.707106781187*(R(3,15))
GIC016(Value=0.0) = -0.707106781187*(R(1,2))+0.707106781187*(R(2,12))
GIC017(Value=4.13260235459) = 0.707106781187*(R(3,4))+0.707106781187*(R(3,15))
GIC018(Value=4.13260235459) = 0.707106781187*(R(1,2))+0.707106781187*(R(2,12))
GIC019(Value=0.0) = -0.707106781187*(R(2,9))+0.707106781187*(R(3,9))
GIC020(Value=4.12706024365) = 0.707106781187*(R(2,9))+0.707106781187*(R(3,9))
GIC021(Value=-0.0573424722848) = 0.816496580928*(A(5,1,6))-0.408248290464*(A(2,1,5))-0.408248290464*(A(2,1,6))
GIC022(Value=0.0136523036609) = 0.707106781187*(A(2,1,5))-0.707106781187*(A(2,1,6))
GIC023(Value=-0.0650891780287) = 0.816496580928*(A(5,1,6))-0.408248290464*(A(4,1,5))-0.408248290464*(A(4,1,6))
GIC024(Value=0.0195508295595) = 0.707106781187*(A(4,1,5))-0.707106781187*(A(4,1,6))
GIC025(Value=0.0337761539671) = 0.816496580928*(A(18,2,9))-0.408248290464*(A(18,2,12))-0.408248290464*(A(18,2,1))
GIC026(Value=0.0) = 0.707106781187*(A(18,2,12))-0.707106781187*(A(18,2,1))
GIC027(Value=0.0337761539671) = 0.816496580928*(A(19,3,9))-0.408248290464*(A(19,3,15))-0.408248290464*(A(19,3,4))
GIC028(Value=0.0) = 0.707106781187*(A(19,3,15))-0.707106781187*(A(19,3,4))
GIC029(Value=-0.0650891780287) = 0.816496580928*(A(7,4,8))-0.408248290464*(A(1,4,7))-0.408248290464*(A(1,4,8))
GIC030(Value=0.0195508295595) = 0.707106781187*(A(1,4,7))-0.707106781187*(A(1,4,8))
GIC031(Value=-0.0573424722848) = 0.816496580928*(A(7,4,8))-0.408248290464*(A(3,4,7))-0.408248290464*(A(3,4,8))
GIC032(Value=0.0136523036609) = 0.707106781187*(A(3,4,7))-0.707106781187*(A(3,4,8))
GIC033(Value=-0.0619062683331) = 0.816496580928*(A(10,9,11))-0.408248290464*(A(2,9,10))-0.408248290464*(A(2,9,11))
GIC034(Value=0.0) = 0.707106781187*(A(2,9,10))-0.707106781187*(A(2,9,11))
GIC035(Value=-0.0619062683331) = 0.816496580928*(A(10,9,11))-0.408248290464*(A(3,9,10))-0.408248290464*(A(3,9,11))
GIC036(Value=0.0) = 0.707106781187*(A(3,9,10))-0.707106781187*(A(3,9,11))

```

```

GIC037(Value=-0.0573424722848) = 0.816496580928*(A(13,12,14))-0.408248290464*(A(2,12,13))-0.408248290464*(A(2,12,14))
GIC038(Value=-0.0136523036609) = 0.707106781187*(A(2,12,13))-0.707106781187*(A(2,12,14))
GIC039(Value=-0.0650891780287) = 0.816496580928*(A(13,12,14))-0.408248290464*(A(15,12,13))-0.408248290464*(A(15,12,14))
GIC040(Value=-0.0195508295595) = 0.707106781187*(A(15,12,13))-0.707106781187*(A(15,12,14))
GIC041(Value=-0.0573424722848) = 0.816496580928*(A(16,15,17))-0.408248290464*(A(3,15,16))-0.408248290464*(A(3,15,17))
GIC042(Value=-0.0136523036609) = 0.707106781187*(A(3,15,16))-0.707106781187*(A(3,15,17))
GIC043(Value=-0.0650891780287) = 0.816496580928*(A(16,15,17))-0.408248290464*(A(12,15,16))-0.408248290464*(A(12,15,17))
GIC044(Value=-0.0195508295595) = 0.707106781187*(A(12,15,16))-0.707106781187*(A(12,15,17))
GIC045(Value=-0.0207227541011) = 0.632455532034*(A(3,4,1))-0.511667273602*(A(4,1,2))+0.195439507585*(A(1,2,9))
+0.195439507585*(A(2,9,3))-0.511667273602*(A(9,3,4))
GIC046(Value=-0.063778079142) = 0.37174803446*(A(4,1,2))-0.601500955008*(A(1,2,9))+0.601500955008*(A(2,9,3))-0.37174803446*(
A(9,3,4))
GIC047(Value=-0.0207227541011) = 0.632455532034*(A(3,15,12))-0.511667273602*(A(15,12,2))+0.195439507585*(A(12,2,9))
+0.195439507585*(A(2,9,3))-0.511667273602*(A(9,3,15))
GIC048(Value=-0.063778079142) = 0.37174803446*(A(15,12,2))-0.601500955008*(A(12,2,9))+0.601500955008*(A(2,9,3))
-0.37174803446*(A(9,3,15))
V0001(Value=-55.8772472164) = D(1,2,9,3)
V0002(Value=55.8772472164) = D(2,9,3,4)
V0003(Value=-35.2663208258) = D(9,3,4,1)
V0004(Value=0.0) = D(3,4,1,2)
V0005(Value=35.2663208258) = D(4,1,2,9)
V0006(Value=55.8772472164) = D(12,2,9,3)
V0007(Value=-55.8772472164) = D(2,9,3,15)
V0008(Value=35.2663208258) = D(9,3,15,12)
V0009(Value=0.0) = D(3,15,12,2)
V0010(Value=-35.2663208258) = D(15,12,2,9)

```

Gaussian 16 output excerpt

The complete Gaussian log is retained in the reproducibility archive. The excerpt below records the optimization progress and termination diagnostics.

Listing 3: Selected Gaussian 16 output lines for the norbornane **ReadAllGIC** run.

```

138: CrdQ2X: Updating Cartesian coordinates based on modified values of the internal ones.
590: SCF Done: E(RHF) = -268.892840294 A.U. after 9 cycles
913: Step number 1 out of a maximum of 80
1272: SCF Done: E(RHF) = -268.893823525 A.U. after 7 cycles
1332: Step number 2 out of a maximum of 80
1425: Optimization completed.
1426: -- Stationary point found.
1853: Normal termination of Gaussian 16 at Wed Jul 8 13:46:24 2026.

```

Advanced Standalone Interface Probes

The standalone distribution also contains two examples that exercise the interfaces not covered by a single covalent molecule. Every build writes three coordinated artifacts: the frozen **xyzin** contract, a readable **.smith.out** report modeled on the essential coordinate section of the former Merlino output, and a commercial Gaussian 16 **ReadAllGIC** input. The report records the family, reduction class, irrep, active/frozen status, reference value, native unit, and primitive coefficients of each selected coordinate. Non-totally symmetric coordinates are present in the Gaussian file with the **Frozen** option; helper center and fragment definitions are written as inactive Gaussian functions.

Formic-acid-water non-covalent complex

The eight-atom complex is processed with the reduced perception profile and an automatic connected-component fragment definition. It closes at rank 18/18. The final six protected rows are three relative fragment translations and three relative fragment orientations; the other twelve rows span the intramolecular motions. The excerpt below is generated, not manually transcribed.

Listing 4: Coordinate-definition excerpt for the formic-acid-water complex. The complete report is supplied as **si/formic_acid_water_smith_report.txt**.

```

Coordinate Definitions
-----
1 GIC001 Str0001 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=1.095460024 unit=angstrom components=P001:+1

```

```

2 GIC002 Str0002 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=1.211503996 unit=angstrom components=P002:+1
3 GIC003 Str0003 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=1.325944816 unit=angstrom components=P003:+1
4 GIC004 Str0004 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=0.985874998 unit=angstrom components=P004:+1
5 GIC005 Str0005 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=0.9603233822 unit=angstrom components=P005:+1
6 GIC006 Str0006 family=STRETCH class=ORDINARY irrep=A state=ACTIVE value=0.9705527871 unit=angstrom components=P006:+1
7 GIC007 Bend0001 family=BEND class=ORDINARY irrep=A state=ACTIVE value=2.151557636 unit=radian components=P016:+1
8 GIC008 Bend0002 family=BEND class=ORDINARY irrep=A state=ACTIVE value=1.936214312 unit=radian components=P017:+1
9 GIC009 ImpD0001 family=IMPROPER_DIHEDRAL class=ORDINARY irrep=A state=ACTIVE value=3.141106217 unit=radian components=
  P023:+1
10 GIC010 Bend0004 family=BEND class=ORDINARY irrep=A state=ACTIVE value=1.886705122 unit=radian components=P019:+1
11 GIC011 Bend0005 family=BEND class=ORDINARY irrep=A state=ACTIVE value=1.856621311 unit=radian components=P020:+1
12 GIC012 Tors0001 family=TORSION class=ORDINARY irrep=A state=ACTIVE value=-3.141071603 unit=radian components=P021:+1
13 GIC013 FTrn0001 family=FRAG_TRANSLATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=2.794364267 unit=angstrom
  components=P008:+1
14 GIC014 FTrn0002 family=FRAG_TRANSLATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=-0.5396128667 unit=angstrom
  components=P009:+1
15 GIC015 FTrn0003 family=FRAG_TRANSLATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=0.1935490667 unit=angstrom
  components=P010:+1
16 GIC016 FRot0001 family=FRAG_ORIENTATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=0 unit=radian components=
  P011:+1
17 GIC017 FRot0002 family=FRAG_ORIENTATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=0 unit=radian components=
  P012:+1
18 GIC018 FRot0003 family=FRAG_ORIENTATION class=SPECIAL_PROTECTED irrep=A state=ACTIVE value=0 unit=radian components=
  P013:+1

```

Listing 5: Gaussian 16 ReadAllGIC input generated for the formic-acid–water fragment contract. Fragment objects and body-frame helpers are declared before the 18 active rows.

```

#p hf/sto-3g opt=(readallgic,calcf, maxcycle=80) output=pickett

formic_acid_water SMITH/SONIC Gaussian 16 optimization

O 1
C      -1.17172700      -0.01899900      -0.00137000
H      -2.25686900       0.13036900      -0.01510700
O      -0.65137600      -1.11304500       0.00496400
O      -0.53354400       1.14322800       0.00760300
H       0.43520300       0.96063300       0.01934300
O       1.93014500      -0.02597600      -0.05226900
H       2.59464300      -0.12891700       0.63334500
H       1.35131700      -0.80263400       0.00883100

F001=Fragment(1-5)
F002=Fragment(6-8)
CxFO01(Inactive)=XCntr(F001)
CyFO01(Inactive)=YCntr(F001)
CzFO01(Inactive)=ZCntr(F001)
CxFO02(Inactive)=XCntr(F002)
CyFO02(Inactive)=YCntr(F002)
CzFO02(Inactive)=ZCntr(F002)
RPF001(Inactive)=SQRT((X(5)-CxFO01)**2+(Y(5)-CyFO01)**2+(Z(5)-CzFO01)**2)
PxFO01(Inactive)=[X(5)-CxFO01]/RPF001
PyFO01(Inactive)=[Y(5)-CyFO01]/RPF001
PzFO01(Inactive)=[Z(5)-CzFO01]/RPF001
QxFO01(Inactive)=PyFO01*[Z(3)-CzFO01]-PzFO01*[Y(3)-CyFO01]
QyFO01(Inactive)=PzFO01*[X(3)-CxFO01]-PxFO01*[Z(3)-CzFO01]
QzFO01(Inactive)=PxFO01*[Y(3)-CyFO01]-PyFO01*[X(3)-CxFO01]
RQF001(Inactive)=SQRT(QQxFO01**2+QQyFO01**2+QQzFO01**2)
QxFO01(Inactive)=QQxFO01/RQF001
QyFO01(Inactive)=QQyFO01/RQF001
QzFO01(Inactive)=QQzFO01/RQF001
SxFO01(Inactive)=PyFO01*QzFO01-PzFO01*QyFO01
SyFO01(Inactive)=PzFO01*QxFO01-PxFO01*QzFO01
SzFO01(Inactive)=PxFO01*QyFO01-PyFO01*QxFO01
RPF002(Inactive)=SQRT((X(8)-CxFO02)**2+(Y(8)-CyFO02)**2+(Z(8)-CzFO02)**2)
PxFO02(Inactive)=[X(8)-CxFO02]/RPF002
PyFO02(Inactive)=[Y(8)-CyFO02]/RPF002
PzFO02(Inactive)=[Z(8)-CzFO02]/RPF002
QQxFO02(Inactive)=PyFO02*[Z(6)-CzFO02]-PzFO02*[Y(6)-CyFO02]
QyFO02(Inactive)=PzFO02*[X(6)-CxFO02]-PxFO02*[Z(6)-CzFO02]
QzFO02(Inactive)=PxFO02*[Y(6)-CyFO02]-PyFO02*[X(6)-CxFO02]
RQF002(Inactive)=SQRT(QQxFO02**2+QQyFO02**2+QQzFO02**2)
QxFO02(Inactive)=QQxFO02/RQF002
QyFO02(Inactive)=QQyFO02/RQF002
QzFO02(Inactive)=QQzFO02/RQF002
SxFO02(Inactive)=PyFO02*QzFO02-PzFO02*QyFO02
SyFO02(Inactive)=PzFO02*QxFO02-PxFO02*QzFO02
SzFO02(Inactive)=PxFO02*QyFO02-PyFO02*QxFO02
R11F002F001(Inactive)=PxFO02*PxFO01+PyFO02*PyFO01+PzFO02*PzFO01

```

```

R12F002F001(Inactive)=PxF002*QxF001+PyF002*QyF001+PzF002*QzF001
R13F002F001(Inactive)=PxF002*SxF001+PyF002*SyF001+PzF002*SzF001
R21F002F001(Inactive)=QxF002*PxF001+QyF002*PyF001+QzF002*PzF001
R22F002F001(Inactive)=QxF002*QxF001+QyF002*QyF001+QzF002*QzF001
R23F002F001(Inactive)=QxF002*SxF001+QyF002*SyF001+QzF002*SzF001
R31F002F001(Inactive)=SxF002*PxF001+SyF002*PyF001+SzF002*PzF001
R32F002F001(Inactive)=SxF002*QxF001+SyF002*QyF001+SzF002*QzF001
R33F002F001(Inactive)=SxF002*SxF001+SyF002*SyF001+SzF002*SzF001
KwF002F001(Inactive)=0.5*SQRT(R11F002F001+R22F002F001+R33F002F001+1)
KxF002F001(Inactive)=(R23F002F001-R32F002F001)/(4*KwF002F001)
KyF002F001(Inactive)=(R31F002F001-R13F002F001)/(4*KwF002F001)
KzF002F001(Inactive)=(R12F002F001-R21F002F001)/(4*KwF002F001)
KnF002F001(Inactive)=SQRT(KxF002F001**2+KyF002F001**2+KzF002F001**2+1.0D-24)
ThF002F001(Inactive)=2*ATAN(KnF002F001/KwF002F001)
ExF002F001(Inactive)=ThF002F001*KxF002F001/KnF002F001
EyF002F001(Inactive)=ThF002F001*KyF002F001/KnF002F001
EzF002F001(Inactive)=ThF002F001*KzF002F001/KnF002F001
GIC001(Value=1.09546002426) = R(1,2)
GIC002(Value=1.21150399623) = R(1,3)
GIC003(Value=1.32594481625) = R(1,4)
GIC004(Value=0.985874997976) = R(4,5)
GIC005(Value=0.960323382242) = R(6,7)
GIC006(Value=0.9705527871) = R(6,8)
GIC007(Value=123.275171935) = A(2,1,3)
GIC008(Value=110.936908332) = A(2,1,4)
GIC009(Value=179.972129264) = D(2,1,4,3)
GIC010(Value=108.100240696) = A(1,4,5)
GIC011(Value=106.376565278) = A(7,6,8)
GIC012(Value=-179.970146027) = D(2,1,4,5)
GIC013 = CxF002-CxF001
GIC014 = CyF002-CyF001
GIC015 = CzF002-CzF001
GIC016 = ExF002F001
GIC017 = EyF002F001
GIC018 = EzF002F001

```

η^3 allyl–palladium interaction center

The ten-atom idealized allyl–PdCl probe consumes a frozen ORACLE-state fixture. Its center record has identifier C001, kind ETA3_CENTER, and atoms 3–5. SMITH retains the Pd–center distance as a protected CENTER_ATOM_DISTANCE; the contract closes at rank 24/24 and gives a reference value of 1.8000 Å. This is a perception/coordinate interface test rather than an optimized transition-metal benchmark.

Listing 6: Coordinate-definition excerpt for the η^3 allyl–palladium probe. The complete report is supplied as `si/eta3_allyl_palladium_smith_report.txt`.

```

Coordinate Definitions
-----
1 GIC001 CnA0001 family=CENTER_ATOM_DISTANCE class=SPECIAL_PROTECTED irrep=UNASSIGNED state=ACTIVE value=1.8 unit=
  angstrom components=P012:+1
2 GIC002 Str0001 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.3 unit=angstrom components=P001:+1
3 GIC003 Str0002 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.140093456 unit=angstrom components=
  P002:+1
4 GIC004 Str0003 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2 unit=angstrom components=P003:+1
5 GIC005 Str0004 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.140093456 unit=angstrom components=
  P004:+1
6 GIC006 Str0005 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.334166406 unit=angstrom components=
  P005:+1
7 GIC007 Str0006 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.070046728 unit=angstrom components=
  P006:+1
8 GIC008 Str0007 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.087428159 unit=angstrom components=
  P007:+1
9 GIC009 Str0009 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.09 unit=angstrom components=P009:+1
10 GIC010 Str0010 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.070046728 unit=angstrom components=
  P010:+1
11 GIC011 Str0011 family=STRETCH class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.087428159 unit=angstrom components=
  P011:+1
12 GIC012 Bend0001 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.488746022 unit=radian components=P013
  :+1
13 GIC013 LinB0001 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P014:+1
14 GIC014 LinB0003 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P021:+1
15 GIC015 LinB0004 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P022:+1
16 GIC016 Bend0007 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.400238589 unit=radian components=P023
  :+1
17 GIC017 Bend0009 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.000947705 unit=radian components=P025
  :+1

```

```

18 GIC018 LinB0005 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P029:+1
19 GIC019 LinB0006 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P030:+1
20 GIC020 LinB0007 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P035:+1
21 GIC021 LinB0008 family=LINEAR_BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P036:+1
22 GIC022 Bend0017 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=1.400238589 unit=radian components=P037
   :+1
23 GIC023 Bend0019 family=BEND class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=2.000947705 unit=radian components=P039
   :+1
24 GIC024 Tors0005 family=TORSION class=ORDINARY irrep=UNASSIGNED state=ACTIVE value=0 unit=radian components=P045:+1

```

Listing 7: Gaussian 16 `ReadAllGIC` input for the η^3 probe. The Cartesian components of the ligand center are inactive helper functions and the Pd-center distance is the first active GIC.

```

#p hf/sto-3g opt=(readallgic,calcf, maxcycle=80) output=pickett

eta3_allyl_palladium SMITH/SONIC Gaussian 16 optimization

O 1
Pd      0.00000000      0.00000000      0.00000000
Cl      0.00000000      0.00000000     -2.30000000
C      -1.30000000      0.00000000      1.70000000
C       0.00000000      0.00000000      2.00000000
C       1.30000000      0.00000000      1.70000000
H      -1.95000000      0.00000000      2.55000000
H      -1.65000000      0.90000000      1.20000000
H       0.00000000      0.00000000      3.09000000
H       1.95000000      0.00000000      2.55000000
H       1.65000000     -0.90000000      1.20000000

CxC001(Inactive)=(X(3)+X(4)+X(5))/3
CyC001(Inactive)=(Y(3)+Y(4)+Y(5))/3
CzC001(Inactive)=(Z(3)+Z(4)+Z(5))/3
GIC001 = SQRT((CxC001-X(1))**2+(CyC001-Y(1))**2+(CzC001-Z(1))**2)
GIC002(Value=2.3) = R(1,2)
GIC003(Value=2.1400934559) = R(1,3)
GIC004(Value=2.0) = R(1,4)
GIC005(Value=2.1400934559) = R(1,5)
GIC006(Value=1.33416640641) = R(3,4)
GIC007(Value=1.07004672795) = R(3,6)
GIC008(Value=1.08742815855) = R(3,7)
GIC009(Value=1.09) = R(4,8)
GIC010(Value=1.07004672795) = R(5,9)
GIC011(Value=1.08742815855) = R(5,10)
GIC012(Value=142.594643369) = A(2,1,3)
GIC013 = L(2,1,4,0,-1)
GIC014 = L(1,3,6,0,-1)
GIC015 = L(1,3,6,0,-2)
GIC016(Value=80.2277614486) = A(1,3,7)
GIC017(Value=114.645858551) = A(4,3,7)
GIC018 = L(1,4,8,0,-1)
GIC019 = L(1,4,8,0,-2)
GIC020 = L(1,5,9,0,-1)
GIC021 = L(1,5,9,0,-2)
GIC022(Value=80.2277614486) = A(1,5,10)
GIC023(Value=114.645858551) = A(4,5,10)
GIC024(Value=0.0) = D(4,3,1,5)

```

Both generated `xyzin` files were read directly by MORPHEUS without format translation. LINK constructed SONIC optimizer direction matrices of dimensions 18×24 and 24×30 , respectively, confirming that the serialized contracts are consumable by the two downstream workflows.