

Supporting Information for SONIC: Symmetry-Oriented Non-redundant Internal Coordinates

Vincenzo Barone

Norbornane SMITH/SONIC Standalone Input and Gaussian 16 Export

This Supporting Information records the minimal standalone input required to generate the norbornane SONIC coordinate contract and the corresponding commercial Gaussian 16 `ReadAllGIC` input used in the compatibility test. The first listing is intentionally not the enriched `xyzin` container written after molecular perception and coordinate construction. It contains only a standard XYZ geometry followed by the minimum SMITH directives needed for this Gaussian-compatible export. In particular, `g16 = true` selects the Gaussian-style improper-dihedral construction in place of native SONIC out-of-plane rows. For this one-file example, the standalone package uses its pinned reduced ORACLE profile to supply the graph, cycles, symmetry and continuous atom descriptors needed by SMITH. This convenience profile is recorded in the generated provenance and is distinct from the full ORACLE perception application, a development of PROXIMA that will be described separately. The full application is currently in final testing and will be released when ready.

The exact standalone workflow is:

```
python -m matrix smith standalone norbornane_smith_input.xyzin norbornane.xyzin
python -m matrix smith gaussian-input norbornane.xyzin norbornane_g16_readallgic.gjf \
--g16 --title "norbornane SONIC ReadAllGIC optimization" \
--route "#p hf/sto-3g opt=(readallgic,calcf, maxcycle=80)"
```

Equivalently, after installation of MATRIX the console-script shorthand is `smith standalone ...` followed by `smith gaussian-input ... -g16`. The reduced package distributed with the manuscript constructs the same contract with `smith-sonic build norbornane.smith.xyz norbornane.xyzin`; Gaussian export remains part of the complete MATRIX installation. The `-g16` export switch is what suppresses active multi-dihedral SONIC rows in the Gaussian file and writes their component periodic `D(...)` coordinates instead; the non-redundant SONIC rows remain in the `xyzin` contract used for post-processing.

SMITH/SONIC input

Listing 1: Minimal norbornane SMITH/SONIC standalone input: standard XYZ block plus the required export directives.

```
19
Norbornane starting geometry for standalone SMITH/SONIC ReadAllGIC export
C      1.25441300      0.78233900     -0.49340600
C      0.00000000      1.13336700      0.33992900
C     -0.00000000     -1.13336700      0.33992900
C      1.25441300     -0.78233900     -0.49340600
H      1.20544300      1.20489500     -1.50351600
H      2.16019200      1.17688700     -0.01817100
H      1.20544300     -1.20489500     -1.50351600
H      2.16019200     -1.17688700     -0.01817100
C      0.00000000      0.00000000      1.38887600
H     -0.89255700      0.00000000      2.02655300
H      0.89255700     -0.00000000      2.02655300
C     -1.25441300      0.78233900     -0.49340600
H     -2.16019200      1.17688700     -0.01817100
H     -1.20544300      1.20489500     -1.50351600
C     -1.25441300     -0.78233900     -0.49340600
```

```

H      -2.16019200      -1.17688700      -0.01817100
H      -1.20544300      -1.20489500      -1.50351600
H       0.00000000       2.15523000       0.73149700
H      -0.00000000      -2.15523000       0.73149700

#SMITH
schema = matrix.smith.input.v1
symmetrize = false
g16 = true

```

Generated Gaussian 16 input

Listing 2: Commercial Gaussian 16-compatible ReadAllGIC input generated automatically from the SMITH/SONIC contract. Multi-dihedral SONIC ring-puckering rows are absent by construction; their component periodic dihedrals appear as V0001, V0002,

```

#p hf/sto-3g opt=(readallgic,calcf, maxcycle=80) output=pickett

norbornane SONIC ReadAllGIC optimization

O 1
C      1.25441300      0.78233900     -0.49340600
C      0.00000000      1.13336700      0.33992900
C     -0.00000000     -1.13336700      0.33992900
C      1.25441300     -0.78233900     -0.49340600
H      1.20544300      1.20489500     -1.50351600
H      2.16019200      1.17688700     -0.01817100
H      1.20544300     -1.20489500     -1.50351600
H      2.16019200     -1.17688700     -0.01817100
C      0.00000000      0.00000000      1.38887600
H     -0.89255700      0.00000000      2.02655300
H      0.89255700     -0.00000000      2.02655300
C     -1.25441300      0.78233900     -0.49340600
H     -2.16019200      1.17688700     -0.01817100
H     -1.20544300      1.20489500     -1.50351600
C     -1.25441300     -0.78233900     -0.49340600
H     -2.16019200     -1.17688700     -0.01817100
H     -1.20544300     -1.20489500     -1.50351600
H      0.00000000      2.15523000      0.73149700
H     -0.00000000     -2.15523000      0.73149700

GIC001(Value=0.0) = 0.707106781187*(R(9,10))-0.707106781187*(R(9,11))
GIC002(Value=2.93156150623) = 0.707106781187*(R(9,10))+0.707106781187*(R(9,11))
GIC003(Value=1.09633572703) = R(1,6)
GIC004(Value=1.09633572703) = R(4,8)
GIC005(Value=1.09633572703) = R(12,13)
GIC006(Value=1.09633572703) = R(15,16)
GIC007(Value=1.09602638934) = R(4,7)
GIC008(Value=1.09602638934) = R(12,14)
GIC009(Value=1.09602638934) = R(15,17)
GIC010(Value=1.09602638934) = R(1,5)
GIC011(Value=1.09431690538) = R(2,18)
GIC012(Value=1.09431690538) = R(3,19)
GIC013(Value=1.564678) = R(1,4)
GIC014(Value=1.564678) = R(12,15)
GIC015(Value=0.0) = 0.707106781187*(R(3,4))-0.707106781187*(R(3,15))
GIC016(Value=0.0) = -0.707106781187*(R(1,2))+0.707106781187*(R(2,12))
GIC017(Value=4.13260235459) = 0.707106781187*(R(3,4))+0.707106781187*(R(3,15))
GIC018(Value=4.13260235459) = 0.707106781187*(R(1,2))+0.707106781187*(R(2,12))
GIC019(Value=0.0) = -0.707106781187*(R(2,9))+0.707106781187*(R(3,9))
GIC020(Value=4.12706024365) = 0.707106781187*(R(2,9))+0.707106781187*(R(3,9))
GIC021(Value=-0.0573424722848) = 0.816496580928*(A(5,1,6))-0.408248290464*(A(2,1,5))-0.408248290464*(A(2,1,6))
GIC022(Value=0.0136523036609) = 0.707106781187*(A(2,1,5))-0.707106781187*(A(2,1,6))
GIC023(Value=-0.0650891780287) = 0.816496580928*(A(5,1,6))-0.408248290464*(A(4,1,5))-0.408248290464*(A(4,1,6))
GIC024(Value=0.0195508295595) = 0.707106781187*(A(4,1,5))-0.707106781187*(A(4,1,6))
GIC025(Value=0.0337761539671) = 0.816496580928*(A(18,2,9))-0.408248290464*(A(18,2,12))-0.408248290464*(A(18,2,1))
GIC026(Value=0.0) = 0.707106781187*(A(18,2,12))-0.707106781187*(A(18,2,1))
GIC027(Value=0.0337761539671) = 0.816496580928*(A(19,3,9))-0.408248290464*(A(19,3,15))-0.408248290464*(A(19,3,4))
GIC028(Value=0.0) = 0.707106781187*(A(19,3,15))-0.707106781187*(A(19,3,4))
GIC029(Value=-0.0650891780287) = 0.816496580928*(A(7,4,8))-0.408248290464*(A(1,4,7))-0.408248290464*(A(1,4,8))
GIC030(Value=0.0195508295595) = 0.707106781187*(A(1,4,7))-0.707106781187*(A(1,4,8))
GIC031(Value=-0.0573424722848) = 0.816496580928*(A(7,4,8))-0.408248290464*(A(3,4,7))-0.408248290464*(A(3,4,8))
GIC032(Value=0.0136523036609) = 0.707106781187*(A(3,4,7))-0.707106781187*(A(3,4,8))
GIC033(Value=-0.0619062683331) = 0.816496580928*(A(10,9,11))-0.408248290464*(A(2,9,10))-0.408248290464*(A(2,9,11))
GIC034(Value=0.0) = 0.707106781187*(A(2,9,10))-0.707106781187*(A(2,9,11))
GIC035(Value=-0.0619062683331) = 0.816496580928*(A(10,9,11))-0.408248290464*(A(3,9,10))-0.408248290464*(A(3,9,11))

```

```

GIC036(Value=0.0) = 0.707106781187*(A(3,9,10))-0.707106781187*(A(3,9,11))
GIC037(Value=-0.0573424722848) = 0.816496580928*(A(13,12,14))-0.408248290464*(A(2,12,13))-0.408248290464*(A(2,12,14))
GIC038(Value=-0.0136523036609) = 0.707106781187*(A(2,12,13))-0.707106781187*(A(2,12,14))
GIC039(Value=-0.0650891780287) = 0.816496580928*(A(13,12,14))-0.408248290464*(A(15,12,13))-0.408248290464*(A(15,12,14))
GIC040(Value=-0.0195508295595) = 0.707106781187*(A(15,12,13))-0.707106781187*(A(15,12,14))
GIC041(Value=-0.0573424722848) = 0.816496580928*(A(16,15,17))-0.408248290464*(A(3,15,16))-0.408248290464*(A(3,15,17))
GIC042(Value=-0.0136523036609) = 0.707106781187*(A(3,15,16))-0.707106781187*(A(3,15,17))
GIC043(Value=-0.0650891780287) = 0.816496580928*(A(16,15,17))-0.408248290464*(A(12,15,16))-0.408248290464*(A(12,15,17))
GIC044(Value=-0.0195508295595) = 0.707106781187*(A(12,15,16))-0.707106781187*(A(12,15,17))
GIC045(Value=-0.0207227541011) = 0.632455532034*(A(3,4,1))-0.511667273602*(A(4,1,2))+0.195439507585*(A(1,2,9))
+0.195439507585*(A(2,9,3))-0.511667273602*(A(9,3,4))
GIC046(Value=-0.063778079142) = 0.37174803446*(A(4,1,2))-0.601500955008*(A(1,2,9))+0.601500955008*(A(2,9,3))-0.37174803446*(A(9,3,4))
GIC047(Value=-0.0207227541011) = 0.632455532034*(A(3,15,12))-0.511667273602*(A(15,12,2))+0.195439507585*(A(12,2,9))
+0.195439507585*(A(2,9,3))-0.511667273602*(A(9,3,15))
GIC048(Value=-0.063778079142) = 0.37174803446*(A(15,12,2))-0.601500955008*(A(12,2,9))+0.601500955008*(A(2,9,3))
-0.37174803446*(A(9,3,15))
V0001(Value=-55.8772472164) = D(1,2,9,3)
V0002(Value=55.8772472164) = D(2,9,3,4)
V0003(Value=-35.2663208258) = D(9,3,4,1)
V0004(Value=0.0) = D(3,4,1,2)
V0005(Value=35.2663208258) = D(4,1,2,9)
V0006(Value=55.8772472164) = D(12,2,9,3)
V0007(Value=-55.8772472164) = D(2,9,3,15)
V0008(Value=35.2663208258) = D(9,3,15,12)
V0009(Value=0.0) = D(3,15,12,2)
V0010(Value=-35.2663208258) = D(15,12,2,9)

```

Gaussian 16 output excerpt

The complete Gaussian log is retained in the reproducibility archive. The excerpt below records the optimization progress and termination diagnostics.

Listing 3: Selected Gaussian 16 output lines for the norbornane ReadAllGIC run.

```

138: CrdQ2X: Updating Cartesian coordinates based on modified values of the internal ones.
590: SCF Done: E(RHF) = -268.892840294 A.U. after 9 cycles
913: Step number 1 out of a maximum of 80
1272: SCF Done: E(RHF) = -268.893823525 A.U. after 7 cycles
1332: Step number 2 out of a maximum of 80
1425: Optimization completed.
1426: -- Stationary point found.
1853: Normal termination of Gaussian 16 at Wed Jul 8 13:46:24 2026.

```