

APS-05 — your data model

Distributed Booking & Inventory System

Kognivera Hackathon 2026 · Travel & Tourism · data model v1.1.0-rc1

The problem statement itself, the 24-hour MVP scope and the XR device requirement live in the hackathon application, on your statement's page. This document is the data you have been given to build it with: every table, every field, and what each one is for.

You have **41,855 rows across 20 tables**. 14 of them are the tables this statement is built on; the remaining 6 are reference tables the others point at, included so the database works on its own.

All of it is in the `data/` folder beside this document: as `APS-05.db` (SQLite, indexed, ready to query), as CSV, and as DDL for Postgres and SQLite.

What the data gives you

15,030 dated inventory rows with a database-level no-oversell CHECK, deliberately scarce units to contend over, 496 holds across four states, and multi-item bookings with lines already in a compensated state.

Watch out for this one

`booked_units + held_units <= total_units` is a CHECK constraint in the DDL. Your service has to make it true under concurrency, not rely on the database to say no.

The tables this statement is built on

TABLE	ROWS	WHAT YOU USE IT FOR
<code>booking_items</code>	2,669	Line items, so a multi-item booking can be partially compensated — which is the whole point of APS-05's saga.
<code>bookings</code>	1,996	The order header — where inventory, payment and itinerary meet. Idempotency key is mandatory, not optional.
<code>cities</code>	60	The geographic anchor of the whole model. 60 cities; every hotel, POI, package, advisory and weather row hangs off one.
<code>countries</code>	30	ISO country reference. Every city, currency default and calling code resolves here.
<code>currencies</code>	25	carries the true minor-unit exponent so JPY/KWD display correctly even though storage is always DECIMAL(12,2).
<code>flights</code>	4,000	Schedule instances across the search window, so a date search returns results rather than blanks.

TABLE	ROWS	WHAT YOU USE IT FOR
holds	496	TTL reservation with an idempotency key. Expired and released holds are retained (R8) because that history is what makes the demo interesting.
hotel_room_types	1,200	The bookable unit. APS-05's no-oversell guarantee is defended at this grain.
hotels	300	Fewer, richer properties. Depth (reviews, room types, media) matters more than catalogue size —.
inventory_calendar	15,030	Entity x date availability with a database-level no-oversell CHECK. Deliberately scarce units so APS-05's load test has something to defend.
flight_fares	8,002	The bookable unit for flights, and the second entity_type in inventory_calendar.
fx_rates	912	PS-08 cannot convert or settle without a dated rate table. Never overwrite the original amount; convert through here.
hotel_rate_plans	2,400	Makes rate selection a real choice rather than a single price.
payments	1,996	Mock payment records — authorised and captured amounts held separately so a partial capture is representable.

Reference tables, included so the database is valid

You will mostly join through these rather than think about them.

TABLE	ROWS	WHAT IT IS
itineraries	803	A versioned plan belonging to a trip. version is what makes PS-11's conflict handling tractable.
languages	26	Rule R6: BCP-47 is the only legal way to say 'language' anywhere in the model.
trips	600	The container that gives dates, party, destination and budget to everything else. Seven statements produce or consume one.
users	1,200	The traveller identity every personalisation hangs off. Segmented heavy / light / cold_start so APS-04 can prove cold start.
airlines	30	Carrier reference for flight schedule instances.
airports	80	So flights join airport-to-airport rather than city-to-city.

How they fit together

Open `02_DATA_MODEL_DIAGRAM.html` in a browser for the clickable version — it shows these tables and nothing else. Download it first; it will not render inside SharePoint.

Some tables point at "any bookable thing" using an `(entity_type, entity_id)` pair rather than a typed foreign key. That is deliberate: it is what lets one feature refer to a hotel, a flight, a point of interest or a package without a separate join table for each. The legal values of `entity_type` are in `data/enums.json`.

Every field, table by table

Columns marked **PK** are the primary key. **FK** shows what a column points at. Enum columns list their legal values — anything else is rejected by the conformance check.

currencies

Reference & geography · 25 rows · IDs start `cur_`

carries the true minor-unit exponent so JPY/KWD display correctly even though storage is always DECIMAL(12,2).

COLUMN	TYPE	CONSTRAINTS	NOTES
<code>currency_id</code>	text	PK	<code>cur_</code> prefixed.
<code>iso4217</code>	char(3)	UNIQUE · NOT NULL	e.g. INR.
<code>name</code>	text	NOT NULL	
<code>symbol</code>	text	NOT NULL	
<code>minor_unit_exponent</code>	smallint	NOT NULL	0 for JPY/KRW, 2 default, 3 for KWD/BHD.
<code>display_locale</code>	text	NOT NULL	BCP-47 locale used for formatting.
<code>updated_at</code>	timestamptz	NOT NULL	

fx_rates

Reference & geography · 912 rows · IDs start `fxr_`

PS-08 cannot convert or settle without a dated rate table. Never overwrite the original amount; convert through here.

COLUMN	TYPE	CONSTRAINTS	NOTES
<code>fx_rate_id</code>	text	PK	<code>fxr_</code> prefixed.
<code>base_currency</code>	char(3)	FK → <code>currencies.iso4217</code> · NOT NULL	
<code>quote_currency</code>	char(3)	FK → <code>currencies.iso4217</code> · NOT NULL	
<code>rate_date</code>	date	NOT NULL	Rule R4: zoneless calendar date.
<code>rate</code>	decimal(18,8)	NOT NULL	Not money; a ratio, so higher precision is correct here.
<code>source</code>	text	NOT NULL	Synthetic feed identifier.
<code>updated_at</code>	timestamptz	NOT NULL	

Unique together: (`base_currency`, `quote_currency`, `rate_date`)

inventory_calendar

Availability & pricing · 15,030 rows · IDs start `inv_`

Entity x date availability with a database-level no-oversell CHECK. Deliberately scarce units so APS-05's load test has something to defend.

COLUMN	TYPE	CONSTRAINTS	NOTES
<code>inventory_id</code>	text	PK	<code>inv_</code> prefixed.
<code>entity_type</code>	text	NOT NULL · one of <code>room_type</code> , <code>flight_fare</code> , <code>guide</code> , <code>poi</code>	
<code>entity_id</code>	text	NOT NULL	<code>room_type_id</code> or <code>fare_id</code> .
<code>for_date</code>	date	NOT NULL	
<code>total_units</code>	int	NOT NULL	
<code>booked_units</code>	int	NOT NULL	
<code>held_units</code>	int	NOT NULL	
<code>price</code>	decimal(12,2)	NOT NULL	the price for that date.
<code>currency</code>	char(3)	FK → <code>currencies.iso4217</code> · NOT NULL	
<code>min_stay_nights</code>	smallint	NOT NULL	
<code>closed_to_arrival</code>	bool	NOT NULL	
<code>updated_at</code>	timestampz	NOT NULL	

Unique together: (`entity_type`, `entity_id`, `for_date`)

Enforced by the database: `booked_units + held_units <= total_units`

languages

Reference & geography · 26 rows · IDs start `lng_` · reference table

Rule R6: BCP-47 is the only legal way to say 'language' anywhere in the model.

COLUMN	TYPE	CONSTRAINTS	NOTES
<code>language_id</code>	text	PK	<code>lng_</code> prefixed.
<code>bcp47</code>	text	UNIQUE · NOT NULL	e.g. <code>ta</code> , <code>hi</code> , <code>en-IN</code> — never 'Tamil'.
<code>english_name</code>	text	NOT NULL	
<code>native_name</code>	text	NOT NULL	
<code>script</code>	text	NOT NULL	ISO-15924, e.g. <code>Taml</code> , <code>Deva</code> , <code>Latn</code> .
<code>rtl</code>	bool	NOT NULL	Right-to-left rendering flag.

COLUMN	TYPE	CONSTRAINTS	NOTES
tts_supported	bool	NOT NULL	Relevant to PS-13 voice output.
updated_at	timestampz	NOT NULL	

countries

Reference & geography · 30 rows · IDs start `cnt_`

ISO country reference. Every city, currency default and calling code resolves here.

COLUMN	TYPE	CONSTRAINTS	NOTES
country_id	text	PK	Canonical ID, cnt_ prefixed.
iso2	char(2)	UNIQUE · NOT NULL	ISO-3166-1 alpha-2, e.g. IN.
iso3	char(3)	UNIQUE · NOT NULL	ISO-3166-1 alpha-3, e.g. IND.
name	text	NOT NULL	English short name.
default_currency	char(3)	FK → <code>currencies.iso4217</code> · NOT NULL	ISO-4217 code.
calling_code	text	NOT NULL	E.164 country calling code, e.g. +91.
region	text	NOT NULL	UN sub-region grouping.
updated_at	timestampz	NOT NULL	Rule R4: UTC, ISO-8601 with offset.

airlines

Reference & geography · 30 rows · IDs start `arl_` · reference table

Carrier reference for flight schedule instances.

COLUMN	TYPE	CONSTRAINTS	NOTES
airline_id	text	PK	arl_ prefixed.
iata	char(2)	UNIQUE · NOT NULL	Carrier code, e.g. 6E.
name	text	NOT NULL	
alliance	text		star_alliance
country_id	text	FK → <code>countries.country_id</code> · NOT NULL	
low_cost	bool	NOT NULL	Drives fare banding.
updated_at	timestampz	NOT NULL	

cities

Reference & geography · 60 rows · IDs start `cty_`

The geographic anchor of the whole model. 60 cities; every hotel, POI, package, advisory and weather row hangs off one.

COLUMN	TYPE	CONSTRAINTS	NOTES
city_id	text	PK	city_ prefixed.
name	text	NOT NULL	City name.
state	text		State / province, nullable for city-states.
country_id	text	FK → countries.country_id · NOT NULL	
country_code	char(2)	NOT NULL	Denormalised ISO2 for convenient joins.
lat	decimal(9,6)	NOT NULL	Rule R7: WGS-84, 6dp.
lng	decimal(9,6)	NOT NULL	Rule R7: WGS-84, 6dp.
timezone	text	NOT NULL	IANA zone, e.g. Asia/Kolkata.
region	text	NOT NULL	Domestic region grouping, e.g. South India.
population	int		Approximate, for demand weighting.
season_profile	text	NOT NULL · one of winter, summer, monsoon, post_monsoon, spring, autumn	Dominant season at the peak travel window.
peak_months	text	NOT NULL	Comma-separated month numbers, e.g. 10,11,12.
primary_language	text	FK → languages.bcp47 · NOT NULL	Rule R6: BCP-47 tag.
description	text		One-paragraph orientation blurb, used by PS-13.
status	text	NOT NULL · one of active, inactive, archived, draft	
updated_at	timestampz	NOT NULL	

hotels

Supply & catalogue · 300 rows · IDs start htl_

Fewer, richer properties. Depth (reviews, room types, media) matters more than catalogue size —.

COLUMN	TYPE	CONSTRAINTS	NOTES
hotel_id	text	PK	htl_ prefixed.

COLUMN	TYPE	CONSTRAINTS	NOTES
city_id	text	FK → cities.city_id · NOT NULL	
name	text	NOT NULL	~3% near-duplicate names injected deliberately.
property_type	text	NOT NULL · one of hotel, resort, homestay, hostel, apartment, boutique, heritage, guesthouse	
star_rating	smallint	NOT NULL	1–5, CHECK constrained.
guest_score	decimal(2,1)		0.0–10.0; null for a handful of new properties.
review_count	int	NOT NULL	Denormalised count, must agree with hotel_reviews.
address_line	text	NOT NULL	
lat	decimal(9,6)	NOT NULL	
lng	decimal(9,6)	NOT NULL	
distance_to_centre_km	decimal(6,2)	NOT NULL	PS-02 filter: distance to a landmark.
description	text	NOT NULL	Plausible prose, embeddable.
base_currency	char(3)	FK → currencies.iso4217 · NOT NULL	
checkin_time	text	NOT NULL	Local HH:MM at the property.
checkout_time	text	NOT NULL	
chain_code	text		Null for independents.
has_xr_scene	bool	NOT NULL	PS-05 / APS-07 — does an immersive preview exist.
status	text	NOT NULL · one of active, inactive, archived, draft	
created_at	timestampz	NOT NULL	
updated_at	timestampz	NOT NULL	

users

Identity & preference · 1,200 rows · IDs start `usr_` · reference table

The traveller identity every personalisation hangs off. Segmented heavy / light / cold_start so APS-04 can prove cold start.

COLUMN	TYPE	CONSTRAINTS	NOTES
user_id	text	PK	usr_ prefixed.
display_name	text	NOT NULL	Synthetic — no real people (content policy).
email	text	UNIQUE · NOT NULL	Synthetic @example.invalid addresses only.
home_city_id	text	FK → cities.city_id · NOT NULL	
home_currency	char(3)	FK → currencies.iso4217 · NOT NULL	
locale	text	FK → languages.bcp47 · NOT NULL	UI language, BCP-47.
budget_band	text	NOT NULL · one of shoestring, value, mid, premium, luxury	
travel_style	text	NOT NULL · one of budget, comfort, luxury, adventure, slow, cultural, wellness	
traveller_type	text	NOT NULL · one of solo, couple, family, business, friends, senior, backpacker	
segment	text	NOT NULL · one of heavy, light, cold_start	heavy / light / cold_start cohorts.
date_of_signup	date	NOT NULL	
loyalty_tier	text		none
status	text	NOT NULL · one of active, inactive, archived, draft	
created_at	timestampz	NOT NULL	
updated_at	timestampz	NOT NULL	

airports

Reference & geography · 80 rows · IDs start apt_ · reference table

So flights join airport-to-airport rather than city-to-city.

COLUMN	TYPE	CONSTRAINTS	NOTES
airport_id	text	PK	apt_ prefixed.
iata	char(3)	UNIQUE · NOT NULL	IATA code.
icao	char(4)		ICAO code.
name	text	NOT NULL	

COLUMN	TYPE	CONSTRAINTS	NOTES
city_id	text	FK → cities.city_id · NOT NULL	
lat	decimal(9,6)	NOT NULL	
lng	decimal(9,6)	NOT NULL	
timezone	text	NOT NULL	IANA.
is_international	bool	NOT NULL	
updated_at	timestampz	NOT NULL	

flights

Supply & catalogue · 4,000 rows · IDs start `flt_`

Schedule instances across the search window, so a date search returns results rather than blanks.

COLUMN	TYPE	CONSTRAINTS	NOTES
flight_id	text	PK	flt_ prefixed.
airline_id	text	FK → airlines.airline_id · NOT NULL	
flight_number	text	NOT NULL	e.g. 6E-2043.
origin_airport_id	text	FK → airports.airport_id · NOT NULL	
dest_airport_id	text	FK → airports.airport_id · NOT NULL	
departs_at	timestampz	NOT NULL	Rule R4: carries offset.
arrives_at	timestampz	NOT NULL	
duration_minutes	int	NOT NULL	
stops	smallint	NOT NULL	
aircraft_type	text		
cabin_classes	text	NOT NULL	Comma-separated cabin_class values available.
carbon_kg	decimal(8,3)	NOT NULL	Per-seat estimate — APS-09 reads this.
status	text	NOT NULL · one of active, inactive, archived, draft	
updated_at	timestampz	NOT NULL	

hotel_room_types

Supply & catalogue · 1,200 rows · IDs start `rmt_`

The bookable unit. APS-05's no-oversell guarantee is defended at this grain.

COLUMN	TYPE	CONSTRAINTS	NOTES
room_type_id	text	PK	rmt_ prefixed.
hotel_id	text	FK → hotels.hotel_id · NOT NULL	
name	text	NOT NULL	e.g. Deluxe Garden View.
max_occupancy	smallint	NOT NULL	
max_adults	smallint	NOT NULL	
max_children	smallint	NOT NULL	
bed_config	text	NOT NULL · one of single, twin, double, queen, king, bunk, twin_double	
size_sqm	smallint		
base_rate	decimal(12,2)	NOT NULL	NUMERIC, never FLOAT.
currency	char(3)	FK → currencies.iso4217 · NOT NULL	always paired with the amount.
total_units	int	NOT NULL	Deliberately scarce on some rows so APS-05 has contention.
smoking_allowed	bool	NOT NULL	
status	text	NOT NULL · one of active, inactive, archived, draft	
updated_at	timestamptz	NOT NULL	

trips

Trip & itinerary · 600 rows · IDs start `trp_` · reference table

The container that gives dates, party, destination and budget to everything else. Seven statements produce or consume one.

COLUMN	TYPE	CONSTRAINTS	NOTES
trip_id	text	PK	trp_ prefixed.
owner_user_id	text	FK → users.user_id · NOT NULL	
title	text	NOT NULL	
origin_city_id	text	FK → cities.city_id	
destination_city_id	text	FK → cities.city_id · NOT NULL	

COLUMN	TYPE	CONSTRAINTS	NOTES
start_date	date	NOT NULL	Rule R4: zoneless calendar date.
end_date	date	NOT NULL	
party_size	smallint	NOT NULL	
adults	smallint	NOT NULL	
children	smallint	NOT NULL	
trip_type	text	NOT NULL · one of solo, couple, family, business, friends, senior, backpacker	
is_group_trip	bool	NOT NULL	PS-11 / PS-08 filter.
status	text	NOT NULL · one of draft, planning, confirmed, in_progress, completed, cancelled	
home_currency	char(3)	FK → currencies.iso4217 · NOT NULL	
notes	text		
created_at	timestamptz	NOT NULL	
updated_at	timestamptz	NOT NULL	

flight_fares

Supply & catalogue · 8,002 rows · IDs start far_

The bookable unit for flights, and the second entity_type in inventory_calendar.

COLUMN	TYPE	CONSTRAINTS	NOTES
fare_id	text	PK	far_ prefixed.
flight_id	text	FK → flights.flight_id · NOT NULL	
cabin_class	text	NOT NULL · one of economy, premium_economy, business, first	
fare_class	text	NOT NULL · one of saver, flex, standard, corporate, promo	
base_fare	decimal(12,2)	NOT NULL	D3.
taxes	decimal(12,2)	NOT NULL	
currency	char(3)	FK → currencies.iso4217 · NOT NULL	
baggage_kg	smallint	NOT NULL	
cabin_baggage_kg	smallint	NOT NULL	

COLUMN	TYPE	CONSTRAINTS	NOTES
changeable	bool	NOT NULL	
change_fee	decimal(12,2)		
refundable	bool	NOT NULL	
seats_total	int	NOT NULL	
status	text	NOT NULL · one of active, inactive, archived, draft	
updated_at	timestampz	NOT NULL	

hotel_rate_plans

Supply & catalogue · 2,400 rows · IDs start rtp_

Makes rate selection a real choice rather than a single price.

COLUMN	TYPE	CONSTRAINTS	NOTES
rate_plan_id	text	PK	rtp_ prefixed.
room_type_id	text	FK → hotel_room_types.room_type_id · NOT NULL	
plan_type	text	NOT NULL · one of refundable, non_refundable, breakfast_included, half_board, full_board, long_stay	
name	text	NOT NULL	
price_delta	decimal(12,2)	NOT NULL	Signed delta applied to the room base_rate.
currency	char(3)	FK → currencies.iso4217 · NOT NULL	
cancellation_window_hours	int	NOT NULL	0 for non-refundable.
cancellation_penalty_pct	smallint	NOT NULL	
includes_breakfast	bool	NOT NULL	
min_stay_nights	smallint	NOT NULL	
status	text	NOT NULL · one of active, inactive, archived, draft	
updated_at	timestampz	NOT NULL	

itineraries

Trip & itinerary · 803 rows · IDs start itn_ · reference table

A versioned plan belonging to a trip. version is what makes PS-11's conflict handling tractable.

COLUMN	TYPE	CONSTRAINTS	NOTES
itinerary_id	text	PK	itn_ prefixed.
trip_id	text	FK → trips.trip_id · NOT NULL	
name	text	NOT NULL	
version	int	NOT NULL	Monotonic per itinerary.
is_active	bool	NOT NULL	Exactly one active version per trip.
generated_by	text	NOT NULL · one of user , ai_planner , optimizer , agent , vote , import	Which subsystem produced this version.
total_cost	decimal(12,2)	NOT NULL	sum of item costs, half-up at the end.
currency	char(3)	FK → currencies.iso4217 · NOT NULL	
total_duration_minutes	int	NOT NULL	
total_carbon_kg	decimal(10,3)	NOT NULL	APS-09 objective.
optimizer_weights	text		JSON string: {cost, time, carbon} weights that produced it.
status	text	NOT NULL · one of active , inactive , archived , draft	
created_at	timestampz	NOT NULL	
updated_at	timestampz	NOT NULL	

bookings

Booking & money · 1,996 rows · IDs start bkg_

The order header — where inventory, payment and itinerary meet. Idempotency key is mandatory, not optional.

COLUMN	TYPE	CONSTRAINTS	NOTES
booking_id	text	PK	bkg_ prefixed.
user_id	text	FK → users.user_id · NOT NULL	
trip_id	text	FK → trips.trip_id	Null for standalone bookings.
itinerary_id	text	FK → itineraries.itinerary_id	

COLUMN	TYPE	CONSTRAINTS	NOTES
booking_reference	text	UNIQUE · NOT NULL	Human-quotable 6-char reference.
channel	text	NOT NULL · one of web, mobile_app, partner, call_centre, agent	
total_amount	decimal(12,2)	NOT NULL	must equal the sum of booking_items.
currency	char(3)	FK → currencies.iso4217 · NOT NULL	
tax_amount	decimal(12,2)	NOT NULL	
idempotency_key	text	UNIQUE · NOT NULL	APS-05 — retried requests resolve to this same row.
status	text	NOT NULL · one of pending, confirmed, partially_confirmed, cancelled, failed, refunded	
confirmed_at	timestampz		
cancelled_at	timestampz		
cancellation_reason	text		
created_at	timestampz	NOT NULL	
updated_at	timestampz	NOT NULL	

holds

Availability & pricing · 496 rows · IDs start `hld_`

TTL reservation with an idempotency key. Expired and released holds are retained (R8) because that history is what makes the demo interesting.

COLUMN	TYPE	CONSTRAINTS	NOTES
hold_id	text	PK	hld_ prefixed.
inventory_id	text	FK → inventory_calendar.inventory_id · NOT NULL	
user_id	text	FK → users.user_id · NOT NULL	
units	int	NOT NULL	
idempotency_key	text	UNIQUE · NOT NULL	APS-05 — a retried request must never double-book.
created_at	timestampz	NOT NULL	
expires_at	timestampz	NOT NULL	TTL.

COLUMN	TYPE	CONSTRAINTS	NOTES
released_at	timestampz		
booking_id	text	FK → bookings.booking_id	Set when the hold converts.
status	text	NOT NULL · one of active, confirmed, released, expired	
updated_at	timestampz	NOT NULL	

payments

Booking & money · 1,996 rows · IDs start pay_

Mock payment records — authorised and captured amounts held separately so a partial capture is representable.

COLUMN	TYPE	CONSTRAINTS	NOTES
payment_id	text	PK	pay_ prefixed.
booking_id	text	FK → bookings.booking_id · NOT NULL	
method	text	NOT NULL · one of card, upi, netbanking, wallet, mock	
status	text	NOT NULL · one of initiated, authorised, captured, failed, refunded, voided	
authorised_amount	decimal(12,2)	NOT NULL	D3.
captured_amount	decimal(12,2)	NOT NULL	
refunded_amount	decimal(12,2)	NOT NULL	
currency	char(3)	FK → currencies.iso4217 · NOT NULL	
gateway_reference	text	NOT NULL	Synthetic mock reference.
idempotency_key	text	UNIQUE · NOT NULL	
failure_code	text	one of hold_expired, sold_out, over_budget, invalid_id, currency_mismatch, idempotency_conflict, constraint_infeasible, low_confidence	
authorised_at	timestampz		
captured_at	timestampz		
created_at	timestampz	NOT NULL	
updated_at	timestampz	NOT NULL	

booking_items

Booking & money · 2,669 rows · IDs start `bit_`

Line items, so a multi-item booking can be partially compensated — which is the whole point of APS-05's saga.

COLUMN	TYPE	CONSTRAINTS	NOTES
<code>booking_item_id</code>	text	PK	bit_ prefixed.
<code>booking_id</code>	text	FK → <code>bookings.booking_id</code> · NOT NULL	
<code>entity_type</code>	text	NOT NULL · one of <code>hotel</code> , <code>room_type</code> , <code>rate_plan</code> , <code>flight</code> , <code>flight_fare</code> , <code>poi</code> , <code>package</code> , <code>package_component</code> , <code>guide</code> , <code>transfer</code> , <code>event</code> , <code>xr_scene</code>	
<code>entity_id</code>	text	NOT NULL	
<code>inventory_id</code>	text	FK → <code>inventory_calendar.inventory_id</code>	
<code>title</code>	text	NOT NULL	
<code>for_date</code>	date		
<code>units</code>	int	NOT NULL	
<code>unit_price</code>	decimal(12,2)	NOT NULL	D3.
<code>line_total</code>	decimal(12,2)	NOT NULL	units x unit_price, half-up.
<code>currency</code>	char(3)	FK → <code>currencies.iso4217</code> · NOT NULL	
<code>status</code>	text	NOT NULL · one of <code>pending</code> , <code>confirmed</code> , <code>cancelled</code> , <code>compensated</code>	
<code>compensated_at</code>	timestampz		Set when the saga rolls this line back.
<code>updated_at</code>	timestampz	NOT NULL	

The rules that apply to these fields

#	RULE
R1	Additive only. Add columns, tables and stores freely. Never rename, drop or repurpose a field that came with the data.
R2	IDs are opaque prefixed strings — <code>htl_a91f3c</code> . Never integers, never parsed for meaning.
R3	Money is a pair: a 2-place decimal plus an ISO-4217 currency code. Never a float.
R4	Time is ISO-8601 with an offset. <code>_at</code> fields carry an offset; <code>_date</code> fields have no zone.

#	RULE
R5	Enums are lowercase snake_case and the legal values are in data/enums.json.
R6	Language is a BCP-47 tag — ta, not "Tamil".
R7	Geography is WGS-84 to 6 decimal places, lat and lng together or not at all.
R8	Nothing is hard-deleted. Rows carry status and updated_at.

Add whatever you like beside these fields — new columns, new tables, your own vector store, your own services. That is the point of R1. What you must not do is rename or re-key the fields that came with the data, because that is what would stop sixteen independent builds being put together afterwards.

data/WORKING_WITH_THE_DATA.md has the loading instructions, including how to read money without corrupting it. tools/validate_conformance.py tells you in thirty seconds whether you are still conformant.