

Yices-QS, an extension of Yices for quantified satisfiability

Stéphane Graham-Lengrand

SRI International, USA

1 Introduction

Yices-QS is a solver derived from Yices 2, an open-source SMT solver developed and distributed by SRI International. It was mostly developed between May and August 2020, and is entering the SMT-competition for the first time in 2021, in the BV and NRA divisions (single-track). It is available at

<https://github.com/disteph/yicesQS>.

Yices-QS extends Yices to supports quantifiers for complete theories, as an application of features that have been recently added to Yices' MCSAT solver [dMJ13, Jov17], in particular: *satisfiability modulo a model* and *model interpolation*. Until Aman Goel's recent addition of E-graph matching and model-based instantiation in Yices 2 for the UF theory, the support for quantifiers in Yices was limited to the exists-forall fragment, using a variant of counterexample-guided quantifier instantiation (CEGQI) [Dut15]. Yices-QS supports arbitrary quantifiers, and its core algorithm extends Yices' CEGQI approach into an algorithm that can be seen as a form of lazy quantifier elimination, and that leverages MCSAT's new features, mentioned above and offered in Yices's latest C API.

Yices-QS, which is entirely written in OCaml, is also the first development built on top of our new OCaml bindings for Yices 2, available at

https://github.com/SRI-CSL/yices2_ocaml_bindings.

The version entering the 2021 SMT competition is commit 5b6f98a of Yices-QS, using commit fed5994 of the OCaml bindings to call the Yices 2 library at commit 09d18a4, available at

<https://github.com/SRI-CSL/yices2>.

2 Algorithm

Yices-QS does not modify the structure of quantifiers in formulas: it does not prenexify formulas and, more importantly, it does not skolemize them to avoid introducing uninterpreted function symbols.

In that, Yices-QS departs from the standard architecture for quantifier support consisting of keeping a set of universally quantified clauses, to be grounded and sent to a core SMT-solver for ground clauses.

Instead, it sees a formula as a 2-player game, in the tradition of Bjørner & Janota's *Playing with Quantified Satisfaction* [BJ15] and earlier work on QBF. Yices-QS's algorithm is designed to answer queries of the following form:

“Given a formula $A(\bar{z}, \bar{x})$ and a model $\mathfrak{M}_{\bar{z}}$ on \bar{z} , produce either

- $\text{SAT}(U(\bar{z}))$, with $U(\bar{z})$ under-approx. of $\exists \bar{x} A(\bar{z}, \bar{x})$ satisfied by $\mathfrak{M}_{\bar{z}}$; or
- $\text{UNSAT}(O(\bar{z}))$, with $O(\bar{z})$ over-approx. of $\exists \bar{x} A(\bar{z}, \bar{x})$ not satisfied by $\mathfrak{M}_{\bar{z}}$;

where under-approximations and over-approximations are quantifier-free.”

To answer such queries, Yices-QS calls Yices’s new feature *satisfiability modulo a model*, while the production of under- and over-approximations leverages *model interpolation* and *model generalization*.

When the input formula is in the exists-forall fragment, the algorithm degenerates to the one used in Yices’ $\exists\forall$ solver, using quantifier-free solving and *model generalization*, as described in [Dut15]. *Model interpolation*, a form of which is used within MCSAT to solve quantifier-free problems, also becomes useful with more quantifier alternations than $\exists\forall$, and we believe this is a new contribution to the *quantified-problems-as-games* approach, beyond the use of UNSAT cores.

3 Theory-specific aspects

- *Model interpolation* is available in Yices’s MCSAT solver for quantifier-free problems. In particular, it has theory-specific techniques for, among other theories, QF_NRA based on NLSAT [JdM12] (and ultimately, Cylindrical Algebraic Decomposition–CAD), and QF_BV [GLJD20].
- *Model generalization* can be done generically by substitutions [Dut15], but this can be complemented by theory-specific techniques that can provide better generalizations. For QF_NRA, we use model-projection, recently added to Yices’s MCSAT and based on, once again, CAD. For QF_BV, we use invertibility conditions from Niemetz et al. [NPR⁺18], including ϵ -terms, in combination with generalization-by-substitution. For the BV theory, the cegqi solver from [NPR⁺18] is probably the closest to Yices-QS, which approaches BV as an instance of the theory-generic algorithm from Section 2.

Notes:

- For NRA, the presence of division in benchmarks departs from the theoretic applicability of Yices-QS’s algorithm for complete theories, because of division-by-zero (which also makes the theory undecidable). Yices’s CAD-based model-projection in NRA does not support division. In practice, when Yices-QS needs to perform model generalization with a formula involving division, it cannot use CAD model-projection and resorts to generalization-by-substitution. This only works if the model values are rational rather than algebraic irrational, for which we have no term representation. In that last case, Yices-QS gives up. Resorting to generalization-by-substitution for NRA also means that Yices-QS’s algorithm may not terminate.
- Since invertibility conditions for BV [NPR⁺18] capture existentially quantified formulas with quantifier-free formulas, rather than provide over- or under-approximations of them, we plan to explore how to use them for *model interpolation*, while we currently only use them for *model generalization*.
- We also plan to explore other related works such as Monniaux’s *Quantifier Elimination by Lazy Model Enumeration* [Mon10].

References

- BJ15. N. Bjørner and M. Janota. Playing with quantified satisfaction. In M. Davis, A. Fehnker, A. McIver, and A. Voronkov, editors, *Proc. of the 20th Int. Conf. on Logic for Programming, Artificial Intelligence, and Reasoning (LPAR'15)*, volume 9450 of *LNCS*. Springer-Verlag, 2015. <https://doi.org/10.1007/978-3-662-48899-7> 1
- dMJ13. L. M. de Moura and D. Jovanovic. A model-constructing satisfiability calculus. In R. Giacobazzi, J. Berdine, and I. Mastroeni, editors, *Proc. of the 14th Int. Conf. on Verification, Model Checking, and Abstract Interpretation (VMCAI'13)*, volume 7737 of *LNCS*, pages 1–12. Springer-Verlag, 2013. https://doi.org/10.1007/978-3-642-35873-9_1 1
- Dut15. B. Dutertre. Solving exists/forall problems with yices. In *13th International Workshop on Satisfiability Modulo Theories (SMT 2015)*, 2015. <https://yices.cs.sri.com/papers/smt2015.pdf>. 1, 2
- GLJD20. S. Graham-Lengrand, D. Jovanović, and B. Dutertre. Solving bitvectors with MCSAT: explanations from bits and pieces. In N. Peltier and V. Sofronie-Stokkermans, editors, *Proceedings of the 10th International Joint Conference on Automated Reasoning (IJCAR'20)*, volume 12166(1) of *Lecture Notes in Computer Science*, pages 103–121. Springer-Verlag, 2020. 2
- JdM12. D. Jovanović and L. de Moura. Solving non-linear arithmetic. In B. Gramlich, D. Miller, and U. Sattler, editors, *Proc. of the 6th Int. Joint Conf. on Automated Reasoning (IJCAR'12)*, volume 7364 of *LNCS*, pages 339–354. Springer-Verlag, 2012. 2
- Jov17. D. Jovanović. Solving nonlinear integer arithmetic with MCSAT. In A. Bouajjani and D. Monniaux, editors, *Proc. of the 18th Int. Conf. on Verification, Model Checking, and Abstract Interpretation (VMCAI'17)*, volume 10145 of *LNCS*, pages 330–346. Springer-Verlag, 2017. https://doi.org/10.1007/978-3-319-52234-0_18 1
- Mon10. D. Monniaux. Quantifier elimination by lazy model enumeration. In T. Touili, B. Cook, and P. Jackson, editors, *Computer Aided Verification*, pages 585–599. Springer Berlin Heidelberg, 2010. 2
- NPR⁺18. A. Niemetz, M. Preiner, A. Reynolds, C. W. Barrett, and C. Tinelli. Solving quantified bit-vectors using invertibility conditions. In H. Chockler and G. Weissenbacher, editors, *Proc. of the 30th Int. Conf. on Computer Aided Verification (CAV'18)*, volume 10982 of *LNCS*, pages 236–255. Springer-Verlag, 2018. https://doi.org/10.1007/978-3-319-96142-2_16 2