Smart Dongle-WLAN-FE

Smart
WLAN & Fast Ethernet (FE) communication
Support 3rd-party monitoring system [1]

Simple
Plug & Play
Support max. 10 devices

Reliable
IP65
Support auto reconnection

Technical Specification	SDongleA-05
General Data	
Max. Devices Supported	10
Max. Inverters Supported	10
Connection interface	USB
Ethernet Interface	10/100M Ethernet
Installation	Plug-and-play
Indicator	LED Indicator
Dimensions (W * H * D)	146 x 48 x 33 mm (5.1 x 1.9 x 1.3 inch)
Weight	90 g (0.2 lb.)
Degree of protection	IP65
Power consumption (typical)	2.5 W
Operation Mode	STA
Encryption Algorithm	Encryption Mechanism：WPA/WPA2 Encryption：TKIP/CCMP/AES
Wireless Parameter	
Supported standards & frequencies	802.11b/g/n（2.412G—2.484G）
Environment	
Operating temperature range	-30 ℃ to +65 ℃ (-22 ℉ to 149 ℉)
Relative humidity range	5 - 95% RH
Storage temperature range	-40℃ to +70℃ (-40 ℉ to 158 ℉)
Max. operating altitude	4,000 m (13,123 ft.)
Standard Compliance (more available upon request)	
Certificate	SRRC, CE, RCM
Inverter Compatibility	
Supported Master Inverter Model	SUN2000-3/4/5/6/8/10KTL-M0 SUN2000-12/15/17/20KTL-M0

1: 3rd-party management system shall match the communication protocol with Huawei Smart Dongle.