

# NDA: Time Series Analysis

## Part 2: problem-oriented approach

Lionel Tabourier

LIP6 – CNRS and Sorbonne University

`first_name.last_name@lip6.fr`

January 2021

# Summary of Part 1

## About the classic approach

- pre-processing (transformation etc)
- decomposition/modeling
  - model for trend
  - model for seasonal component
  - ARMA model of residuals
- post-processing → model for the whole process

summarized description of a time series

## Advantages and drawbacks

- **powerful** ⇒ understanding, allows prediction, test, ...
- but **heavy procedure**, can be difficult to achieve

Now we look at time series data as (quasi) standard data

# Summary of Part 1

## About the classic approach

- pre-processing (transformation etc)
- decomposition/modeling
  - model for trend
  - model for seasonal component
  - ARMA model of residuals
- post-processing → model for the whole process

summarized description of a time series

## Advantages and drawbacks

- **powerful** ⇒ understanding, allows prediction, test, ...
- but **heavy procedure**, can be difficult to achieve

Now we look at time series data as (quasi) standard data

# Summary of Part 1

## About the classic approach

- pre-processing (transformation etc)
- decomposition/modeling
  - model for trend
  - model for seasonal component
  - ARMA model of residuals
- post-processing → model for the whole process

summarized description of a time series

## Advantages and drawbacks

- **powerful** ⇒ understanding, allows prediction, test, ...
- but **heavy procedure**, can be difficult to achieve

Now we look at time series data as (quasi) standard data

# A problem-oriented approach

Alternative approach **problem-oriented**:  
a specific question to solve  $\Rightarrow$  suited techniques  
*regression, classification, hypothesis testing, clustering...*

**here: investigate a TSA problem and its resolution**

## The problem to solve

Provide resources in a local WiFi network (mall, university, ...)

- forecast the daily demand on the network
- plan and adapt the service in consequence
- raise an alert of exceptionally high demand

## Data available

- data traffic usage per application during 4 months

# A problem-oriented approach

Alternative approach **problem-oriented**:  
a specific question to solve  $\Rightarrow$  suited techniques  
*regression, classification, hypothesis testing, clustering...*

**here: investigate a TSA problem and its resolution**

## The problem to solve

Provide resources in a local WiFi network (mall, university, ...)

- forecast the daily demand on the network
- plan and adapt the service in consequence
- raise an alert of exceptionally high demand

## Data available

- data traffic usage per application during 4 months

# A problem-oriented approach

Alternative approach **problem-oriented**:  
a specific question to solve  $\Rightarrow$  suited techniques  
*regression, classification, hypothesis testing, clustering...*

**here: investigate a TSA problem and its resolution**

## The problem to solve

Provide resources in a local WiFi network (mall, university, ...)

- forecast the daily demand on the network
- plan and adapt the service in consequence
- raise an alert of exceptionally high demand


## Data available

- data traffic usage per application during 4 months

# Approach chosen

Lim at al. - *Characterizing and predicting mobile application usage*

- create classes of usage profiles for each application  
→ **clustering** of past data
- analyze streaming data to attribute a class  
→ **classification** of incoming data




Not a unique solution → need **evaluation** and comparison



# Approach chosen

Lim at al. - *Characterizing and predicting mobile application usage*

- create classes of usage profiles for each application  
→ **clustering** of past data
- analyze streaming data to attribute a class  
→ **classification** of incoming data



Not a unique solution → need **evaluation** and comparison

# Step 1: clustering

## Agglomerative hierarchical clustering


*cf. course on Clustering*

UPGMA method (*Unweighted Pair Group Method with Arithmetic Mean*)


- initialization: each profile is one class
- compute the distances  $d(i, j)$  between pairs
  1. find the lowest distance pair, group them in one class
  2. recompute distances by arithmetic mean:

$$d(A, B) = \frac{1}{|A| \cdot |B|} \sum_{i \in A} \sum_{j \in B} d(i, j)$$

- iterate 1 and 2 until having one class




## Step 1: clustering




## Definition of the distance

Need appropriate notion of distance for time series  
euclidean distance inappropriate




$$d(S_1, S_2) = \sum_t |S_1(t) - S_2(t)|$$

## Step 1: clustering




## Definition of the distance

Need appropriate notion of distance for time series  
dynamic time warping



$$d(S_1, S_2) = \sum_t |S_1(t) - S_2(t')| \text{ s.t. } S_2(t') \text{ is the best match for } S_1(t)$$

# Step 1: clustering




## Criterion to decide the clusters

Several options depending on the application:

- predefined number of clusters
- distance threshold  $\Delta$  between clusters

here: we want homogeneous clusters  $\Rightarrow$  threshold  
parameter  $\Delta$  to set experimentally

## Step 1: clustering




## Criterion to decide the clusters

Several options depending on the application:

- predefined number of clusters
- distance threshold  $\Delta$  between clusters

here: we want homogeneous clusters  $\Rightarrow$  threshold parameter  $\Delta$  to set experimentally

# Step 1: clustering




## Computational complexity

- for each distance computation using DTW:  
ts of size  $n$ , for each point  $n$  comparisons  $\Rightarrow O(n^2)$
- UPGMA with  $S$  profiles:  
simple implementations in  $O(S^3)$ , most efficient in  $O(S^2)$

→ heavy computational costs  
manageable because offline processing (and small dataset)

## Step 1: clustering



## Computational complexity

- for each distance computation using DTW:  
ts of size  $n$ , for each point  $n$  comparisons  $\Rightarrow O(n^2)$
- UPGMA with  $S$  profiles:  
simple implementations in  $O(S^3)$ , most efficient in  $O(S^2)$

→ heavy computational costs

manageable because **offline processing** (and small dataset)




## Step 2: classification

*cf. course on Classification*

### K-nearest neighbors: context

- Each data point is located in a space of features
- Each data point has a class (*ex: red triangles, blue squares*)



### K-nearest neighbors: principle


- For a new unlabeled data point (*ex: green circle*): compute its distance to all labeled data points
- Prediction = dominant class among its  $k$  nearest neighbors

## Step 2: classification

*cf. course on Classification*

### K-nearest neighbors: context

- Each data point is located in a space of features
- Each data point has a class (*ex: red triangles, blue squares*)



### K-nearest neighbors: principle

- For a new unlabeled data point (*ex: green circle*):  
compute its distance to all labeled data points
- Prediction = dominant class among its  $k$  nearest neighbors

## Step 2: classification

### Here

simple: DTW distance to all existing data points  
→ what is the class of the closest profile? ( $k=1$ )

### Computational complexity

- for each distance computation using DTW:  
ts of size  $n$ , for each point  $n$  comparisons  $\Rightarrow O(n^2)$
- comparisons with  $S$  profiles:  $O(S)$

computational costs relatively light  
but must be done in streaming

## Step 2: classification

### Here

simple: DTW distance to all existing data points  
→ what is the class of the closest profile? ( $k=1$ )

### Computational complexity

- for each distance computation using DTW:  
ts of size  $n$ , for each point  $n$  comparisons  $\Rightarrow O(n^2)$
- comparisons with  $S$  profiles:  $O(S)$

computational costs relatively light  
but must be done **in streaming**

## Step 2: classification

### Here

simple: DTW distance to all existing data points  
→ what is the class of the closest profile? ( $k=1$ )

### Computational complexity


- for each distance computation using DTW:  
ts of size  $n$ , for each point  $n$  comparisons  $\Rightarrow O(n^2)$
- comparisons with  $S$  profiles:  $O(S)$

computational costs relatively light  
but must be done **in streaming**

# Quality evaluation

## Classification task

- observe data during part of the day to classify
- $\Rightarrow$  possible **misclassifications**



$\rightarrow$  here we compute **prediction accuracy**  
proportion of accurate classifications


What about the practical efficiency?

# Quality evaluation

## Classification task

- observe data during part of the day to classify
- $\Rightarrow$  possible **misclassifications**

prediction accuracy (as a function of learning duration)




What about the practical efficiency?

# Quality evaluation

## Classification task

- observe data during part of the day to classify
- $\Rightarrow$  possible **misclassifications**

prediction accuracy (as a function of learning duration)



What about the practical efficiency?



# Discussion

## Complete workflow

- acquire data
- offline processing: clustering (classes definition)
- streaming processing: on-the-fly classification
- evaluation of classification

## Choices

- choice of resolution
- methods (of clustering, of classification)
- implementation details: (distance, threshold  $\Delta$ , ...)

under **practical constraints** → computational demand, ...

TS analysis is also a **craft**:  
choices guided by knowledge of the methods and data  
important to identify **why** something works or not. . .

# Discussion

## Complete workflow

- acquire data
- offline processing: clustering (classes definition)
- streaming processing: on-the-fly classification
- evaluation of classification

## Choices

- choice of resolution
- methods (of clustering, of classification)
- implementation details: (distance, threshold  $\Delta$ , ...)

under **practical constraints** → computational demand, ...

TS analysis is also a **craft**:  
choices guided by knowledge of the methods and data  
important to identify **why** something works or not. . .

# Discussion

## Complete workflow

- acquire data
- offline processing: clustering (classes definition)
- streaming processing: on-the-fly classification
- evaluation of classification

## Choices

- choice of resolution
- methods (of clustering, of classification)
- implementation details: (distance, threshold  $\Delta$ , ...)

under **practical constraints**  $\rightarrow$  computational demand, ...

TS analysis is also a **craft**:  
choices guided by knowledge of the methods and data  
important to identify **why** something works or not. . .