

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

SUREN NETWORK
PLAY WITH TECHNOLOGIES

```
R1
R1(config)#ip route 15.0.0.0 255.0.0.0 20.0.0.2
R1(config)#exit
R1#sh ip route
*Jul 21 07:17:00.887: %SYS-5-CONFIG_I: Configured from console by console
R1#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
        a - application route
        + - replicated route, % - next hop override, p - overrides from PFR

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       10.0.0.0/8 is directly connected, Ethernet0/0
L       10.0.0.1/32 is directly connected, Ethernet0/0
S       15.0.0.0/8 [1/0] via 20.0.0.2
20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       20.0.0.0/8 is directly connected, Ethernet0/1
L       20.0.0.1/32 is directly connected, Ethernet0/1
S       21.0.0.0/8 [1/0] via 20.0.0.2
S       30.0.0.0/8 [1/0] via 20.0.0.2
S       162.14.0.0/16 [1/0] via 20.0.0.2
S       172.19.0.0/16 [1/0] via 20.0.0.2
S       192.168.168.0/24 [1/0] via 20.0.0.2
```

Win-1
10.0.0.10

R1

R6
192.168.168.2

Win-3
162.14.0.10

Physical

01 : 00 : 00 START

34°C
Mostly cloudy

Search

ENG
IN

13:25
21-07-2026

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

```
R2#
*Jul 21 07:21:06.616: %SYS-5-CONFIG_I: Configured from console by console
R2#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
I - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
* - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

S 10.0.0.0/8 [1/0] via 20.0.0.1
S 15.0.0.0/8 [1/0] via 30.0.0.2
C 20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 20.0.0.0/8 is directly connected, Ethernet0/0
L 20.0.0.2/32 is directly connected, Ethernet0/0
S 21.0.0.0/8 [1/0] via 30.0.0.2
C 30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 30.0.0.0/8 is directly connected, Ethernet0/1
L 30.0.0.1/32 is directly connected, Ethernet0/1
S 162.14.0.0/16 [1/0] via 30.0.0.2
S 172.19.0.0/16 [1/0] via 30.0.0.2
S 192.168.168.0/24 [1/0] via 30.0.0.2
R2#^Z
R2#
```

Physical

01 : 00 : 00 START

34°C Mostly cloudy

Search

ENG IN

13:26 21-07-2026

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

Win-1
10.0.0.10

R3#
R3#

```
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

S 10.0.0.0/8 [1/0] via 30.0.0.1
S 15.0.0.0/8 [1/0] via 172.19.0.2
S 20.0.0.0/8 [1/0] via 30.0.0.1
C 21.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
L 21.0.0.0/8 is directly connected, Ethernet0/2
L 21.0.0.1/32 is directly connected, Ethernet0/2
C 30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
L 30.0.0.0/8 is directly connected, Ethernet0/0
L 30.0.0.2/32 is directly connected, Ethernet0/0
S 162.14.0.0/16 [1/0] via 21.0.0.2
C 172.19.0.0/16 is variably subnetted, 2 subnets, 2 masks
L 172.19.0.0/16 is directly connected, Ethernet0/1
L 172.19.0.1/32 is directly connected, Ethernet0/1
S 192.168.168.0/24 [1/0] via 21.0.0.2
```

R4
15.0.0.1

Win-2
15.0.0.10

R5
192.168.168.1

R6
162.14.0.1

Win-3
162.14.0.10

Physical

01 : 00 : 00

START

34°C
Mostly cloudy

Search

ENG
IN

13:26
21-07-2026

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

R4

```
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PFR

Gateway of last resort is not set

S 10.0.0.0/8 [1/0] via 172.19.0.1
S 15.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 15.0.0.0/8 is directly connected, Ethernet0/0
L 15.0.0.1/32 is directly connected, Ethernet0/0
S 20.0.0.0/8 [1/0] via 172.19.0.1
S 21.0.0.0/8 [1/0] via 172.19.0.1
S 30.0.0.0/8 [1/0] via 172.19.0.1
S 162.14.0.0/16 [1/0] via 172.19.0.1
S 172.19.0.0/16 is variably subnetted, 2 subnets, 2 masks
C 172.19.0.0/16 is directly connected, Ethernet0/1
L 172.19.0.2/32 is directly connected, Ethernet0/1
S 192.168.168.0/24 [1/0] via 172.19.0.1
```

Win-1 10.0.0.10

R1

R3

R4

R5

R6

Win-2 15.0.0.10

Win-3 162.14.0.10

Physical

01 : 00 : 00

START

34°C Mostly cloudy

Search

ENG IN

13:27 21-07-2026

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

R5

```
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

S   10.0.0.0/8 [1/0] via 21.0.0.1
S   15.0.0.0/8 [1/0] via 21.0.0.1
S   20.0.0.0/8 [1/0] via 21.0.0.1
S   21.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C     21.0.0.0/8 is directly connected, Ethernet0/0
L     21.0.0.2/32 is directly connected, Ethernet0/0
S   30.0.0.0/8 [1/0] via 21.0.0.1
S   162.14.0.0/16 [1/0] via 192.168.168.2
S   172.19.0.0/16 [1/0] via 21.0.0.1
S   192.168.168.0/24 is variably subnetted, 2 subnets, 2 masks
C     192.168.168.0/24 is directly connected, Ethernet0/1
L     192.168.168.1/32 is directly connected, Ethernet0/1
R5#
```

Physical

01 : 00 : 00 START

34°C Mostly cloudy

Search

ENG IN

13:27 21-07-2026

PNETLab | Topology

labs.surennetwork.com/legacy/topology

Ask Gemini

R6

```
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PFR

Gateway of last resort is not set

S 10.0.0.0/8 [1/0] via 192.168.168.1
S 15.0.0.0/8 [1/0] via 192.168.168.1
S 20.0.0.0/8 [1/0] via 192.168.168.1
S 21.0.0.0/8 [1/0] via 192.168.168.1
S 30.0.0.0/8 [1/0] via 192.168.168.1
C 162.14.0.0/16 is variably subnetted, 2 subnets, 2 masks
L 162.14.0.0/16 is directly connected, Ethernet0/0
L 162.14.0.1/32 is directly connected, Ethernet0/0
S 172.19.0.0/16 [1/0] via 192.168.168.1
C 192.168.168.0/24 is variably subnetted, 2 subnets, 2 masks
L 192.168.168.0/24 is directly connected, Ethernet0/1
L 192.168.168.2/32 is directly connected, Ethernet0/1
```

Win-1 10.0.0.10

R1 10.1

R4 172.19.0.2

R5 21.0.0.2

R6 162.14.0.1

Win-2 15.0.0.10

Win-3 162.14.0.10

Physical

01 : 00 : 00

START

34°C Mostly cloudy

Search

ENG IN

13:27 21-07-2026

PNETLab | Topology

labs.surenetwork.com/legacy/topology

Ask Gemini

QEMU (Win-1)

C:\WINDOWS\system32\cmd.exe

Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix . :

IP Address. : 10.0.0.10

Subnet Mask : 255.0.0.0

Default Gateway : 10.0.0.1

C:\Documents and Settings\User>ping 15.0.0.10

Pinging 15.0.0.10 with 32 bytes of data:

Reply from 15.0.0.10: bytes=32 time=3ms TTL=124

Reply from 15.0.0.10: bytes=32 time=3ms TTL=124

Reply from 15.0.0.10: bytes=32 time=1ms TTL=124

Reply from 15.0.0.10: bytes=32 time=1ms TTL=124

Ping statistics for 15.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 3ms, Average = 2ms

C:\Documents and Settings\User>

Old Java ASEM

PuTTY

Trpd32

Start

C:\WINDOWS\system...

8:52 AM

15.0.0.1

15.0.0.10

192.168.168.1

192.168.168.2

162.14.0.1

162.14.0.10

Win-2

Win-3

Physical

01 : 00 : 00

START

34°C

Mostly cloudy

Search

ENG

IN

13:22

21-07-2026

PNETLab | Topology

labs.surenetwork.com/legacy/topology

QEMU (Win-2)

C:\WINDOWS\system32\cmd.exe

Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix . : 15.0.0.10
IP Address : 15.0.0.0
Subnet Mask : 255.0.0.0
Default Gateway : 15.0.0.1

C:\Documents and Settings\user>ping 162.14.0.10

Pinging 162.14.0.10 with 32 bytes of data:

Reply from 162.14.0.10: bytes=32 time=2ms TTL=124
Reply from 162.14.0.10: bytes=32 time=2ms TTL=124
Reply from 162.14.0.10: bytes=32 time=2ms TTL=124
Reply from 162.14.0.10: bytes=32 time=3ms TTL=124

Ping statistics for 162.14.0.10:

Packet: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 3ms, Average = 2ms

C:\Documents and Settings\user>

15.0.0.1

15.0.0.10

192.168.168.1

192.168.168.2

162.14.0.1

162.14.0.10

Win-2

Win-3

Physical

01 : 00 : 00

START

34°C
Mostly cloudy

Search

13:24
21-07-2026