yokshita@yokshithachowdary

GNU nano 8.7.1

```c
#include <stdio.h>

int main()
{
    int n, a[15];
    int i, j, count;
    int missing, duplicate;
    int out = 0, target, r;

    printf("Enter N: ");
    scanf("%d", &n);

    if (n < 5 || n > 15)
    {
        printf("Invalid input");
        return 0;
    }

    printf("Enter ticket IDs: ");
    for (i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);

        if (a[i] < 1 || a[i] > n)
        {
            printf("Invalid input");
            return 0;
        }
```

^G Help ^O Write Out ^F Where Is ^K Cut
^X Exit ^R Read File ^\ Replace ^U Paste

yokshita@yokshithachowdary

GNU nano 8.7.1

```
    for (i = 0; i < n; i++)
    {
        count = 0;
        for (j = 0; j < n; j++)
        {
            if (a[i] == a[j])
                count++;
        }

        if (count == 2)
            duplicate = a[i];
    }

    for (i = 1; i <= n; i++)
    {
        count = 0;

        for (j = 0; j < n; j++)
        {
            if (a[j] == i)
                count++;
        }

        if (count == 0)
            missing = i;
    }

    for (i = 0; i < n - 1; i++)
```

^G Help ^O Write Out ^F Where Is ^K Cut
^U Pas

yokshita@yokshithachowdary

GNU nano 8.7.1

```
    {
        if (a[i] > a[i + 1])
            out++;
}

printf("Original sequence: ");
for (i = 0; i < n; i++)
    printf("%d ", a[i]);

printf("\nDuplicate ID: %d", duplicate);
printf("\nMissing ID: %d", missing);
printf("\nOut-of-order pairs: %d", out);

r = (duplicate * 10 + missing) % n;
target = r + 1;
count = 0;

for (i = 0; i < n; i++)
{
    if (a[i] == target)
        count++;
}

printf("\nTarget ID: %d", target);
printf("\nTarget occurrence count: %d", count);

return 0;
}
```

^G Help ^O Write Out ^F Where Is ^K Cut
^X Exit ^R Read File ^\ Replace ^U Paste

yokshita@yokshithachowdary

```
yokshita@yokshithachowdary:~$ pwd
/home/yokshita
yokshita@yokshithachowdary:~$ cd
yokshita@yokshithachowdary:~$ nano pu.c
yokshita@yokshithachowdary:~$ gcc pu.c
yokshita@yokshithachowdary:~$ ./a.out
Enter N: 6
Enter ticket IDs: 132356
Invalid inputyokshita@yokshithachowdary:~$ ./a.out
Enter N: 6
Enter ticket IDs: 132356
Invalid inputyokshita@yokshithachowdary:~$ ./a.out
Enter N: 6
Enter ticket IDs: 1 3 2 3 5 6
Original sequence: 1 3 2 3 5 6
Duplicate ID: 3
Missing ID: 4
Out-of-order pairs: 1
Target ID: 5
yokshita@yokshithachowdary:~$ ./a.out
Enter N: 5
Enter ticket IDs: 2 1 3 3 5
Original sequence: 2 1 3 3 5
Duplicate ID: 3
Missing ID: 4
Out-of-order pairs: 1
Target ID: 5
yokshita@yokshithachowdary:~$ nano pu.c
yokshita@yokshithachowdary:~$
```

23°C
Partly cloudy

Search