yokshita@yokshithachowdary

GNU nano 8.7.1

```c
#include <stdio.h>
int main()
{
int n1, n2, n3, n4, n5;
float total, average, percentage;
printf("enter marks for five subjects:\n");
scanf("%d", &n1);
scanf("%d", &n2);
scanf("%d", &n3);
scanf("%d", &n4);
scanf("%d", &n5);
total = n1 + n2 + n3 + n4 + n5;
average = total/5;
percentage = (total/500)*100;
printf("total marks =%.2f\n",total);
printf("average marks =%.2f\n",average);
printf("percentage=%.2f\n",percentage);
return 0;

}
```

```
yokshita@yokshithachowdary:~$ gcc challenge1.c
yokshita@yokshithachowdary:~$ ./a.out
enter marks for five subjects:
80
75
90
85
70
total marks =400.00
average marks =80.00
percentage=80.00
yokshita@yokshithachowdary:~$ gcc challenge1.c
yokshita@yokshithachowdary:~$ ./a.out
enter marks for five subjects:
65
72
68
75
80
total marks =360.00
average marks =72.00
percentage=72.00
yokshita@yokshithachowdary:~$ ./a.out
enter marks for five subjects:
95
88
92
90
85
total marks =450.00
average marks =90.00
percentage=90.00
yokshita@yokshithachowdary:~$
```

31°C
Partly sunny
Search