

Configure RFC in SAP Solution Manager

- Release version: Australia
-
- Updated March 12, 2026
-
- ⌚ 1 minute to read

As part of enabling communication with Event Management, you must create a Remote Function Call (RFC) in the SAP Solution Manager and install a transport.

Before you begin

Role required: evt_mgmt_admin

Download the following .psm files and import them into the SAP Solution Manager system.

- <https://downloads.docs.servicenow.com/resource/enus/cad/K900249.PSM>
- <https://downloads.docs.servicenow.com/resource/enus/cad/R900249.PSM>

Procedure

1. On the SAP UI, enter the transaction code SM59 and create a new RFC with the following parameters on the Technical Settings tab:

Table 1. RFC parameters

SAP Parameter	Value
RFC Destination	MID_EVENT_COLLECTOR2
Target Host	Name of the MID Server.
Service No	Listener port on the MID Server
Path Prefix	The URL of the MID Server transform script: <code>/api/mid/em/inbound_event?</code> <code>Transform=TransformEvents_SAPSolman</code>

Figure 1. Technical Settings tab

RFC Destination MID_EVENT_COLLECTOR2

Connection Test 

RFC Destination: MID_EVENT_COLLECTOR2

Connection Type: G HTTP Connection to External Serv Description

Description

Description 1: MID WebService Event Collector Full Event

Description 2:

Description 3:

Administration Technical Settings Logon & Security Special Options

Target System Settings

Target Host: MID SERVER NAME GOES HERE Service No.: 9696

Path Prefix: /api/mid/em/inbound_event?Transform=TransformEvents_SAP_

HTTP Proxy Options

Global Configuration

Proxy Host:

Proxy Service:

Proxy User:

Proxy PW Status: is initial

Proxy Password: *****

2. On the Logon & Security tab, select Basic Authentication and enter your Event Management logon credentials in the User and Password fields.

Figure 2. Logon & Security tab

Administration Technical Settings Logon & Security Special Options

Logon Procedure

Logon with User

☐ Do Not Use a User

☒ Basic Authentication

User: midUser

PW Status: saved

Password: *****

Logon with Ticket

☒ Do Not Send Logon Ticket

☐ Send Logon Ticket Without Target System Reference

☐ Send Assertion Ticket for Dedicated Target System

System ID: Client:

A custom SAP BADI (Business Add-in) named Z_ALRT_REACTION_IMPL is created and stored as a workbench transport request. After installation, this BADI calls the RFC to connect to Event Management.

Display request/task PSMK900100



Request/Task **PSMK900100** Workbench request

Properties Objects Documentation



1 / 7

Short Description	Pr...	Ob...	Object Name	Fu...	Lock/Import Status	L.. IMG Activity
Comment: Object List Inc..	CORR	MERG	PSMK900091 20180911 1159..			
Package	R3TR	DEVC	ZSNOW			
Enhancement Implementati..	R3TR	ENHO	Z_ALERT_REACTION_IMPL			
All Concepts (OTR) of a ..	R3TR	S0TR	ZSNOW			
Table	R3TR	TABL	ZSNOW			
Technical Attributes of ..	LIMU	TABT	ZSNOW			
Table Definition	LIMU	TABD	ZSNOW			