

Configure event collection from Zabbix server

- Release version: Australia
-
- Updated March 12, 2026
-
- ⌚ 2 minutes to read

Configure the Zabbix server connector instance to receiving alerts from the Zabbix server.

Before you begin

Supported versions: from 3.0.0 up to 7.0.0

The Zabbix server connector instance requires a credential that lets the instance access Zabbix server accounts. You can use an existing credential or create a new one.

Role required: evt_mgmt_admin

About this task

This connector has the logPayloadForDebug log parameter enabled, which logs event and metric payloads from the source system. Once debugging is complete, set this parameter to false to prevent overloading the system.

Procedure

1. Navigate to All > Event Management > Integrations > Connector Instances.
2. Click New.
3. On the form, fill in the fields.

Field	Description
Name	Descriptive name for the connector.
Host IP	IP address for the Zabbix server.
Credential	Select the credential with basic authentication that you created for this connector. For more information, see Create Zabbix server credentials.
Schedule (seconds)	Frequency, in seconds, that the system checks for new events from the Zabbix server.

Field	Description
Description	Description for the use of the Zabbix server event collection instance.
Connector Definition	Name of the connector definition. Select Zabbix.
Last error message	Last error message. Automatically updated.
Last run time	Last run time value. Automatically updated.
Last run status	Last run time status. Automatically updated.
MID Servers (MID Server for Connectors section)	Optional. Name of a MID Server. If no MID Server is specified, an available MID Server that has a matching IP range is used. In the MID Servers for Connectors section, specify a MID Server that is up and valid. You can configure several MID Servers. If the first is down, the next MID Server is used. If that MID Server is not available, the next is selected, and so on. MID Servers are sorted according to the order that their details were entered into the MID Server for Connectors section.

4. Right-click the form header and select Save.

The connector instance values are added to the form and the parameters that are relevant to the connector appear.

Connector Instance Values			◀◀ ◀
	≡ Name ▲	≡ Value	
	<u>days_from</u>	2	
	<u>port</u>	80	
	<u>protocol</u>	https	

5. Verify and modify the values, as needed.

In the Connector Instance Values section, the default connector instance values appear.

Table 1. Fields in the Connector Instance Values section

Field	Description
days_from	Number of days for which events must be collected at the first collection cycle. Default value: 2 Note: The maximum number of past events that can be collected is 3,000. The first time that this connector runs, the number of past events is counted in the past from the current date.

Field	Description
port	Port number. Default: 80
protocol	Protocol type. Default: https

6. Right-click the form header and select Save.
7. Click Test Connector to verify the connection between the MID Server and the connector.
8. If the test fails, follow the instructions that are issued by the error to correct the problem and then run another test.

Note:

Use a network tool, such as ping, to verify credential correctness and network connectivity from the MID Server to the Zabbix server.

9. After a successful test, select Active and then click Update.

- **Create Zabbix server credentials**

Create credentials to access Zabbix server.