

Integrate with push connectors

- Release version: Australia
-
- Updated March 12, 2026
-
- ⌚ 3 minutes to read

Integrate with a push connector to connect to an external event source. Push connectors process the collected event messages and transform them to the required event format.

Before you begin

Ensure that the Event Management Connectors (sn_em_connector) plugin is installed.

Role required: evt_mgmt_admin

Note:

If you are upgrading a ServiceNow AI Platform instance from Paris or earlier, you can use legacy listener transform scripts. See Use legacy listener transform scripts for further information.

About this task

The push connectors accept event messages that are generated by external event sources.

Configure a connector to listen to an external event source. Using a custom push connector, send the event messages through either the MID Server or the instance.

Note:

You can use this generic JSON target URL to collect

events: `https://<<INSTANCE>>/api/sn_em_connector/em/inbound_event?`

`source=genericJson` . This URL can be used as-is and requires that an event rule be configured.

Procedure

1. Navigate to All > Event Management > Integrations > Push Connectors.
2. Click New or click the push connector that you want to modify, for example, AWS or Azure.
3. On the form, fill in the fields.

Field	Description
-------	-------------

Field	Description
Name	Unique name for this push connector for easy identification.
Description	Enter a description for the use of the push connector.
Header name	Specify the name of the header that you want the value for, such as Set-Header.
Header value	The value of the header name that you want the value for, such as Set-Header.
Type	Select to send events either Instance or MID. In each case, use the URL of the selected type. See the description of the URL parameter value field.
Active	Select to enable pulling events from this external event source.
Order	Order in which an event rule is evaluated when multiple rules are defined for the same type of event. Event rules are evaluated in ascending order.
URL parameter value	- Send events to the instance. Use the URL in this format for all connectors: <code>https://<<INSTANCE>>/api/sn_em_connector/em/inbound_event?source={URL_parameter_value}</code> - Send events through the MID Server. Use the URL in the format: <code>http://{MID_Server_IP}:{MID_Web_Server_Port}/api/mid/em/inbound_event?Transform={Transform_script}</code> Note: Sending events to the MID Server requires the prior configuration of the MID WebService Event Listener extension.

4. In the Script section:

- If the value selected for the Type field is MID, the Transform script field appears. In this field, specify or search for the name of the MID script include that accepts event messages that the required external event source generates and that the script parses into the required event format. Use this naming convention for the script: `TransformEvents_<your source>`
- If the value selected for the Type field is Instance, the Script editor appears. In the Script editor, enter the customized script that accepts event messages that the required external event source generates and that the script parses into the required event format.

This example shows the fields that have been transformed, being added to an event form.

```

(function process(/*RESTAPIRequest*/ request, body) {
    /*Function that receives a JSON object, adding all its fields to t
    function updateAdditionalInfo(event, field,jsonObject,additionalIn
    for (var key in jsonObject) {
        var newKey = key;
        if (field != "") {
            newKey = field + '_' + key;
        }

        // You can do some transformation here and set fie
        //if(key == "MySource")
        //    event.source = jsonObject[key];
        additionalInfo[newKey] = jsonObject[key];
    }
}

try
{
    gs.info("TransformEvents_generic received body:" + body);
    var jsonObject = JSON.parse(body);
    var event = new GlideRecord('em_event');
    event.source = "GenericJson"; //TODO: Need to define
    event.event_class = "GenericJsonClass"; //TODO: Need to define
    event.severity = "5";

    var additionalInfo = {};
    updateAdditionalInfo(event, "",jsonObject,additionalInfo);
    /*Iterates over Additional information JSON object and add
    var notDone = true;
    while (notDone) {
        notDone = false;
        for (var key in additionalInfo) {
            if (Object.prototype.toString.call(additionalInfo[key]) ==
                notDone = true;
            updateAdditionalInfo(event, key,additionalInfo[key],ac
                additionalInfo[key] = "";
        }
    }

    gs.info("TransformEvents_generic generated additional info
    event.additional_info = JSON.stringify(additionalInfo);
    event.insert();
}
catch(er){
    gs.error(er);
    status=500;
    return er;
}

```

```
    return "success";  
  })(request, body);
```

- **Use legacy listener transform scripts**

Use legacy listener transform scripts when upgrading a ServiceNow AI Platform instance from Paris or earlier. These scripts can be run as part of existing integrated systems, or in unison with Event Management push connectors.

- **Integrate AWS platform as a data source**

Integrate Amazon Web Services (AWS) with Event Management. To add AWS platform as a data source, configuration is required in the AWS platform.

- **Integrate Azure Monitor as an authenticated data source**

Integrate Microsoft Azure with Event Management by adding the Azure Monitor as an authenticated data source.

- **Event collection from Microsoft Azure Monitor**

The MID WebServer Event Collector enables you to collect JSON formatted event messages sent from the Microsoft Azure portal.

- **Event collection from BMC TrueSight and BMC TrueSight_v2**

The MID WebService Event Collector enables you to collect JSON formatted event messages sent from BMC TrueSight Operations Management (TrueSight), previously known as BMC ProactiveNet Performance Management (BPPM), utilizing event stream notification capabilities.

- **Metric collection from OpenTelemetry (Otel) metrics**

The MID WebService metric Collector enables you to collect JSON and protobuf formatted metrics sent from OpenTelemetry (Otel).

- **Integrate New Relic platform events**

Integrate New Relic with Event Management by adding a standard webhook in the New Relic old and new consoles.

- **Integrate Catchpoint events**

Integrate Catchpoint with Event Management by adding an alert webhook in the Catchpoint platform.

- **Integrate Google Cloud Platform (GCP) events**

Integrate Google Cloud Platform (GCP) with Event Management by adding a standard webhook in the GCP console.

- **Event collection from Google Cloud Platform (GCP)**

The MID WebService Event Collector enables you to collect JSON formatted event messages sent from Google Cloud Platform (GCP).

- **Integrate Grafana events**

Integrate Grafana with Event Management by adding Grafana as an authenticated data source.

- **Integrate Honeycomb events**

Integrate Honeycomb with Event Management by creating a webhook and configuring it as a trigger in the Honeycomb platform.

- **Integrate Instana events**

Integrate Instana with Event Management by adding Instana as an authenticated data source.

- **Integrate ServiceNow Cloud Observability Events**

Integrate ServiceNow Cloud Observability with Event Management by adding a standard webhook in the ServiceNow Cloud Observability platform. Download the Event Management Connector plugin from the ServiceNow Store so you can integrate with ServiceNow Cloud Observability.

- **Integrate Logicmonitor events**

Integrate Logicmonitor with Event Management to send events into ServiceNow by adding a webhook using Basic Authentication, it will also be available with bi-directional functionality.

- **Event collection from Logicmonitor**

The MID WebService Event Collector enables you to collect JSON formatted event messages from the Logicmonitor.

- **Integrate Oracle Cloud Infrastructure alarms**

Integrate Oracle Cloud Infrastructure (OCI) alarms with Event Management to send events into ServiceNow by adding a https subscription using Basic Authentication.

- **Integrate Prometheus events**

Integrate Prometheus with Event Management by adding a standard webhook in Prometheus's Alert Manager.

- **Integrate Sentry events**

Integrate Sentry with Event Management by adding a standard webhook in the Sentry platform.

- **Integrate Scout APM events**

Enable the collection of events from Scout APM by authenticating Scout APM as a data source to integrate it with Event Management.

- **Integrate Sumo Logic events**

Use the Sumo Logic push connector to integrate Sumo Logic with Event Management by adding a standard webhook in the Sumo Logic platform.

- **Integrate Panopta as a data source**

Integrate the Panopta cloud-based monitoring solution with Event Management. To add Panopta as a data source, configuration is required in Panopta.

- **Integrate Event Integration (EIF) format event connector**

Use the push connector that allows events to be forwarded from products, generally from IBM, that support the Event Integration (EIF) format to a MID Server.