

Integrate Event Integration (EIF) format event connector

- Release version: Australia
-
- Updated March 12, 2026
-
- ⌚ 2 minutes to read

Use the push connector that allows events to be forwarded from products, generally from IBM, that support the Event Integration (EIF) format to a MID Server.

Before you begin

Ensure that the Event Management Connectors (sn_em_connector) plugin is installed on the ServiceNow AI Platform instance.

Ensure the MID Server is assigned with `EventManagement` or `ALL` applications.

Role required: `evt_mgmt_integration`

About this task

Configure the Event Management environment for the collection of events from products that support the EIF format to a MID Server.

Procedure

1. Navigate to `All > Event Management > Integrations > EIF` listener context.
2. Click New.
3. Create a new EIF listener context by completing the EIF listener context form:
 - a. On the form, fill in the fields.

Table 1. EIF listener context form

Field	Description
Name	Unique name for the EIF listener context.
Short Description	Short description of the MID Server extension execution context.

Field	Description
Port	Port for the EIF listener to receive EIF events. The default value is 9998. However, if the port is already in use, you can use any other free port instead.
Status	The status of the EIF listener. This field is blank until the listener is run. After the listener has run, the value is automatically populated to one of the following statuses: - Started: The listener is running. - Stopped: The listener is not running. - Offline: The MID Server is down. - Error: The listener failed with an error.
Execute on	The MID Server location for running the listener.
MID Server	The name of the designated MID Server when you select Specific MID Server in the Execute on field.
Executing on	The name of the MID Server on which the extension is running. This field is automatically populated with the name of the MID Server even if it's down. If you stop the extension, this field is empty.

b. On the form, you can select the related links on the EIF listener context form.

Table 2. Commands available on the EIF listener context form

Related Link	Description
Start	Select this option if the listener is not running. The listener is started on the configured MID Server and port number.
Stop	Select this option to stop the running listener on the configured MID Server.
Restart	Select this option to stop then start the listener on the configured MID Server and port number.

Related Link	Description
Update Parameters	Select this option if you want to make changes to the listener configuration of the current running listener. If the parameters are valid, the listener disconnects and reconnects with new parameters.
Test Parameters	Select this option to test if the port is a valid number.

4. When you're finished, right-click the form header and select Save.
5. Click Update.
6. If you want to check the incoming EIF traffic, complete the following steps:
 - a. Navigate to MID Server > Servers.
 - b. Select the MID Server the EIF extension is running.
 - c. Under the Configuration Parameters tab, add the mid.log.level properties.

What to do next

If the MID Server fails to start, you can review the MID Server log errors.

- **EIF events warning severity**

If the EIF event payload has a warning severity, it will be mapped differently in the ServiceNow instance.