

Set additional info fields to match CI attribute format

- Release version: Australia
-
- Updated May 5, 2026
-
- ⌚ 1 minute to read

Set additional info fields in alerts to match the field and value format of CI attributes in CI records. This ensures accurate alert-to-CI binding, improving alert tracking and reducing manual effort.

Before you begin

Ensure that you are on the Enrich Alerts page and the Improve configuration item (CI) identification toggle switch is enabled.

Role required: evt_mgmt_admin, evt_team_operator, or srm_responder

About this task

The system attempts to match the Additional Info fields of the alert with attributes in the CI table. If exactly one matching CI is found, the alert is linked to that CI. For CI identification to be successful, add new fields or ensure that your alert has additional info fields corresponding to column name for CI attributes. For example, use column name ip_address instead of the column label IP Address. Each matching key name must have matching values. If there are matching fields in your alert that you don't wish to use for binding, copy them to another field then clear the original field.

Procedure

1. Under Improve configuration item (CI) identification, in the Select which CI class you'd like to identify field, select the CI class.

Alert Automation Enrich alerts CI Class: Windo... +

Enrich alerts

[Save automation](#)

Change alert values

Change values of a field to a format that is easier to read, filter and group. [Learn more.](#)

Improve configuration item (CI) identification

Identify CIs other than a host for better alert grouping, team assignment, and service health. [Learn more.](#)

This action will override the default behavior of using the Node field for CI identification.

- Select which CI class you'd like to identify:
 - ☐ Identify CI running on a specific host
 - ☒ The alert's node field will be automatically cleared

Windows Server [View items](#)
- Match your alert's additional info fields to your desired CI's attributes. Each additional info field with the same name of a CI attribute should have matching values, and all the matching attributes should uniquely identify a single CI. Follow these steps:
 - View the items for the CI class you want to identify.
 - Select a CI and open its record page.
 - Back on this page (enrich automation), use the actions 'extract', 'copy and compose,' and 'change alert values' to set at least one additional info field to match the CI attribute's name and value.
- (Optional) Test the CI identification on sample events.

[Test CI identification](#)

And finally...

Example source events [Test CI identification](#)

Preview 2 of 3 recent events

Standard events fields

Time of event	2025-07-10 03:22:54
Description	CRUPRGWMIDCAV15:Free swap spac...
Severity	Critical
Metric Name	Free swap space in %
Node	cruprgwmidcav15
Resource	
Source	Zabbix
Message key	108743
Type	High swap space usage

Additional info

u_eventid	31385766
u_event_objectid	108743
u_item_id	278826
u_item_key_	system.swap.pfree
u_event_name	CRUPRGWMIDCAV15
u_event_clock	1752141305
u_trigger_triggerid	108743
u_trigger_express...	max(/CRUPRGWMIDCAV15/system.swap...
u_item_name	Free swap space in %
u_item_interfaceid	0
u_trigger_descript...	High swap space usage
u_event_source	0
u_hostid	12068

2. Select View items next to the Select which CI class you'd like to identify field to open the list of CIs of the selected CI class.

Alert Automation Enrich alerts CI Class: Windo... +

CI Class: Windows Server 295

Last refreshed just now.

Name	Operating System	OS Version
cruprgwmidalt25	Windows 2019 Standard	10.0.17763
cruprgwmidaltv45	Windows 2019 Standard	
cruprgwmidaltv70	Windows 2019 Standard	10.0.17763
cruprgwmidaltv07	Windows 2019 Standard	10.0.17763
cruprgwmidaltv42	Windows 2019 Standard	10.0.17763
cruprgwmidaltv38	Windows 2019 Standard	10.0.17763
cruprgwmidaltv97	Windows 2019 Standard	10.0.17763
cruprgwmidaltv48	Windows 2019 Standard	10.0.17763
cruprgwmidaltv99	Windows 2019 Standard	10.0.17763
cruprgwmidaltv12	Windows 2019 Standard	10.0.17763
cruprgwmidaltv15	Windows 2019 Standard	10.0.17763
cruprgwmidaltv74	Windows 2019 Standard	
cruprgwmidaltv27	Windows 2019 Standard	10.0.17763
cruprgwmidaltv71	Windows 2019 Standard	10.0.17763
cruprgwmidaltv86	Windows 2019 Standard	10.0.17763
cruprgwmidaltv36	Windows 2019 Standard	10.0.17763

Showing 61-80 of 295

3. Select a CI name to open its details or record page.

At least one field and its corresponding value from the CI details page must appear in the Additional info field of the alert.

Alert Automation Enrich alerts cruprgwmidcav15 +

cruprgwmidcav15

Class: Windows Server | Discovery source: ServiceNow | Updated: 2025-02-16 07:40:43

[Open dependency view](#) [Save](#) [...](#)

Overview **Details** Reliability Metrics Related records

Key Attributes

Name: cruprgwmidcav15

Location:

Description:

Created: 2025-01-21 04:41:58 | Created by: miduser

Updated: 2025-02-16 07:40:43 | Updated by: miduser

Support group: | Supported by:

Managed by: | Managed By Group:

Environment:

Activity

miduser

Field changes • 2025-01-21 04:41:58

Asset: 6e518ea0871f5690207e99b83cb352c

Attestation Status: Not Yet Reviewed

Attested: false

CD: false

[Show more](#)

Service Relationships

This CI is not associated with any application services

4. In the Enrich Alerts page, use Extract fields, Copy or Compose fields, and Change alert values to set at least one Additional info field in your alert to precisely match the field and value format of the CI attributes in the CI record.

Example: Suppose the CI record page has the name field with the value CRUPRGWMIDCAV15. To include these fields and their values in the Additional info field of the alert, set the fields as shown in the image.

Map the ``${u_host_host}`` field to a new field called name. This field is added to the Additional info and is used for CI identification during the binding stage.

Enrich alerts

Copy or compose fields
Copy or combine fields and text to populate an alert field. [Learn more.](#)

Composition: `${u_host_host}` → Output to field: `name` ☐ Set as a tag [Delete](#)

Change alert values
Change values of a field to a format that is easier to read, filter and group. [Learn more.](#)

Improve configuration item (CI) identification
Identify CIs other than a host for better alert grouping, team assignment, and service health. [Learn more.](#)

This action will override the default behavior of using the Node field for CI identification.

1. Select which CI class you'd like to identify:

- ☐ Identify CI running on a specific host
- ☒ The alert's node field will be automatically cleared

`Windows Server` [View items](#)

2. Match your alert's additional info fields to your desired CI's attributes. Each additional info field with the same name of a CI attribute should have matching values, and all the matching attributes should uniquely identify a single CI. Follow these steps:

- View the items for the CI class you want to identify.
- Select a CI and open its record page.

Example source events [Test CI identification](#)

Preview 2 of 3 recent events

Type	High swap space usage
Additional info	
u_eventid	31385766
u_event_objectid	108743
u_item_itemid	278826
u_item_key	system.swap.pfree
u_event_name	CRUPRGWMIDCAV15
u_event_clock	1752141305
u_trigger_triggerid	108743
u_trigger_express...	max(/CRUPRGWMIDCAV15/system.swap...
u_item_name	Free swap space in %
u_item_interfaceid	0
u_trigger_descript...	High swap space usage
u_event_source	0
u_hostid	12068
u_host_host	CRUPRGWMIDCAV15
t_Location	Crucible
u_trigger_value	1
u_item_description	The free space of the swap volume/file ex...
u_event_object	0
u_item_templateid	42486
u_item_lastvalue	16.317971
u_event_acknowl...	0
u_event_value	1