

Dynatrace advanced settings fields

- Release version: Australia
-
- Updated March 12, 2026
-
- ⌚ 1 minute to read

Populate the pull connector advanced settings fields to optimize event retrieval and synchronization based on specific requirements such as connection preferences, event frequency, and time zone settings.

Table 1. Dynatrace advanced settings fields

Field	Description
Base API path	Root URL or endpoint used to connect to the Dynatrace Metrics API. All API requests are made relative to this base path.
Initial sync in mins	Time, in minutes, that the system takes to complete the first synchronization of data with the Dynatrace Metrics API. For example, if the value is 15, the connector fetches metrics from the past 15 minutes. Default: 15
Max metrics per query	Maximum number of metrics that can be requested in a single query to the Dynatrace Metrics API. The value cannot exceed 32, the maximum limit allowed by Dynatrace. Requests exceeding this limit must be split into multiple queries. Default: 32
Page Size	Number of records returned in a single response when querying the Dynatrace Metrics API. If the total results exceed this number, multiple pages are returned. Default: 500
Port	Port number used for connecting to the Dynatrace server.

Field	Description
Request per minute	Maximum number of API requests that can be sent to the Dynatrace Metrics API within one minute. Exceeding this limit may result in throttling or temporary blocking of requests. Note: Relevant only when you enable Throttle API calls. Default: 1000
Throttle API calls	Limits the rate of API requests to the Dynatrace Metrics API, preventing overload, request failures, or temporary blocking. Enable this option to automatically limit the rate of API requests, preventing overloading the Dynatrace Metrics API and avoiding request failures. Default: false
Protocol	Communication protocol used for retrieving events from Dynatrace server. Default: https
Debugging	• Debug: Provides detailed logs for troubleshooting. • Log payload: Displays raw log data. Use only for debugging, as it can quickly fill the MID Server logs.

To return to the procedure, see [Configure Dynatrace metric pull connector](#).