

Configure event collection from Logicmonitor

- Release version: Australia
-
- Updated March 12, 2026
-
- ⌚ 1 minute to read

The Logicmonitor pull connector sends information from Event Management to Logicmonitor. It sends responses received from a Push connector in a bi-directional environment to Logicmonitor.

Before you begin

Role required: evt_mgmt_admin

About this task

Starting from the Xanadu release, the OOTB (Out-Of-The-Box) rules provided with the connector, which you have not previously used (i.e., neither activated, deactivated, nor modified), will now have theApply additional matching rulescheck box set to true. Previously, this check box was disabled. This change allows you to execute more event rules or automation using the same filter conditions for the connector.

Note:

This feature applies only to active event rules.

Procedure

1. Navigate toAll > Event Management > Event Connectors (Pull) > Connector Instances.
2. ClickNew.
TheConnector Instance New Recordpage appears.
3. Enter values in the required fields, which are indicated by a red asterisk.

Field	Description
Name	Descriptive name for the connector.
Connector definition	Search for and selectLogic Monitor.
Credential	SelectBasic Authfor basic authentication. Provide access_id and access_key from Logicmonitor's token based API

Field	Description
	authentication in the credentials as the basic authentication username and password.
Host IP	The Logicmonitor IP address.

When adding bi-directional functionality for a Push connector, the Connector Instance name must match the Source Instance field of the event generated by that source.

		Time of event ▼	Source	Description	Node	Source instance	Type	Resource	Message key	Updated	State
☐		2021-07-27 10:38:54	logicmonitor	LMD319350 ***Cleared***error - 838066286...	8380662863455396356	logicmonitor	alert	Collector Thread: CPU-dns	LMD319350	2021-07-27 10:38:55	Ready
☐		2021-07-27 10:37:54	logicmonitor	LMD319350 error - 8380662863455396356 Co...	8380662863455396356	logicmonitor	alert	Collector Thread: CPU-dns	LMD319350	2021-07-27 10:38:02	Processed

The source of events is logicmonitor so you should create an instance with the name logicmonitor.

All > Active = true

		Name	Active	Event collection last run time	Connector definition	Last event collection signature ▲	Last event collection status
		logicmonitor	true	2021-07-27 11:21:41	Logic Monitor		Success

Note:

The Update queue business rule in the Alert table identifies each manual update of the alert and updates the connector queue accordingly. By default, changes to all alert fields are tracked.

4. Select the Active check box and click Save.

The LogicMonitor pull connector does not retrieve Events or populate the Events [em_event] table.