


Capacitors



Max. Operating Voltage

Code	Max. Voltage
1H	50V
2A	100V
2T	150V
2D	200V
2E	250V
2G	400V
2J	630V

Capacitance Conversion Values

Microfarads (μF)	Nanofarads (nF)	Picofarads (pF)
0.000001 μF	0.001 nF	1 pF
0.00001 μF	0.01 nF	10 pF
0.0001 μF	0.1 nF	100 pF
0.001 μF	1 nF	1,000 pF
0.01 μF	10 nF	10,000 pF
0.1 μF	100 nF	100,000 pF
1 μF	1,000 nF	1,000,000 pF
10 μF	10,000 nF	10,000,000 pF
100 μF	100,000 nF	100,000,000 pF

Tolerance

Code	Percentage
B	± 0.1 pF
C	±0.25 pF
D	±0.5 pF
F	±1%
G	±2%
H	±3%
J	±5%
K	±10%
M	±20%
Z	+80%, -20%

ערך: אבי יומטוביאן yomtov7@gmail.com


INDUCTOR COLOR GUIDE

Result Is In μH

4-BAND-CODE → → 270μH ± 5%

COLOR	1st BAND	2nd BAND	MULTIPLIER	TOLERANCE
BLACK	0	0	1	± 20%
BROWN	1	1	10	Military ± 1%
RED	2	2	100	Military ± 2%
ORANGE	3	3	1,000	Military ± 3%
YELLOW	4	4	10,000	Military ± 4%
GREEN	5	5		
BLUE	6	6		
VIOLET	7	7		
GREY	8	8		
WHITE	9	9		
NONE				Military ± 20%
GOLD			0.1 / Mil. Dec. Pt.	Both ± 5%
SILVER			0.01	Both ± 10%

Military Identifier



6.8μH ± 10%
MILITARY CODE