CYBERSRS

Secure Campus Wi-Fi Management System

Software Requirements Specification

DRAFT — human review required

Version 1 • 2026-10-29T13:36:54.004529+00:00

AI-generated advisory document. Review by a qualified professional is required.

Automated checks do not prove completeness or semantic correctness. SDLC suitability scores are rule-based points, not probabilities.

Content SHA-256: 9c1bde3733f6e04eaacaee1c9fadb487db780fb35bd80c7e01dbe14f31e6fb42

Contents

1. Introduction 3

2. Functional requirements 4

3. Non-functional requirements 6

4. Security, privacy and compliance 7

5. Data requirements 7

6. Network and interfaces 7

7. Compliance and policy applicability matrix 7

8. Architecture 7

9. Threats 9

10. Risks 9

11. User stories and use cases 9

12. Verification and acceptance 9

13. Glossary 11

14. SDLC recommendation and workflow 12

SDLC rankings and decision evidence 15

Evidence register 16

Source references 17

Validation findings 18

Human review history 18

AI drafting record 18

Requirements traceability matrix 19

1. Introduction

Original project description

Design a secure campus Wi-Fi management system for a university that provides wireless access to students, faculty, staff, and guests across academic buildings, hostels, laboratories, and administrative offices. The system should use centralized authentication, role-based access control, separate guest access from internal university resources, monitor active wireless sessions, detect repeated authentication failures and unauthorized access attempts, and generate security alerts. Network administrators should be able to configure wireless access policies, review connected devices, revoke access, and inspect audit logs. The solution should support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

Summary: This specification records the project purpose, stakeholder constraints and unresolved decisions stated in the source evidence below.

Items

Stakeholder source statement E-001

Detail: Design a secure campus Wi-Fi management system for a university that provides wireless access to students, faculty, staff, and guests across academic buildings, hostels, laboratories, and administrative offices.

Status: confirmed

Evidence ids: E-001

Stakeholder source statement E-002

Detail: The system should use centralized authentication, role-based access control, separate guest access from internal university resources, monitor active wireless sessions, detect repeated authentication failures and unauthorized access attempts, and generate security alerts.

Status: confirmed

Evidence ids: E-002

Stakeholder source statement E-003

Detail: Network administrators should be able to configure wireless access policies, review connected devices, revoke access, and inspect audit logs.

Status: confirmed

Evidence ids: E-003

Stakeholder source statement E-004

Detail: The solution should support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

Status: confirmed

Evidence ids: E-004

Open issues: How will device-level policies be enforced on personal devices?; What specific authentication protocols (e.g., 802.1X) are required for internal access?; How will repeated

authentication failures trigger alerts or automated actions?; What is the retention period and access control for audit logs?

2. Functional requirements

Applicability reason: Source-backed obligations; unspecified decisions remain open.

Requirements

FR-001 - provide wireless access to students, faculty, staff, and guests across academic buildings, hostels, laboratories, and administrative offices.

Statement: The system shall provide wireless access to students, faculty, staff, and guests across academic buildings, hostels, laboratories, and administrative offices.

Rationale: Implements stakeholder source E-001.

Priority: must

Dimensions: business

Basis: explicit

Evidence ids: E-001

Acceptance criteria

Given: A user in an academic building attempts to connect to the campus Wi-Fi

When: The user selects the university Wi-Fi network and enters credentials

Then: The system establishes a wireless connection for the user

Method: test

Observable evidence: Test capture of successful device association and IP assignment

FR-002 - use centralized authentication, role-based access control, separate guest access from internal university resources, monitor active wireless sessions, detect repeated authentication failures and unauthorized access attempts, and generate security alerts.

Statement: The system shall use centralized authentication, role-based access control, separate guest access from internal university resources, monitor active wireless sessions, detect repeated authentication failures and unauthorized access attempts, and generate security alerts.

Rationale: Implements stakeholder source E-002.

Priority: should

Dimensions: business

Basis: explicit

Evidence ids: E-002

Acceptance criteria

Given: A user with invalid credentials repeatedly attempts to authenticate

When: The system processes the authentication requests

Then: The system detects repeated failure and generates a security alert

Method: test

Observable evidence: Test capture of generated security alert in real-time

Given: A device attempts to access internal university resources without proper authorization

When: The system evaluates the request against role-based policies

Then: The system blocks unauthorized access.

Method: test

Observable evidence: Test capture of blocked session and before/after state of device connectivity

FR-003 - Network administrators should be able to configure wireless access policies, review connected devices, revoke access, and inspect audit logs.

Statement: Network administrators should be able to configure wireless access policies, review connected devices, revoke access, and inspect audit logs.

Rationale: Implements stakeholder source E-003.

Priority: should

Dimensions: business

Basis: explicit

Evidence ids: E-003

Acceptance criteria

Given: An administrator accesses the management interface

When: The administrator configures a new access policy for guest users

Then: The system applies the policy and updates device access rules

Method: test

Observable evidence: Test capture of policy configuration and applied rule state

Given: An administrator initiates a revocation request for a connected device

When: The system processes the revocation command

Then: The system processes the revocation command

Method: test

Observable evidence: Test capture of permission state

Given: An administrator requests audit log inspection

When: The administrator accesses the logs interface

Then: The system returns a list of recent access events with timestamps and user identifiers

Method: inspection

Observable evidence: Test capture of returned audit log entries

3. Non-functional requirements

Applicability reason: Source-backed obligations; unspecified decisions remain open.

Requirements

NFR-001 - The solution shall support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

Statement: The solution shall support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

Rationale: Implements stakeholder source E-004.

Priority: should

Dimensions: availability

Basis: explicit

Evidence ids: E-004

Acceptance criteria

Given: A university employee uses a personally owned device that has been pre-approved by the IT department

When: The device connects to the campus wireless network

Then: The system shall authenticate the device using university-managed credentials and enforce security policies consistent with approved device configurations

Method: test

Observable evidence: Test capture of device authentication response and policy enforcement state

Given: A personal device is not pre-approved by the IT department

When: The device attempts to connect to the campus wireless network

Then: The device is denied access to the campus wireless network

Method: test

Observable evidence: Test capture of the resulting state

Unresolved decisions: Definition of 'approved personal devices' including hardware, OS versions, and security posture thresholds; Thresholds for scalability under concurrent device load across campus locations; Mechanism for real-time monitoring of device health and compliance status during operation

4. Security, privacy and compliance

Applicability reason: Existing canonical requirements, where applicable, are linked below; this section adds no separate obligation. Unresolved stakeholder decisions remain open.

Related requirement ids: FR-002; FR-003

5. Data requirements

Applicability reason: Existing canonical requirements, where applicable, are linked below; this section adds no separate obligation. Unresolved stakeholder decisions remain open.

Related requirement ids: FR-003; NFR-001

6. Network and interfaces

Applicability reason: Existing canonical requirements, where applicable, are linked below; this section adds no separate obligation. Unresolved stakeholder decisions remain open.

Related requirement ids: FR-001; FR-002; FR-003

7. Compliance and policy applicability matrix

Open decisions: How will device-level policies be enforced on personal devices?; What specific authentication protocols (e.g., 802.1X) are required for internal access?; How will repeated authentication failures trigger alerts or automated actions?; What is the retention period and access control for audit logs?

8. Architecture

Summary: Proposed logical components and interactions mapped to canonical source obligations.

Items

Wireless Access Gateway

Detail: Proposed logical owner for FR-001, NFR-001.

Status: proposed

Evidence ids: E-001; E-004

Requirement ids: FR-001; NFR-001

Component name: Wireless Access Gateway

Responsibility: The system shall provide wireless access to students, faculty, staff, and guests across academic buildings, hostels, laboratories, and administrative offices. The solution shall support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

Centralized Authentication Engine

Detail: Proposed logical owner for FR-002.

Status: proposed

Evidence ids: E-002

Requirement ids: FR-002

Component name: Centralized Authentication Engine

Responsibility: The system shall use centralized authentication, role-based access control, separate guest access from internal university resources, monitor active wireless sessions, detect repeated authentication failures and unauthorized access attempts, and generate security alerts.

Policy and Device Management Interface

Detail: Proposed logical owner for FR-003, NFR-001.

Status: proposed

Evidence ids: E-003; E-004

Requirement ids: FR-003; NFR-001

Component name: Policy and Device Management Interface

Responsibility: Network administrators should be able to configure wireless access policies, review connected devices, revoke access, and inspect audit logs. The solution shall support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

Data flows

Proposed source-defined interaction

Detail: Proposed directed path for NFR-001.

Status: proposed

Evidence ids: E-004

Requirement ids: NFR-001

From component: Wireless Access Gateway

To component: Policy and Device Management Interface

Data or action: The solution shall support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

Proposed source-defined interaction

Detail: Proposed directed path for NFR-001.

Status: proposed

Evidence ids: E-004

Requirement ids: NFR-001

From component: Policy and Device Management Interface

To component: Wireless Access Gateway

Data or action: The solution shall support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

Trust boundaries

Proposed source-defined trust boundary

Detail: Proposed logical trust-domain crossing for NFR-001.

Status: proposed

Evidence ids: E-004

Requirement ids: NFR-001

Untrusted component: Wireless Access Gateway

Trusted component: Policy and Device Management Interface

Enforcement: The solution shall support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

9. Threats

Assumptions

1. These are defensive planning hypotheses, not observed incidents or approved extra controls. Unrecognized threats and actual implementation effectiveness require human review.

10. Risks

11. User stories and use cases

12. Verification and acceptance

Tests

Id: TEST-001

Requirement ids: FR-001

Procedure

1. Given: A user in an academic building attempts to connect to the campus Wi-Fi
2. When: The user selects the university Wi-Fi network and enters credentials

Expected result: Expected: The system establishes a wireless connection for the user

Evidence to record: Evidence: Test capture of successful device association and IP assignment

Test type: positive

Id: TEST-002

Requirement ids: FR-002

Procedure

1. Given: A user with invalid credentials repeatedly attempts to authenticate
2. When: The system processes the authentication requests

Expected result: Expected: The system detects repeated failure and generates a security alert

Evidence to record: Evidence: Test capture of generated security alert in real-time

Test type: positive

Id: TEST-003

Requirement ids: FR-002

Procedure

1. Given: A device attempts to access internal university resources without proper authorization
2. When: The system evaluates the request against role-based policies

Expected result: Expected: The system blocks unauthorized access.

Evidence to record: Evidence: Test capture of blocked session and before/after state of device connectivity

Test type: negative

Id: TEST-004

Requirement ids: FR-003

Procedure

1. Given: An administrator accesses the management interface
2. When: The administrator configures a new access policy for guest users

Expected result: Expected: The system applies the policy and updates device access rules

Evidence to record: Evidence: Test capture of policy configuration and applied rule state

Test type: positive

Id: TEST-005

Requirement ids: FR-003

Procedure

1. Given: An administrator initiates a revocation request for a connected device
2. When: The system processes the revocation command

Expected result: Expected: The system processes the revocation command

Evidence to record: Evidence: Test capture of permission state

Test type: negative

Id: TEST-006

Requirement ids: FR-003

Procedure

1. Given: An administrator requests audit log inspection

2. When: The administrator accesses the logs interface

Expected result: Expected: The system returns a list of recent access events with timestamps and user identifiers

Evidence to record: Evidence: Test capture of returned audit log entries

Test type: inspection

Id: TEST-007

Requirement ids: NFR-001

Procedure

1. Given: A university employee uses a personally owned device that has been pre-approved by the IT department
2. When: The device connects to the campus wireless network

Expected result: Expected: The system shall authenticate the device using university-managed credentials and enforce security policies consistent with approved device configurations

Evidence to record: Evidence: Test capture of device authentication response and policy enforcement state

Test type: positive

Id: TEST-008

Requirement ids: NFR-001

Procedure

1. Given: A personal device is not pre-approved by the IT department
2. When: The device attempts to connect to the campus wireless network

Expected result: Expected: The device is denied access to the campus wireless network

Evidence to record: Evidence: Test capture of the resulting state

Test type: negative

Limitations: These verification plans have not been executed; their acceptance outcomes require testing.

13. Glossary

Summary: Source-present terminology; definitions introduce no additional product obligation.

Items

Access control

Detail: Rules and enforcement governing which principals may perform actions on resources.

Status: proposed

Evidence ids: E-002

Policy

Detail: A rule or decision governing permitted actions; its project-specific meaning remains defined by the source requirements.

Status: proposed

Evidence ids: E-003

Audit record

Detail: A stored record of an event. Required event scope and retention are determined by the linked source, not this definition.

Status: proposed

Evidence ids: E-003

Log

Detail: A collection of event records. This term does not itself require additional logging fields, events or access permissions.

Status: proposed

Evidence ids: E-003

14. SDLC recommendation and workflow

Selected model: Agile

Justification: The selection of Agile as the required model is based on a uniform score of 40 across all candidates, with no differentiating input evidence provided to favor one methodology over another. Given the absence of explicit factors such as budget, delivery timelines, failure consequences, feedback mechanisms, legacy systems, regulation, schedule constraints, stability needs, uncertainty levels, or verification requirements, no candidate model can be objectively ranked for suitability. The equal scores indicate a lack of evidence to support any specific lifecycle model. As a result, Agile is provisionally selected due to its iterative nature and alignment with dynamic security and access control requirements—particularly in environments where rapid feedback and adaptation are needed. However, this decision remains provisional pending resolution of the unknown factors listed. Without clear input on these factors, no model can be definitively justified beyond equal suitability. The existing requirements emphasize real-time monitoring, role-based access, policy configuration, and audit log inspection—all of which benefit from iterative development and continuous feedback loops inherent in Agile. Nevertheless, without evidence to support or exclude any model, the selection remains unvalidated and subject to reevaluation if new data becomes available.

Tradeoffs

1. Recurring delivery requires stakeholder review and backlog refinement; a cycle does not guarantee completeness or remove unresolved decisions.

Phases

Name: Requirements and verification planning

Phase type: planning

Activities

1. Review and baseline the source-defined work group: FR-001: The system shall provide wireless access to students, faculty, staff, and guests across academic buildings, hostels, laboratories, and administrative offices.; FR-002: The system shall use centralized authentication, role-based access control, separate guest access from internal university resources, monitor active wireless sessions, detect repeated authentication failures and unauthorized access attempts, and generate security alerts.; FR-003: Network administrators should be able to configure wireless access policies, review connected devices, revoke access, and inspect audit logs.; NFR-001: The solution shall support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.
2. Create the unit, integration, system and acceptance test plan before implementation; retain each authored acceptance criterion.

Roles: Proposed project owner; Proposed development lead; Proposed verification reviewer

Deliverables

1. Versioned requirements baseline
2. Unit, integration, system and acceptance test plan
3. Unresolved-decision record

Entry criteria

1. Authoritative inputs and canonical requirements are available for review.

Exit criteria

1. A human reviewer has recorded the baseline decision and disposition of unresolved scope.

Security checks

1. Review design and test evidence for violations of source-defined permissions and exclusions.

Human approval: Pending human decision by Proposed project owner on this phase's deliverables and unresolved decisions; no approval is recorded by generation.

Requirement ids: FR-001; FR-002; FR-003; NFR-001

Name: Agile delivery cycle

Phase type: iteration

Activities

1. Review and prioritize the backlog for the next iteration without changing source-defined scope.
2. Implement the source-defined work group: FR-001: The system shall provide wireless access to students, faculty, staff, and guests across academic buildings, hostels, laboratories, and administrative offices.; FR-002: The system shall use centralized authentication, role-based access control, separate guest access from internal university resources, monitor active wireless sessions, detect repeated authentication failures and unauthorized access attempts, and generate security alerts.; FR-003: Network administrators should be able to configure wireless access policies, review connected devices, revoke access, and inspect audit logs.; NFR-001: The solution shall support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.
3. In an authorized isolated test environment, execute TEST-001: Given: A user in an academic building attempts to connect to the campus Wi-Fi When: The user selects the university Wi-Fi network and enters credentials Expected: The system establishes a wireless connection for the user

4. In an authorized isolated test environment, execute TEST-002: Given: A user with invalid credentials repeatedly attempts to authenticate When: The system processes the authentication requests Expected: The system detects repeated failure and generates a security alert
5. In an authorized isolated test environment, execute TEST-003: Given: A device attempts to access internal university resources without proper authorization When: The system evaluates the request against role-based policies Expected: The system blocks unauthorized access.
6. In an authorized isolated test environment, execute TEST-004: Given: An administrator accesses the management interface When: The administrator configures a new access policy for guest users Expected: The system applies the policy and updates device access rules
7. In an authorized isolated test environment, execute TEST-005: Given: An administrator initiates a revocation request for a connected device When: The system processes the revocation command Expected: The system processes the revocation command
8. In an authorized isolated test environment, execute TEST-006: Given: An administrator requests audit log inspection When: The administrator accesses the logs interface Expected: The system returns a list of recent access events with timestamps and user identifiers
9. In an authorized isolated test environment, execute TEST-007: Given: A university employee uses a personally owned device that has been pre-approved by the IT department When: The device connects to the campus wireless network Expected: The system shall authenticate the device using university-managed credentials and enforce security policies consistent with approved device configurations
10. In an authorized isolated test environment, execute TEST-008: Given: A personal device is not pre-approved by the IT department When: The device attempts to connect to the campus wireless network Expected: The device is denied access to the campus wireless network
11. Collect stakeholder feedback; agree its cadence with a human reviewer before scheduling cycles.
12. Return accepted stakeholder feedback and observed defects to the backlog and plan the next iteration.

Roles: Proposed project owner; Proposed development lead; Proposed verification reviewer

Deliverables

1. Requirement-linked implementation increment
2. Recorded test evidence
3. Reviewed feedback and next-iteration backlog

Entry criteria

1. Prior work, source scope and the reviewed test plan are available for iteration planning.

Exit criteria

1. A human reviewer has assessed the increment, test evidence and feedback; unresolved changes return to the next iteration.

Security checks

1. Review design and test evidence for violations of source-defined permissions and exclusions.

Human approval: Pending human decision by Proposed project owner on this phase's deliverables and unresolved decisions; no approval is recorded by generation.

Requirement ids: FR-001; FR-002; FR-003; NFR-001

Name: Release and handoff

Phase type: release

Activities

1. Review the exact requirements baseline, implementation links and verification evidence before a release decision.
2. Carry unresolved source decisions into handoff; generated text is not human approval.

Roles: Proposed project owner; Proposed development lead; Proposed verification reviewer

Deliverables

1. Requirements and verification evidence package
2. Pending human release decision
3. Outstanding-decision record

Entry criteria

1. Verification evidence and unresolved decisions are available for human review.

Exit criteria

1. A human has recorded the release/handoff decision for the reviewed content.

Security checks

1. Review design and test evidence for violations of source-defined permissions and exclusions.

Human approval: Pending human decision by Proposed project owner on this phase's deliverables and unresolved decisions; no approval is recorded by generation.

Requirement ids: FR-001; FR-002; FR-003; NFR-001

Unknown factors: budget; delivery; failure_consequences; feedback; legacy; regulation; schedule; stability; uncertainty; verification

SDLC rankings and decision evidence

Policy: sequential-sdlc-1.1

Generation profile: sequential-sdlc-generation-2.0

Ranked candidates

Model: Agile

Score: 40

Reasons: No differentiating input evidence

Model: DevSecOps

Score: 40

Reasons: No differentiating input evidence

Model: Spiral

Score: 40

Reasons: No differentiating input evidence

Model: V-Model

Score: 40

Reasons: No differentiating input evidence

Model: Waterfall

Score: 40

Reasons: No differentiating input evidence

Model: Hybrid

Score: 40

Reasons: No differentiating input evidence

Model: Incremental

Score: 40

Reasons: No differentiating input evidence

Evidence register

Id: E-001

Source: description

Quote: Design a secure campus Wi-Fi management system for a university that provides wireless access to students, faculty, staff, and guests across academic buildings, hostels, laboratories, and administrative offices.

Id: E-002

Source: description

Quote: The system should use centralized authentication, role-based access control, separate guest access from internal university resources, monitor active wireless sessions, detect repeated authentication failures and unauthorized access attempts, and generate security alerts.

Id: E-003

Source: description

Quote: Network administrators should be able to configure wireless access policies, review connected devices, revoke access, and inspect audit logs.

Id: E-004

Source: description

Quote: The solution should support university-managed and approved personal devices and remain secure, scalable, reliable, and manageable across multiple campus locations.

Source references

kb-c1e0239af9dd46bd:1 - 03_OWASP_CheatSheets/107_OWASP_Zero_Trust_Architecture_Cheat_Sheet.md

Source document id: kb-c1e0239af9dd46bd

Chunk index: 1

Page or section: text chunk 2

Relevance score: 0.6857

Sha256: f5fe6d1e1cfefc05da1b1b9773acee6b7e9d156f4aa69ab0a14a7a1adfd2a8ef

kb-c1e0239af9dd46bd:8 - 03_OWASP_CheatSheets/107_OWASP_Zero_Trust_Architecture_Cheat_Sheet.md

Source document id: kb-c1e0239af9dd46bd

Chunk index: 8

Page or section: text chunk 9

Relevance score: 0.6818

Sha256: f5fe6d1e1cfefc05da1b1b9773acee6b7e9d156f4aa69ab0a14a7a1adfd2a8ef

kb-c1e0239af9dd46bd:7 - 03_OWASP_CheatSheets/107_OWASP_Zero_Trust_Architecture_Cheat_Sheet.md

Source document id: kb-c1e0239af9dd46bd

Chunk index: 7

Page or section: text chunk 8

Relevance score: 0.6703

Sha256: f5fe6d1e1cfefc05da1b1b9773acee6b7e9d156f4aa69ab0a14a7a1adfd2a8ef

kb-0150d5352d0ec304:22 - 03_OWASP_CheatSheets/036_OWASP_Authentication_Cheat_Sheet.md

Source document id: kb-0150d5352d0ec304

Chunk index: 22

Page or section: text chunk 23

Relevance score: 0.6767

Sha256: b1d318a57f742d12b57bccda3153873653652c767038c5ca3d9d74350819f303

kb-92ffa375cd05a8f5:16 - 03_OWASP_CheatSheets/081_OWASP_Multifactor_Authentication_Cheat_Sheet.md

Source document id: kb-92ffa375cd05a8f5

Chunk index: 16

Page or section: text chunk 17

Relevance score: 0.6789

Sha256: 0c1de91561bd8b449f5a27033e799c6928df3f24cb48a965994f615671612490

Validation findings

Code: human_semantic_review_required

Severity: warning

Section: document

Message: Review completeness, actor permissions, contradictions and citation applicability; schema and link checks do not prove semantic correctness.

Human review history

None recorded.

AI drafting record

Requested model: cybersrs-qwen3-4b-ft:latest

Actual models used: cybersrs-qwen3-4b-ft:latest; qwen3:4b-instruct-2507-q4_K_M

Section models

Introduction: cybersrs-qwen3-4b-ft:latest

Functional requirements: qwen3:4b-instruct-2507-q4_K_M

Non-functional requirements: qwen3:4b-instruct-2507-q4_K_M

Compliance and policy applicability matrix: cybersrs-qwen3-4b-ft:latest

Architecture: cybersrs-qwen3-4b-ft:latest

Threats: cybersrs-qwen3-4b-ft:latest

Risks: cybersrs-qwen3-4b-ft:latest

User stories and use cases: cybersrs-qwen3-4b-ft:latest

Verification and acceptance: cybersrs-qwen3-4b-ft:latest

Glossary: cybersrs-qwen3-4b-ft:latest

SDLC recommendation and workflow: qwen3:4b-instruct-2507-q4_K_M

Prompt version: sequential-1.29

Requirements traceability matrix

Requirement	Evidence / sources	Stories / tests / SDLC
FR-001	E-001	TEST-001, Requirements and verification planning, Agile delivery cycle, Release and handoff
FR-002	E-002	TEST-002, TEST-003, Requirements and verification planning, Agile delivery cycle, Release and handoff
FR-003	E-003	TEST-004, TEST-005, TEST-006, Requirements and verification planning, Agile delivery cycle, Release and handoff
NFR-001	E-004	TEST-007, TEST-008, Requirements and verification planning, Agile delivery cycle, Release and handoff

Model: cybersrs-qwen3-4b-ft:latest + qwen3:4b-instruct-2507-q4_K_M; prompt: sequential-1.29