

Synthetic Operating System Reference

z/OS V9R9

SA22-0000-00

This fixture was generated for tests. It contains no real vendor content.

Contents

Chapter 1 System parameters	3
Chapter 2 Operator messages	5
Appendix A Notices	7

Figures

Figure 1. Layout	5
------------------------	---

Chapter 1 System parameters

IEASYSxx contains system initialization parameters. The synthetic LFAREA parameter defines the size of the invented lookaside facility.

PROGxx controls the synthetic program authorization list. APF entries are described here for testing only.

Chapter 1 System parameters

Table 1. Synthetic parameters

Parameter	Meaning
LFAREA	Lookaside facility size
PROGxx	Program authorization

Chapter 2 Operator messages

IEA500I

IEA500I BEFORE IOS IOSCMDS COMMAND REJECTED, REASON=yy

Explanation: A synthetic IOSCMDS command was rejected by the fixture before IOS initialization completed. yy is a two digit reason code.

System action: The system ignores the synthetic command.

Operator response: Reissue the command after initialization completes.

Chapter 2 Operator messages

Syntax diagrams for the synthetic IOSCMDS command:

```
>>-IOSCMDS--+-APPLY--+-parameter-name-----><
      +-LIST--+
```

::= describes the invented command grammar for testing.

Appendix A Notices

This is synthetic back matter used to test skip rules.