

5.3_cross_entropy_logistic_regression_v2

March 28, 2022

Logistic Regression Training Negative Log likelihood (Cross-Entropy)

Objective

How Cross-Entropy using random initialization influence the accuracy of the model.

Table of Contents

In this lab, you will see what happens when you use the Cross-Entropy or total loss function using random initialization for a parameter value.

Make Some Data

Create the Model and Cost Function the PyTorch way

Train the Model: Batch Gradient Descent

Estimated Time Needed: 30 min

Preparation

We'll need the following libraries:

```
[1]: # Import the libraries we need for this lab

import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits import mplot3d
import torch
from torch.utils.data import Dataset, DataLoader
import torch.nn as nn
```

The class `plot_error_surfaces` is just to help you visualize the data space and the parameter space during training and has nothing to do with Pytorch.

```
[2]: # Create class for plotting and the function for plotting

class plot_error_surfaces(object):

    # Construtor
    def __init__(self, w_range, b_range, X, Y, n_samples = 30, go = True):
        W = np.linspace(-w_range, w_range, n_samples)
        B = np.linspace(-b_range, b_range, n_samples)
```

```

w, b = np.meshgrid(W, B)
Z = np.zeros((30, 30))
count1 = 0
self.y = Y.numpy()
self.x = X.numpy()
for w1, b1 in zip(w, b):
    count2 = 0
    for w2, b2 in zip(w1, b1):
        yhat= 1 / (1 + np.exp(-1*(w2*self.x+b2)))
        Z[count1,count2]=-1*np.mean(self.y*np.log(yhat+1e-16) +(1-self.
↪y)*np.log(1-yhat+1e-16))
        count2 += 1
    count1 += 1
self.Z = Z
self.w = w
self.b = b
self.W = []
self.B = []
self.LOSS = []
self.n = 0
if go == True:
    plt.figure()
    plt.figure(figsize=(7.5, 5))
    plt.axes(projection='3d').plot_surface(self.w, self.b, self.Z,
↪rstride=1, cstride=1, cmap='viridis', edgecolor='none')
    plt.title('Loss Surface')
    plt.xlabel('w')
    plt.ylabel('b')
    plt.show()
    plt.figure()
    plt.title('Loss Surface Contour')
    plt.xlabel('w')
    plt.ylabel('b')
    plt.contour(self.w, self.b, self.Z)
    plt.show()

# Setter
def set_para_loss(self, model, loss):
    self.n = self.n + 1
    self.W.append(list(model.parameters())[0].item())
    self.B.append(list(model.parameters())[1].item())
    self.LOSS.append(loss)

# Plot diagram
def final_plot(self):
    ax = plt.axes(projection='3d')
    ax.plot_wireframe(self.w, self.b, self.Z)

```

```

        ax.scatter(self.W, self.B, self.LOSS, c='r', marker='x', s=200, alpha=1)
    plt.figure()
    plt.contour(self.w, self.b, self.Z)
    plt.scatter(self.W, self.B, c='r', marker='x')
    plt.xlabel('w')
    plt.ylabel('b')
    plt.show()

    # Plot diagram
    def plot_ps(self):
        plt.subplot(121)
        plt.ylim
        plt.plot(self.x, self.y, 'ro', label="training points")
        plt.plot(self.x, self.W[-1] * self.x + self.B[-1], label="estimated_
↪line")
        plt.plot(self.x, 1 / (1 + np.exp(-1 * (self.W[-1] * self.x + self.
↪B[-1]))), label='sigmoid')
        plt.xlabel('x')
        plt.ylabel('y')
        plt.ylim((-0.1, 2))
        plt.title('Data Space Iteration: ' + str(self.n))
        plt.show()
        plt.subplot(122)
        plt.contour(self.w, self.b, self.Z)
        plt.scatter(self.W, self.B, c='r', marker='x')
        plt.title('Loss Surface Contour Iteration' + str(self.n))
        plt.xlabel('w')
        plt.ylabel('b')

    # Plot the diagram
    def PlotStuff(X, Y, model, epoch, leg=True):
        plt.plot(X.numpy(), model(X).detach().numpy(), label=('epoch ' +
↪str(epoch)))
        plt.plot(X.numpy(), Y.numpy(), 'r')
        if leg == True:
            plt.legend()
        else:
            pass

```

Set the random seed:

```

[3]: # Set random seed

torch.manual_seed(0)

```

```

[3]: <torch._C.Generator at 0x7f4387f93090>

```

Get Some Data

```
[4]: # Create the data class

class Data(Dataset):

    # Constructor
    def __init__(self):
        self.x = torch.arange(-1, 1, 0.1).view(-1, 1)
        self.y = torch.zeros(self.x.shape[0], 1)
        self.y[self.x[:, 0] > 0.2] = 1
        self.len = self.x.shape[0]

    # Getter
    def __getitem__(self, index):
        return self.x[index], self.y[index]

    # Get length
    def __len__(self):
        return self.len
```

Make Data object

```
[5]: # Create Data object

data_set = Data()
```

Create the Model and Total Loss Function (Cost)

Create a custom module for logistic regression:

```
[6]: # Create logistic_regression class

class logistic_regression(nn.Module):

    # Constructor
    def __init__(self, n_inputs):
        super(logistic_regression, self).__init__()
        self.linear = nn.Linear(n_inputs, 1)

    # Prediction
    def forward(self, x):
        yhat = torch.sigmoid(self.linear(x))
        return yhat
```

Create a logistic regression object or model:

```
[7]: # Create the logistic_regression result
```

```
model = logistic_regression(1)
```

Replace the random initialized variable values. These random initialized variable values did not converge for the RMS Loss but will converge for the Cross-Entropy Loss.

```
[8]: # Set the weight and bias
```

```
model.state_dict()['linear.weight'].data[0] = torch.tensor([[ -5]])  
model.state_dict()['linear.bias'].data[0] = torch.tensor([[ -10]])  
print("The parameters: ", model.state_dict())
```


The parameters: OrderedDict([('linear.weight', tensor([[-5.]])), ('linear.bias', tensor([[-10.]])])


Create a `plot_error_surfaces` object to visualize the data space and the parameter space during training:

```
[9]: # Create the plot_error_surfaces object
```

```
get_surface = plot_error_surfaces(15, 13, data_set[:,0], data_set[:,1], 30)
```

<Figure size 432x288 with 0 Axes>





Define the cost or criterion function:

```
[10]: # Create dataloader, criterion function and optimizer

def criterion(yhat,y):
    out = -1 * torch.mean(y * torch.log(yhat) + (1 - y) * torch.log(1 - yhat))
    return out

# Build in criterion
# criterion = nn.BCELoss()

trainloader = DataLoader(dataset = data_set, batch_size = 3)
learning_rate = 2
optimizer = torch.optim.SGD(model.parameters(), lr = learning_rate)
```

Train the Model via Batch Gradient Descent


Train the model



```
[11]: # Train the Model



def train_model(epochs):
    for epoch in range(epochs):
        for x, y in trainloader:
            yhat = model(x)
```


```
    loss = criterion(yhat, y)
    optimizer.zero_grad()
    loss.backward()
    optimizer.step()
    get_surface.set_para_loss(model, loss.tolist())
    if epoch % 20 == 0:
        get_surface.plot_ps()

train_model(100)
```









Get the actual class of each sample and calculate the accuracy on the test data:

```
[12]: # Make the Prediction

yhat = model(data_set.x)
label = yhat > 0.5
print("The accuracy: ", torch.mean((label == data_set.y.type(torch.ByteTensor)).
    ↪type(torch.float)))
```

The accuracy: tensor(1.)

The accuracy is perfect.

About the Authors:

Joseph Santarcangelo has a PhD in Electrical Engineering, his research focused on using machine learning, signal processing, and computer vision to determine how videos impact human cognition. Joseph has been working for IBM since he completed his PhD.

Other contributors: Michelle Carey, Mavis Zhou

0.1 Change Log

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2020-09-23	2.0	Shubham	Migrated Lab to Markdown and added to course repo in GitLab

##

© IBM Corporation 2020. All rights reserved.