

# Deep Langevin FTS

---

Langevin Field-Theoretic Simulation (L-FTS) Accelerated by Deep Learning (DL)

## Features

---

- L-FTS incorporated with DL
- AB Diblock Copolymer Melt
- Chain Model: Continuous, Discrete
- Periodic Boundaries
- Pseudospectral Method
- Platforms: CUDA

## Dependencies

---

### Linux System

### Anaconda

### Langevin FTS

Install **v1.0-paper** release.

```
git clone -b v1.0-paper https://github.com/yongdd/langevin-fts.git
```

## Installation

---

**Langevin FTS**, **PyTorch** and **PyTorch-lightning** should be installed in the same virtual environment. For instance, if you have installed **Langevin FTS** in virtual environment **lfts**, install **PyTorch** and **PyTorch-lightning** after activating **lfts** using the following commands. (Assuming the name of your virtual environment is **lfts**)

```
conda activate lfts
git clone -b v1.0-paper https://github.com/yongdd/deep-langevin-fts.git
conda install pip protobuf=3.19 matplotlib pytorch torchvision
torchaudio cudatoolkit=11.3 -c pytorch
pip install pytorch-lightning
```

The above commands will install the following libraries.

- **PyTorch**  
An open source machine learning framework  
<https://pytorch.org/get-started/locally/>
- **PyTorch-lightning** High-level interface for PyTorch  
<https://www.pytorchlightning.ai/>

# Usage

---

## 1. Set Simulation Parameters

```
vi input_parameters.yaml
```

Edit `input_parameters.yaml`. All the system parameters are stored in this file. If you do not want to touch the DL part, only edit this file and proceed.

## 2. Generate Training Data

```
python make_training_data.py
```

You may need to change the initial fields by modifying `w_plus` and `w_minus` in `make_training_data.py`. Training data will be stored in `data_training` folder, and it will generate `LastTrainingStep.mat` file. This generated file will be used as initial field for `find_best_epoch.py` and `run_simulation.py`.

## 3. Train a Neural Network

```
python train.py  
python find_best_epoch.py
```

If you are plan to use multiple GPUs for training, edit `gpus` in `train.py`. To obtain the same training results using multiple GPUs, you need to change `batch_size` so that `gpus * batch_size` does not change. For example, if you use 4 GPUs, set `gpus=4` and `batch_size=8`, which is effectively the same as setting `gpus=1` and `batch_size=32`. For each epoch, the weight of model will be stored in `saved_model_weights` folder.

Lastly, `find_best_epoch.py` will tell you which training result is the best. The training result is not always the same. If you are not satisfied with the result, run `train.py` once again.

## 4. Run Simulation

Edit `run_simulation.py` to use the best epoch. For example, set `model_file = "saved_model_weights/epoch_92.pth"` if the 92nd epoch was the best one. Then, run the simulation.

```
python run_simulation.py
```

Polymer density, fields and structure function will be recored in `data_simulation` folder.

## 5. Data Visualization

Matlab and Python scripts for visualization and renormalization are provided in `tools` folder of `yongdd/langevin-fts` repository.

# Citation

---

Daeseong Yong, and Jaeup U. Kim, Accelerating Langevin Field-theoretic Simulation of Polymers with Deep Learning, **2022**, in revision