

# MATH1332: Minor Thesis Presentation

## Identifying Optimal Set of Pairwise Interaction Terms by SP-FSR Algorithm and Empirical Comparison with Other Methods

Yong Kai Wong

30 May 2018

# Background

- A motivating example: do gene interactions help predict cancer type?
- How to determine interactions in high dimensions *optimally*?
- Focus on pairwise interaction terms (no quadratic terms)
- Given  $p$  features with 2-way pairwise interaction terms, the number of possible features is

$$p + \binom{p}{2} = \frac{p(p+1)}{2}$$

- SP-FSR algorithm [Aksakalli and Malekipirbazari, 2016] shows excellent performance in feature selection. Can we utilise it to identify interaction terms?

# Organisation of the presentation

- ① Basic terminology
- ② Earlier and current methods to identify pairwise interaction terms
- ③ SP-FSR algorithm for interaction identification
- ④ Experimental setup and results
- ⑤ Discussion
- ⑥ Conclusion

# Notations and terminology

- $Y$ : response feature
- $X_j$ : explanatory feature  $j$  for  $j = 1, 2, \dots, p$
- Model formulation:

$$g(Y) = \beta_0 + \sum_{j=1}^p \beta_j X_j + \sum_{i < j} \beta_{i:j} X_j X_i$$

- A precise definition [Lim and Hastie, 2018, p.1]:

*“When a function  $f(x_1, x_2)$  cannot be expressed as  $h_1(x_1) + h_2(x_2)$  for some functions  $h_1$  and  $h_2$ , we say that there is an interaction in  $f$  between  $x_1$  and  $x_2$ .”*

- Introduction of “hierarchy”

# Terminology: hierarchy

Lim and Hastie [2018] define:

Hierarchy	Description
Strong	Interactions are only among pairs of nonzero main effects
Weak	Each interaction has only one of its main effects present
Anti-hierarchical	Interactions are only among pairs of main effects that are not present
Pure interaction	No main effects present; only interactions

# Terminology: an example of hierarchy

Consider three explanatory features:  $\mathbf{X} = \{X_1, X_2, X_3\}$

- ① Strong hierarchy:  $\{X_1, X_2, X_1X_2\}$
- ② Weak hierarchy:  $\{X_1, X_1X_2, X_1X_3\}$
- ③ Anti-hierarchical:  $\{X_2, X_1X_3\}$
- ④ Pure interaction:  $\{X_2X_3, X_1X_3, X_1X_2\}$

In practice, how do we know? How can we detect?

# Main methods to identify pairwise interaction terms

- ① Statistical hypothesis test [Cox, 1984]
- ② Regularisation, e.g. LASSO
- ③ Wrapper Feature Selection [Kohavi and John, 1997]

# Statistical hypothesis test: an example

Considers two models:

- ①  $g(Y) = \beta_0 + \beta_1 X_1 + \beta_2 X_2$
- ②  $g(Y) = \beta_0 + \beta_1 X_1 + \beta_2 X_2 + \beta_{1:2} X_1 X_2$

Run hypothesis on test on  $\beta_{1:2} = 0$ .



# Regularisation

- Let  $l(y_i; \beta)$  be the **negative** log-likelihood contribution
- Elastic-net [Friedman et al., 2010]

$$\arg \min_{\beta} \frac{1}{n} \sum_{i=1}^n l(y_i; \beta) + \lambda[(1 - \alpha) \|\beta\|_2^2 / 2 + \alpha \|\beta\|_1]$$

- `glinternet` [Lim and Hastie, 2018]: group-based LASSO ( $\alpha = 1$ ) by imposing additional constraints on  $\beta_{k:j}$  and  $\beta_j$

# Wrapper feature selection

Extending feature selection by including interaction terms

- ① SFFS: Sequential (Floating) Forward Selection [Pudil et al., 1994]
- ② ~~SFBS: Sequential (Floating) Backward Selection~~ [1994]
- ③ GA: Genetic Algorithm [Siedlecki and Sklansky, 2011]
- ④ SP-FSR [2016]

# SP-FSR algorithm

- Introduced by Aksakalli and Malekipirbazari [2016]
- Based on Simultaneous Perturbation Stochastic Approximation [Spall, 1992]
- Refined by Yenice et al. [2018]
- Pseudo gradient descent method on the loss function
- spFSR package is now available in R [Aksakalli et al., 2018]

# SP-FSR algorithm: pseudo code

# SP-FSR algorithm to identify interactions

- Assume a strong hierarchy
- Simplified version of **two-step SP-FSR** algorithm:
  - 1 Identify the optimal set of  $k$  main effects using SP-FSR
  - 2 Search  $k'$ , number of interactions from  $k$  main effects with SP-FSR
- $k$  and  $k'$  can be determined via grid search or automatically

# Experimental setup

- Assume strong hierarchy
- Comparison methods: SP-FSR, SFFS, GA and `glinternet`
- Accuracy evaluation: Area under curve (AUC)
- Information criteria: AIC and BIC
- Model: logistic regression
- Datasets with binary targets:

- 1 Ionosphere
- 2 Sonar


# Experimental result: Ionosphere I

- Source: UCI (Lichman [2013])
- $n = 351, p = 33$

Method	k	k'	AUC	BIC	AIC
GA	17	71	0.9430	1747.094	1403.484
glinternet	25	23	0.9899	249.0249	434.3426
SFFS	6	4	0.9402	197.1674	239.6360
SP-FSR (Full grid search)	14	36	0.9963	151.2322	348.1323
SP-FSR (Automode)	13	14	0.9825	145.0256	253.127
Baseline	33	0	0.9815	179.0528	310.3195

Note: glinternet yields  $\lambda$  of 0.0005

# Experimental result: Ionosphere II



**Figure 1:** Comparison between glinternet and SP-FSR with full grid search



# Experimental result: Ionosphere III

# Key critiques

- No experiments on other continuous and multinomial  $Y$
- No assessment of underlying assumptions
- No quadratic and higher-order terms

# Conclusion

- SP-FSR
- The puzzle remains: do we really need to enforce (strong) hierarchy?

# Acknowledgement

- Dr Vural Aksakalli (VA) as my supervisor and mentor
- VA, Dr Babak Abbasi, and Zeren D. Yenice for spFSR package
- Zeren D. Yenice, Niranjana Adhikari, Vural Aksakalli, Dr Alev Taskin Gumus, and Babak Abbasi for their previous works on SP-FSR algorithm

# References I

- Vural Aksakalli and Milad Malekipirbazari. Feature selection via binary simultaneous perturbation stochastic approximation. *Pattern Recognition Letters*, 75(Supplement C):41 – 47, 2016. ISSN 0167-8655. doi: <https://doi.org/10.1016/j.patrec.2016.03.002>. URL <http://www.sciencedirect.com/science/article/pii/S0167865516000702>.
- Vural Aksakalli, Babak Abbasi, and Yong Kai Wong. *spFSR: Feature Selection and Ranking by Simultaneous Perturbation Stochastic Approximation*, 2018. <https://www.featureranking.com/>, <https://arxiv.org/abs/1804.05589>.
- D. R. Cox. Interaction. *International Statistical Review / Revue Internationale de Statistique*, 52(1):1–24, 1984. URL <http://www.jstor.org/stable/1403235>.

# References II

- Jerome Friedman, Trevor Hastie, and Rob Tibshirani. Regularization paths for generalized linear models via coordinate descent. *Journal of Statistical Software, Articles*, 33(1):1–22, 2010. ISSN 1548-7660. doi: 10.18637/jss.v033.i01. URL <https://www.jstatsoft.org/v033/i01>.
- R. Kohavi and G.H. John. Wrappers for feature subset selection. *Artificial Intelligence*, 1(2):273–324, 1997.
- M. Lichman. UCI machine learning repository, 2013. URL <http://archive.ics.uci.edu/ml>.
- Michael Lim and Trevor Hastie. *glinternet: Learning Interactions via Hierarchical Group-Lasso Regularization*, 2018. URL <https://CRAN.R-project.org/package=glinternet>. R package version 1.0.7.

## References III

- P. Pudil, F. J. Ferri, J. Novovicova, and J. Kittler. Floating search methods for feature selection with nonmonotonic criterion functions. In *Proceedings of the 12th IAPR International Conference on Pattern Recognition, Vol. 3 - Conference C: Signal Processing (Cat. No.94CH3440-5)*, volume 2, pages 279–283 vol.2, Oct 1994. doi: 10.1109/ICPR.1994.576920.
- W. Siedlecki and J. Sklansky. *A Note on Genetic Algorithm for Large-Scale Feature Selection*, pages 88–107. 2011. doi: 10.1142/9789814343138\_0005. URL [https://www.worldscientific.com/doi/abs/10.1142/9789814343138\\_0005](https://www.worldscientific.com/doi/abs/10.1142/9789814343138_0005).
- James C. Spall. Multivariate stochastic approximation using a simultaneous perturbation gradient approximation. *IEEE*, 37(3):322–341, 3 1992.
- Zeren D. Yenice, Niranjana Adhikari, Yong Kai Wong, Vural Aksakalli, Alev Taskin Gumus, and Babak Abbasi. Spsa-fsr: Simultaneous perturbation stochastic approximation in feature selection and ranking. 2018. URL <https://arxiv.org/abs/1804.05589>.